

LED INVERTER STREET LIGHT 60W WITH RTC

HLSLD-ML04-60-CWL-INV-RTC-R

As per IS 10322 (Part-5/Sec-3) & IEC 60598-1


Product Description: Energy efficient 60W LED Street Light

Technical Specifications:

Housing Material:	Aluminum PDC, Top maintainable
Front Cover:	Clear toughened glass
Lens:	Suitable high efficient secondary lens
LED:	LM80 certified LED
LED Lumen Maintenance:	50,000 hours @ L70
Control Gear:	Isolated, Electronic, CC driver RTC enabled
Internal Wiring:	Insulated Cu wire
Hardware:	SS & MS Zinc plated and passivated
Ingress Protection:	IP66
Impact Resistance:	IK05
Operating Voltage:	140V~270V
Operating Temperature:	-10°C~ 50°C



GA Drawing:



All dimensions in mm (Tolerance: ± 5 mm)

Additional Specifications:

Emergency Light Output: Initial Lumen at Battery mode will reduce to 15-20%

Emergency time: 1.5-2 hours Max. (Battery Back-up with Li-ion Battery).

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	60W $\pm 10\%$	<289mA	≥ 0.95	$\geq 100\text{lm/W}$	5700K	≥ 70	$\leq 10\%$	$\geq 85\%$

System Protections:

Open & Short circuit protection, reverse polarity protection, high voltage cut off at 300V ± 10 V and 5KV Internal Surge protection.

Application:

Street and road lighting, city squares, periphery lighting, complex boundary lighting, outdoor lighting, etc.

Mounting:

Pole mounting, suitable up to 50mm OD pipe bracket.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt. Ltd. reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.	Prepared by :	MK/NK	Industrial Luminaire :
	Checked by :	AS	Cat. Ref. : HLSLD-ML04-60-CWL-INV-RTC-R
	Approved by :	RL	Document No :HWR-2019

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.