

HALONIX TECHNOLOGIES PRIVATE LIMITED

Regd Office:-

B-31, Noida Phase - II, Dist.-Gautam Budh Nagar, U.P, Pin-201305

TECHNICAL DATA SHEET

LED 50W Bulb

As per IS 16102 (Part-1 &2)

Product Description: Energy efficient 50W LED Bulb

Technical Specifications:

Main Housing / Heat Sink Material: Aluminium inserted thermo plastic

PC Front Cover: E40 Base Cap:

LED: LM80 certified LED Lumen Maintenance: 50000 hours @ L70 Control Gear: Electronic, CC Driver


Internal Wiring: Insulated Cu wire

SS & MS Zinc plated and passivated Hardwares: IP20

Ingress Protection:

140V~ 270V Operating Voltage Range: Operating Temperature: -10°C~ 50°C

GA Drawing:



All dimensions in mm (Tolerance: ±5mm)

Electrical & Photometry Parameters:

| Rated Voltage | System | System | Power | System Lumen | CCT (As per ANSI) | CRI | THD | Driver |
|---------------|---------|---------|--------|--------------|-------------------|-----|------|------------|
| & Frequency | Wattage | Current | Factor | Efficacy | | | | Efficiency |
| 240V, 50Hz | 50W±10% | <249mA | ≥0.90 | ≥100lm/W | 6500K | ≥80 | ≤30% | ≥85% |

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 2.5KV internal.

Application:

Home lights, etc.

Mounting:

Wall or surface mounting.

| Note: Due to continuous efforts in developing products, | -1 / | MK/NK | Industrial Luminaire : |
|---|---------------|-------|------------------------|
| improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the | | AS | Cat. Ref. : |
| luminaries without any prior notice. | Approved by : | RL | Document No : |

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.