

Item No.	Quantities estimated but may be more or less		Item of work	Tendered Rate		Total amount according to estimated quantities
	Qty.	Unit		In Figures	In Words	
<b>1</b>	<b>2-A</b>	<b>2-B</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>
30-A	24.00	No.	Supplying and erecting LED street light / Flood light fittings with High power White LEDs wattage of 1Watt and above assembled on single MCPCB, efficiency more than 130 lm/w and corrosion free High pressure die cast aluminum housing with smooth finish powder coated and heat sink extruded aluminium with diffuser and Polycarbonate optics/ lenses with company mark/name engraved or embossed 120 to 300 V,Power Factor more than 0.95, THD < 10 %, CCT 5000 K to 5700K, Uniformity ratio >0.45, Luminaire efficacy> 85 lumens/watt . LED driver efficiency > 85 %. CREE / OSRAM / PHILIPS Lumileds / NICHIA / SEOUL/ Bridgelux (U.S.A.) make LED used for luminaire. ( Each fittings required LM-79 & LM-80 certificates) <b>(With 3 Years Complete Replacement Warranty &amp; Charges of ERDA testing will be Deducted from Bill)</b> (A) Street Light (IP-65), Surge -4KV (b) 15 to 24 Watts Cat III			

Item No.	Quantities estimated but may be more or less		Item of work	Tendered Rate		Total amount according to estimated quantities
	Qty.	Unit		In Figures	In Words	
1	2-A	2-B	3	4	5	6
30-B	144.00	No.	Supplying and erecting LED street light / Flood light fittings with High power White LEDs wattage of 1Watt and above assembled on single MCPCB, efficiency more than 130 lm/w and corrosion free High pressure die cast aluminum housing with smooth finish powder coated and heat sink extruded aluminium with diffuser and Polycarbonate optics/ lenses with company mark/name engraved or embossed 120 to 300 V,Power Factor more than 0.95, THD < 10 %, CCT 5000 K to 5700K, Uniformity ratio >0.45, Luminaire efficacy> 85 lumens/watt . LED driver efficiency > 85 %. CREE / OSRAM / PHILIPS Lumileds / NICHIA / SEOUL/ Bridgelux (U.S.A.) make LED used for luminaire. ( Each fittings required LM-79 & LM-80 certificates) <b>(With 3 Years Complete Replacement Warranty &amp; Charges of ERDA testing will be Deducted from Bill)</b> (A) Street Light (IP-65), Surge -4KV (f)90 watts Cat III			

Item No.	Quantities estimated but may be more or less		Item of work	Tendered Rate		Total amount according to estimated quantities
	Qty.	Unit		In Figures	In Words	
<b>1</b>	<b>2-A</b>	<b>2-B</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>
30-C	188.00	No.	Supplying and erecting LED street light / Flood light fittings with High power White LEDs wattage of 1Watt and above assembled on single MCPCB, efficiency more than 130 lm/w and corrosion free High pressure die cast aluminum housing with smooth finish powder coated and heat sink extruded aluminium with diffuser and Polycarbonate optics/ lenses with company mark/name engraved or embossed 120 to 300 V,Power Factor more than 0.95, THD < 10 %, CCT 5000 K to 5700K, Uniformity ratio >0.45, Luminaire efficacy > 85 lumens/watt . LED driver efficiency > 85 %. CREE / OSRAM / PHILIPS Lumileds / NICHIA / SEOUL/ Bridgelux (U.S.A.) make LED used for luminaire. ( Each fittings required LM-79 & LM-80 certificates) <b>(With 3 Years Complete Replacement Warranty &amp; Charges of ERDA testing will be Deducted from Bill)</b> (A) Street Light (IP-65), Surge -4KV (g) 120 watts Cat III			
					<b>TOTAL...</b>	
					<b>(Rs. in Words Rs. only)</b>	