

45W LED WELL GLASS CW

Photometric & Electrical Measurement (As per IES LM 79-08 / IS 16106-12)

45W Energy Efficient LED Well Glass

Issued by: Halonix Technologies Private Limited (NABL Certification No: TC-7634) 02/01/2019

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Test Report

Report Number: 01-02-2019 -001	Date:	01-02-2019	
Product Description: 45W Energy Efficient LED Well Glass			
Product Catalogue Reference: HLWG-10-45-CW	Brand:	HALONIX	
Construction:	•	•	
Pressure die casted aluminum housing, PC front visor, SMD LED,	, Electronic driver etc.		
Test Details:	Document References/Standard:		
 Light intensity distribution Measurement Total Lumen output Measurement Electrical Parameters Measurement 	 IES-LM-79-08 "Electrical and Photometric Measurements of Solid-State Lighting Products" IS: 16106-2012 "Method of Electrical and Photometric solid state lighting (LED) Products" IS: 16105-2012 "Method of measurement of Lumen maintenance of solid state light sources" 		
Enclosures:			
Prepared By:	Approved By:		
Sanjay Sharma	Rajeev Chhabra		

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Photometric Measurement Data:

Total Measured Lumen:

Light Intensity Distribution:

Approved By: Rajeev Chhabra

CCT:

Fax:

Web: http://www.halonix.co.in

Electrical & Photometric Test Report

Photometric Test Report: (As Per IES	LM 79-08)					
Sample ID: 01-02-2019 -001						
Catalogue Reference:	HLWG-10-45-CW		Testing Date:	01-02-2019		
Testing Agency:	HTPL Laboratory		Brand:	HALONIX		
Equipment Used:	EVERFINE Brand Gonio Photometer (Type: GO - 2000B V1) and Globe					
	Photometer (Type: PMS – 50/80) with Power Meter					
Ambient Temperature:	25±2°C	Relative Humidity:	65%			
Test Voltage:	240V	Frequency:	50Hz			
Stabilization Time:	30Min	Total Operating Time:	1.30Hours			
Rated Performance Parameters:						
Rated Wattage :	45W	Rated Input Current:	0.217A			
Nomical CCT :	5700K	Nominal CRI :	>70			
	•					
Measured Electrical Parameters:						
Supply Voltage:	240V	Input Current :	0.188A			
Frequency:	50Hz					
Total Power :	44.41W	Power Factor :	0.984			

Luminaries Efficacy:

Attached (Refer to Page No. 4) **Tested By:** Sanjay Sharma

CRI:

101.11lm/W

4490.3lm

5809K

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India


Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Light intensity Distribution Diagram



Catalogue Reference	HLWG-10-45-CW	Sample ID	01-02-2019 -001