

LED 15W Down Light**HLDLS-S06-15-CW**

As per IS 10322 & IEC 60598-1

**Product Description:** Energy efficient 15W LED Down Light**Technical Specifications:**

Main Housing / Heat Sink Material:

Duly powder coated Aluminium PDC

Front Cover:

PMMA

LED:

LM80 certified LED

Control Gear:

External CC driver

Internal Wiring:

Insulated Cu wire

Hardware:

SS & MS Zinc plated and passivated

Ingress Protection:


IP20

Operating Voltage:

140V~270V

Operating Temperature:

-10°C~ 50°C

GA Drawing:All dimensions in mm (Tolerance: ± 5 mm)**Electrical & Photometry Parameters:**

| Rated Voltage & Frequency | System Wattage | System Current | Power Factor | System Lumen Efficacy | CCT (As per ANSI) | CRI | THD | Driver Efficiency |
|---------------------------|----------------|----------------|--------------|-----------------------|-------------------|-----------|------------|-------------------|
| 240V, 50Hz | 15W \pm 10% | <76mA | >0.90 | \geq 70lm/W | 6500K | \geq 80 | \leq 15% | \geq 85% |

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 2.5KV internal.

Application:

Offices, commercial complexes, showrooms, retail outlets, malls, reception lobbies, hotel lobbies, high roof Indoor lighting applications, etc.

Mounting:

Surface mounting.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.

Prepared by :

MK/NK

Industrial Luminaire :

Checked by :

AS

Cat. Ref. : HLDLS- S06 -15-CW

Approved by :

RL

Document No :

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.