

### 65W LED HW STREET LIGHT

Photometric & Electrical Measurement (As per IES LM 79-08 / IS 16106-12)

65W Energy Efficient LED Street Light

Issued by: Halonix Technologies Private Limited (NABL Certification No: TC-7634) 06/10/2019

# HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

#### **Test Report**

<b>Report Number:</b> 10-06-2019 -001	Date	2: 10-06-2019	
Product Description: 65W Energy Efficient LED Street Light			
Product Catalogue Reference: HLSLD-ML04-65-CWL	Bran	d: HALONIX	
Construction:	•	•	
Pressure die casted aluminum housing, Glass front visor, SMD L	ED, Electronic driver etc.		
Test Details:	Test Details: Document References/Standard		
<ul> <li>Light intensity distribution Measurement</li> <li>Total Lumen output Measurement</li> <li>Electrical Parameters Measurement</li> </ul>	-		
Enclosures:			
Prepared By:	Approved By:		
Sanjay Sharma	Rajeev Chhabra		

### HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

**Photometric Measurement Data:** 

**Total Measured Lumen:** 

**Light Intensity Distribution:** 

Approved By: Rajeev Chhabra

CCT:

Fax:

Web: http://www.halonix.co.in

#### **Electrical & Photometric Test Report**

Photometric Test Report: (As Per IES	LM 79-08)					
Sample ID: 10-06-2019 -001						
Catalogue Reference:	HLSLD-ML04-65-CWL		Testing Date:	10-06-2019		
Testing Agency:	HTPL Laboratory		Brand:	HALONIX		
Equipment Used:	EVERFINE Brand Gonio Photometer (Type: GO - 2000B V1) and Globe					
	Photometer (Type: PMS – 50/80) with Power Meter					
·						
Ambient Temperature:	25±2°C	Relative Humidity:	65%			
Test Voltage:	240V	Frequency:	50Hz			
Stabilization Time:	30Min	Total Operating Time: 1.30Hours				
Rated Performance Parameters:						
Rated Wattage :	65W	Rated Input Current:	0.314A			
Nomical CCT :	5700K	Nominal CRI :	>70			
			•			
Measured Electrical Parameters:						
Supply Voltage:	240V	Input Current :	0.277A			
Frequency:	50Hz					
Total Power :	64.89W	Power Factor :	0.976			
		,				

6586.98lm 5861K Luminaries Efficacy:

Attached (Refer to Page No. 4) **Tested By:** Sanjay Sharma

CRI:

101.51lm/W

# HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

#### **Light intensity Distribution Diagram**



Catalogue Reference	HLSLD-ML04-65-CWL	Sample ID	10-06-2019 -001