

30W LED HW STREET LIGHT

Photometric & Electrical Measurement (As per IES LM 79-08 / IS 16106-12)

30W Energy Efficient LED Street Light

Issued by: Halonix Technologies Private Limited (NABL Certification No: TC-7634) 12/18/2018

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Test Report

Report Number: 18-12-2018 -002	Da	ate: 18-12-2018
Product Description: 30W Energy Efficient LED Street Light		
Product Catalogue Reference: HLSLD-09-30-CWL-R	Bra	and: HALONIX
Construction: Pressure die casted aluminum housing, Glass front visor, SMD L	ED, Electronic driver etc.	
Test Details:	Document Refer	rences/Standard:
 Light intensity distribution Measurement Total Lumen output Measurement Electrical Parameters Measurement 	 IES-LM-79-08 "Electrical and Photometric Measurements of Solid-State Lighting Products" IS: 16106-2012 "Method of Electrical and Photometric solid state lighting (LED) Products" IS: 16105-2012 "Method of measurement of Lumen maintenance of solid state light sources" 	
Enclosures:		
Prepared By:	Approved By:	
Sanjay Sharma	Rajeev Chhabra	

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Photometric Test Report: (As Per IES LM 79-08)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Total Measured Lumen:

Light Intensity Distribution:

Approved By: Rajeev Chhabra

CCT:

Electrical & Photometric Test Report

Catalogue Reference:	HLSLD-09-3	HLSLD-09-30-CWL-R		18-12-2018	
Testing Agency:	HTPL Labor	HTPL Laboratory		HALONIX	
Equipment Used:	EVERFINE B	EVERFINE Brand Gonio Photometer (Type: GO - 2000B V1) and Globe			
•	Photomete	Photometer (Type: PMS – 50/80) with Power Meter			
Ambient Temperature:	25±2°C	Relative Humidity:	65%		
Test Voltage:	240V	Frequency:	50Hz		
Stabilization Time:	30Min	Total Operating Time:	1.30Hours		
	•	<u> </u>			
Rated Performance Paramete	rs:				
	rs:	Rated Input Current:	0.145A		
Rated Wattage :		Rated Input Current: Nominal CRI:	0.145A >70		
Rated Wattage :	30W	· · · · · · · · · · · · · · · · · · ·			
Rated Wattage : Nomical CCT :	30W 5700K	· · · · · · · · · · · · · · · · · · ·			
Rated Wattage : Nomical CCT : Measured Electrical Paramete	30W 5700K	· · · · · · · · · · · · · · · · · · ·			
Rated Performance Paramete Rated Wattage : Nomical CCT : Measured Electrical Paramete Supply Voltage : Frequency :	30W 5700K	Nominal CRI :	>70		

3051.24lm 5785K Luminaries Efficacy:

Attached (Refer to Page No. 4) **Tested By:** Sanjay Sharma

CRI:

101.98lm/W

72.5

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Light intensity Distribution Diagram



Catalogue Reference	HLSLD-09-30-CWL-R	Sample ID	18-12-2018 -002