

## **LED 6W Aviation Light**

### **HAVL 01 S 230**




**Product Description:** Energy efficient low intensity 6W LED Aviation Light

### **Technical Specifications:**

Main Housing:	Aluminum PDC
Cover:	Acrylic
LED:	LM80 certified LED
Lumen Maintenance:	50000 hours @ L70
Control Gear:	Isolated, Electronic Driver
Internal Wiring:	Insulated Cu wire
Hardware:	SS & MS Zinc plated and passivate
Ingress Protection:	IP65
Operating Voltage Range:	140V~270V
Operating Temperature:	-10°C~50°C

### **GA Drawing:**



All dimensions in mm (Tolerance:  $\pm 10\text{mm}$ )

### **Electrical & Photometry Parameters:**

Rated Voltage & Frequency	System Wattage	System Current	Intensity	Color
240V, 50Hz	6W $\pm 10\%$	<33mA	>10 cd	RED

### **System Protections:**

Open & Short circuit protection, reverse polarity protection.

### **Application:**

High rise structures, transmission towers, chimneys, airport area etc.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt. Ltd. reserves the right to make changes in the design and data and withdraw the luminaires without any prior notice.	Prepared by :	NK	Industrial Luminaire :
	Checked by :	AS	Cat. Ref. : HAVL 01 S 230
	Approved by :	RL	Document No :

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.