

LED 45W Batten Light with Dali dimming

HLLL-P02-45-CW-HL2-DALI

As per IS: 10322 & 60598-1




Product Description: Energy efficient 45W LED Batten Light.

Technical Specifications:

Main Housing:	Powder coated MS housing
Front Cover:	Opal glare free PC diffuser
LED:	LM80 certified LED
Control Gear:	Electronic, CC driver
Internal Wiring:	Insulated Cu wire
Hardware:	SS & MS zinc plated and passivated
Ingress Protection:	IP20
Operating Voltage:	140V~ 270V
Operating Temperature:	-10°C~ 50°C

GA Drawing:



All dimensions in mm (Tolerance: ± 5 mm)

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (AS per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	45W $\pm 10\%$	<248mA	≥ 0.90	$\geq 120\text{lm/W}$	6500K	≥ 80	$\leq 15\%$	$\geq 85\%$

System Protections:

Open & Short circuit protection, reverse polarity protection and surge protection of up to 3KV.

Application:

Offices, commercial complexes, showrooms, retail outlets, malls, reception lobbies, hotel lobbies, indoor lighting applications.

Mounting:

Surface / Pendant.

Note : Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.

Prepared by :

MK/NK

Industrial Luminaire :

Checked by :

AS

Cat. Ref. : HLLL-P02-45-CW-HL2-DALI

Approved by :

RL

Document No :

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.