

30W LED WELL GLASS CW

Photometric & Electrical Measurement (As per IES LM 79-08 / IS 16106-12)

30W Energy Efficient LED Well Glass

Issued by: Halonix Technologies Private Limited (NABL Certification No: TC-7634) 01/17/2019

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Test Report

Report Number: 17-01-2019 -002	Date	17-01-2019	
Product Description: 30W Energy Efficient LED Well Glass			
Product Catalogue Reference: HLWG-10-30-CW-2M	Brand	: HALONIX	
Construction:	•	•	
Pressure die casted aluminum housing, PC front visor, SMD LED	, Electronic driver etc.		
Test Details:	Document References/Standard:		
 Light intensity distribution Measurement Total Lumen output Measurement Electrical Parameters Measurement 	 IES-LM-79-08 "Electrical and Photometric Measurements of Solid-State Lighting Products" IS: 16106-2012 "Method of Electrical and Photometric solid state lighting (LED) Products" IS: 16105-2012 "Method of measurement of Lumen maintenance of solid state light sources" 		
Enclosures:			
Prepared By:	Approved By:		
Sanjay Sharma	Rajeev Chhabra		

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

CCT:

Light Intensity Distribution:

Approved By: Rajeev Chhabra

Web: http://www.halonix.co.in

Electrical & Photometric Test Report

Photometric Test Report: (As Per II	ES LM 79-08)					
Sample ID: 17-01-2019 -002						
Catalogue Reference:	HLWG-10-30-	HLWG-10-30-CW-2M		17-01-2019		
Testing Agency:	HTPL Laborat	HTPL Laboratory		HALONIX		
Equipment Used:	EVERFINE Bra	EVERFINE Brand Gonio Photometer (Type: GO - 2000B V1) and Globe				
	Photometer (Photometer (Type: PMS – 50/80) with Power Meter				
Ambient Temperature:	25±2°C	Relative Humidity:	65%			
Test Voltage:	240V	Frequency:	50Hz			
Stabilization Time:	30Min	Total Operating Time:	1.30Hours			
	-					
Rated Performance Parameters:						
Rated Wattage :	30W	Rated Input Current:	0.145A			
Nomical CCT :	5700K	Nominal CRI:	>70			
Measured Electrical Parameters:						
Supply Voltage:	240V	Input Current :	0.127A			
Frequency:	50Hz					
Total Power :	29.91W	Power Factor :	0.981			
		<u>, </u>	,			
Photometric Measurement Data:						
Total Measured Lumen :	3050.22lm	Luminaries Efficacy:	101.98lm/W			

CRI:

Attached (Refer to Page No. 4) **Tested By:** Sanjay Sharma

5891K

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India


Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Light intensity Distribution Diagram



Catalogue Reference	HLWG-10-30-CW-2M	Sample ID	17-01-2019 -002