

LED 60W Flood Light with SPD

HLFLD-ML21-60-CWL-LW

As per IS 10322(Part-5/Sec-5) & IEC 60598-1


Product Description: Energy efficient 60W LED Flood Light

Technical Specifications:

Main Housing/Heat Sink Material:	Aluminum PDC
Front Cover:	Clear toughened glass
LED:	LM80 certified LED
Lumen Maintenance:	50000 hours @ L70
Lens:	Suitable high efficient secondary lens
Control Gear:	Isolated, Electronic, CC driver
Internal Wiring:	Insulated Cu wire
Hardware:	SS & MS Zinc plated and passivated
Ingress Protection:	IP66
Impact resistance:	IK05
Operating Voltage Range:	140V~ 270V
Operating Temperature:	-10°C~ 50°C



GA Drawing:



All dimensions in mm (Tolerance: $\pm 5\text{mm}$)

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	60W $\pm 10\%$	<289mA	≥ 0.95	$\geq 100\text{lm/W}$	5700K	≥ 70	$\leq 10\%$	$\geq 85\%$

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 5KV internal and 10KV SPD.

Application:

Open area lighting, industrial periphery lighting, parking, etc.

Mounting:

Through bracket.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.	Prepared by :	MK/NK	Industrial Luminaire :
	Checked by :	AS	Cat. Ref. : HLFLD-ML21-60-CWL-LW
	Approved by :	RL	Document No : STR-2019

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.