

LED 30W Flood Light with SPD**HLFLD-ML21-30-CWL**

As per IS 10322(Part-5/Sec-5) & IEC 60598-1

Product Description: Energy efficient 30W LED Flood Light**Technical Specifications:**

Main Housing/Heat Sink Material:

Front Cover:

LED:

Lumen Maintenance:

Lens:

Control Gear:

Internal Wiring:

Hardware:

Ingress Protection:

Impact resistance:

Operating Voltage Range:

Operating Temperature:

Aluminum PDC

Clear toughened glass

LM80 certified LED

50000 hours @ L70

Suitable high efficient secondary lens

Isolated, Electronic, CC driver

Insulated Cu wire


SS & MS Zinc plated and passivated

IP66

IK07

140V~ 270V

-10°C~ 50°C

**GA Drawing:**All dimensions in mm (Tolerance: ± 5 mm)**Electrical & Photometry Parameters:**

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CC (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	30W $\pm 10\%$	<145mA	≥ 0.95	$\geq 100\text{lm/W}$	5700K	≥ 70	$\leq 10\%$	$\geq 85\%$

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 5KV internal and 10KV SPD.

Application:

Open area lighting, industrial periphery lighting, parking, etc.

Mounting:

Through bracket.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaires without any prior notice.

Prepared by :

MK/NK

Industrial Luminaire :

Checked by :

AS

Cat. Ref. : HLFLD-ML21-30-CWL

Approved by :

RL

Document No : STR-2019

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.