

LED 18W COB Down Light

HLDLR-30-18-WW

As per IS 10322 & IEC 60598-1




Product Description: Energy efficient 18W LED Down Light

Technical Specifications:

Main Housing / Heat Sink Material:	Aluminium PDC
Front Cover:	Clear glass
LED:	LM80 certified LED
Control Gear:	External CC driver
Internal Wiring:	Insulated Cu wire
Hardwares:	SS & MS Zinc plated and passivated
Ingress Protection:	IP20
Operating Voltage:	140V~270V
Operating Temperature:	-10°C~ 50°C
Beam Angle:	36 Deg

GA Drawing:



Cutout Dia – 145mm

All dimensions in mm (Tolerance: ± 5 mm)

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	18W \pm 10%	<88mA	≥ 0.95	≥ 95 lm/W	3000K	≥ 90	$\leq 10\%$	$\geq 85\%$

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 3KV internal.

Application:

Offices, commercial complexes, showrooms, retail outlets, malls, reception lobbies, hotel lobbies, high roof Indoor lighting applications, etc.

Mounting:

Recessed mounting.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaries without any prior notice.	Prepared by :	HVS	Industrial Luminaire :
	Checked by :	AS	Cat. Ref. : HLDLR-30-18-WW
	Approved by :	RL	Document No : 042019

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.