Regd Office:

B-31, Noida Phase – II, Dist. - Gautam Budh Nagar, U.P, Pin: 201305

TECHNICAL DATA SHEET

LED 36W Well Glass

HLWG-10-36-CW

As per IS 10322(Part-5/Sec-1) & IEC 60598-1

Product Description: Energy efficient 36W LED Well Glass

escription: Energy emcient 36W LED Well Glass



Technical Specifications:

Main Housing: Powder coated Aluminum PDC Cover: Diffused opal polycarbonate

LED: Lumen Maintenance: LM80 certified LED. 50000 hours @ L70.

Control Gear: Isolated, Electronic, CC Driver.


Internal Wiring: insulated Cu wire


Hardware: SS & MS Zinc plated and passivate.

Ingress Protection: IP66
Impact resistance: IK05

Operating Voltage Range: $100V^270V$ Operating Temperature: $-10^{\circ}C^{\circ}50^{\circ}C$

GA Drawing:





All dimensions in mm (Tolerance: ±10mm)

Electrical & Photometry Parameters:

Rated Voltage	System	System	Power	Lumen	CCT	CRI	THD	Driver
& Frequency	Wattage	Current	Factor	Efficacy	(as per ANSI)			Efficiency
240V, 50Hz	36W±10%	<174mA	>0.95	≥100lm/W	5700K	>70	<10%	>85%

System Protections:

Open & Short circuit protection, reverse polarity protection, high voltage cut off at 300V±10V, surge protection of 5KV internal.

Application:

Industries, steel plants, thermal plants, cement plants, material handling plants, etc.

Mounting:

Through eye bolt.

Note: Due to continuous efforts in developing products,	Prepared by :	MK/NK	Industrial Luminaire :
improvement M/s Halonix Technologies Pvt. Ltd. reserves the right to make changes in the design and data and	Checked by :	AS	Cat. Ref. : HLWG-10-36-CW
withdraw the luminaries without any prior notice.	Approved by :	RL	Document No : KON-2019