

72W LED HW STREET LIGHT

Photometric & Electrical Measurement (As per IES LM 79-08 / IS 16106-12)

72W Energy Efficient LED Street Light

Issued by: Halonix Technologies Private Limited (NABL Certification No: TC-7634) 06/13/2019

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Test Report

Report Number: 13-06-2019 -001		: 13-06-2019	
Product Description: 72W Energy Efficient LED Street Light			
Product Catalogue Reference: HLSLD-ML04-72-CWL	Brand	I: HALONIX	
Construction:	•	•	
Pressure die casted aluminum housing, Glass front visor, SMD L	ED, Electronic driver etc.		
Test Details:	Document References/Standard:		
 Light intensity distribution Measurement Total Lumen output Measurement Electrical Parameters Measurement 	 IES-LM-79-08 "Electrical and Photometric Measurements of Solid-State Lighting Products" IS: 16106-2012 "Method of Electrical and Photometric solid state lighting (LED) Products" IS: 16105-2012 "Method of measurement of Lumen maintenance of solid state light sources" 		
Enclosures:			
Prepared By:	Approved By:		
Sanjay Sharma	Rajeev Chhabra		

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Photometric Test Report: (As Per IES LM 79-08)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Photometric Measurement Data:

Total Measured Lumen:

Light Intensity Distribution:

Approved By: Rajeev Chhabra

CCT:

Fax:

Web: http://www.halonix.co.in

Electrical & Photometric Test Report

Sample ID: 13-06-2019 -001	•				
Catalogue Reference:	HLSLD-ML0	HLSLD-ML04-72-CWL		13-06-2019	
Testing Agency:	HTPL Labor	HTPL Laboratory		HALONIX	
Equipment Used:	EVERFINE B	EVERFINE Brand Gonio Photometer (Type: GO - 2000B V1) and Globe			
	Photomete	Photometer (Type: PMS – 50/80) with Power Meter			
Ambient Temperature:	25±2°C	Relative Humidity:	65%		
Test Voltage:	240V	Frequency:	50Hz		
Stabilization Time:	30Min	Total Operating Time: 1.30Hours			
Rated Performance Parameters:					
Rated Wattage :	72W	Rated Input Current:	0.347A		
Nomical CCT :	6000K	Nominal CRI:	>70		
Measured Electrical Parameters:					
Supply Voltage:	240V	Input Current :	0.305A		
Frequency:	50Hz				
Total Power :	71.51W	Power Factor :	0.977		

7232.52lm

5863K

Luminaries Efficacy:

Attached (Refer to Page No. 4)

Tested By: Sanjay Sharma

CRI:

101.14lm/W

72.2

HALONIX TECHNOLOGIES PRIVATE LIMITED HTPL LABORATORY (NABL Certificate No: TC-7634)

Plot-5, Sector-12, IIE, SIDCUL

Haridwar (Uttarakhand), PIN-249403, India

Contact:

Email: customercare@halonix.co.in

Fax:

Web: http://www.halonix.co.in

Light intensity Distribution Diagram



				_
Catalogue Reference	HLSLD-ML04-72-CWL	Sample ID	13-06-2019 -001	