


LED 40W Batten (Flare Square)

HLB-08-40-CW

As per IS 10322 & IEC 60598-1



Product Description: Energy efficient 40W LED Batten

Technical Specifications:

Main Housing:	Aluminum extruded
Front Cover:	Opal glare free PC diffuser
LED:	LM80 certified LED
Lumen Maintenance:	50000 hours @ L70
Control Gear:	Electronic, CC Driver
Internal Wiring:	Insulated Cu wire
Hardwares:	SS & MS Zinc plated and passivated
Ingress Protection:	IP20
Operating Voltage Range:	140V~ 270V
Operating Temperature:	-10°C~ 50°C

GA Drawing:



All dimensions are in mm (Tolerance: ±5mm)

Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	40W±10%	<193mA	≥0.95	≥110lm/W	5700K	≥80	≤15%	≥90%

System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 3KV internal.

Application:

Offices, hospitals, retail outlets, banks, etc.

Mounting:

Surface or wall mounting.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaires without any prior notice.	Prepared by :	MK/NK	Industrial Luminaire :
	Checked by :	AS	Cat. Ref. : HLB-08-40-CW
	Approved by :	RL	Document No : HW-2019

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.