


**LED 22W 1X1 Panel Light****HLFPS11-06-22-CW**

As per IS 10322 &amp; IEC 60598-1

**Product Description:** Energy efficient 30W LED 1X1 Panel Light**Technical Specifications:**

Main Housing:	Duly powder coated CRCA sheet steel
Front Cover:	PMMA
LED:	LM80 certified LED
Lumen Maintenance:	50000 hours @ L70
Control Gear:	Isolated, Electronic, CC Driver
Internal Wiring:	Insulated Cu wire
Hardware:	SS & MS Zinc plated and passivated
Ingress Protection:	IP20
Operating Voltage Range:	140V~ 270V
Operating Temperature:	-10°C~ 50°C

**GA Drawing:**All dimensions in mm (Tolerance:  $\pm 5$ mm)**Electrical & Photometry Parameters:**

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (AS per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	22W $\pm 10\%$	<105mA	$\geq 0.95$	$\geq 90$ lm/W	6500K	$\geq 80$	$\leq 10\%$	$\geq 85\%$

**System Protections:**

Open &amp; Short circuit protection, reverse polarity protection, surge protection of 3KV internal.

**Application:**

Offices, hospitals, retail outlets, banks, etc.

**Mounting:**

Recessed mounting.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaires without any prior notice.

Prepared by :

MK/NK

Industrial Luminaire :

Checked by :

AS

Cat. Ref. :

Approved by :

RL

Document No : OF-2020

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.