

## LED 60W Flood Light with SPD

### HLFLD-ML21-60-CWL

As per IS 10322(Part-5/Sec-5) & IEC 60598-1

**Product Description:** Energy efficient 60W LED Flood Light

### Technical Specifications:

Main Housing/Heat Sink Material:

Aluminum PDC

Front Cover:

Clear toughened glass

LED:

LM80 certified LED

Lumen Maintenance:

50000 hours @ L70

Lens:

Suitable high efficient secondary lens

Control Gear:

Isolated, Electronic, CC driver

Internal Wiring:

Insulated Cu wire

Hardware:

SS & MS Zinc plated and passivated

Ingress Protection:

IP66

Impact resistance:

IK05

Operating Voltage Range:


90V~ 300V

Operating Temperature:

-10°C~ 50°C



### GA Drawing:



All dimensions in mm (Tolerance:  $\pm 5$ mm)

### Electrical & Photometry Parameters:

Rated Voltage & Frequency	System Wattage	System Current	Power Factor	System Lumen Efficacy	CCT (As per ANSI)	CRI	THD	Driver Efficiency
240V, 50Hz	60W $\pm 10\%$	<289mA	$\geq 0.95$	$\geq 100\text{lm/W}$	5700K	$\geq 70$	$\leq 10\%$	$\geq 85\%$

### System Protections:

Open & Short circuit protection, reverse polarity protection, surge protection of 5KV internal and 10KV SPD.

### Application:

Open area lighting, industrial periphery lighting, parking, etc.

### Mounting:

Through bracket.

Note: Due to continuous efforts in developing products, improvement M/s Halonix Technologies Pvt Ltd reserves the right to make changes in the design and data and withdraw the luminaires without any prior notice.

Prepared by :

MK/NK

Industrial Luminaire :

Checked by :

AS

Cat. Ref. : HLFLD-ML21-60-CWL

Approved by :

RL

Document No : STR-2019

As improvement in design & method of manufacturing is a continuous process, the product supplied may differ in details from above given data.