CSE 444: Database Internals

Section 4:

Query Optimizer

Plan for Today

- Problem 1A, 1B: Estimating cost of a plan
 - You try to compute the cost for 5 mins
 - We go over the solution together

- Problem 2: Sellinger Optimizer
 - We will do it together

1. Estimating Cost of a given plan

```
Student (<u>sid</u>, name, age, address)
Book(<u>bid</u>, title, author)
Checkout(<u>sid</u>, bid, date)
```

Query:


SELECT S.name
FROM Student S, Book B, Checkout C
WHERE S.sid = C.sid
AND B.bid = C.bid
AND B.author = 'Olden Fames'
AND S.age > 12
AND S.age < 20

S(<u>sid</u>,name,age,addr) B(<u>bid</u>,title,author) C(<u>sid,bid</u>,date)

Assumptions

- Student: S, Book: B, Checkout: C
- Sid, bid foreign key in C referencing S and B resp.
- There are 10,000 Student records stored on 1,000 pages.
- There are 50,000 Book records stored on 5,000 pages.
- There are 300,000 Checkout records stored on 15,000 pages.
- There are 500 different authors.
- Student ages range from 7 to 24.

Physical Query Plan – 1A



 $S(\underline{sid}, name, age, addr)$ T(S)=10,000 $B(\underline{bid}, title, author)$ T(B)=50,000 T(C)=300,000

B(S)=1,000 V(B,author) = 500 B(B)=5,000 7 <= age <= 24 V(B,author) = 500

Solution – 1A

```
(On the fly) (d) \Pi_{\text{name}}
        (On the fly) (c) \sigma_{12 < age < 20} \Lambda author = 'Olden Fames'
(Tuple-based nested loop
B inner)
                                              (b)
                                      bid
(Block-nested loop,
                                             Book B
S outer, C inner)
                                             File scan
                Student S
                                 Checkout C
                                (File scan)
             (File scan)
```


```
(a) B(S) + B(S) * B(C)
    = 1000 + 1000 * 15000
    = 15,001,000
  cardinality = 300,000
      (foreign key join, output
      pipelined to next join)
Also, applying the formula, join
size=T(S) * T(C)/max (V(S, sid), V(C, sid))
= T(S) since V(S, sid) > = V(C, sid) and
T(S) = V(S, sid)
(b) T(S ⋈ C) * B(B)
    = 300,000 * 5,000 = 15 * 10^{8}
  cardinality = 300,000
      (foreign key join, don't need
      scanning for outer relation)
(C, d) cost 0 (on the fly)
Cardinality:
300,000 * 1/500 * 7/18
= 234 (approx)
(assuming uniformity and
independence)
Total cost = 1,515,001,000
Final cardinality = 234 (approx)
```

S(<u>sid</u>,name,age,addr) B(<u>bid</u>,title,author) C(<u>sid,bid</u>,date)

```
B(S)=1,000
B(B)=5,000
B(C)=15,000
```

Physical Query Plan – 1B

(Index scan)



Book B

(Index scan)

Q. Compute

- the cost and cardinality in steps
 (a) to (g)
- 2. the total cost

Assumptions:

- Unclustered B+tree index on B.author
- Clustered B+tree index on C.bid
- All index pages are in memory
- Unlimited memory

Student S

(File scan)

```
T(S)=10,000
                                                                 B(S)=1,000
S(<u>sid</u>,name,age,addr)
                                                                                       V(B,author) = 500
B(<u>bid</u>,title,author): Un. B+ on author T(B)=50,000
                                                                 B(B)=5,000
                                                                                       7 <= age <= 24
                                             T(C)=300,000
C(sid,bid,date): Cl. B+ on bid
                                                                 B(C)=15,000
                                                                    (a) T(B) / V(B, author)
          Solution – 1B
                                                                         cost = 50,000/500 = 100 (unclustered)
                                                                       cardinality = 100
                             (On the fly) (g) \Pi_{\text{name}}
                                                                    (b) Cost 0, cardinality 100
                                                                    (c)
                           (On the fly)
                                      (f) \sigma_{12 < age < 20}
                                                                          one index lookup per outer B tuple
                                                                          1 book has 6 checkouts (uniformity)
                                                                          # C tuples per page = T(C)/B(C) = 20
           (Block nested loop
                                                                          6 tuples fit in at most 2 consecutive pages
                                                        (e)
                                                                          (clustered) – could assume 1 page as well
           S inner)
                                               sid
                                                                    Cost <= 100 * 2= 200
                                                                       cardinality = 100 * 6 = 600
                                                                           (= 100 * T(C)/ MAX(100, V(C, bid)) assuming
                            (d) \prod_{sid} (On the fly)
                                                                            V(C, bid) = V(B, bid) = T(B) = 50,000
                                                                    (d) Cost 0, cardinality 600
  (Indexed-nested loop,
                                                                    (e) Outer relation is already in memory,
  B outer, C inner)
                                          (C)
                                                 Student S
                                                                    need to scan S relation
                                 bid
                                                                    cost B(S) = 1000
                                                     (File scan)
                                                                    Cardinality = 600
       (On the fly)
                  (b) \Pi
                                                                    (f) Cost = 0
                                    Checkout C
      (a) \sigma_{\text{author}} = \text{`Olden Fames'}
                                                                    Cardinality = 600 * 7/18 = 234 (approx)
                                                                    (d) Cost 0, cardinality 234
                                   (Index scan)
                 Book B
                                                                    Total cost = 1300 (compare with 1,515,001,000 in 1A!)
          (Index scan)
                                                                    Final cardinality = 234 (approx) (same as 1A!)
```