### Problem 1.

(30 points)

- (a) Use the forward-difference and backward-difference formulas to determine each missing entry in the following table with  $f(x) = \sin x$ , compute the errors and find error bounds using error formulas.
- (b) Choose your favorite function f, nonzero number x. Generate approximations of  $f'_n(x)$  to f'(x) by

$$f'_n(x) = \frac{f(x+10^{-n}) - f(x)}{10^{-n}}$$

for n = 1, 2, ..., 10 and describe what happens.

#### Solution

#### Part (a)

x	f(x)	f'(x)	$\cos x$	$\varepsilon =  \cos x - f'(x) $
0.5	0.4794	0.85200	0.87758	0.025580
0.6	0.5646	0.79600	0.82534	0.029340
0.7	0.6442	0.79600	0.76484	0.031160

We find the error term  $\left| \frac{h}{2} f''(\xi) \right|$  from the following formula

$$f'(x_0) = \frac{f(x_0 + h) - f(x_0)}{h} - \frac{h}{2}f''(\xi)$$

This error bound will be the same for forward and backward difference. We have  $f''(x) = -\sin x$  and h = 0.1 in all cases, thus our error is given by  $\lfloor \frac{0.1}{2} \sin \xi \rfloor$  where  $\xi$  is a value within the bounds of our difference. For each, we therefore want to maximize the value  $\sin \xi$ .

f'(0.5):  $max_{0.5,0.6} \sin \xi = 0.564642 \Rightarrow = \frac{0.1}{2}0.564642 = 0.028232$ Thus we have an error bound of 0.02832 which is just a bit over our actual error of 0.025580.

f'(0.6):  $max_{0.6,0.7} \sin \xi = 0.644218 \Rightarrow = \frac{0.1}{2}0.644218 = 0.03221$ Thus we have an error bound of 0.03221 a little bit worse than before. Our actual error of 0.029340 fits nicely within this bound.

f'(0.7):  $max_{0.6,0.7} \sin \xi = 0.644218 \Rightarrow = \frac{0.1}{2}0.644218 = 0.03221$ Since we are taking the backward difference, we come to the same error bound as the forward difference for f'(0.6), that is 0.03221. Our actual error for this value is the worst at 0.031160 but still within the error bounds like we would expect.

## Part (b)

Let  $f(x) = \sin(x)$ , and x = 3. We have  $f'(x) = \cos(x)$ , thus  $f'(3) = \cos(3) = -0.9899924966$ .

n	$f_n'(x)$	$  f'_n(x) - f'(x)  $
1	-0.995393456265767	0.005400959665322
2	-0.990681590968298	0.000689094367853
3	-0.990062891599724	0.000070394999279
4	-0.989999550952969	0.000007054352524
5	-0.989993202188399	0.000000705587954
6	-0.989992567285158	0.000000070684713
7	-0.989992501865267	0.000000005264821
8	-0.989992490763036	0.000000005837409
9	-0.989992560151975	0.000000063551530
10	-0.989992532396400	0.000000035795954

In general, for larger values of n we would expect the error between our approximation and the actual derivative to go down. However, if we in the above example we can see the error actually increase from n=7 to n=8 and from n=8 to n=9. We do see a decrease again from n=9 to n=10 however we still don't have the precision found at n=7 right before our estimates started to get worse.

### Problem 2.

(60 points)

(a) Approximate the following integral using the Trapezoidal rule, find a bound for the error using error formula and compare this to the actual error:

$$\int_{0.5}^{1} x^4 dx$$
.

- (b) Repeat part (a) using Simpson's rule.
- (c) Repeat part (a) using Composite Trapezoidal rule with n=4.
- (d) Repeat part (a) using Composite Simpson rule with n = 4.
- (e) Write a code to implement part (c) and (d) in MATLAB.
- (f) Write a function v = CompositeTrapezoidalRule(f, a, b, n) to implement Composite trapezoidal rule with a given n for

$$\int_{a}^{b} f(x)dx,$$

verify your code with part (c).

#### Solution

#### Part (a)

By the trapezoidal rule, our approximation is given by  $\frac{h}{2}[f(x_0) + f(x_1)]$ . Where  $x_0 = 0.5, x_1 = 1$  gives us  $f(x_0) = 0.0625, f(x_1) = 1.0$ . The estimate is given by  $1.0625\frac{0.5}{2} = 0.26562$ . The actual value of the integral is 0.19375, thus our actual error is |0.26562 - 0.19375| = 0.071875.

The trapezoidal rule has an error term of  $\frac{h^3}{12}f''(\xi)$ . Where  $f''(\xi) = 12\xi^2$ , maximizing this on the bounds (0.5, 1) gives us 12, thus our error bound  $= \frac{0.5^3}{12}12 = 0.5^3 = 0.125$ . Note that our actual error 0.071875 is within this error bound.

# Part (b)

First we compute the values needed by Simpson's rule. We have a=0.5, b=1.0 thus  $h=(1.0-0.5)/2=0.25, x_0=a=0.5, x_1=a+h=0.75, x_2=1.0$ . Simpson's rule is given by  $\frac{h}{3}[f(x_0)+4f(x_1)+f(x_2)]$ , filling in our values gives us  $\frac{0.25}{3}[0.5^4+4\times0.75^4+1^4]=0.08333[0.0625+1.2656+1]=0.08333[2.3281]=0.194$ . Given the actual value of the integral as 0.19375 our actual error is then |0.194-0.19375|=0.00025057.

Simpson's rule has an error term of  $\frac{h^5}{90}f^{(4)}(\xi)$ . Where  $f^{(4)}(\xi) = 24$ . Our error bound is then  $24\frac{0.25^5}{90} = 0.00026042$ . Our actual error sneaks just under this error bound.

### Part (c)

For Composite Trapezoidal Rule with n=4, we have  $h=(1.0-0.5)/4=0.125, x_i=[0.5,0.625,0.75,0.875,1.0], i\in[0,1,\ldots,4]$ . The Composite Trapezoidal Approximation is given by  $\frac{h}{2}[f(a)+2\sum_{j=1}^{n-1}f(x_j)+f(b)]$ . Plugging in our values gives us

$$\int_{0.5}^{1} x^4 dx \approx \frac{0.125}{2} [f(0.5) + 2(f(0.625) + f(0.75) + f(0.875)) + f(1.0)]$$

$$= \frac{0.125}{2} [0.0625 + 2(1.0557) + 1]$$

$$= \frac{0.125}{2} [3.1739]$$

$$= 0.19837$$

With an actual value of 0.19375 our actual error is 0.19837 - 0.19375 = 0.0046188.

The error term is given by  $\frac{b-a}{12}h^2f''(\mu)$ . From part (a) we know we can maximize  $f''(\mu)$  as 12. Thus the error bound is  $12\frac{1-0.5}{12}0.125^2=0.0078125$ . Again, our actual is nicely within this bound.

### Part (d)

For Composite Simpson's Rule with n=4, we have  $h=(1.0-0.5)/4=0.125, x_i=[0.5,0.625,0.75,0.875,1.0], i\in[0,1,\ldots,4]$ , these are the same values obtained from Composite Trapezoidal Rule. The desired approximation is given by  $\frac{h}{3}[f(a)+2\sum_{j=1}^{(n/2)-1}f(x_{2j}+4\sum_{j=1}^{n/2}f(x_{2j-1})+f(b)]$ . Plugging in our values gives us

$$\begin{split} \int_{0.5}^{1} x^4 dx \approx & \frac{0.125}{3} [f(0.5) + 2(f(0.75)) + 4(f(0.625) + f(0.875)) + f(1.0)] \\ = & \frac{0.125}{3} [0.625 + 2(0.31641) + 4(0.73877) + 1.0] \\ = & \frac{0.125}{3} [4.6504] \\ = & 0.193766276 \end{split}$$

With an actual value of 0.19375 our actual error is 0.193766276 - 0.19375 = 0.0000162760416666519.

The error term is given by  $\frac{b-a}{180}h^4f^{(4)}(\mu)$ . From part (b) we know we  $f^{(4)}(\mu)=24$ . Putting it all together yields  $24\frac{1.0-0.5}{180}0.125^4=0.0000162760416666667$ . Here we have a pretty accurate error bound and our actual value is falling just under it, though at this number of significant digits we might expect computer precision to be affecting our results.

### Part (e)

For CompositeTrapezoidalRule see my answer to part (f).

```
function v = CompositeSimpsonsRule(f, a, b, n)
        h = (b-a)/n;
        x = (a+h):h:b;
        i = 1:((n/2)-1);
        j = 1:(n/2);
        part1 = 2 * sum(f(x(2.*i)));
        part2 = 4 * sum(f(x(2.*j-1)));
        inner = f(a) + part1 + part2 + f(b);
        v = (h/3) * inner;
end
Running
                CompositeSimpsonsRule(@(x)x.^4, 0.5, 1, 4)
produces a result of 0.19377 which is the same I found in part (d).
Part (f)
function v = CompositeTrapezoidalRule(f, a, b, n)
        h = (b-a)/n;
        x = (a+h):h:b;
        j = 1:(n-1);
        part = 2 * sum(f(x(j)));
        inner = f(a) + part + f(b);
        v = (h/2) * inner;
end
Running
```

 $CompositeTrapezoidalRule(@(x)x.^4, 0.5, 1, 4)$ 

produces a result of 0.19830 which is roughly the same I found in part (c). There is some variation at later significant digits, but I would attribute to truncation when computing by hand.

# Problem 3.

(20 points)

(a) Show that the following quadrature formula has a degree of precision equal to 3,

$$\int_{-1}^{1} f(x)dx = f(-\frac{\sqrt{3}}{3}) + f(\frac{\sqrt{3}}{3}).$$

(b) Approximate the following integral using Gaussian quadrature with n=2,3,5,

$$\int_{1}^{1.5} x^2 \ln x dx$$

# Problem 4.

(20 points)

(a) Use Composite Simpson rule with n=4 to approximate the following integral

$$\int_0^1 x^{-1/4} \sin x dx$$

(b) Use Composite Simpson rule with n=6 to approximate the following integral

$$\int_{1}^{\infty} \frac{\cos x}{x^3} dx$$

## Problem 5.

(30 points)

(a) Use the Gaussian Elimination with Backward substitution to solve the following linear system (must show intermediate steps).

$$2x_1 - 1.5x_2 + 3x_3 = 1$$

$$-x_1 + 2x_3 = 3$$

$$4x_1 - 4.5x_2 + 5x_3 = 1$$

- (b) Repeat (a) using the Gaussian Elimination with partial pivoting and Backward substitution (must show intermediate steps).
- (c) Repeat (a) using Gaussian Elimination with scaled partial pivoting and Backward substitution (must show intermediate steps).

## Problem 6.

(20 points)

(a) Solve the following linear system with forward and backward substitution,

$$\begin{bmatrix} 1 & 0 & 0 \\ 2 & 1 & 0 \\ -1 & 0 & 1 \end{bmatrix} \begin{bmatrix} 2 & 3 & -1 \\ 0 & -2 & 1 \\ 0 & 0 & 3 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_3 \end{bmatrix} = \begin{bmatrix} 2 \\ -1 \\ 1 \end{bmatrix}$$

(b) Use the LU factorization (no permutation) with forward and backward substitution to solve the following linear system (Use the sample MATLAB codes posted on classpage as discussed in class),

$$2x_1 + 3x_2 - x_3 = 2$$
$$4x_1 + 4x_2 - x_3 = -1$$
$$-2x_1 - 3x_2 + 4x_3 = 1$$

# Problem 7.

(20 points)

(a) Use the  $A = LDL^t$  factorization to solve the following linear system,

$$2x_1 - x_2 = 2$$

$$-x_1 + 2x_2 - x_3 = -1$$

$$-x_2 + 2x_3 = 1$$

(b) Repeat (a) with Cholesky factorization  $A = LL^t$ .