



AALBORG UNIVERSITY

STUDENT REPORT

ED5-3-E16

XXX

Students:

Alexandra Dorina Török

Andrius Kulšinskas

Supervisors:

Christian Mai

November 2, 2016



AALBORG UNIVERSITY
STUDENT REPORT

**School of Information and
Communication Technology**

Niels Bohrs Vej 8
DK-6700 Esbjerg
<http://sict.aau.dk>

Title:

xxx

Abstract:

xxx

Theme:

Scientific Theme

Project Period:

Autumn Semester 2016

Project Group:

ED5-3-E16

Participant(s):

Alexandra Dorina Török
Andrius Kulšinskas

Supervisor(s):

Christian Mai

Copies: x

Page Numbers: 10

Date of Completion:

November 2, 2016

The content of this report is freely available, but publication (with reference) may only be pursued due to agreement with the author.

Contents

Preface	1
1 Introduction	2
1.1 Introduction	2
2 Problem Description	3
2.1 Physical Setup	3
2.1.1 Motors	3
2.1.2 Propellers	4
2.1.3 Electric Speed Controller	4
2.1.4 Ardupilot	4
2.1.5 Power Distribution Board	4
2.1.6 Battery	4
2.2 Flight Dynamics	4
3 Mathematical Modelling	6
4 Experiments	7
5 Discussion	8
6 Conclusion	9
7 Appendix	10
7.1 Appendix code	10

Preface

The project entitled *xxx* was made by two students from the Electronics and Computer Engineering programme at Aalborg University Esbjerg, for the P5 project during the fifth semester.

From hereby on, every mention of 'we' refers to the two co-authors listed below.

Aalborg University, November 2, 2016.

Andrius Kulšinskas
<akulsi14@student.aau.dk>

Alexandra Dorina Török
<atarak14@student.aau.dk>

Chapter 1

Introduction

1.1 Introduction

The theme of this semester's project lies within *Automation*. Automation can be simply described as being the use of diverse control systems for fulfilling a certain task with little to no human interaction. As known from the previous semester, a control system is an instrument which has the role of adapting the behaviour of a system according to a desired state, also known as steady-state or reference. Any control system has three components: measurement, control and actuation. Without one of these, automation would not be possible. Essentially, the measure reflects the current state of the system, the controller is the brain that given the measurement decides which action will be performed and the actuator is the one executing the action.

Project ideas around the topic of automation are unlimited, since it is so widely spread. Having discussed a few of them that would meet the semester's requirements, we finally decided to work on the control of a quadcopter. Our decision was for the most part based on the fact that the university had the required equipment available, which enabled us to start working on the project right-away.

Quadcopters are popularly referred to as drones and they have increased their areas of operation from the military sector to more commercial uses such as search and rescue/healthcare, geographic mapping, aerial photography, surveillance etc. Our goal for the project is to design a control system that makes it possible for the quadcopter to be stable - hovering and to also act according to the user's input - manoeuvring. Basically, our input will be a certain height and the quadcopter has to automatically adjust to that height and maintain its' stability when no further inputs are given. A safety feature - obstacle avoidance will also be implemented.

Chapter 2

Problem Description

Quadcopter control is a complex, yet interesting problem. One of the reasons why this control problem is challenging is the fact that a quadcopter has six degrees of freedom, but only four inputs which affects the linearity of the dynamics and makes the quadcopter underactuated. One other important thing to mention is that quadcopters, unlike ground vehicles, have very little friction that prevents their motion, so they have to provide their own damping in order to be able to stop or maintain stability.

This chapter will give a general overview on the pieces of technical equipment which we are using and show what the purpose of each one is. It will also present how our scopes - hovering and manouvering can be achieved by designing and implementing a control system. A solution in terms of the structure of our control system will be identified. We will also delve into the basic working principle of a quadcopter/flight dynamics.

2.1 Physical Setup

2.1.1 Motors

Controlling a quadcopter can be done efficiently by using high-quality motors with fast response, which will ensure more of a stable flight. The motors must also be powerful enough to be able to lift the quadcopter and perform the required aerial movements.

The motor that we are using is the xx Brushless DC Motor. -more on this later after looking at specs-

-insert figure

2.1.2 Propellers

The propellers don't have such strict requirements as the motors. They are needed to be light and have a size and lift potential in order for the quadcopter to hover at less than 50% of the motor capacity. For our quadcopter, we are using plastic - insert size- propellers with light weight. The length is given by the first measurement - x, while the pitch by the second one - x.

-insert figure-

2.1.3 Electric Speed Controller

The purpose of an electric speed controller (ESC) is to vary the electric motor's speed. We need the ESC to have a fast response, for the same reasons mentioned for the motors in -section-. The ESC that we are using is the TURNIGY PLUSH-30A.

+more from datasheet

-insert figure-

2.1.4 Ardupilot

ardupilot - features: accelerometer, gyroscope, magnetometer 3 axis

2.1.5 Power Distribution Board

To reduce the number of connections straight to the battery, we used the xx Power distribution board from xx. A board like is an easy solution since all we have to do is connect the four ESCs to the board and then connect the board to the battery.

-insert figure-

2.1.6 Battery

specs.

-insert figure-

2.2 Flight Dynamics

Before we begin doing any work, it is important to understand how quadcopter works. A quadcopter, as the name suggest, runs on four motors usually placed at equal distances from each other (figure here)

By controlling the speed at which the motors rotate, it is possible to change how quadcopter moves. Movement can be broken down in 3 separate sets of motor speeds:

1) If the two back motors rotate faster than the two frontal motors, the quadcopter will pitch forward. Switching the speeds will result in aft pitch. 2) If the two left motors have higher RPM than the two motors on the right side, the vehicle will roll to the right. Swapping the speeds differences will result in a roll to the left. 3) Increasing the speed of one of the diagonal pair of the motors will result in yaw to the direction of the torque of the motors. The copter will then spin around its axis.

Now that the effect of speed of the motors is established, it is important to talk about the forces in play. There are 4 main forces affecting quadcopter - thrust, lift, draw and drop (figure again)

The drop - or the gravitational force - affects the vehicle at all times. As any object on Earth, its mass is driven towards the centre of the planet.

The thrust is the force generated by the motors that is allowing the vehicle to move horizontally.

The lift force is also generated by the motors and allows the vehicle to move up.

Draw force - ???

A powered off motors is only affected by the drop force and therefore stays on the ground. In order to lift it up, we need to understand the relationship between quadcopter and the thrust to weight ratio - or TWR for short. This ratio can be determined by equation F_t/F_g and describes the vehicle's ability to move up. With TWR expressed as a number, three cases can be identified: 1) $TWR < 1$: The gravitational force is higher than the lift force and therefore the quadcopter is drawn towards the ground. 2) $TWR = 1$: The forces are equal, causing quadcopter's altitude to stay constant. 3) $TWR > 1$: The thrust is higher than drop force, allowing vehicle to move upwards.

Therefore, in order to get a quadcopter up in the air, it is necessary to generate enough thrust for TWR ration to be higher than one. In order to land it, the TWR must be smaller than 1, allowing the quadcopter to move downwards.

Chapter 3

Mathematical Modelling

3.1 Motor Dynamics

Chapter 4

Experiments

Chapter 5

Discussion

Chapter 6

Conclusion

Chapter 7

Appendix

7.1 Appendix code