


2 Interval scheduling

- Job j starts at s_j and finishes at f_j .
- Two jobs **compatible** if they don't overlap.
- Goal: find maximum subset of mutually compatible jobs.



2

Interval scheduling

- Job j starts at s_j and finishes at f_j .
- Two jobs compatible if they don't overlap.
- Goal: find maximum subset of mutually compatible jobs.


مسئله زمان بندی بازه‌ای یا

"Activity Selection"

مسئله انتخاب فعالیت

(CLRS 16.1)

مسئله اصلی: تالار سخنرانی: لیستی از تقاضاها برای برگزاری سخنرانی داده شده



در هر تقاضا

زمان آغاز s_j

و زمان پایان f_j

از قبل مشخص است

jobs d and g are incompatible

Interval scheduling: greedy algorithms

Greedy template. Consider jobs in some "natural order."

Take each job provided it's compatible with the ones already taken.

1 • [Earliest start time] Consider jobs in ascending order of s_j .

2 • [Earliest finish time] Consider jobs in ascending order of f_j .

3 • [Shortest interval] Consider jobs in ascending order of $f_j - s_j$.

4 • [Fewest conflicts] For each job j , count the number of conflicting jobs c_j . Schedule in ascending order of c_j .

در این مسئله بررسی
feasibility

همانا بررسی
است.
ما همپوشانی بودن

قاعده زودآمدترین

*
قاعده زودپایانترین


قاعده کوتاهترین زمان

قاعده کم تعداداخلترین


Interval scheduling: greedy algorithms

Greedy template. Consider jobs in some natural order.


Take each job provided it's compatible with the ones already taken.



سوال نقض برای قاعده
زود آمدترین
نقطه a انتخاب می شود
در حالیکه جواب بهینه $\{b, c, d, e\}$



سوال نقض برای قاعده
کوچکترین زمان
نقطه a انتخاب می شود
در حالیکه جواب بهینه $\{b, c\}$



سوال نقض برای قاعده
کم تداخل ترین
نقطه a انتخاب می شود
در حالیکه جواب بهینه $\{b, c\}$

Interval scheduling: earliest-finish-time-first algorithm



EARLIEST-FINISH-TIME-FIRST ($n, s_1, s_2, \dots, s_n, f_1, f_2, \dots, f_n$)

Sort jobs by finish time so that $f_1 \leq f_2 \leq \dots \leq f_n$

$A \leftarrow \phi$ ← set of jobs selected

FOR $j = 1$ **TO** n

IF job j is compatible with A

$A \leftarrow A \cup \{j\}$

RETURN A

Proposition. Can implement earliest-finish-time first in $O(n \log n)$ time.

- Keep track of job j^* that was added last to A .
- Job j is compatible with A iff $s_j \geq f_{j^*}$.
- Sorting by finish time takes $O(n \log n)$ time.


فرض می‌کنیم پیش از فراخوانی تابع زیر، بازه‌ها به ترتیب صعودی بر حسب f مرتب شده باشند. می‌توان نشان داد جواب مسئله (حداکثر تعداد بازه‌های دو به دو ناهمپوشان) برای مسئله انتخاب فعالیت توسط معیار انتخاب برپایه Earliest-finish-time

GREEDY-ACTIVITY-SELECTOR(s, f)

```

1   $n = s.length$ 
2   $A = \{a_1\}$  // selected jobs;  $A$ 
3   $k = 1$  // index of last selected job
4  for  $m = 2$  to  $n$ 
5      if  $s[m] \geq f[k]$  // feasibility test
6           $A = A \cup \{a_m\}$ 
7           $k = m$ 
8  return  $A$ 

```



قاعده زود پایان کردن

بدست می‌آید.

۳ فعالیت انتخاب می‌شود


$$T(n) = O(n \lg n) + O(n) = O(n \lg n)$$

Interval scheduling: analysis of earliest-finish-time-first algorithm

Theorem. The earliest-finish-time-first algorithm is optimal.

Pf. [by contradiction]

- Assume greedy is not optimal, and let's see what happens.
- Let i_1, i_2, \dots, i_k denote set of jobs selected by greedy.
- Let j_1, j_2, \dots, j_m denote set of jobs in an optimal solution with $i_1 = j_1, i_2 = j_2, \dots, i_r = j_r$ for the largest possible value of r . ($r < m$)




Interval scheduling: analysis of earliest-finish-time-first algorithm

Theorem. The earliest-finish-time-first algorithm is optimal.

Pf. [by contradiction]

- Assume greedy is not optimal, and let's see what happens.
- Let i_1, i_2, \dots, i_k denote set of jobs selected by greedy.
- Let j_1, j_2, \dots, j_m denote set of jobs in an optimal solution with $i_1 = j_1, i_2 = j_2, \dots, i_r = j_r$ for the largest possible value of r .



③ Interval partitioning

مسئله افزایش بازه‌ای

"مسئله کمینه‌سازی تالارهای سخنرانی"

Interval partitioning.

- Lecture j starts at s_j and finishes at f_j .
- Goal: find minimum number of classrooms to schedule all lectures so that no two lectures occur at the same time in the same room.

مابسته قبل n سخنرانی،

بازمان آغاز s_j

وزمان پایان f_j

داره شده است


می‌خواهیم با

تخصیص

کمترین تعداد تالار

Ex. This schedule uses 4 classrooms to schedule 10 lectures.

$n=10$




Interval partitioning

Interval partitioning.

- Lecture j starts at s_j and finishes at f_j .
- Goal: find minimum number of classrooms to schedule all lectures so that no two lectures occur at the same time in the same room.

Ex. This schedule uses 3 classrooms to schedule 10 lectures.



Interval partitioning: greedy algorithms


Greedy template. Consider lectures in some natural order. Assign each lecture to an available classroom (which one?); allocate a new classroom if none are available.

- 1 • [Earliest start time] Consider lectures in ascending order of s_j . زود آمدترین
- 2 • [Earliest finish time] Consider lectures in ascending order of f_j . زود پایان ترین
- 3 • [Shortest interval] Consider lectures in ascending order of $f_j - s_j$. کوته ترین بازه
- 4 • [Fewest conflicts] For each lecture j , count the number of conflicting lectures c_j . Schedule in ascending order of c_j . کم تداخل ترین

Interval partitioning: greedy algorithms

Greedy template. Consider lectures in some natural order.
Assign each lecture to an available classroom (which one?);
allocate a new classroom if none are available.

counterexample for earliest finish time




سؤال نقص برای انتخاب

زود پایان ترین ← 3
تعداد کلاسهای

مورد نیاز
در حالت جواب بهینه {a,d}, {b,c}
← 2 کلاس


counterexample for shortest interval



سؤال نقص برای انتخاب ← 3 کلاس

کوچکترین بازه
در حالت جواب بهینه 2 کلاس

counterexample for fewest conflicts



سؤال نقص برای انتخاب ← 3 کلاس

کم داخل ترین
در حالت جواب بهینه 2 کلاس

Interval partitioning: earliest-start-time-first algorithm



EARLIEST-START-TIME-FIRST ($n, s_1, s_2, \dots, s_n, f_1, f_2, \dots, f_n$)

Sort lectures by start time so that $s_1 \leq s_2 \leq \dots \leq s_n$.

$d \leftarrow 0$ \leftarrow number of allocated classrooms تعداد کلاسهای مورد نیاز

FOR $j = 1$ **TO** n

IF lecture j is compatible with some classroom

Schedule lecture j in any such classroom k .

ELSE

Allocate a new classroom $d + 1$.

Schedule lecture j in classroom $d + 1$.

$d \leftarrow d + 1$

RETURN schedule.

Interval partitioning: earliest-start-time-first algorithm

Proposition. The earliest-start-time-first algorithm can be implemented in $O(n \log n)$ time.

Pf. Store classrooms in a **priority queue** (key = finish time of its last lecture).

- To determine whether lecture j is compatible with some classroom, compare s_j to key of min classroom k in priority queue.
- To add lecture j to classroom k , increase key of classroom k to f_j .
- Total number of priority queue operations is $O(n)$.
- Sorting by start time takes $O(n \log n)$ time. ■

Remark. This implementation chooses the classroom k whose finish time of its last lecture is the **earliest**.


Interval partitioning: lower bound on optimal solution

Def. The **depth** of a set of open intervals is the maximum number that contain any given time.

Key observation. Number of classrooms needed \geq depth.

Q. Does number of classrooms needed always equal depth?

A. Yes! Moreover, earliest-start-time-first algorithm finds one.



Interval partitioning: analysis of earliest-start-time-first algorithm

Observation. The earliest-start-time first algorithm never schedules two incompatible lectures in the same classroom.

Theorem. Earliest-start-time-first algorithm is optimal.

Pf.

- Let d = number of classrooms that the algorithm allocates.
- Classroom d is opened because we needed to schedule a lecture, say j , that is incompatible with all $d - 1$ other classrooms.
- These d lectures each end after s_j .
- Since we sorted by start time, all these incompatibilities are caused by lectures that start no later than s_j .
- Thus, we have d lectures overlapping at time $s_j + \epsilon$.
- Key observation \Rightarrow all schedules use $\geq d$ classrooms. ■