

Tecnológico de Monterrey Campus Guadalajara

Hijos del Puntero

Imanol González, Sebastián Certuche, Francisco Chávez

2026-08-31

1 Contest 1

2 Data structures 1

3 Strings 3

4 Mathematics 5

5 Numerical 6

6 Number theory 10

7 Combinatorial 11

8 Graph 12

9 Geometry 18

10 Various 22

Contest (1)

template.cpp

23 lines

```
#include <bits/stdc++.h>
using namespace std;

typedef long long lli;
typedef long double ld;
typedef pair<lli, lli> ii;
typedef vector<lli> vi;

#define endl '\n'
#define _ ios::sync_with_stdio(0);cin.tie(0);cout.tie(0);
#define f first
#define s second
#define pb push_back
#define sz(c) (lli)c.size()
#define all(c) c.begin(), c.end()
#define fore(i, a, b) for (lli i = (a), I = (b); i < I; i++)
#define ford(i, a, b) for (lli i = (a), I = (b); i-- > I;)

#define perr(x) cerr << #x << " " << (x) << endl

int main() { _
  return 0;
}
```

.bashrc

3 lines

```
alias c='g++ -Wall -Wconversion -Wfatal-errors -g -std=c++17 \
  -fsanitize=undefined,address'
xmodmap -e 'clear lock' -e 'keycode 66=less greater' #caps = <>
```

hash.sh

3 lines

```
# Hashes a file, ignoring all whitespace and comments. Use for
# verifying that code was correctly typed.
cpp -dD -P -fpreprocessed | tr -d '[:space:]'| md5sum |cut -c-6
```

Data structures (2)

ChullTrick.h

Description: Convex Hull Trick. Evaluates $\min / \max(m_i x + c_i)$ dynamically when line slopes are added in monotonic order.
Time: Add $\mathcal{O}(1)$ amortized - Query $\mathcal{O}(\log N)$ or $\mathcal{O}(1)$.

0fee90, 34 lines

```
typedef lli tc;
struct Line{tc m,h;};
struct CHT { // for minimum (for maximum just change the sign
     of lines)
  vector<Line> c;
  int pos=0;
  tc in(Line a, Line b){
    tc x=b.h-a.h,y=a.m-b.m;
    return x/y+(x%y?!((x>0)^(y>0)):0); // ==ceil(x/y)
  }
  void add(tc m, tc h){ // m's should be non increasing
    Line l=(Line){m,h};
    if(c.size()&&m==c.back().m){
      l.h=min(h,c.back().h);c.pop_back();if(pos)pos--;
    }
    while(c.size()>1&&in(c.back(),l)<=in(c[c.size()-2],c.back()
        )){
      c.pop_back();if(pos)pos--;
    }
    c.pb(l);
  }
  inline bool fbin(tc x, int m){return in(c[m],c[m+1])>x;}
  tc eval(tc x){
    // O(log n) query:
    int s=0,e=c.size();
    while(e-s>1){int m=(s+e)/2;
      if(fbin(x,m-1))e=m;
      else s=m;
    }
    return c[s].m*x+c[s].h;
    // O(1) query (for ordered x's):
    while(pos>0&&fbin(x,pos-1))pos--;
    while(pos<c.size()-1&&!fbin(x,pos))pos++;
    return c[pos].m*x+c[pos].h;
  }
};
```

ChullTrickDynamic.h

Description: Dynamic variant of CHT maintaining lines in a std::set without slope monotonicity constraints.
Time: Add $\mathcal{O}(\log N)$ - Query $\mathcal{O}(\log N)$.

59e1a4, 39 lines

```
typedef lli tc;
const tc is_query=-(1LL<<62); // special value for query
struct Line {
  tc m,b;
  mutable multiset<Line>::iterator it,end;
  const Line* succ(multiset<Line>::iterator it) const {
    return (++it==end? NULL : &*it);}
  bool operator<(const Line& rhs) const {
    if(rhs.b!=is_query)return m<rhs.m;
    const Line *s=succ(it);
    if(!s)return 0;
    return b-s->b<(s->m-m)*rhs.m;
  }
};
struct HullDynamic : public multiset<Line> { // for maximum
  bool bad(iterator y){
    iterator z=next(y);
    if(y==begin()){
      if(z==end())return false;
      return y->m==z->m&&y->b<=z->b;
    }
    iterator x=prev(y);
    if(z==end())return y->m==x->m&&y->b<=x->b;
    return (x->b-y->b)*(z->m-y->m)>=(y->b-z->b)*(y->m-x->m);
  }
  iterator next(iterator y){return ++y;}
  iterator prev(iterator y){return --y;}
  void add(tc m, tc b){
    iterator y=insert((Line){m,b});
    y->it=y;y->end=end();
    if(bad(y)){erase(y);return;}
    while(next(y)!=end()&&bad(next(y)))erase(next(y));
    while(y!=begin()&&bad(prev(y)))erase(prev(y));
  }
  tc eval(tc x){
    Line l=*lower_bound((Line){x,is_query});
    return l.m*x+l.b;
  }
};
```

OrderStatisticTree.h

Description: A set (not multiset!) with support for finding the n'th element, and finding the index of an element. To get a map, change `null_type`.
Time: $\mathcal{O}(\log N)$

b9b97b, 18 lines

```
// #include <bits/extc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

template<class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

void example() {
  Tree<int> t, t2; t.insert(8);
  auto it = t.insert(10).first;
  assert(it == t.lower_bound(9));
  assert(t.order_of_key(10) == 1);
  assert(t.order_of_key(11) == 2);
  assert(*t.find_by_order(0) == 8);
  t.join(t2); // assuming T < T2 or T > T2, merge t2 into t
}
```

Segtree.h

Description: Recursive implementation of segment tree, easy to modify. Answers Queries [L,R]
Time: $\mathcal{O}(\log N)$.

2add14, 28 lines

```
struct Segtree{
  #define mid (l + r) / 2
  #define left(u) (u + 1)
  #define right(u) (u + ((mid - l + 1) << 1))
  struct Node{
    lli s;
    Node(lli s = 0): s(s) {}
    Node operator + (const Node &n){
      return Node(s + n.s);
    }
  };
  vector<Node> st;
  Segtree(int n): st(2 * n) {}
  void update(int u, int l, int r, int kth, lli val){ // O(logN
       )
    if(l == r){
      st[u].s = val;
      return;
    }
    if(kth <= mid) update(left(u), l, mid, kth, val);
    else update(right(u), mid + 1, r, kth, val);
    st[u] = st[left(u)] + st[right(u)];
  }
```

```
  Node query(int u, int l, int r, int ll, int rr){ // O(logN)
    if(l > r or r < ll or l > rr) return Node();
    if(ll <= l and r <= rr) return st[u];
    return query(left(u), l, mid, ll, rr) + query(right(u), mid
          + 1, r, ll, rr);
  }
};
```

SegtreeIterative.h

Description: Iterative implementation of segment tree, faster but not easy to modify. Answers Queries [L,R]
Time: $\mathcal{O}(\log N)$.

02441f, 23 lines

```
struct Segtree {
  struct Node {
    lli x;
    Node(lli x = 0) : x(x) {}
    Node operator+(const Node& n) { return Node(x + n.x); }
  };
  int n;
  vector<Node> st;
  Segtree(int n) : n(n), st(2 * n) {}
  void update(int i, lli x) {
    i += n;
    st[i] = Node(x); // update
    for(; i; i /= 2) st[i / 2] = st[i] + st[i ^ 1];
  }
  lli query(int l, int r) { // [l,r]
    Node ll, rr;
    for(l += n, r += n + 1; l < r; l /= 2, r /= 2) {
      if(l & 1) ll = ll + st[l++];
      if(r & 1) rr = st[--r] + rr;
    }
    return (ll + rr).x;
  }
};
```

SegtreeLazy.h

Description: Segment tree with ability to add or set values of large intervals. Answers Queries [L,R]
Time: $\mathcal{O}(\log N)$.

5fed49, 52 lines

```
struct LazySegtree{
  #define mid (l + r) / 2
  #define left(u) (u + 1)
  #define right(u) (u + ((mid - l + 1) << 1))
  struct Node{
    lli s, lazy;
    Node(lli s = 0, lli lazy = 0) : s(s), lazy(lazy) {}
    Node operator + (const Node &n){
      return Node(s + n.s);
    }
  };
  vector<Node> st;
  int N;
  LazySegtree(int n) : st(2 * n), N(n) {}
  void push(int u, int l, int r){
    if(st[u].lazy){
      if(l < r){
        st[left(u)].lazy += st[u].lazy;
        st[right(u)].lazy += st[u].lazy;
      }
      st[u].s += st[u].lazy * (r - l + 1);
      st[u].lazy = 0;
    }
  }

  void update(int u, int l, int r, int ll, int rr, lli val){
    push(u,l,r);
    if(l > r or r < ll or l > rr) return;
    if(ll <= l and r <= rr){
      st[u].lazy += val;
      push(u,l,r);
      return;
    }
    update(left(u), l, mid, ll, rr, val);
    update(right(u), mid + 1, r, ll, rr, val);
    st[u] = st[left(u)] + st[right(u)];
  }
  Node query(int u, int l, int r, int ll, int rr){
    push(u,l,r);
    if(l > r or r < ll or l > rr) return Node();
    if(ll <= l and r <= rr) return st[u];
    return query(left(u), l, mid, ll, rr) + query(right(u), mid
          + 1, r, ll, rr);
  }

  void update(int ll, int rr, lli val){
        update(0,0,N-1,ll,rr,val);
  }

  Node query(int ll, int rr){
        return query(0,0,N-1,ll,rr);
  }
};
```

SegtreePersistent.h

Description: Preserves historical versions of the segment tree after point updates. Answers Queries [L,R)
Time: $\mathcal{O}(\log N)$.

eab3d2, 26 lines

```
const lli NEUT = 0;
struct STree { // persistent segment tree for min over integers
  vi st, L, R; int n,tam,rt;
  STree(int n): st(1,NEUT),L(1,0),R(1,0),n(n),rt(0),tam(1){}
  int new_node(int v, int l=0, int r=0){
    int ks=sz(st); st.pb(v); L.pb(l); R.pb(r); return ks;
  }
  int upd(int k, int s, int e, int p, int v){
    int ks=new_node(st[k],L[k],R[k]);
    if(s+1==e){st[ks]=v;return ks;}
    int m=(s+e)/2,ps;
    if(p<m)ps=upd(L[ks],s,m,p,v),L[ks]=ps;
    else ps=upd(R[ks],m,e,p,v),R[ks]=ps;
    st[ks]=oper(st[L[ks]],st[R[ks]]);
    return ks;
  }
  int query(int k, int s, int e, int a, int b){
    if(e<=a||b<=s)return NEUT;
    if(a<=s&&e<=b)return st[k];
    int m=(s+e)/2;
    return oper(query(L[k],s,m,a,b),query(R[k],m,e,a,b));
  }
  int upd(int k, int p, int v){return rt=upd(k,0,n,p,v);}
  int upd(int p, int v){return upd(rt,p,v);} // update on last
       root
  int query(int k,int a, int b){return query(k,0,n,a,b);};
};
```

SegtreeSparse.h

Description: Dynamic node allocation over huge index domains without coordinate compression.
Time: $\mathcal{O}(\log C)$ (C: coordinate range).

9e8d7f, 43 lines

```
#define mid l + (r - l) / 2
struct Node{
  lli s, mx;
  Node(lli s = 0, lli mx = -INF): s(s), mx(mx) {};
  Node operator + (const Node& n) {
    return Node(s + n.s, max(mx, n.mx));
  }
};
struct ST {
  Node data;
  lli l, r;
  // ST(Node data = Node()): data(data), l(0), r(0) {}
};
ST st[MAXN];
lli curst = 1; // 0 = NULL
lli newST(){
  st[curst].data = Node();
  st[curst].l = 0;
  st[curst].r = 0;
  return curst++;
}
Node data(lli u){return u ? st[u].data : Node();}
void pull(lli u){st[u].data = data(st[u].l) + data(st[u].r);}
void update(lli u, lli l, lli r, lli kth, Node val){
  if(l == r){
    st[u].data = val;
    return;
  }
  if(kth <= mid){
    if(!st[u].l) st[u].l = newST();
    update(st[u].l, l, mid, kth, val);
  }
  else {
    if(!st[u].r) st[u].r = newST();
    update(st[u].r, mid + 1, r, kth, val);
  }
  pull(u);
}
Node query(lli u, lli l, lli r, lli ll, lli rr){
  if(!u or l > r or r < ll or l > rr) return Node();
  if(ll <= l and r <= rr) return st[u].data;
  return query(st[u].l, l, mid, ll, rr) + query(st[u].r, mid +
       1, r, ll, rr);
}
```

Segtree2D.h

Description: Point update and 2D rectangular range associative queries.
Time: Build: $\mathcal{O}(NM)$ Update and Query: $\mathcal{O}(\log N)$.

185ce7, 27 lines

```
int n,m; int a[MAXN][MAXN],st[2*MAXN][2*MAXN];
void build(){
  fore(i,0,n)fore(j,0,m)st[i+n][j+m]=a[i][j];
  fore(i,0,n)for(int j=m-1;j;--j)
    st[i+n][j]=op(st[i+n][j<<1],st[i+n][j<<1|1]);
  for(int i=n-1;i;--i)fore(j,0,2*m)
    st[i][j]=op(st[i<<1][j],st[i<<1|1][j]);
}
void upd(int x, int y, int v){
  st[x+n][y+m]=v;
  for(int j=y+m;j>1;j>>=1)st[x+n][j>>1]=op(st[x+n][j],st[x+n][j
       ^1]);
  for(int i=x+n;i>1;i>>=1)for(int j=y+m;j;j>>=1)
    st[i>>1][j]=op(st[i][j],st[i^1][j]);
}
int query(int x0, int x1, int y0, int y1){
  int r=NEUT;
  for(int i0=x0+n,i1=x1+n;i0<i1;i0>>=1,i1>>=1){
    int t[4],q=0;
    if(i0&1)t[q++]=i0++;
    if(i1&1)t[q++]=--i1;
    fore(k,0,q)for(int j0=y0+m,j1=y1+m;j0<j1;j0>>=1,j1>>=1){
      if(j0&1)r=op(r,st[t[k]][j0++]);
      if(j1&1)r=op(r,st[t[k]][--j1]);
```

```
    }
  }
  return r;
}
```

TreapImplicit.h

Description: Dynamic array supporting range reverse, insertions, deletions, and shifts.
Usage: `split(root, l, r, L); split(r, mid, r, len); // isolates [L, L + len - 1] in mid`
`merge(root, l, mid); merge(root, root, r); // restores the tree`
Time: $\mathcal{O}(\log N)$. f552b6, 52 lines

```
// example that supports range reverse and addition updates,
     and range sum query
// (commented parts are specific to this  problem)
typedef struct item *pitem;
struct item {
  int pr,cnt,val;
//  int sum; // (paramters for range query)
//  bool rev;int add; // (parameters for lazy prop)
  pitem l,r;
  item(int val): pr(rand()),cnt(1),val(val),l(0),r(0)/*,sum(val
      ),rev(0),add(0)*/ {}
};
void push(pitem it){
  if(it){
    /*if(it->rev){
      swap(it->l,it->r);
      if(it->l)it->l->rev^=true;
      if(it->r)it->r->rev^=true;
      it->rev=false;
    }
    it->val+=it->add;it->sum+=it->cnt*it->add;
    if(it->l)it->l->add+=it->add;
    if(it->r)it->r->add+=it->add;
    it->add=0;*/
  }
}
int cnt(pitem t){return t?t->cnt:0;}
// int sum(pitem t){return t?push(t),t->sum:0;}
void upd_cnt(pitem t){
  if(t){
    t->cnt=cnt(t->l)+cnt(t->r)+1;
    // t->sum=t->val+sum(t->l)+sum(t->r);
  }
}
void merge(pitem& t, pitem l, pitem r){
  push(l);push(r);
  if(!l||!r)t=l?l:r;
  else if(l->pr>r->pr)merge(l->r,l->r,r),t=l;
  else merge(r->l,l,r->l),t=r;
  upd_cnt(t);
}
void split(pitem t, pitem& l, pitem& r, int sz){ // sz:desired
     size of l
  if(!t){l=r=0;return;}
  push(t);
  if(sz<=cnt(t->l))split(t->l,l,t->l,sz),r=t;
  else split(t->r,t->r,r,sz-1-cnt(t->l)),l=t;
  upd_cnt(t);
}
void output(pitem t){ // useful for debugging
  if(!t)return;
  push(t);
  output(t->l);printf(" %d",t->val);output(t->r);
}
// use merge and split for range updates and queries
```

Strings (3)

AhoCorasick.h

Description: Online Aho-Corasick automaton for multiple string matching using suffix link memoization via map transitions.
Usage: `aho_init();`
`add_string(pattern, id);`
`int next_state = go(u, c);`
Time: Construction: $\mathcal{O}\left(\sum |S| \log \Sigma\right)$, Matching: $\mathcal{O}\left(|T| \log \Sigma\right)$. 12eeeb, 35 lines

```
struct vertex {
  map<char,int> next,go;
  int p,link;
  char pch;
  vector<int> leaf;
  vertex(int p=-1, char pch=-1):p(p),pch(pch),link(-1){}
};
vector<vertex> t;
void aho_init(){ //do not forget!!
  t.clear();t.push_back(vertex());
}
void add_string(string s, int id){
  int v=0;
  for(char c:s){
    if(!t[v].next.count(c)){
      t[v].next[c]=t.size();
      t.push_back(vertex(v,c));
    }
    v=t[v].next[c];
  }
  t[v].leaf.push_back(id);
}
int go(int v, char c);
int get_link(int v){
  if(t[v].link<0)
    if(!v||!t[v].p)t[v].link=0;
    else t[v].link=go(get_link(t[v].p),t[v].pch);
  return t[v].link;
}
int go(int v, char c){
  if(!t[v].go.count(c))
    if(t[v].next.count(c))t[v].go[c]=t[v].next[c];
    else t[v].go[c]=v==0?0:go(get_link(v),c);
  return t[v].go[c];
}
```

Hashing.h

Description: Self-explanatory methods for string hashing. 2d2a67, 44 lines

```
// Arithmetic mod 2^64-1. 2x slower than mod 2^64 and more
// code, but works on evil test data (e.g. Thue-Morse, where
// ABBA... and BAAB... of length 2^10 hash the same mod 2^64).
// "typedef ull H;" instead if you think test data is random,
// or work mod 10^9+7 if the Birthday paradox is not a problem.
typedef uint64_t ull;
struct H {
  ull x; H(ull x=0) : x(x) {}
  H operator+(H o) { return x + o.x + (x + o.x < x); }
  H operator-(H o) { return *this + ~o.x; }
  H operator*(H o) { auto m = (__uint128_t)x * o.x;
    return H((ull)m) + (ull)(m >> 64); }
  ull get() const { return x + !~x; }
  bool operator==(H o) const { return get() == o.get(); }
  bool operator<(H o) const { return get() < o.get(); }
};
static const H C = (ll)1e11+3; // (order ~ 3e9; random also ok)

struct HashInterval {
  vector<H> ha, pw;
  HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
    pw[0] = 1;
    rep(i,0,sz(str))
      ha[i+1] = ha[i] * C + str[i],
      pw[i+1] = pw[i] * C;
  }
  H hashInterval(int a, int b) { // hash [a, b)
    return ha[b] - ha[a] * pw[b - a];
  }
};

vector<H> getHashes(string& str, int length) {
  if (sz(str) < length) return {};
  H h = 0, pw = 1;
  rep(i,0,length)
    h = h * C + str[i], pw = pw * C;
  vector<H> ret = {h};
  rep(i,length,sz(str)) {
    ret.push_back(h = h * C + str[i] - pw * str[i-length]);
  }
  return ret;
}

H hashString(string& s){H h{}; for(char c:s) h=h*C+c;return h;}
```

KMP.h

Description: Computes prefix function (longest proper border) and finds all occurrences of pattern t in text s.
Usage: `vector<int> pi = kmppre(t);`
`kmp(s, t);`
Time: $\mathcal{O}(|S| + |T|)$ eeeb20, 16 lines

```
vector<int> kmppre(string& t){ // r[i]: longest border of t[0,i
    )
  vector<int> r(t.size()+1);r[0]=-1;
  int j=-1;
  for(int i = 0; i < (int)(t.size()); ++i){
    while(j>=0&&t[i]!=t[j])j=r[j];
    r[i+1]=++j;
  }
  return r;
}
void kmp(string& s, string& t){ // find t in s
  int j=0;vector<int> b=kmppre(t);
  for(int i = 0; i < (int)(s.size()); ++i){
    while(j>=0&&s[i]!=t[j])j=b[j];
    if(++j==(int)t.size())printf("Match at %d\n",i-j+1),j=b[j];
  }
}
```

LCP.h

Description: Kasai's algorithm to compute the Longest Common Prefix (LCP) array from a suffix array.
Usage: `vector<int> lcp = computeLCP(s, sa);`
Time: $\mathcal{O}(N)$ b173e2, 14 lines

```
vector<int> computeLCP(string& s, vector<int>& sa){
  int n=(int)s.size(),L=0;
  vector<int> lcp(n),plcp(n),phi(n);
  phi[sa[0]]=-1;
  for(int i = 1; i < n; ++i) phi[sa[i]]=sa[i-1];
  for(int i = 0; i < n; ++i){
    if(phi[i]<0){plcp[i]=0;continue;}
    while(s[i+L]==s[phi[i]+L])L++;
    plcp[i]=L;
    L=max(L-1,0);
  }
  for(int i = 0; i < n; ++i) lcp[i]=plcp[sa[i]];
  return lcp; // lcp[i]=LCP(sa[i-1],sa[i])
```

```
}
```

Manacher.h

Description: Computes maximal palindromic radii centered at every character (odd) and between characters (even).
Usage: `manacher(s); // populates d1 (odd) and d2 (even)`
Time: $\mathcal{O}(N)$

3663a6, 22 lines

```
const int MAXN = 1e6;
int d1[MAXN];//d1[i] = max odd palindrome centered on i
int d2[MAXN];//d2[i] = max even palindrome centered on i
//s  aabbaacaabbaa
//d1 1111117111111
//d2 0103010010301
void manacher(string& s){
  int l=0,r=-1,n=s.size();
  for(int i = 0; i < n; ++i){
    int k=i>r?1:min(d1[l+r-i],r-i);
    while(i+k<n&&i-k>=0&&s[i+k]==s[i-k])k++;
    d1[i]=k--;
    if(i+k>r)l=i-k,r=i+k;
  }
  l=0;r=-1;
  for(int i = 0; i < n; ++i){
    int k=i>r?0:min(d2[l+r-i+1],r-i+1);k++;
    while(i+k<=n&&i-k>=0&&s[i+k-1]==s[i-k])k++;
    d2[i]=--k;
    if(i+k-1>r)l=i-k,r=i+k-1;
  }
}
```

MinRotation.h

Description: Computes the lexicographically smallest circular shift / rotation of a sequence or string.
Usage: `vi min_rot = getminlex(s);`
Time: $\mathcal{O}(N)$

653eec, 17 lines

```
vi getminlex(vi s){
  int n=sz(s),k=0; fore(i,0,n) s.pb(s[i]);
  vi f(2*n,-1);
  fore(j,1,2*n){
    int i=f[j-k-1];
    while(i>=0&&s[j]!=s[k+i+1]){
      if(s[j]<s[k+i+1]) k=j-i-1;
      i=f[i];
    }
    if(s[j]!=s[k+i+1]){
      if(s[j]<s[k])k=j;
      f[j-k]=-1;
    } else f[j-k]=i+1;
  }
  vi ans; fore(i,0,n) ans.pb(s[k+i]);
  return ans;
}
```

PalindromicTree.h

Description: Palindromic Tree (EERTREE) supporting online palindromic factorization and counts of distinct palindromic substrings.
Usage: `palindromic_tree pt;`
`for(int i = 0; i < n; ++i) pt.add(i, s);`
Time: $\mathcal{O}(N \log \Sigma)$ or $\mathcal{O}(N)$ for fixed alphabet.

714af6, 27 lines

```
struct palindromic_tree{
    static const int SIGMA=26;
    struct Node{
        int len, link, to[SIGMA];
        long long cnt;
        Node(int len, int link=0, long long cnt=1):len(len),
             link(link),cnt(cnt){
            memset(to,0,sizeof(to));
        }
    };
    vector<Node> ns;
    int last;
    palindromic_tree():last(0){ns.push_back(Node(-1));ns.
         push_back(Node(0));}
    void add(int i, string &s){
        int p=last, c=s[i]-'a';
        while(s[i-ns[p].len-1]!=s[i])p=ns[p].link;
        if(ns[p].to[c]){
            last=ns[p].to[c];
            ns[last].cnt++;
        }else{
            int q=ns[p].link;
            while(s[i-ns[q].len-1]!=s[i])q=ns[q].link;
            q=max(1,ns[q].to[c]);
            last=ns[p].to[c]=(int)(ns.size());
            ns.push_back(Node(ns[p].len+2,q,1));
        }
    }
};
```

SuffixArray.h

Description: Constructs the suffix array for a string using prefix doubling and counting sort.
Usage: `vector<int> sa = constructSA(s);`
Time: $\mathcal{O}(N \log N)$

a409a1, 26 lines

```
#define RB(x) (x<n?r[x]:0)
void csort(vector<int>& sa, vector<int>& r, int k){
  int n=sa.size();
  vector<int> f(max(255,n),0),t(n);
  fore(i,0,n)f[RB(i+k)]++;
  int sum=0;
  fore(i,0,max(255,n))f[i]=(sum+=f[i])-f[i];
  fore(i,0,n)t[f[RB(sa[i]+k)]++]=sa[i];
  sa=t;
}
vector<int> constructSA(string& s){ // O(n logn)
  int n=s.size(),rank;
  vector<int> sa(n),r(n),t(n);
  fore(i,0,n)sa[i]=i,r[i]=s[i];
  for(int k=1;k<n;k*=2){
    csort(sa,r,k);csort(sa,r,0);
    t[sa[0]]=rank=0;
    fore(i,1,n){
      if(r[sa[i]]!=r[sa[i-1]]||RB(sa[i]+k)!=RB(sa[i-1]+k))rank
          ++;
      t[sa[i]]=rank;
    }
    r=t;
    if(r[sa[n-1]]==n-1)break;
  }
  return sa;
}
```

SuffixArraySlow.h

Description: Simple suffix array construction.
Usage: `vector<int> sa = constructSA(s);`
Time: $\mathcal{O}\left(N \log^2 N\right)$

c9dbaf, 15 lines

```
const int MAXN = 1;
pair<int, int> sf[MAXN];
bool sacomp(int lhs, int rhs) {return sf[lhs]<sf[rhs];}
vector<int> constructSA(string& s){ // O(n log^2(n))
  int n=s.size();                   // (sometimes fast enough)
  vector<int> sa(n),r(n);
  for(int i = 0; i < n; ++i) r[i]=s[i];
  for(int m=1;m<n;m*=2){
    for(int i = 0; i < n; ++i) sa[i]=i,sf[i]={r[i],i+m<n?r[i+m
        ]:-1};
    stable_sort(sa.begin(),sa.end(),sacomp);
    r[sa[0]]=0;
    for(int i = 1; i < n; ++i) r[sa[i]]=sf[sa[i]]!=sf[sa[i-1]]?
        i:r[sa[i-1]];
  }
  return sa;
}
```

SuffixAutomaton.h

Description: Online Suffix Automaton (DAWG) building the minimal automaton recognizing all substrings of a text.
Usage: `sa_init();`
`for(char c : s) sa_extend(c);`
Time: $\mathcal{O}(N \log \Sigma)$

51e851, 25 lines

```
struct state {int len,link;map<char,int> next;}; //clear next!!
state st[100005];
int sz,last;
void sa_init(){
  last=st[0].len=0;sz=1;
  st[0].link=-1;
}
void sa_extend(char c){
  int k=sz++,p;
  st[k].len=st[last].len+1;
  for(p=last;p!=-1&&!st[p].next.count(c);p=st[p].link)st[p].
      next[c]=k;
  if(p==-1)st[k].link=0;
  else {
    int q=st[p].next[c];
    if(st[p].len+1==st[q].len)st[k].link=q;
    else {
      int w=sz++;
      st[w].len=st[p].len+1;
      st[w].next=st[q].next;st[w].link=st[q].link;
      for(;p!=-1&&st[p].next[c]==q;p=st[p].link)st[p].next[c]=w
          ;
      st[q].link=st[k].link=w;
    }
  }
  last=k;
}
```

SuffixTree.h

Description: Online Suffix Tree construction (Ukkonen's algorithm).
Usage: `SuffixTree st;`
`for(char c : s) st.add(c);`
Time: $\mathcal{O}(N \log \Sigma)$

384f5e, 40 lines

```
const int MAXN = 1e5;
int INF = 1e9;
struct SuffixTree {
  char s[MAXN];
  map<int,int> to[MAXN];
  int len[MAXN]={INF},fpos[MAXN],link[MAXN];
  int node,pos,sz=1,n=0;
  int make_node(int p, int l){
    fpos[sz]=p;len[sz]=l;return sz++;}
  void go_edge(){
    while(pos>len[to[node][s[n-pos]]]){
      node=to[node][s[n-pos]];
      pos-=len[node];
    }
  }
  void add(int c){
    s[n++]=c;pos++;
```

```
    int last=0;
    while(pos>0){
      go_edge();
      int edge=s[n-pos];
      int& v=to[node][edge];
      int t=s[fpos[v]+pos-1];
      if(v==0){
        v=make_node(n-pos,INF);
        link[last]=node;last=0;
      }
      else if(t==c){link[last]=node;return;}
      else {
        int u=make_node(fpos[v],pos-1);
        to[u][c]=make_node(n-1,INF);
        to[u][t]=v;
        fpos[v]+=pos-1;len[v]-=pos-1;
        v=u;link[last]=u;last=u;
      }
      if(node==0)pos--;
      else node=link[node];
    }
  }
};
```

Zfunc.h

Description: Computes the Z-function where $Z[i]$ is the length of the longest common prefix between s and $s[i \dots n-1]$.
Usage: `vector<int> z = z_function(s);`
Time: $\mathcal{O}(N)$

233b5c, 10 lines

```
vector<int> z_function(string& s){
  int l=0,r=0,n=s.size();
  vector<int> z(s.size(),0); // z[i] = max k: s[0,k) == s[i,i+k)
  for(int i = 1; i < n; ++i){
    if(i<=r)z[i]=min(r-i+1,z[i-l]);
    while(i+z[i]<n&&s[z[i]]==s[i+z[i]])z[i]++;
    if(i+z[i]-1>r)l=i,r=i+z[i]-1;
  }
  return z;
}
```

Mathematics (4)

4.1 Equations

$$ax^2+bx+c=0 \Rightarrow x=\frac{-b\pm\sqrt{b^2-4ac}}{2a}$$

The extremum is given by $x=-b/2a$.

$$\begin{aligned} ax+by&=e \\ cx+dy&=f \end{aligned} \Rightarrow \begin{aligned} x&=\frac{ed-bf}{ad-bc} \\ y&=\frac{af-ec}{ad-bc} \end{aligned}$$

In general, given an equation $Ax=b$, the solution to a variable x_i is given by

$$x_i=\frac{\det A_i'}{\det A}$$

where A_i' is A with the i'th column replaced by b.

4.2 Recurrences

If $a_n=c_1a_{n-1}+\cdots+c_ka_{n-k}$, and $r_1,\dots,r_k$ are distinct roots of $x^k-c_1x^{k-1}-\cdots-c_k$, there are $d_1,\dots,d_k$ s.t.

$$a_n=d_1r_1^n+\cdots+d_kr_k^n.$$

Non-distinct roots r become polynomial factors, e.g. $a_n=(d_1n+d_2)r^n$.

4.3 Trigonometry

$$\sin(v+w)=\sin v\cos w+\cos v\sin w$$
$$\cos(v+w)=\cos v\cos w-\sin v\sin w$$

$$\tan(v+w)=\frac{\tan v+\tan w}{1-\tan v\tan w}$$
$$\sin v+\sin w=2\sin\frac{v+w}{2}\cos\frac{v-w}{2}$$
$$\cos v+\cos w=2\cos\frac{v+w}{2}\cos\frac{v-w}{2}$$

$$(V+W)\tan(v-w)/2=(V-W)\tan(v+w)/2$$

where V,W are lengths of sides opposite angles v,w.

$$a\cos x+b\sin x=r\cos(x-\phi)$$
$$a\sin x+b\cos x=r\sin(x+\phi)$$

where $r=\sqrt{a^2+b^2}, \phi=\operatorname{atan2}(b,a)$.

4.4 Geometry

4.4.1 Triangles

Side lengths: a,b,c

Semiperimeter: $p=\frac{a+b+c}{2}$

Area: $A=\sqrt{p(p-a)(p-b)(p-c)}$

Circumradius: $R=\frac{abc}{4A}$

Inradius: $r=\frac{A}{p}$

Length of median (divides triangle into two equal-area triangles): $m_a=\frac{1}{2}\sqrt{2b^2+2c^2-a^2}$

Length of bisector (divides angles in two):

$$s_a=\sqrt{bc\left[1-\left(\frac{a}{b+c}\right)^2\right]}$$

Law of sines: $\frac{\sin\alpha}{a}=\frac{\sin\beta}{b}=\frac{\sin\gamma}{c}=\frac{1}{2R}$

Law of cosines: $a^2=b^2+c^2-2bc\cos\alpha$

Law of tangents: $\frac{a+b}{a-b}=\frac{\tan\frac{\alpha+\beta}{2}}{\tan\frac{\alpha-\beta}{2}}$


4.4.2 Quadrilaterals

With side lengths a,b,c,d, diagonals e,f, diagonals angle θ, area A and magic flux $F=b^2+d^2-a^2-c^2$:

$$4A=2ef\cdot\sin\theta=F\tan\theta=\sqrt{4e^2f^2-F^2}$$

For cyclic quadrilaterals the sum of opposite angles is $180°$, $ef=ac+bd$, and $A=\sqrt{(p-a)(p-b)(p-c)(p-d)}$.

4.4.3 Spherical coordinates



$$\begin{aligned} x&=r\sin\theta\cos\phi & r&=\sqrt{x^2+y^2+z^2} \\ y&=r\sin\theta\sin\phi & \theta&=\operatorname{acos}(z/\sqrt{x^2+y^2+z^2}) \\ z&=r\cos\theta & \phi&=\operatorname{atan2}(y,x) \end{aligned}$$

4.5 Derivatives/Integrals

$$\frac{d}{dx}\arcsin x=\frac{1}{\sqrt{1-x^2}} \qquad \frac{d}{dx}\arccos x=-\frac{1}{\sqrt{1-x^2}}$$
$$\frac{d}{dx}\tan x=1+\tan^2 x \qquad \frac{d}{dx}\arctan x=\frac{1}{1+x^2}$$
$$\int\tan ax=-\frac{\ln|\cos ax|}{a} \qquad \int x\sin ax=\frac{\sin ax-ax\cos ax}{a^2}$$
$$\int e^{-x^2}=\frac{\sqrt{\pi}}{2}\operatorname{erf}(x) \qquad \int xe^{ax}dx=\frac{e^{ax}}{a^2}(ax-1)$$

Integration by parts:

$$\int_a^b f(x)g(x)dx=[F(x)g(x)]_a^b-\int_a^b F(x)g'(x)dx$$

4.6 Sums

$$c^a+c^{a+1}+\cdots+c^b=\frac{c^{b+1}-c^a}{c-1}, c\neq 1$$

$$1+2+3+\cdots+n=\frac{n(n+1)}{2}$$
$$1^2+2^2+3^2+\cdots+n^2=\frac{n(2n+1)(n+1)}{6}$$
$$1^3+2^3+3^3+\cdots+n^3=\frac{n^2(n+1)^2}{4}$$
$$1^4+2^4+3^4+\cdots+n^4=\frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$$

4.7 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \ldots, (-\infty < x < \infty)$$

$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \ldots, (-1 < x \leq 1)$$

$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \ldots, (-1 \leq x \leq 1)$$

$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \ldots, (-\infty < x < \infty)$$

$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \ldots, (-\infty < x < \infty)$$

4.8 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x. It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

4.8.1 Discrete distributions

Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is $\mathrm{Bin}(n, p)$, $n = 1, 2, \ldots, 0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np,\ \sigma^2 = np(1-p)$$

$\mathrm{Bin}(n, p)$ is approximately $\mathrm{Po}(np)$ for small p.

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\mathrm{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1},\ k = 1, 2, \ldots$$

$$\mu = \frac{1}{p},\ \sigma^2 = \frac{1-p}{p^2}$$

Poisson distribution

The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\mathrm{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda}\frac{\lambda^k}{k!}, k = 0, 1, 2, \ldots$$

$$\mu = \lambda,\ \sigma^2 = \lambda$$

4.8.2 Continuous distributions

Uniform distribution

If the probability density function is constant between a and b and 0 elsewhere it is $\mathrm{U}(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2},\ \sigma^2 = \frac{(b-a)^2}{12}$$

Exponential distribution

The time between events in a Poisson process is $\mathrm{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda},\ \sigma^2 = \frac{1}{\lambda^2}$$

Normal distribution

Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

4.9 Markov chains

A *Markov chain* is a discrete random process with the property that the next state depends only on the current state. Let $X_1, X_2, \ldots$ be a sequence of random variables generated by the Markov process. Then there is a transition matrix $\mathbf{P} = (p_{ij})$, with $p_{ij} = \Pr(X_n = i | X_{n-1} = j)$, and $\mathbf{p}^{(n)} = \mathbf{P}^n\mathbf{p}^{(0)}$ is the probability distribution for X_n (i.e., $p_i^{(n)} = \Pr(X_n = i)$), where $\mathbf{p}^{(0)}$ is the initial distribution.

π is a stationary distribution if $\pi = \pi\mathbf{P}$. If the Markov chain is *irreducible* (it is possible to get to any state from any state), then $\pi_i = \frac{1}{\mathbb{E}(T_i)}$ where $\mathbb{E}(T_i)$ is the expected time between two visits in state i. π_j/π_i is the expected number of visits in state j between two visits in state i.

For a connected, undirected and non-bipartite graph, where the transition probability is uniform among all neighbors, π_i is proportional to node i's degree.

A Markov chain is *ergodic* if the asymptotic distribution is independent of the initial distribution. A finite Markov chain is ergodic iff it is irreducible and *aperiodic* (i.e., the gcd of cycle lengths is 1). $\lim_{k\to\infty} \mathbf{P}^k = \mathbf{1}\pi$.

A Markov chain is an A-chain if the states can be partitioned into two sets $\mathbf{A}$ and $\mathbf{G}$, such that all states in $\mathbf{A}$ are absorbing ($p_{ii} = 1$), and all states in $\mathbf{G}$ leads to an absorbing state in $\mathbf{A}$. The probability for absorption in state $i \in \mathbf{A}$, when the initial state is j, is $a_{ij} = p_{ij} + \sum_{k\in\mathbf{G}} a_{ik}p_{kj}$. The expected time until absorption, when the initial state is i, is $t_i = 1 + \sum_{k\in\mathbf{G}} p_{ki}t_k$.

Numerical (5)

5.1 Polynomials and recurrences

Polynomial.h

c9b7b0, 17 lines

```
struct Poly {
  vector<double> a;
  double operator()(double x) const {
    double val = 0;
    for (int i = sz(a); i--;) (val *= x) += a[i];
    return val;
  }
  void diff() {
    rep(i,1,sz(a)) a[i-1] = i*a[i];
    a.pop_back();
  }
  void divroot(double x0) {
    double b = a.back(), c; a.back() = 0;
    for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
    a.pop_back();
  }
};
```

PolyRoots.h

Description: Finds the real roots to a polynomial.
Usage: `polyRoots({{2,-3,1}},-1e9,1e9) // solve x^2-3x+2 = 0`
Time: $\mathcal{O}\left(n^2 \log(1/\epsilon)\right)$

"Polynomial.h"

b00bfe, 23 lines

```
vector<double> polyRoots(Poly p, double xmin, double xmax) {
  if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
  vector<double> ret;
  Poly der = p;
  der.diff();
  auto dr = polyRoots(der, xmin, xmax);
  dr.push_back(xmin-1);
  dr.push_back(xmax+1);
  sort(all(dr));
  rep(i,0,sz(dr)-1) {
    double l = dr[i], h = dr[i+1];
    bool sign = p(l) > 0;
    if (sign ^ (p(h) > 0)) {
      rep(it,0,60) { // while (h - l > 1e-8)
        double m = (l + h) / 2, f = p(m);
        if ((f <= 0) ^ sign) l = m;
        else h = m;
      }
```

```
      ret.push_back((l + h) / 2);
    }
  }
  return ret;
}
```

PolyInterpolate.h

Description: Given n points (x[i], y[i]), computes an n-1-degree polynomial p that passes through them: $p(x) = a[0] * x^0 + ... + a[n-1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$.
Time: $\mathcal{O}(n^2)$

08bf48, 13 lines

```
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
  vd res(n), temp(n);
  rep(k,0,n-1) rep(i,k+1,n)
    y[i] = (y[i] - y[k]) / (x[i] - x[k]);
  double last = 0; temp[0] = 1;
  rep(k,0,n) rep(i,0,n) {
    res[i] += y[k] * temp[i];
    swap(last, temp[i]);
    temp[i] -= last * x[k];
  }
  return res;
}
```

BerlekampMassey.h

Description: Recovers any n-order linear recurrence relation from the first $2n$ terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size $\leq n$.
Usage: `berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}`
Time: $\mathcal{O}(N^2)$

"../number-theory/ModPow.h" 96548b, 20 lines

```
vector<ll> berlekampMassey(vector<ll> s) {
  int n = sz(s), L = 0, m = 0;
  vector<ll> C(n), B(n), T;
  C[0] = B[0] = 1;

  ll b = 1;
  rep(i,0,n) { ++m;
    ll d = s[i] % mod;
    rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
    if (!d) continue;
    T = C; ll coef = d * modpow(b, mod-2) % mod;
    rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
    if (2 * L > i) continue;
    L = i + 1 - L; B = T; b = d; m = 0;
  }

  C.resize(L + 1); C.erase(C.begin());
  for (ll& x : C) x = (mod - x) % mod;
  return C;
}
```

LinearRecurrence.h

Description: Generates the k'th term of an n-order linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$, given $S[0 \dots \geq n-1]$ and $tr[0 \dots n-1]$. Faster than matrix multiplication. Useful together with Berlekamp–Massey.
Usage: `linearRec({0, 1}, {1, 1}, k) // k'th Fibonacci number`
Time: $\mathcal{O}(n^2 \log k)$

f4e444, 26 lines

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
  int n = sz(tr);

  auto combine = [&](Poly a, Poly b) {
    Poly res(n * 2 + 1);
    rep(i,0,n+1) rep(j,0,n+1)
      res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
    for (int i = 2 * n; i > n; --i) rep(j,0,n)
      res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
    res.resize(n + 1);
    return res;
  };

  Poly pol(n + 1), e(pol);
  pol[0] = e[1] = 1;

  for (++k; k; k /= 2) {
    if (k % 2) pol = combine(pol, e);
    e = combine(e, e);
  }

  ll res = 0;
  rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
  return res;
}
```

5.2 Optimization

GoldenSectionSearch.h

Description: Finds the argument minimizing the function f in the interval $[a, b]$ assuming f is unimodal on the interval, i.e. has only one local minimum and no local maximum. The maximum error in the result is eps. Works equally well for maximization with a small change in the code. See TernarySearch.h in the Various chapter for a discrete version.
Usage: `double func(double x) { return 4+x+.3*x*x; }`
`double xmin = gss(-1000,1000,func);`
Time: $\mathcal{O}(\log((b-a)/\epsilon))$

31d45b, 14 lines

```
double gss(double a, double b, double (*f)(double)) {
  double r = (sqrt(5)-1)/2, eps = 1e-7;
  double x1 = b - r*(b-a), x2 = a + r*(b-a);
  double f1 = f(x1), f2 = f(x2);
  while (b-a > eps)
    if (f1 < f2) { //change to > to find maximum
      b = x2; x2 = x1; f2 = f1;
      x1 = b - r*(b-a); f1 = f(x1);
    } else {
      a = x1; x1 = x2; f1 = f2;
      x2 = a + r*(b-a); f2 = f(x2);
    }
  return a;
}
```

HillClimbing.h

Description: Poor man's optimization for unimodal functions.

8eeeaf, 14 lines

```
typedef array<double, 2> P;

template<class F> pair<double, P> hillClimb(P start, F f) {
  pair<double, P> cur(f(start), start);
  for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
    rep(j,0,100) rep(dx,-1,2) rep(dy,-1,2) {
      P p = cur.second;
      p[0] += dx*jmp;
      p[1] += dy*jmp;
      cur = min(cur, make_pair(f(p), p));
    }
  }
  return cur;
}
```

Integrate.h

Description: Simple integration of a function over an interval using Simpson's rule. The error should be proportional to h^4, although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

4756fc, 7 lines

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
  double h = (b - a) / 2 / n, v = f(a) + f(b);
  rep(i,1,n*2)
    v += f(a + i*h) * (i&1 ? 4 : 2);
  return v * h / 3;
}
```

IntegrateAdaptive.h

Description: Fast integration using an adaptive Simpson's rule.
Usage: `double sphereVolume = quad(-1, 1, [](double x) {`
`return quad(-1, 1, [&](double y) {`
`return quad(-1, 1, [&](double z) {`
`return x*x + y*y + z*z < 1; });});});`

92dd79, 15 lines

```
typedef double d;
#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6

template <class F>
d rec(F& f, d a, d b, d eps, d S) {
  d c = (a + b) / 2;
  d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
  if (abs(T - S) <= 15 * eps || b - a < 1e-10)
    return T + (T - S) / 15;
  return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2, S2);
}
template<class F>
d quad(d a, d b, F f, d eps = 1e-8) {
  return rec(f, a, b, eps, S(a, b));
}
```

Simplex.h

Description: Solves a general linear maximization problem: maximize $c^T x$ subject to $Ax \leq b$, $x \geq 0$. Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of $c^T x$ otherwise. The input vector is set to an optimal x (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that $x = 0$ is viable.
Usage: `vvd A = {{1,-1}, {-1,1}, {-1,-2}};`
`vd b = {1,1,-4}, c = {-1,-1}, x;`
`T val = LPSolver(A, b, c).solve(x);`
Time: $\mathcal{O}(NM * \#pivots)$, where a pivot may be e.g. an edge relaxation. $\mathcal{O}(2^n)$ in the general case.

aa8530, 68 lines

```
typedef double T; // long double, Rational, double + mod<P>...
typedef vector<T> vd;
typedef vector<vd> vvd;

const T eps = 1e-8, inf = 1/.0;
#define MP make_pair
#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j

struct LPSolver {
  int m, n;
  vi N, B;
  vvd D;

  LPSolver(const vvd& A, const vd& b, const vd& c) :
    m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
      rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
      rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i];}
      rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
      N[n] = -1; D[m+1][n] = 1;
    }
```

```
  void pivot(int r, int s) {
    T *a = D[r].data(), inv = 1 / a[s];
    rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
      T *b = D[i].data(), inv2 = b[s] * inv;
      rep(j,0,n+2) b[j] -= a[j] * inv2;
      b[s] = a[s] * inv2;
    }
    rep(j,0,n+2) if (j != s) D[r][j] *= inv;
    rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
    D[r][s] = inv;
    swap(B[r], N[s]);
  }

  bool simplex(int phase) {
    int x = m + phase - 1;
    for (;;) {
      int s = -1;
      rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
      if (D[x][s] >= -eps) return true;
      int r = -1;
      rep(i,0,m) {
        if (D[i][s] <= eps) continue;
        if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
                     < MP(D[r][n+1] / D[r][s], B[r])) r = i;
      }
      if (r == -1) return false;
      pivot(r, s);
    }
  }

  T solve(vd &x) {
    int r = 0;
    rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
    if (D[r][n+1] < -eps) {
      pivot(r, n);
      if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
      rep(i,0,m) if (B[i] == -1) {
        int s = 0;
        rep(j,1,n+1) ltj(D[i]);
        pivot(i, s);
      }
    }
    bool ok = simplex(1); x = vd(n);
    rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
    return ok ? D[m][n+1] : inf;
  }
};
```

5.3 Matrices

Determinant.h

Description: Calculates determinant of a matrix. Destroys the matrix.
Time: $\mathcal{O}\left(N^3\right)$

bd5cec, 15 lines

```
double det(vector<vector<double>>& a) {
  int n = sz(a); double res = 1;
  rep(i,0,n) {
    int b = i;
    rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
    if (i != b) swap(a[i], a[b]), res *= -1;
    res *= a[i][i];
    if (res == 0) return 0;
    rep(j,i+1,n) {
      double v = a[j][i] / a[i][i];
      if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
    }
  }
  return res;
}
```

IntDeterminant.h

Description: Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.
Time: $\mathcal{O}\left(N^3\right)$

3313dc, 18 lines

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
  int n = sz(a); ll ans = 1;
  rep(i,0,n) {
    rep(j,i+1,n) {
      while (a[j][i] != 0) { // gcd step
        ll t = a[i][i] / a[j][i];
        if (t) rep(k,i,n)
          a[i][k] = (a[i][k] - a[j][k] * t) % mod;
        swap(a[i], a[j]);
        ans *= -1;
      }
    }
    ans = ans * a[i][i] % mod;
    if (!ans) return 0;
  }
  return (ans + mod) % mod;
}
```

SolveLinear.h

Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost.
Time: $\mathcal{O}\left(n^2m\right)$

44c9ab, 38 lines

```
typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd>& A, vd& b, vd& x) {
  int n = sz(A), m = sz(x), rank = 0, br, bc;
  if (n) assert(sz(A[0]) == m);
  vi col(m); iota(all(col), 0);

  rep(i,0,n) {
    double v, bv = 0;
    rep(r,i,n) rep(c,i,m)
      if ((v = fabs(A[r][c])) > bv)
        br = r, bc = c, bv = v;
    if (bv <= eps) {
      rep(j,i,n) if (fabs(b[j]) > eps) return -1;
      break;
    }
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) swap(A[j][i], A[j][bc]);
    bv = 1/A[i][i];
    rep(j,i+1,n) {
      double fac = A[j][i] * bv;
      b[j] -= fac * b[i];
      rep(k,i+1,m) A[j][k] -= fac*A[i][k];
    }
    rank++;
  }

  x.assign(m, 0);
  for (int i = rank; i--;) {
    b[i] /= A[i][i];
    x[col[i]] = b[i];
    rep(j,0,i) b[j] -= A[j][i] * b[i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

SolveLinear2.h

Description: To get all uniquely determined values of x back from SolveLinear, make the following changes:

"SolveLinear.h" 08e495, 7 lines

```
rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
  rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
  x[col[i]] = b[i] / A[i][i];
fail:; }
```

SolveLinearBinary.h

Description: Solves $Ax = b$ over $\mathbb{F}_2$. If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys A and b.
Time: $\mathcal{O}\left(n^2m\right)$

fa2d7a, 34 lines

```
typedef bitset<1000> bs;

int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
  int n = sz(A), rank = 0, br;
  assert(m <= sz(x));
  vi col(m); iota(all(col), 0);
  rep(i,0,n) {
    for (br=i; br<n; ++br) if (A[br].any()) break;
    if (br == n) {
      rep(j,i,n) if(b[j]) return -1;
      break;
    }
    int bc = (int)A[br]._Find_next(i-1);
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) if (A[j][i] != A[j][bc]) {
      A[j].flip(i); A[j].flip(bc);
    }
    rep(j,i+1,n) if (A[j][i]) {
      b[j] ^= b[i];
      A[j] ^= A[i];
    }
    rank++;
  }

  x = bs();
  for (int i = rank; i--;) {
    if (!b[i]) continue;
    x[col[i]] = 1;
    rep(j,0,i) b[j] ^= A[j][i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

MatrixInverse.h

Description: Invert matrix A. Returns rank; result is stored in A unless singular (rank $<$ n). Can easily be extended to prime moduli; for prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1})$ (mod p^k) where A^{-1} starts as the inverse of A mod p, and k is doubled in each step.
Time: $\mathcal{O}\left(n^3\right)$

ebfff6, 35 lines

```
int matInv(vector<vector<double>>& A) {
  int n = sz(A); vi col(n);
  vector<vector<double>> tmp(n, vector<double>(n));
  rep(i,0,n) tmp[i][i] = 1, col[i] = i;

  rep(i,0,n) {
    int r = i, c = i;
    rep(j,i,n) rep(k,i,n)
      if (fabs(A[j][k]) > fabs(A[r][c]))
        r = j, c = k;
```

```
    if (fabs(A[r][c]) < 1e-12) return i;
    A[i].swap(A[r]); tmp[i].swap(tmp[r]);
    rep(j,0,n)
      swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
    swap(col[i], col[c]);
    double v = A[i][i];
    rep(j,i+1,n) {
      double f = A[j][i] / v;
      A[j][i] = 0;
      rep(k,i+1,n) A[j][k] -= f*A[i][k];
      rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
    }
    rep(j,i+1,n) A[i][j] /= v;
    rep(j,0,n) tmp[i][j] /= v;
    A[i][i] = 1;
  }

  for (int i = n-1; i > 0; --i) rep(j,0,i) {
    double v = A[j][i];
    rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
  }

  rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
  return n;
}
```

Tridiagonal.h

Description: $x = \text{tridiagonal}(d, p, q, b)$ solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & 0 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}.$$

This is useful for solving problems on the type

$$a_i = b_i a_{i-1} + c_i a_{i+1} + d_i,\ 1 \le i \le n,$$

where a_0, a_{n+1}, b_i, c_i and d_i are known. a can then be obtained from

$$\{a_i\} = \text{tridiagonal}(\{1, -1, -1, ..., -1, 1\}, \{0, c_1, c_2, \ldots, c_n\}, \{b_1, b_2, \ldots, b_n, 0\}, \{a_0, d_1, d_2, \ldots, d_n, a_{n+1}\}).$$

Fails if the solution is not unique.
If $|d_i| > |p_i| + |q_{i-1}|$ for all i, or $|d_i| > |p_{i-1}| + |q_i|$, or the matrix is positive definite, the algorithm is numerically stable and neither `tr` nor the check for `diag[i] == 0` is needed.
Time: $\mathcal{O}(N)$

8f9fa8, 26 lines

```
typedef double T;
vector<T> tridiagonal(vector<T> diag, const vector<T>& super,
    const vector<T>& sub, vector<T> b) {
  int n = sz(b); vi tr(n);
  rep(i,0,n-1) {
    if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] == 0
      b[i+1] -= b[i] * diag[i+1] / super[i];
      if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i];
      diag[i+1] = sub[i]; tr[++i] = 1;
    } else {
      diag[i+1] -= super[i]*sub[i]/diag[i];
      b[i+1] -= b[i]*sub[i]/diag[i];
    }
  }
  for (int i = n; i--;) {
    if (tr[i]) {
      swap(b[i], b[i-1]);
      diag[i-1] = diag[i];
      b[i] /= super[i-1];
    } else {
      b[i] /= diag[i];
      if (i) b[i-1] -= b[i]*super[i-1];
    }
  }
  return b;
}
```

5.4 Fourier transforms

FastFourierTransform.h

Description: fft(a) computes $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$ for all k. N must be a power of 2. Useful for convolution: `conv(a, b) = c`, where $c[x] = \sum a[i]b[x-i]$. For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by n, reverse(start+1, end), FFT back. Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice 10^{16}; higher for random inputs). Otherwise, use NTT/FFTMod.
Time: $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ ($\sim 1s$ for $N = 2^{22}$)

00ced6, 35 lines

```
typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vector<complex<long double>> R(2, 1);
  static vector<C> rt(2, 1);  // (^ 10% faster if double)
  for (static int k = 2; k < n; k *= 2) {
    R.resize(n); rt.resize(n);
    auto x = polar(1.0L, acos(-1.0L) / k);
    rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-rolled)
      a[i + j + k] = a[i + j] - z;
      a[i + j] += z;
    }
}
vd conv(const vd& a, const vd& b) {
  if (a.empty() || b.empty()) return {};
  vd res(sz(a) + sz(b) - 1);
  int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
  vector<C> in(n), out(n);
  copy(all(a), begin(in));
  rep(i,0,sz(b)) in[i].imag(b[i]);
  fft(in);
  for (C& x : in) x *= x;
  rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
  fft(out);
  rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
  return res;
}
```

FastFourierTransformMod.h

Description: Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice 10^{16} or higher). Inputs must be in $[0, \text{mod})$.
Time: $\mathcal{O}(N \log N)$, where $N = |A| + |B|$ (twice as slow as NTT or FFT)

"FastFourierTransform.h" b82773, 22 lines

```
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  vl res(sz(a) + sz(b) - 1);
  int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt(M));
  vector<C> L(n), R(n), outs(n), outl(n);
  rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
  rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
  fft(L), fft(R);
  rep(i,0,n) {
    int j = -i & (n - 1);
    outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
    outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
  }
  fft(outl), fft(outs);
  rep(i,0,sz(res)) {
    ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
    ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
    res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
  }
  return res;
}
```

NumberTheoreticTransform.h

Description: ntt(a) computes $\hat{f}(k) = \sum_x a[x] g^{xk}$ for all k, where $g = \text{root}^{(mod-1)/N}$. N must be a power of 2. Useful for convolution modulo specific nice primes of the form $2^a b + 1$, where the convolution result has size at most 2^a. For arbitrary modulo, see FFTMod. `conv(a, b) = c`, where $c[x] = \sum a[i]b[x-i]$. For manual convolution: NTT the inputs, multiply pointwise, divide by n, reverse(start+1, end), NTT back. Inputs must be in $[0, \text{mod})$.
Time: $\mathcal{O}(N \log N)$

"../number-theory/ModPow.h" ced03d, 35 lines

```
const ll mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
typedef vector<ll> vl;
void ntt(vl &a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vl rt(2, 1);
  for (static int k = 2, s = 2; k < n; k *= 2, s++) {
    rt.resize(n);
    ll z[] = {1, modpow(root, mod >> s)};
    rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
      a[i + j + k] = ai - z + (z > ai ? mod : 0);
      ai += (ai + z >= mod ? z - mod : z);
    }
}
vl conv(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
      n = 1 << B;
  int inv = modpow(n, mod - 2);
  vl L(a), R(b), out(n);
  L.resize(n), R.resize(n);
  ntt(L), ntt(R);
  rep(i,0,n)
    out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
  ntt(out);
  return {out.begin(), out.begin() + s};
}
```

FastSubsetTransform.h

Description: Transform to a basis with fast convolutions of the form $c[z] = \sum_{z=x \oplus y} a[x] \cdot b[y]$, where $\oplus$ is one of AND, OR, XOR. The size of a must be a power of two.
Time: $\mathcal{O}(N \log N)$

464cf3, 16 lines

```
void FST(vi& a, bool inv) {
  for (int n = sz(a), step = 1; step < n; step *= 2) {
```

```
    for (int i = 0; i < n; i += 2 * step) rep(j,i,i+step) {
      int &u = a[j], &v = a[j + step]; tie(u, v) =
        inv ? pii(v - u, u) : pii(v, u + v); // AND
        inv ? pii(v, u - v) : pii(u + v, u); // OR
        pii(u + v, u - v);                   // XOR
    }
  }
  if (inv) for (int& x : a) x /= sz(a); // XOR only
}
vi conv(vi a, vi b) {
  FST(a, 0); FST(b, 0);
  rep(i,0,sz(a)) a[i] *= b[i];
  FST(a, 1); return a;
}
```

Number theory (6)

6.1 Modular arithmetic

ModularArithmetic.h

Description: Operators for modular arithmetic. You need to set `mod` to some number first and then you can use the structure.

`"euclid.h"` ea1ac7, 19 lines

```
const ll mod = 17; // change to something else
struct Mod {
  ll x;
  Mod(ll y) : Mod(y%mod+mod,0){}
  Mod(ll y,int) : x(y<mod?y:y-mod){}
  Mod operator+(Mod b) { return {x + b.x,0}; }
  Mod operator-(Mod b) { return {x - b.x + mod,0}; }
  Mod operator*(Mod b) { return {x * b.x % mod,0}; }
  Mod operator/(Mod b) { return *this * invert(b); }
  Mod invert(Mod a) {
    ll x, y, g = euclid(a.x, mod, x, y);
    assert(g == 1); return x;
  }
  Mod operator^(ll e) {
    if (!e) return 1;
    Mod r = *this ^ (e / 2); r = r * r;
    return e&1 ? *this * r : r;
  }
};
```

ModInverse.h

Description: Pre-computation of modular inverses. Assumes LIM $\leq$ mod and that mod is a prime.

6f684f, 3 lines

```
const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
rep(i,2,LIM) inv[i] = mod - (mod / i) * inv[mod % i] % mod;
```

ModPow.h

b83e45, 8 lines

```
const ll mod = 1000000007; // faster if const

ll modpow(ll b, ll e) {
  ll ans = 1;
  for (; e; b = b * b % mod, e /= 2)
    if (e & 1) ans = ans * b % mod;
  return ans;
}
```

ModLog.h

Description: Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or -1 if no such x exists. modLog(a,1,m) can be used to calculate the order of a.
Time: $\mathcal{O}\left(\sqrt{m}\right)$

c040b8, 11 lines

```
ll modLog(ll a, ll b, ll m) {
  ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
  unordered_map<ll, ll> A;
  while (j <= n && (e = f = e * a % m) != b % m)
    A[e * b % m] = j++;
  if (e == b % m) return j;
  if (__gcd(m, e) == __gcd(m, b))
    rep(i,2,n+2) if (A.count(e = e * f % m))
      return n * i - A[e];
  return -1;
}
```

ModSum.h

Description: Sums of mod'ed arithmetic progressions.
`modsum(to, c, k, m)` $= \sum_{i=0}^{to-1} (ki + c)\%m$. `divsum` is similar but for floored division.
Time: $\log(m)$, with a large constant.

5c5bc5, 16 lines

```
typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }

ull divsum(ull to, ull c, ull k, ull m) {
  ull res = k / m * sumsq(to) + c / m * to;
  k %= m; c %= m;
  if (!k) return res;
  ull to2 = (to * k + c) / m;
  return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
}

ll modsum(ull to, ll c, ll k, ll m) {
  c = ((c % m) + m) % m;
  k = ((k % m) + m) % m;
  return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}
```

ModMulLL.h

Description: Calculate $a \cdot b \bmod c$ (or $a^b \bmod c$) for $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$.
Time: $\mathcal{O}(1)$ for `modmul`, $\mathcal{O}(\log b)$ for `modpow`

bbbd8f, 11 lines

```
typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
  ll ret = a * b - M * ull(1.L / M * a * b);
  return ret + M * (ret < 0) - M * (ret >= (ll)M);
}
ull modpow(ull b, ull e, ull mod) {
  ull ans = 1;
  for (; e; b = modmul(b, b, mod), e /= 2)
    if (e & 1) ans = modmul(ans, b, mod);
  return ans;
}
```

ModSqrt.h

Description: Tonelli-Shanks algorithm for modular square roots. Finds x s.t. $x^2 = a \pmod p$ ($-x$ gives the other solution).
Time: $\mathcal{O}\left(\log^2 p\right)$ worst case, $\mathcal{O}(\log p)$ for most p

`"ModPow.h"` 19a793, 24 lines

```
ll sqrt(ll a, ll p) {
  a %= p; if (a < 0) a += p;
  if (a == 0) return 0;
  assert(modpow(a, (p-1)/2, p) == 1); // else no solution
  if (p % 4 == 3) return modpow(a, (p+1)/4, p);
  // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
  ll s = p - 1, n = 2;
  int r = 0, m;
  while (s % 2 == 0)
    ++r, s /= 2;
  while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
  ll x = modpow(a, (s + 1) / 2, p);
  ll b = modpow(a, s, p), g = modpow(n, s, p);
  for (;; r = m) {
    ll t = b;
    for (m = 0; m < r && t != 1; ++m)
      t = t * t % p;
    if (m == 0) return x;
    ll gs = modpow(g, 1LL << (r - m - 1), p);
    g = gs * gs % p;
    x = x * gs % p;
    b = b * g % p;
  }
}
```

6.2 Primality

FastEratosthenes.h

Description: Prime sieve for generating all primes smaller than LIM.
Time: LIM=1e9 $\approx$ 1.5s

6b2912, 20 lines

```
const int LIM = 1e6;
bitset<LIM> isPrime;
vi eratosthenes() {
  const int S = (int)round(sqrt(LIM)), R = LIM / 2;
  vi pr = {2}, sieve(S+1); pr.reserve(int(LIM/log(LIM)*1.1));
  vector<pii> cp;
  for (int i = 3; i <= S; i += 2) if (!sieve[i]) {
    cp.push_back({i, i * i / 2});
    for (int j = i * i; j <= S; j += 2 * i) sieve[j] = 1;
  }
  for (int L = 1; L <= R; L += S) {
    array<bool, S> block{};
    for (auto &[p, idx] : cp)
      for (int i=idx; i < S+L; idx = (i+=p)) block[i-L] = 1;
    rep(i,0,min(S, R - L))
      if (!block[i]) pr.push_back((L + i) * 2 + 1);
  }
  for (int i : pr) isPrime[i] = 1;
  return pr;
}
```

MillerRabin.h

Description: Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to $7 \cdot 10^{18}$; for larger numbers, use Python and extend A randomly.
Time: 7 times the complexity of $a^b \mod c$.

`"ModMulLL.h"` 60dcd1, 12 lines

```
bool isPrime(ull n) {
  if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
  ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
      s = __builtin_ctzll(n-1), d = n >> s;
  for (ull a : A) {   // ^ count trailing zeroes
    ull p = modpow(a%n, d, n), i = s;
    while (p != 1 && p != n - 1 && a % n && i--)
      p = modmul(p, p, n);
    if (p != n-1 && i != s) return 0;
  }
  return 1;
}
```

Factor.h

Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).
Time: $\mathcal{O}\left(n^{1/4}\right)$, less for numbers with small factors.

`"ModMulLL.h", "MillerRabin.h"` d8d98d, 18 lines

```
ull pollard(ull n) {
  ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
  auto f = [&](ull x) { return modmul(x, x, n) + i; };
  while (t++ % 40 || __gcd(prd, n) == 1) {
    if (x == y) x = ++i, y = f(x);
    if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;
```

```
    x = f(x), y = f(f(y));
  }
  return __gcd(prd, n);
}
vector<ull> factor(ull n) {
  if (n == 1) return {};
  if (isPrime(n)) return {n};
  ull x = pollard(n);
  auto l = factor(x), r = factor(n / x);
  l.insert(l.end(), all(r));
  return l;
}
```

6.3 Divisibility

euclid.h

Description: Finds two integers x and y, such that $ax + by = \gcd(a, b)$. If you just need gcd, use the built in __gcd instead. If a and b are coprime, then x is the inverse of $a \pmod b$.

33ba8f, 5 lines

```
ll euclid(ll a, ll b, ll &x, ll &y) {
  if (!b) return x = 1, y = 0, a;
  ll d = euclid(b, a % b, y, x);
  return y -= a/b * x, d;
}
```

CRT.h

Description: Chinese Remainder Theorem.

crt(a, m, b, n) computes x such that $x \equiv a \pmod m$, $x \equiv b \pmod n$. If $|a| < m$ and $|b| < n$, x will obey $0 \le x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.

Time: $\log(n)$

"euclid.h" 04d93a, 7 lines

```
ll crt(ll a, ll m, ll b, ll n) {
  if (n > m) swap(a, b), swap(m, n);
  ll x, y, g = euclid(m, n, x, y);
  assert((a - b) % g == 0); // else no solution
  x = (b - a) % n * x % n / g * m + a;
  return x < 0 ? x + m*n/g : x;
}
```

6.3.1 Bézout's identity

For $a \neq, b \neq 0$, then $d = gcd(a, b)$ is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If (x, y) is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

phiFunction.h

Description: *Euler's* ϕ function is defined as $\phi(n) :=$ # of positive integers $\le n$ that are coprime with n. $\phi(1) = 1$, p prime $\Rightarrow \phi(p^k) = (p-1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1} p_2^{k_2} ... p_r^{k_r}$ then $\phi(n) = (p_1 - 1)p_1^{k_1 - 1} ... (p_r - 1)p_r^{k_r - 1}$. $\phi(n) = n \cdot \prod_{p|n}(1 - 1/p)$.
$\sum_{d|n} \phi(d) = n$, $\sum_{1 \le k \le n, \gcd(k,n)=1} k = n\phi(n)/2, n > 1$

Euler's thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod n$.

Fermat's little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod p$ $\forall a$.

cf7d6d, 8 lines

```
const int LIM = 5000000;
int phi[LIM];

void calculatePhi() {
  rep(i,0,LIM) phi[i] = i&1 ? i : i/2;
  for (int i = 3; i < LIM; i += 2) if(phi[i] == i)
    for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

6.4 Fractions

ContinuedFractions.h

Description: Given N and a real number $x \ge 0$, finds the closest rational approximation p/q with $p, q \le N$. It will obey $|p/q - x| \le 1/qN$.

For consecutive convergents, $p_{k+1}q_k - q_{k+1}p_k = (-1)^k$. ($p_k/q_k$ alternates between $> x$ and $< x$.) If x is rational, y eventually becomes ∞; if x is the root of a degree 2 polynomial the a's eventually become cyclic.

Time: $\mathcal{O}(\log N)$

dd6c5e, 21 lines

```
typedef double d; // for N ~ 1e7; long double for N ~ 1e9
pair<ll, ll> approximate(d x, ll N) {
  ll LP = 0, LQ = 1, P = 1, Q = 0, inf = LLONG_MAX; d y = x;
  for (;;) {
    ll lim = min(P ? (N-LP) / P : inf, Q ? (N-LQ) / Q : inf),
       a = (ll)floor(y), b = min(a, lim),
       NP = b*P + LP, NQ = b*Q + LQ;
    if (a > b) {
      // If b > a/2, we have a semi-convergent that gives us a
      // better approximation; if b = a/2, we *may* have one.
      // Return {P, Q} here for a more canonical approximation.
      return (abs(x - (d)NP / (d)NQ) < abs(x - (d)P / (d)Q)) ?
        make_pair(NP, NQ) : make_pair(P, Q);
    }
    if (abs(y = 1/(y - (d)a)) > 3*N) {
      return {NP, NQ};
    }
    LP = P; P = NP;
    LQ = Q; Q = NQ;
  }
}
```

FracBinarySearch.h

Description: Given f and N, finds the smallest fraction $p/q \in [0, 1]$ such that $f(p/q)$ is true, and $p, q \le N$. You may want to throw an exception from f if it finds an exact solution, in which case N can be removed.

Usage: fracBS([](Frac f) { return f.p>=3*f.q; }, 10); // {1,3}

Time: $\mathcal{O}(\log(N))$

27ab3e, 25 lines

```
struct Frac { ll p, q; };

template<class F>
Frac fracBS(F f, ll N) {
  bool dir = 1, A = 1, B = 1;
  Frac lo{0, 1}, hi{1, 1}; // Set hi to 1/0 to search (0, N]
  if (f(lo)) return lo;
  assert(f(hi));
  while (A || B) {
    ll adv = 0, step = 1; // move hi if dir, else lo
    for (int si = 0; step; (step *= 2) >>= si) {
      adv += step;
      Frac mid{lo.p * adv + hi.p, lo.q * adv + hi.q};
      if (abs(mid.p) > N || mid.q > N || dir == !f(mid)) {
        adv -= step; si = 2;
      }
    }
    hi.p += lo.p * adv;
    hi.q += lo.q * adv;
    dir = !dir;
    swap(lo, hi);
    A = B; B = !!adv;
  }
  return dir ? hi : lo;
}
```

6.5 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2), \;\; b = k \cdot (2mn), \;\; c = k \cdot (m^2 + n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either m or n even.

6.6 Primes

$p = 962592769$ is such that $2^{21} \mid p - 1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a, except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

6.7 Estimates

$\sum_{d|n} d = O(n \log \log n)$.

The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

6.8 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d) g(n/d)$$

Other useful formulas/forms:

$\sum_{d|n} \mu(d) = [n = 1]$ (very useful)

$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(d/n) g(d)$

$g(n) = \sum_{1 \le m \le n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \le m \le n} \mu(m) g(\lfloor \frac{n}{m} \rfloor)$

Combinatorial (7)

7.1 Permutations

7.1.1 Factorial

n	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
n	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
n	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL_MAX		

IntPerm.h
Description: Permutation -> integer conversion. (Not order preserving.) Integer -> permutation can use a lookup table.
Time: $\mathcal{O}(n)$
044568, 6 lines

```
int permToInt(vi& v) {
  int use = 0, i = 0, r = 0;
  for(int x:v) r = r * ++i + __builtin_popcount(use & -(1<<x)),
    use |= 1 << x;                    // (note: minus, not ~!)
  return r;
}
```

7.1.2 Cycles

Let $g_S(n)$ be the number of n-permutations whose cycle lengths all belong to the set S. Then

$$\sum_{n=0}^{\infty} g_S(n)\frac{x^n}{n!} = \exp\left(\sum_{n\in S}\frac{x^n}{n}\right)$$

7.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1)+D(n-2)) = nD(n-1)+(-1)^n = \left\lfloor \frac{n!}{e} \right\rceil$$

7.1.4 Burnside's lemma

Given a group G of symmetries and a set X, the number of elements of X *up to symmetry* equals

$$\frac{1}{|G|}\sum_{g\in G}|X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

If $f(n)$ counts "configurations" (of some sort) of length n, we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n}\sum_{k=0}^{n-1} f(\gcd(n,k)) = \frac{1}{n}\sum_{k|n} f(k)\phi(n/k).$$

7.2 Partitions and subsets

7.2.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1,\ p(n) = \sum_{k\in\mathbb{Z}\setminus\{0\}} (-1)^{k+1} p(n-k(3k-1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

n	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	~2e5	~2e8

7.2.2 Lucas' Theorem

Let n, m be non-negative integers and p a prime. Write $n = n_k p^k + ... + n_1 p + n_0$ and $m = m_k p^k + ... + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^{k}\binom{n_i}{m_i} \pmod p$.

7.2.3 Binomials

multinomial.h
Description: Computes $\binom{k_1+\cdots+k_n}{k_1,k_2,\ldots,k_n} = \frac{(\sum k_i)!}{k_1!k_2!\ldots k_n!}$.
a0a312, 5 lines

```
ll multinomial(vi& v) {
  ll c = 1, m = v.empty() ? 1 : v[0];
  rep(i,1,sz(v)) rep(j,0,v[i]) c = c * ++m / (j+1);
  return c;
}
```

7.3 General purpose numbers

7.3.1 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t-1}$ (FFT-able).
$B[0,\ldots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \ldots]$

Sums of powers:

$$\sum_{i=1}^{n} n^m = \frac{1}{m+1}\sum_{k=0}^{m}\binom{m+1}{k}B_k\cdot(n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\sum_{i=m}^{\infty} f(i) = \int_m^{\infty} f(x)dx - \sum_{k=1}^{\infty}\frac{B_k}{k!}f^{(k-1)}(m)$$

$$\approx \int_m^{\infty} f(x)dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m))$$

7.3.2 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n,k) = c(n-1,k-1) + (n-1)c(n-1,k),\ c(0,0) = 1$$
$$\textstyle\sum_{k=0}^{n} c(n,k)x^k = x(x+1)\ldots(x+n-1)$$

$c(8,k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$
$c(n,2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \ldots$

7.3.3 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j:s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j:s s.t. $\pi(j) \geq j$, k j:s s.t. $\pi(j) > j$.

$$E(n,k) = (n-k)E(n-1,k-1) + (k+1)E(n-1,k)$$

$$E(n,0) = E(n,n-1) = 1$$

$$E(n,k) = \sum_{j=0}^{k}(-1)^j\binom{n+1}{j}(k+1-j)^n$$

7.3.4 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n,k) = S(n-1,k-1) + kS(n-1,k)$$

$$S(n,1) = S(n,n) = 1$$

$$S(n,k) = \frac{1}{k!}\sum_{j=0}^{k}(-1)^{k-j}\binom{k}{j}j^n$$

7.3.5 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \ldots$. For p prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod p$$

7.3.6 Labeled unrooted trees

on n vertices: n^{n-2}
on k existing trees of size n_i: $n_1 n_2 \cdots n_k n^{k-2}$
with degrees d_i: $(n-2)!/((d_1-1)!\cdots(d_n-1)!)$

7.3.7 Catalan numbers

$$C_n = \frac{1}{n+1}\binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1,\ C_{n+1} = \frac{2(2n+1)}{n+2}C_n,\ C_{n+1} = \sum C_i C_{n-i}$$

$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \ldots$

- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n+1$ leaves (0 or 2 children).
- ordered trees with $n+1$ vertices.
- ways a convex polygon with $n+2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

Graph (8)

8.1 Fundamentals

BellmanFord.h
Description: Calculates shortest paths from s in a graph that might have negative edge weights. Unreachable nodes get dist = inf; nodes reachable through negative-weight cycles get dist = -inf. Assumes $V^2 \max|w_i| < \sim 2^{63}$.
Time: $\mathcal{O}(VE)$
830a8f, 23 lines

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }};
struct Node { ll dist = inf; int prev = -1; };

void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {
  nodes[s].dist = 0;
  sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });

  int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices
  rep(i,0,lim) for (Ed ed : eds) {
```

```
    Node cur = nodes[ed.a], &dest = nodes[ed.b];
    if (abs(cur.dist) == inf) continue;
    ll d = cur.dist + ed.w;
    if (d < dest.dist) {
      dest.prev = ed.a;
      dest.dist = (i < lim-1 ? d : -inf);
    }
  }
  rep(i,0,lim) for (Ed e : eds) {
    if (nodes[e.a].dist == -inf)
      nodes[e.b].dist = -inf;
  }
}
```

FloydWarshall.h

Description: Calculates all-pairs shortest path in a directed graph that might have negative edge weights. Input is an distance matrix m, where $m[i][j] = \texttt{inf}$ if i and j are not adjacent. As output, $m[i][j]$ is set to the shortest distance between i and j, inf if no path, or -inf if the path goes through a negative-weight cycle.
Time: $\mathcal{O}\left(N^3\right)$

531245, 12 lines

```
const ll inf = 1LL << 62;
void floydWarshall(vector<vector<ll>>& m) {
  int n = sz(m);
  rep(i,0,n) m[i][i] = min(m[i][i], 0LL);
  rep(k,0,n) rep(i,0,n) rep(j,0,n)
    if (m[i][k] != inf && m[k][j] != inf) {
      auto newDist = max(m[i][k] + m[k][j], -inf);
      m[i][j] = min(m[i][j], newDist);
    }
  rep(k,0,n) if (m[k][k] < 0) rep(i,0,n) rep(j,0,n)
    if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -inf;
}
```

TopoSort.h

Description: Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than n – nodes reachable from cycles will not be returned.
Time: $\mathcal{O}\left(|V| + |E|\right)$

d678d8, 8 lines

```
vi topoSort(const vector<vi>& gr) {
  vi indeg(sz(gr)), q;
  for (auto& li : gr) for (int x : li) indeg[x]++;
  rep(i,0,sz(gr)) if (indeg[i] == 0) q.push_back(i);
  rep(j,0,sz(q)) for (int x : gr[q[j]])
    if (--indeg[x] == 0) q.push_back(x);
  return q;
}
```

8.2 Network flow

PushRelabel.h

Description: Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only.
Time: $\mathcal{O}\left(V^2\sqrt{E}\right)$

0ae1d4, 48 lines

```
struct PushRelabel {
  struct Edge {
    int dest, back;
    ll f, c;
  };
  vector<vector<Edge>> g;
  vector<ll> ec;
  vector<Edge*> cur;
  vector<vi> hs; vi H;
  PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}

  void addEdge(int s, int t, ll cap, ll rcap=0) {
    if (s == t) return;
    g[s].push_back({t, sz(g[t]), 0, cap});
    g[t].push_back({s, sz(g[s])-1, 0, rcap});
  }

  void addFlow(Edge& e, ll f) {
    Edge &back = g[e.dest][e.back];
    if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
    e.f += f; e.c -= f; ec[e.dest] += f;
    back.f -= f; back.c += f; ec[back.dest] -= f;
  }
  ll calc(int s, int t) {
    int v = sz(g); H[s] = v; ec[t] = 1;
    vi co(2*v); co[0] = v-1;
    rep(i,0,v) cur[i] = g[i].data();
    for (Edge& e : g[s]) addFlow(e, e.c);

    for (int hi = 0;;) {
      while (hs[hi].empty()) if (!hi--) return -ec[s];
      int u = hs[hi].back(); hs[hi].pop_back();
      while (ec[u] > 0)  // discharge u
        if (cur[u] == g[u].data() + sz(g[u])) {
          H[u] = 1e9;
          for (Edge& e : g[u]) if (e.c && H[u] > H[e.dest]+1)
            H[u] = H[e.dest]+1, cur[u] = &e;
          if (++co[H[u]], !--co[hi] && hi < v)
            rep(i,0,v) if (hi < H[i] && H[i] < v)
              --co[H[i]], H[i] = v + 1;
          hi = H[u];
        } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
          addFlow(*cur[u], min(ec[u], cur[u]->c));
        else ++cur[u];
    }
  }
  bool leftOfMinCut(int a) { return H[a] >= sz(g); }
};
```

MinCostMaxFlow.h

Description: Min-cost max-flow. If costs can be negative, call setpi before maxflow, but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only.
Time: $\mathcal{O}\left(FE\log(V)\right)$ where F is max flow. $\mathcal{O}\left(VE\right)$ for setpi.

58385b, 79 lines

```
#include <bits/extc++.h>

const ll INF = numeric_limits<ll>::max() / 4;

struct MCMF {
  struct edge {
    int from, to, rev;
    ll cap, cost, flow;
  };
  int N;
  vector<vector<edge>> ed;
  vi seen;
  vector<ll> dist, pi;
  vector<edge*> par;

  MCMF(int N) : N(N), ed(N), seen(N), dist(N), pi(N), par(N) {}

  void addEdge(int from, int to, ll cap, ll cost) {
    if (from == to) return;
    ed[from].push_back(edge{ from,to,sz(ed[to]),cap,cost,0 });
    ed[to].push_back(edge{ to,from,sz(ed[from])-1,0,-cost,0 });
  }

  void path(int s) {
    fill(all(seen), 0);
    fill(all(dist), INF);
    dist[s] = 0; ll di;

    __gnu_pbds::priority_queue<pair<ll, int>> q;
    vector<decltype(q)::point_iterator> its(N);
    q.push({ 0, s });

    while (!q.empty()) {
      s = q.top().second; q.pop();
      seen[s] = 1; di = dist[s] + pi[s];
      for (edge& e : ed[s]) if (!seen[e.to]) {
        ll val = di - pi[e.to] + e.cost;
        if (e.cap - e.flow > 0 && val < dist[e.to]) {
          dist[e.to] = val;
          par[e.to] = &e;
          if (its[e.to] == q.end())
            its[e.to] = q.push({ -dist[e.to], e.to });
          else
            q.modify(its[e.to], { -dist[e.to], e.to });
        }
      }
    }
    rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
  }

  pair<ll, ll> maxflow(int s, int t) {
    ll totflow = 0, totcost = 0;
    while (path(s), seen[t]) {
      ll fl = INF;
      for (edge* x = par[t]; x; x = par[x->from])
        fl = min(fl, x->cap - x->flow);

      totflow += fl;
      for (edge* x = par[t]; x; x = par[x->from]) {
        x->flow += fl;
        ed[x->to][x->rev].flow -= fl;
      }
    }
    rep(i,0,N) for(edge& e : ed[i]) totcost += e.cost * e.flow;
    return {totflow, totcost/2};
  }

  // If some costs can be negative, call this before maxflow:
  void setpi(int s) { // (otherwise, leave this out)
    fill(all(pi), INF); pi[s] = 0;
    int it = N, ch = 1; ll v;
    while (ch-- && it--)
      rep(i,0,N) if (pi[i] != INF)
        for (edge& e : ed[i]) if (e.cap)
          if ((v = pi[i] + e.cost) < pi[e.to])
            pi[e.to] = v, ch = 1;
    assert(it >= 0); // negative cost cycle
  }
};
```

EdmondsKarp.h

Description: Flow algorithm with guaranteed complexity $O(VE^2)$. To get edge flow values, compare capacities before and after, and take the positive values only.

482fe0, 36 lines

```
template<class T> T edmondsKarp(vector<unordered_map<int, T>>&
    graph, int source, int sink) {
  assert(source != sink);
  T flow = 0;
  vi par(sz(graph)), q = par;

  for (;;) {
    fill(all(par), -1);
```

```
    par[source] = 0;
    int ptr = 1;
    q[0] = source;

    rep(i,0,ptr) {
      int x = q[i];
      for (auto e : graph[x]) {
        if (par[e.first] == -1 && e.second > 0) {
          par[e.first] = x;
          q[ptr++] = e.first;
          if (e.first == sink) goto out;
        }
      }
    }
    return flow;
out:
    T inc = numeric_limits<T>::max();
    for (int y = sink; y != source; y = par[y])
      inc = min(inc, graph[par[y]][y]);

    flow += inc;
    for (int y = sink; y != source; y = par[y]) {
      int p = par[y];
      if ((graph[p][y] -= inc) <= 0) graph[p].erase(y);
      graph[y][p] += inc;
    }
  }
}
```

MinCut.h

Description: After running max-flow, the left side of a min-cut from s to t is given by all vertices reachable from s, only traversing edges with positive residual capacity.

GlobalMinCut.h

Description: Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.
Time: $\mathcal{O}\left(V^3\right)$

8b0e19, 21 lines

```
pair<int, vi> globalMinCut(vector<vi> mat) {
  pair<int, vi> best = {INT_MAX, {}};
  int n = sz(mat);
  vector<vi> co(n);
  rep(i,0,n) co[i] = {i};
  rep(ph,1,n) {
    vi w = mat[0];
    size_t s = 0, t = 0;
    rep(it,0,n-ph) { // O(V^2) -> O(E log V) with prio. queue
      w[t] = INT_MIN;
      s = t, t = max_element(all(w)) - w.begin();
      rep(i,0,n) w[i] += mat[t][i];
    }
    best = min(best, {w[t] - mat[t][t], co[t]});
    co[s].insert(co[s].end(), all(co[t]));
    rep(i,0,n) mat[s][i] += mat[t][i];
    rep(i,0,n) mat[i][s] = mat[s][i];
    mat[0][t] = INT_MIN;
  }
  return best;
}
```

GomoryHu.h

Description: Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path.
Time: $\mathcal{O}(V)$ Flow Computations

"PushRelabel.h" 0418b3, 13 lines

```
typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
  vector<Edge> tree;
  vi par(N);
  rep(i,1,N) {
    PushRelabel D(N); // Dinic also works
    for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
    tree.push_back({i, par[i], D.calc(i, par[i])});
    rep(j,i+1,N)
      if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
  }
  return tree;
}
```

8.3 Matching

HopcroftKarp.h

Description: Fast bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and r should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $r[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.
Time: $\mathcal{O}\left(E\sqrt{V}\right)$

731cfb, 20 lines

```
int hopcroftKarp(vector<vi>& g, vi& r) {
  int n = sz(g), res = 0;
  vi l(n, -1), q(n), d(n);
  auto dfs = [&](auto f, int u) -> bool {
    int t = exchange(d[u], 0) + 1;
    for (int v : g[u])
      if (r[v] == -1 || (d[r[v]] == t && f(f, r[v])))
        return l[u] = v, r[v] = u, 1;
    return 0;
  };
  for (int t = 0, f = 0;; t = f = 0, d.assign(n, 0)) {
    rep(i,0,n) if (l[i] == -1) q[t++] = i, d[i] = 1;
    rep(i,0,t) for (int v : g[q[i]]) {
      if (r[v] == -1) f = 1;
      else if (!d[r[v]]) d[r[v]] = d[q[i]] + 1, q[t++] = r[v];
    }
    if (!f) return res;
    rep(i,0,n) if (l[i] == -1) res += dfs(dfs, i);
  }
}
```

DFSMatching.h

Description: Simple bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and *btoa* should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.
Usage: `vi btoa(m, -1); dfsMatching(g, btoa);`
Time: $\mathcal{O}(VE)$

522b98, 22 lines

```
bool find(int j, vector<vi>& g, vi& btoa, vi& vis) {
  if (btoa[j] == -1) return 1;
  vis[j] = 1; int di = btoa[j];
  for (int e : g[di])
    if (!vis[e] && find(e, g, btoa, vis)) {
      btoa[e] = di;
      return 1;
    }
  return 0;
}
int dfsMatching(vector<vi>& g, vi& btoa) {
  vi vis;
  rep(i,0,sz(g)) {
    vis.assign(sz(btoa), 0);
    for (int j : g[i])
      if (find(j, g, btoa, vis)) {
        btoa[j] = i;
        break;
      }
  }
  return sz(btoa) - (int)count(all(btoa), -1);
}
```

MinimumVertexCover.h

Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

"DFSMatching.h" da4196, 20 lines

```
vi cover(vector<vi>& g, int n, int m) {
  vi match(m, -1);
  int res = dfsMatching(g, match);
  vector<bool> lfound(n, true), seen(m);
  for (int it : match) if (it != -1) lfound[it] = false;
  vi q, cover;
  rep(i,0,n) if (lfound[i]) q.push_back(i);
  while (!q.empty()) {
    int i = q.back(); q.pop_back();
    lfound[i] = 1;
    for (int e : g[i]) if (!seen[e] && match[e] != -1) {
      seen[e] = true;
      q.push_back(match[e]);
    }
  }
  rep(i,0,n) if (!lfound[i]) cover.push_back(i);
  rep(i,0,m) if (seen[i]) cover.push_back(n+i);
  assert(sz(cover) == res);
  return cover;
}
```

WeightedMatching.h

Description: Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes cost[N][M], where cost[i][j] = cost for L[i] to be matched with R[j], and returns (min cost, match), where L[i] is matched with R[match[i]]. Negate costs for max cost. Requires $N \leq M$.
Time: $\mathcal{O}\left(N^2M\right)$

8f41c7, 24 lines

```
template<class T>
pair<T, vi> weightedMatching(vector<vector<T>> &C) {
  int i = sz(C), m = i ? sz(C[0]) : 0, c, s, r;
  vector<T> dist(m), pot(m);
  vi match(i), rev(m, -1), cols(m), prev(m);
  T d = 0, nd, cost = 0;
  while (i--) {
    rep(c,0,m) dist[c] = C[i][c], cols[c] = c, prev[c] = i;
    for (s = 0;;) {
      rep(j,s,m) {
        c = cols[j], nd = dist[c] - pot[c];
        if (j == s || d > nd) d = nd, swap(cols[s], cols[j]);
      }
      if ((r = rev[c = cols[s++]]) == -1) break;
      rep(j,0,m) if (dist[j] > (nd = C[r][j]-C[r][c]+dist[c]))
        dist[j] = nd, prev[j] = r;
    }
    cost += dist[c];
    while (s--) pot[cols[s]] = dist[cols[s]] - d;
    for (; r != i; swap(c, match[r]))
      r = rev[c] = prev[c];
  }
  return {cost, match};
}
```

GeneralMatching.h

Description: Matching for general graphs. Fails with probability N/mod.

Time: $\mathcal{O}\left(N^3\right)$

"../numerical/MatrixInverse-mod.h" cb1912, 40 lines

```
vector<pii> generalMatching(int N, vector<pii>& ed) {
  vector<vector<ll>> mat(N, vector<ll>(N)), A;
  for (pii pa : ed) {
    int a = pa.first, b = pa.second, r = rand() % mod;
    mat[a][b] = r, mat[b][a] = (mod - r) % mod;
  }

  int r = matInv(A = mat), M = 2*N - r, fi, fj;
  assert(r % 2 == 0);

  if (M != N) do {
    mat.resize(M, vector<ll>(M));
    rep(i,0,N) {
      mat[i].resize(M);
      rep(j,N,M) {
        int r = rand() % mod;
        mat[i][j] = r, mat[j][i] = (mod - r) % mod;
      }
    }
  } while (matInv(A = mat) != M);

  vi has(M, 1); vector<pii> ret;
  rep(it,0,M/2) {
    rep(i,0,M) if (has[i])
      rep(j,i+1,M) if (A[i][j] && mat[i][j]) {
        fi = i; fj = j; goto done;
    } assert(0); done:
    if (fj < N) ret.emplace_back(fi, fj);
    has[fi] = has[fj] = 0;
    rep(sw,0,2) {
      ll a = modpow(A[fi][fj], mod-2);
      rep(i,0,M) if (has[i] && A[i][fj]) {
        ll b = A[i][fj] * a % mod;
        rep(j,0,M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
      }
      swap(fi,fj);
    }
  }
  return ret;
}
```

8.4 DFS algorithms

SCC.h

Description: Finds strongly connected components in a directed graph. If vertices u, v belong to the same component, we can reach u from v and vice versa.

Usage: `scc(graph, [&](vi& v) { ... })` visits all components in reverse topological order. `comp[i]` holds the component index of a node (a component only has edges to components with lower index). `ncomps` will contain the number of components.

Time: $\mathcal{O}\left(E+V\right)$

76b5c9, 24 lines

```
vi val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
  int low = val[j] = ++Time, x; z.push_back(j);
  for (auto e : g[j]) if (comp[e] < 0)
    low = min(low, val[e] ?: dfs(e,g,f));

  if (low == val[j]) {
    do {
      x = z.back(); z.pop_back();
      comp[x] = ncomps;
      cont.push_back(x);
    } while (x != j);
    f(cont); cont.clear();
    ncomps++;
  }
  return val[j] = low;
}
template<class G, class F> void scc(G& g, F f) {
  int n = sz(g);
  val.assign(n, 0); comp.assign(n, -1);
  Time = ncomps = 0;
  rep(i,0,n) if (comp[i] < 0) dfs(i, g, f);
}
```

BiconnectedComponents.h

Description: Finds all biconnected components in an undirected graph, and runs a callback for the edges in each. In a biconnected component there are at least two internally disjoint paths between any two nodes (a cycle exists through them). Note that a node can be in several components. An edge which is not in a component is a bridge, i.e., not part of any cycle.

Usage: `int eid = 0; ed.resize(N);`
`for each edge (a,b) {`
`ed[a].emplace_back(b, eid);`
`ed[b].emplace_back(a, eid++); }`
`bicomps([&](const vi& edgelist) {...});`

Time: $\mathcal{O}\left(E+V\right)$

c6b7c7, 32 lines

```
vi num, st;
vector<vector<pii>> ed;
int Time;
template<class F>
int dfs(int at, int par, F& f) {
  int me = num[at] = ++Time, top = me;
  for (auto [y, e] : ed[at]) if (e != par) {
    if (num[y]) {
      top = min(top, num[y]);
      if (num[y] < me)
        st.push_back(e);
    } else {
      int si = sz(st);
      int up = dfs(y, e, f);
      top = min(top, up);
      if (up == me) {
        st.push_back(e);
        f(vi(st.begin() + si, st.end()));
        st.resize(si);
      }
      else if (up < me) st.push_back(e);
      else { /* e is a bridge */ }
    }
  }
  return top;
}

template<class F>
void bicomps(F f) {
  num.assign(sz(ed), 0);
  rep(i,0,sz(ed)) if (!num[i]) dfs(i, -1, f);
}
```

2sat.h

Description: Calculates a valid assignment to boolean variables a, b, c,... to a 2-SAT problem, so that an expression of the type $(a||b)\&\&(!a||c)\&\&(d||!b)\&\&\ldots$ becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions (~x).

Usage: `TwoSat ts(number of boolean variables);`
`ts.either(0, ~3); // Var 0 is true or var 3 is false`
`ts.setValue(2); // Var 2 is true`
`ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true`
`ts.solve(); // Returns true iff it is solvable`
`ts.values[0..N-1] holds the assigned values to the vars`

Time: $\mathcal{O}\left(N+E\right)$, where N is the number of boolean variables, and E is the number of clauses.

5f9706, 56 lines

```
struct TwoSat {
  int N;
  vector<vi> gr;
  vi values; // 0 = false, 1 = true

  TwoSat(int n = 0) : N(n), gr(2*n) {}

  int addVar() { // (optional)
    gr.emplace_back();
    gr.emplace_back();
    return N++;
  }

  void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
  }
  void setValue(int x) { either(x, x); }

  void atMostOne(const vi& li) { // (optional)
    if (sz(li) <= 1) return;
    int cur = ~li[0];
    rep(i,2,sz(li)) {
      int next = addVar();
      either(cur, ~li[i]);
      either(cur, next);
      either(~li[i], next);
      cur = ~next;
    }
    either(cur, ~li[1]);
  }

  vi val, comp, z; int time = 0;
  int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
      low = min(low, val[e] ?: dfs(e));
    if (low == val[i]) do {
      x = z.back(); z.pop_back();
      comp[x] = low;
      if (values[x>>1] == -1)
        values[x>>1] = x&1;
    } while (x != i);
    return val[i] = low;
  }

  bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
  }
};
```

EulerWalk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.

Time: $\mathcal{O}\left(V+E\right)$

780b64, 15 lines

```
vi eulerWalk(vector<vector<pii>>& gr, int nedges, int src=0) {
  int n = sz(gr);
```

```
  vi D(n), its(n), eu(nedges), ret, s = {src};
  D[src]++; // to allow Euler paths, not just cycles
  while (!s.empty()) {
    int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
    if (it == end){ ret.push_back(x); s.pop_back(); continue; }
    tie(y, e) = gr[x][it++];
    if (!eu[e]) {
      D[x]--, D[y]++;
      eu[e] = 1; s.push_back(y);
    }}
  for (int x : D) if (x < 0 || sz(ret) != nedges+1) return {};
  return {ret.rbegin(), ret.rend()};
}
```

8.5 Coloring

EdgeColoring.h

Description: Given a simple, undirected graph with max degree D, computes a $(D+1)$-coloring of the edges such that no neighboring edges share a color. (D-coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)
Time: $\mathcal{O}(NM)$

e210e2, 31 lines

```
vi edgeColoring(int N, vector<pii> eds) {
  vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
  for (pii e : eds) ++cc[e.first], ++cc[e.second];
  int u, v, ncols = *max_element(all(cc)) + 1;
  vector<vi> adj(N, vi(ncols, -1));
  for (pii e : eds) {
    tie(u, v) = e;
    fan[0] = v;
    loc.assign(ncols, 0);
    int at = u, end = u, d, c = free[u], ind = 0, i = 0;
    while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
      loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
    cc[loc[d]] = c;
    for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
      swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
    while (adj[fan[i]][d] != -1) {
      int left = fan[i], right = fan[++i], e = cc[i];
      adj[u][e] = left;
      adj[left][e] = u;
      adj[right][e] = -1;
      free[right] = e;
    }
    adj[u][d] = fan[i];
    adj[fan[i]][d] = u;
    for (int y : {fan[0], u, end})
      for (int& z = free[y] = 0; adj[y][z] != -1; z++);
  }
  rep(i,0,sz(eds))
    for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
  return ret;
}
```

8.6 Heuristics

MaximalCliques.h

Description: Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.
Time: $\mathcal{O}\left(3^{n/3}\right)$, much faster for sparse graphs

b0d5b1, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
  if (!P.any()) { if (!X.any()) f(R); return; }
  auto q = (P | X)._Find_first();
  auto cands = P & ~eds[q];
  rep(i,0,sz(eds)) if (cands[i]) {
    R[i] = 1;
    cliques(eds, f, P & eds[i], X & eds[i], R);
    R[i] = P[i] = 0; X[i] = 1;
  }
}
```

MaximumClique.h

Description: Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.
Time: Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

f7c0bc, 49 lines

```
typedef vector<bitset<200>> vb;
struct Maxclique {
  double limit=0.025, pk=0;
  struct Vertex { int i, d=0; };
  typedef vector<Vertex> vv;
  vb e;
  vv V;
  vector<vi> C;
  vi qmax, q, S, old;
  void init(vv& r) {
    for (auto& v : r) v.d = 0;
    for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
    sort(all(r), [](auto a, auto b) { return a.d > b.d; });
    int mxD = r[0].d;
    rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
  }
  void expand(vv& R, int lev = 1) {
    S[lev] += S[lev - 1] - old[lev];
    old[lev] = S[lev - 1];
    while (sz(R)) {
      if (sz(q) + R.back().d <= sz(qmax)) return;
      q.push_back(R.back().i);
      vv T;
      for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
      if (sz(T)) {
        if (S[lev]++ / ++pk < limit) init(T);
        int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
        C[1].clear(), C[2].clear();
        for (auto v : T) {
          int k = 1;
          auto f = [&](int i) { return e[v.i][i]; };
          while (any_of(all(C[k]), f)) k++;
          if (k > mxk) mxk = k, C[mxk + 1].clear();
          if (k < mnk) T[j++].i = v.i;
          C[k].push_back(v.i);
        }
        if (j > 0) T[j - 1].d = 0;
        rep(k,mnk,mxk + 1) for (int i : C[k])
          T[j].i = i, T[j++].d = k;
        expand(T, lev + 1);
      } else if (sz(q) > sz(qmax)) qmax = q;
      q.pop_back(), R.pop_back();
    }
  }
  vi maxClique() { init(V), expand(V); return qmax; }
  Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i,0,sz(e)) V.push_back({i});
  }
};
```

MaximumIndependentSet.h

Description: To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertexCover.

8.7 Trees

BinaryLifting.h

Description: Calculate power of two jumps in a tree, to support fast upward jumps and LCAs. Assumes the root node points to itself.
Time: construction $\mathcal{O}(N \log N)$, queries $\mathcal{O}(\log N)$

bfce85, 25 lines

```
vector<vi> treeJump(vi& P){
  int on = 1, d = 1;
  while(on < sz(P)) on *= 2, d++;
  vector<vi> jmp(d, P);
  rep(i,1,d) rep(j,0,sz(P))
    jmp[i][j] = jmp[i-1][jmp[i-1][j]];
  return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps){
  rep(i,0,sz(tbl))
    if(steps&(1<<i)) nod = tbl[i][nod];
  return nod;
}

int lca(vector<vi>& tbl, vi& depth, int a, int b) {
  if (depth[a] < depth[b]) swap(a, b);
  a = jmp(tbl, a, depth[a] - depth[b]);
  if (a == b) return a;
  for (int i = sz(tbl); i--;) {
    int c = tbl[i][a], d = tbl[i][b];
    if (c != d) a = c, b = d;
  }
  return tbl[0][a];
}
```

LCA.h

Description: Data structure for computing lowest common ancestors in a tree (with 0 as root). C should be an adjacency list of the tree, either directed or undirected.
Time: $\mathcal{O}(N \log N + Q)$

"../data-structures/RMQ.h" 0f62fb, 21 lines

```
struct LCA {
  int T = 0;
  vi time, path, ret;
  RMQ<int> rmq;

  LCA(vector<vi>& C) : time(sz(C)), rmq((dfs(C,0,-1), ret)) {}
  void dfs(vector<vi>& C, int v, int par) {
    time[v] = T++;
    for (int y : C[v]) if (y != par) {
      path.push_back(v), ret.push_back(time[v]);
      dfs(C, y, v);
    }
  }

  int lca(int a, int b) {
    if (a == b) return a;
    tie(a, b) = minmax(time[a], time[b]);
    return path[rmq.query(a, b)];
  }
  //dist(a,b){return depth[a] + depth[b] - 2*depth[lca(a,b)];}
};
```

CompressTree.h

Description: Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most $|S|-1$) pairwise LCA's and compressing edges. Returns a list of (par, orig_index) representing a tree rooted at 0. The root points to itself.
Time: $\mathcal{O}(|S| \log |S|)$

"LCA.h" 9775a0, 21 lines

```
typedef vector<pair<int, int>> vpi;
```

```
vpi compressTree(LCA& lca, const vi& subset) {
  static vi rev; rev.resize(sz(lca.time));
  vi li = subset, &T = lca.time;
  auto cmp = [&](int a, int b) { return T[a] < T[b]; };
  sort(all(li), cmp);
  int m = sz(li)-1;
  rep(i,0,m) {
    int a = li[i], b = li[i+1];
    li.push_back(lca.lca(a, b));
  }
  sort(all(li), cmp);
  li.erase(unique(all(li)), li.end());
  rep(i,0,sz(li)) rev[li[i]] = i;
  vpi ret = {pii(0, li[0])};
  rep(i,0,sz(li)-1) {
    int a = li[i], b = li[i+1];
    ret.emplace_back(rev[lca.lca(a, b)], b);
  }
  return ret;
}
```

HLD.h

Description: Decomposes a tree into vertex disjoint heavy paths and light edges such that the path from any leaf to the root contains at most log(n) light edges. Code does additive modifications and max queries, but can support commutative segtree modifications/queries on paths and subtrees. Takes as input the full adjacency list. VALS_EDGES being true means that values are stored in the edges, as opposed to the nodes. All values initialized to the segtree default. Root must be 0.
Time: $\mathcal{O}\left((\log N)^2\right)$

"../data-structures/LazySegmentTree.h" 9547af, 46 lines

```
template <bool VALS_EDGES> struct HLD {
  int N, tim = 0;
  vector<vi> adj;
  vi par, siz, rt, pos;
  Node *tree;
  HLD(vector<vi> adj_)
    : N(sz(adj_)), adj(adj_), par(N, -1), siz(N, 1),
      rt(N),pos(N),tree(new Node(0, N)){ dfsSz(0); dfsHld(0); }
  void dfsSz(int v) {
    for (int& u : adj[v]) {
      adj[u].erase(find(all(adj[u]), v));
      par[u] = v;
      dfsSz(u);
      siz[v] += siz[u];
      if (siz[u] > siz[adj[v][0]]) swap(u, adj[v][0]);
    }
  }
  void dfsHld(int v) {
    pos[v] = tim++;
    for (int u : adj[v]) {
      rt[u] = (u == adj[v][0] ? rt[v] : u);
      dfsHld(u);
    }
  }
  template <class B> void process(int u, int v, B op) {
    for (;; v = par[rt[v]]) {
      if (pos[u] > pos[v]) swap(u, v);
      if (rt[u] == rt[v]) break;
      op(pos[rt[v]], pos[v] + 1);
    }
    op(pos[u] + VALS_EDGES, pos[v] + 1);
  }
  void modifyPath(int u, int v, int val) {
    process(u, v, [&](int l, int r) { tree->add(l, r, val); });
  }
  int queryPath(int u, int v) { // Modify depending on problem
    int res = -1e9;
    process(u, v, [&](int l, int r) {
      res = max(res, tree->query(l, r));
    });
    return res;
  }
  int querySubtree(int v) { // modifySubtree is similar
    return tree->query(pos[v] + VALS_EDGES, pos[v] + siz[v]);
  }
};
```

LinkCutTree.h

Description: Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.
Time: All operations take amortized $\mathcal{O}(\log N)$.

0fb462, 90 lines

```
struct Node { // Splay tree. Root's pp contains tree's parent.
  Node *p = 0, *pp = 0, *c[2];
  bool flip = 0;
  Node() { c[0] = c[1] = 0; fix(); }
  void fix() {
    if (c[0]) c[0]->p = this;
    if (c[1]) c[1]->p = this;
    // (+ update sum of subtree elements etc. if wanted)
  }
  void pushFlip() {
    if (!flip) return;
    flip = 0; swap(c[0], c[1]);
    if (c[0]) c[0]->flip ^= 1;
    if (c[1]) c[1]->flip ^= 1;
  }
  int up() { return p ? p->c[1] == this : -1; }
  void rot(int i, int b) {
    int h = i ^ b;
    Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
    if ((y->p = p)) p->c[up()] = y;
    c[i] = z->c[i ^ 1];
    if (b < 2) {
      x->c[h] = y->c[h ^ 1];
      y->c[h ^ 1] = x;
    }
    z->c[i ^ 1] = this;
    fix(); x->fix(); y->fix();
    if (p) p->fix();
    swap(pp, y->pp);
  }
  void splay() {
    for (pushFlip(); p; ) {
      if (p->p) p->p->pushFlip();
      p->pushFlip(); pushFlip();
      int c1 = up(), c2 = p->up();
      if (c2 == -1) p->rot(c1, 2);
      else p->p->rot(c2, c1 != c2);
    }
  }
  Node* first() {
    pushFlip();
    return c[0] ? c[0]->first() : (splay(), this);
  }
};

struct LinkCut {
  vector<Node> node;
  LinkCut(int N) : node(N) {}

  void link(int u, int v) { // add an edge (u, v)
    assert(!connected(u, v));
    makeRoot(&node[u]);
    node[u].pp = &node[v];
  }
  void cut(int u, int v) { // remove an edge (u, v)
    Node *x = &node[u], *top = &node[v];
    makeRoot(top); x->splay();
    assert(top == (x->pp ?: x->c[0]));
    if (x->pp) x->pp = 0;
    else {
      x->c[0] = top->p = 0;
      x->fix();
    }
  }
  bool connected(int u, int v) { // are u, v in the same tree?
    Node* nu = access(&node[u])->first();
    return nu == access(&node[v])->first();
  }
  void makeRoot(Node* u) {
    access(u);
    u->splay();
    if(u->c[0]) {
      u->c[0]->p = 0;
      u->c[0]->flip ^= 1;
      u->c[0]->pp = u;
      u->c[0] = 0;
      u->fix();
    }
  }
  Node* access(Node* u) {
    u->splay();
    while (Node* pp = u->pp) {
      pp->splay(); u->pp = 0;
      if (pp->c[1]) {
        pp->c[1]->p = 0; pp->c[1]->pp = pp; }
      pp->c[1] = u; pp->fix(); u = pp;
    }
    return u;
  }
};
```

DirectedMST.h

Description: Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.
Time: $\mathcal{O}(E \log V)$

"../data-structures/UnionFindRollback.h" 39e620, 60 lines

```
struct Edge { int a, b; ll w; };
struct Node {
  Edge key;
  Node *l, *r;
  ll delta;
  void prop() {
    key.w += delta;
    if (l) l->delta += delta;
    if (r) r->delta += delta;
    delta = 0;
  }
  Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
  if (!a || !b) return a ?: b;
  a->prop(), b->prop();
  if (a->key.w > b->key.w) swap(a, b);
  swap(a->l, (a->r = merge(b, a->r)));
  return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }

pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
  RollbackUF uf(n);
  vector<Node*> heap(n);
  for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
  ll res = 0;
```

```
  vi seen(n, -1), path(n), par(n);
  seen[r] = r;
  vector<Edge> Q(n), in(n, {-1,-1}), comp;
  deque<tuple<int, int, vector<Edge>>> cycs;
  rep(s,0,n) {
    int u = s, qi = 0, w;
    while (seen[u] < 0) {
      if (!heap[u]) return {-1,{}};
      Edge e = heap[u]->top();
      heap[u]->delta -= e.w, pop(heap[u]);
      Q[qi] = e, path[qi++] = u, seen[u] = s;
      res += e.w, u = uf.find(e.a);
      if (seen[u] == s) {
        Node* cyc = 0;
        int end = qi, time = uf.time();
        do cyc = merge(cyc, heap[w = path[--qi]]);
        while (uf.join(u, w));
        u = uf.find(u), heap[u] = cyc, seen[u] = -1;
        cycs.push_front({u, time, {&Q[qi], &Q[end]}});
      }
    }
    rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
  }

  for (auto& [u,t,comp] : cycs) { // restore sol (optional)
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto& e : comp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
  }
  rep(i,0,n) par[i] = in[i].a;
  return {res, par};
}
```

8.8 Math

8.8.1 Number of Spanning Trees

Create an $N \times N$ matrix `mat`, and for each edge $a \to b \in G$, do `mat[a][b]--, mat[b][b]++` (and `mat[b][a]--, mat[a][a]++` if G is undirected). Remove the ith row and column and take the determinant; this yields the number of directed spanning trees rooted at i (if G is undirected, remove any row/column).

8.8.2 Erdős–Gallai theorem

A simple graph with node degrees $d_1 \geq \cdots \geq d_n$ exists iff $d_1 + \cdots + d_n$ is even and for every $k = 1 \ldots n$,

$$\sum_{i=1}^{k} d_i \leq k(k-1) + \sum_{i=k+1}^{n} \min(d_i, k).$$

Geometry (9)

9.1 Geometric primitives

Point.h


Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)

47ec0a, 28 lines

```
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
  typedef Point P;
  T x, y;
  explicit Point(T x=0, T y=0) : x(x), y(y) {}
  bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
  bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
  P operator+(P p) const { return P(x+p.x, y+p.y); }
  P operator-(P p) const { return P(x-p.x, y-p.y); }
  P operator*(T d) const { return P(x*d, y*d); }
  P operator/(T d) const { return P(x/d, y/d); }
  T dot(P p) const { return x*p.x + y*p.y; }
  T cross(P p) const { return x*p.y - y*p.x; }
  T cross(P a, P b) const { return (a-*this).cross(b-*this); }
  T dist2() const { return x*x + y*y; }
  double dist() const { return sqrt((double)dist2()); }
  // angle to x-axis in interval [-pi, pi]
  double angle() const { return atan2(y, x); }
  P unit() const { return *this/dist(); } // makes dist()=1
  P perp() const { return P(-y, x); } // rotates +90 degrees
  P normal() const { return perp().unit(); }
  // returns point rotated 'a' radians ccw around the origin
  P rotate(double a) const {
    return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
  friend ostream& operator<<(ostream& os, P p) {
    return os << "(" << p.x << "," << p.y << ")"; }
};
```

lineDistance.h

Description:
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. a==b gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.




"Point.h" 53630a, 4 lines

```
template<class P>
double lineDist(P a, P b, P p) {
  return (double)(b-a).cross(p-a)/(b-a).dist();
}
```

SegmentDistance.h

Description:
Returns the shortest distance between point p and the line segment from point s to e.




Usage:
```
Point<double> a, b(2,2), p(1,1);
bool onSegment = segDist(a,b,p) < 1e-10;
```

"Point.h" d5f39f, 6 lines

```
typedef Point<double> P;
double segDist(P s, P e, P p) {
  if (s==e) return (p-s).dist();
  auto d = (e-s).dist2(), t = min(d,max(.0,(p-s).dot(e-s)));
  return ((p-s)*d-(e-s)*t).dist()/d;
}
```

SegmentIntersection.h

Description:
If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.




Usage:
```
vector<P> inter = segInter(s1,e1,s2,e2);
if (sz(inter)==1)
cout << "segments intersect at " << inter[0] << endl;
```

"Point.h", "OnSegment.h" 9d57f2, 13 lines

```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
  auto oa = c.cross(d, a), ob = c.cross(d, b),
       oc = a.cross(b, c), od = a.cross(b, d);
  // Checks if intersection is single non-endpoint point.
  if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
    return {(a * ob - b * oa) / (ob - oa)};
  set<P> s;
  if (onSegment(c, d, a)) s.insert(a);
  if (onSegment(c, d, b)) s.insert(b);
  if (onSegment(a, b, c)) s.insert(c);
  if (onSegment(a, b, d)) s.insert(d);
  return {all(s)};
}
```

lineIntersection.h

Description:
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.



Usage:
```
auto res = lineInter(s1,e1,s2,e2);
if (res.first == 1)
cout << "intersection point at " << res.second << endl;
```

"Point.h" a01f81, 8 lines

```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
  auto d = (e1 - s1).cross(e2 - s2);
  if (d == 0) // if parallel
    return {-(s1.cross(e1, s2) == 0), P(0, 0)};
  auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
  return {1, (s1 * p + e1 * q) / d};
}
```

sideOf.h

Description: Returns where p is as seen from s towards e. 1/0/-1 $\Leftrightarrow$ left/on line/right. If the optional argument *eps* is given 0 is returned if p is within distance *eps* from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.

Usage:
```
bool left = sideOf(p1,p2,q)==1;
```

"Point.h" ca4665, 9 lines

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }

template<class P>
int sideOf(P s, P e, P p, double eps) {
  auto a = (e-s).cross(p-s);
  double l = (e-s).dist()*eps;
  return (a > l) - (a < -l);
}
```

OnSegment.h


Description: Returns true iff p lies on the line segment from s to e. Use `(segDist(s,e,p)<=epsilon)` instead when using Point<double>.

"Point.h" c597e8, 3 lines

```
template<class P> bool onSegment(P s, P e, P p) {
  return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```

linearTransformation.h

Description:



Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.

"Point.h" 7871e9, 5 lines

```
typedef Point<double> P;
P linearTransformation(P p0, P p1, P q0, P q1, P r) {
  P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
  return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}
```

Angle.h

Description: A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.

Usage: `vector<Angle> v = {w[0], w[0].t360() ...}; // sorted`
`int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }`
`// sweeps j such that (j-i) represents the number of positively oriented triangles with vertices at 0 and i`

0f0602, 35 lines

```
struct Angle {
  int x, y;
  int t;
  Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
  Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
  int half() const {
    assert(x || y);
    return y < 0 || (y == 0 && x < 0);
  }
  Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
  Angle t180() const { return {-x, -y, t + half()}; }
  Angle t360() const { return {x, y, t + 1}; }
};
bool operator<(Angle a, Angle b) {
  // add a.dist2() and b.dist2() to also compare distances
  return make_tuple(a.t, a.half(), a.y * (ll)b.x) <
         make_tuple(b.t, b.half(), a.x * (ll)b.y);
}

// Given two points, this calculates the smallest angle between
// them, i.e., the angle that covers the defined line segment.
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {
  if (b < a) swap(a, b);
  return (b < a.t180() ?
          make_pair(a, b) : make_pair(b, a.t360()));
}
Angle operator+(Angle a, Angle b) { // point a + vector b
  Angle r(a.x + b.x, a.y + b.y, a.t);
  if (a.t180() < r) r.t--;
  return r.t180() < a ? r.t360() : r;
}
Angle angleDiff(Angle a, Angle b) { // angle b - angle a
  int tu = b.t - a.t; a.t = b.t;
  return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu - (b < a)};
}
```

9.2 Circles

CircleIntersection.h

Description: Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

"Point.h" 84d6d3, 11 lines

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
  if (a == b) { assert(r1 != r2); return false; }
  P vec = b - a;
  double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
         p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
  if (sum*sum < d2 || dif*dif > d2) return false;
  P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
  *out = {mid + per, mid - per};
  return true;
}
```

CircleTangents.h

Description: Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents – 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.

"Point.h" b0153d, 13 lines

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
  P d = c2 - c1;
  double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
  if (d2 == 0 || h2 < 0)  return {};
  vector<pair<P, P>> out;
  for (double sign : {-1, 1}) {
    P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
    out.push_back({c1 + v * r1, c2 + v * r2});
  }
  if (h2 == 0) out.pop_back();
  return out;
}
```

CirclePolygonIntersection.h

Description: Returns the area of the intersection of a circle with a ccw polygon.


Time: $\mathcal{O}(n)$

"../../content/geometry/Point.h" 19add1, 19 lines

```
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
  auto tri = [&](P p, P q) {
    auto r2 = r * r / 2;
    P d = q - p;
    auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
    auto det = a * a - b;
    if (det <= 0) return arg(p, q) * r2;
    auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
    if (t < 0 || 1 <= s) return arg(p, q) * r2;
    P u = p + d * s, v = q + d * (t-1);
    return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;
  };
  auto sum = 0.0;
  rep(i,0,sz(ps))
    sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);
  return sum;
}
```

circumcircle.h

Description:



The circumcirle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.

"Point.h" 6cffc5, 9 lines

```
typedef Point<double> P;
double ccRadius(P A, P B, P C) {
  return (B-A).dist()*(C-B).dist()*(A-C).dist()/
      abs((B-A).cross(C-A))/2;
}
P ccCenter(P A, P B, P C) {
  P b = C-A, c = B-A;
  return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}
```

MinimumEnclosingCircle.h

Description: Computes the minimum circle that encloses a set of points.

Time: expected $\mathcal{O}(n)$

"circumcircle.h" 09dd0a, 17 lines

```
pair<P, double> mec(vector<P> ps) {
  shuffle(all(ps), mt19937(time(0)));
  P o = ps[0];
  double r = 0, EPS = 1 + 1e-8;
  rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
    o = ps[i], r = 0;
    rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
      o = (ps[i] + ps[j]) / 2;
      r = (o - ps[i]).dist();
      rep(k,0,j) if ((o - ps[k]).dist() > r * EPS) {
        o = ccCenter(ps[i], ps[j], ps[k]);
        r = (o - ps[i]).dist();
      }
    }
  }
  return {o, r};
}
```

9.3 Polygons

InsidePolygon.h

Description: Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.

Usage: `vector<P> v = {P{4,4}, P{1,2}, P{2,1}};`
`bool in = inPolygon(v, P{3, 3}, false);`

Time: $\mathcal{O}(n)$

"Point.h", "OnSegment.h", "SegmentDistance.h" 2bf504, 11 lines

```
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
  int cnt = 0, n = sz(p);
  rep(i,0,n) {
    P q = p[(i + 1) % n];
    if (onSegment(p[i], q, a)) return !strict;
    //or: if (segDist(p[i], q, a) <= eps) return !strict;
    cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
  }
  return cnt;
}
```

PolygonArea.h

Description: Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

"Point.h" f12300, 6 lines

```
template<class T>
T polygonArea2(vector<Point<T>>& v) {
  T a = v.back().cross(v[0]);
  rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
  return a;
}
```

PolygonCenter.h

Description: Returns the center of mass for a polygon.


Time: $\mathcal{O}(n)$

"Point.h" 9706dc, 9 lines

```
typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
  P res(0, 0); double A = 0;
  for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
```

```
    res = res + (v[i] + v[j]) * v[j].cross(v[i]);
    A += v[j].cross(v[i]);
  }
  return res / A / 3;
}
```

PolygonCut.h



Description:
Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.
Usage: `vector<P> p = ...;`
`p = polygonCut(p, P(0,0), P(1,0));`

"Point.h" d07181, 13 lines

```
typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
  vector<P> res;
  rep(i,0,sz(poly)) {
    P cur = poly[i], prev = i ? poly[i-1] : poly.back();
    auto a = s.cross(e, cur), b = s.cross(e, prev);
    if ((a < 0) != (b < 0))
      res.push_back(cur + (prev - cur) * (a / (a - b)));
    if (a < 0)
      res.push_back(cur);
  }
  return res;
}
```

ConvexHull.h



Description:
Returns a vector of the points of the convex hull in counterclockwise order. Points on the edge of the hull between two other points are not considered part of the hull.
Time: $\mathcal{O}(n \log n)$

"Point.h" 310954, 13 lines

```
typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
  if (sz(pts) <= 1) return pts;
  sort(all(pts));
  vector<P> h(sz(pts)+1);
  int s = 0, t = 0;
  for (int it = 2; it--; s = --t, reverse(all(pts)))
    for (P p : pts) {
      while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
      h[t++] = p;
    }
  return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```

HullDiameter.h

Description: Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).
Time: $\mathcal{O}(n)$

"Point.h" c571b8, 12 lines

```
typedef Point<ll> P;
array<P, 2> hullDiameter(vector<P> S) {
  int n = sz(S), j = n < 2 ? 0 : 1;
  pair<ll, array<P, 2>> res({0, {S[0], S[0]}});
  rep(i,0,j)
    for (;; j = (j + 1) % n) {
      res = max(res, {(S[i] - S[j]).dist2(), {S[i], S[j]}});
      if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]) >= 0)
        break;
    }
  return res.second;
}
```

PointInsideHull.h

Description: Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.
Time: $\mathcal{O}(\log N)$

"Point.h", "sideOf.h", "OnSegment.h" 71446b, 14 lines

```
typedef Point<ll> P;

bool inHull(const vector<P>& l, P p, bool strict = true) {
  int a = 1, b = sz(l) - 1, r = !strict;
  if (sz(l) < 3) return r && onSegment(l[0], l.back(), p);
  if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
  if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b], p)<= -r)
    return false;
  while (abs(a - b) > 1) {
    int c = (a + b) / 2;
    (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
  }
  return sgn(l[a].cross(l[b], p)) < r;
}
```

LineHullIntersection.h

Description: Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon: $\bullet$ $(-1,-1)$ if no collision, $\bullet$ $(i,-1)$ if touching the corner i, $\bullet$ (i,i) if along side $(i,i+1)$, $\bullet$ (i,j) if crossing sides $(i,i+1)$ and $(j,j+1)$. In the last case, if a corner i is crossed, this is treated as happening on side $(i,i+1)$. The points are returned in the same order as the line hits the polygon. `extrVertex` returns the point of a hull with the max projection onto a line.
Time: $\mathcal{O}(\log n)$

"Point.h" 7cf45b, 39 lines

```
#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
template <class P> int extrVertex(vector<P>& poly, P dir) {
  int n = sz(poly), lo = 0, hi = n;
  if (extr(0)) return 0;
  while (lo + 1 < hi) {
    int m = (lo + hi) / 2;
    if (extr(m)) return m;
    int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
    (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi : lo) = m;
  }
  return lo;
}

#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
  int endA = extrVertex(poly, (a - b).perp());
  int endB = extrVertex(poly, (b - a).perp());
  if (cmpL(endA) < 0 || cmpL(endB) > 0)
    return {-1, -1};
  array<int, 2> res;
  rep(i,0,2) {
    int lo = endB, hi = endA, n = sz(poly);
    while ((lo + 1) % n != hi) {
      int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
      (cmpL(m) == cmpL(endB) ? lo : hi) = m;
    }
    res[i] = (lo + !cmpL(hi)) % n;
    swap(endA, endB);
  }
  if (res[0] == res[1]) return {res[0], -1};
  if (!cmpL(res[0]) && !cmpL(res[1]))
    switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {
      case 0: return {res[0], res[0]};
      case 2: return {res[1], res[1]};
    }
  return res;
}
```

9.4 Misc. Point Set Problems

ClosestPair.h

Description: Finds the closest pair of points.
Time: $\mathcal{O}(n \log n)$

"Point.h" ac41a6, 17 lines

```
typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
  assert(sz(v) > 1);
  set<P> S;
  sort(all(v), [](P a, P b) { return a.y < b.y; });
  pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
  int j = 0;
  for (P p : v) {
    P d{1 + (ll)sqrt(ret.first), 0};
    while (v[j].y <= p.y - d.x) S.erase(v[j++]);
    auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
    for (; lo != hi; ++lo)
      ret = min(ret, {(*lo - p).dist2(), {*lo, p}});
    S.insert(p);
  }
  return ret.second;
}
```

kdTree.h

Description: KD-tree (2d, can be extended to 3d)

"Point.h" 69ff55, 63 lines

```
typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();

bool on_x(P a, P b) { return a.x < b.x; }
bool on_y(P a, P b) { return a.y < b.y; }

struct Node {
  P pt; // if this is a leaf, the single point in it
  T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds
  Node *first = 0, *second = 0;

  T distance(P p) { // min squared distance to a point
    T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
    T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
    return (P(x,y) - p).dist2();
  }

  Node(vector<P>&& vp) : pt(vp[0]) {
    for (P p : vp) {
      x0 = min(x0, p.x); x1 = max(x1, p.x);
      y0 = min(y0, p.y); y1 = max(y1, p.y);
    }
    if (vp.size() > 1) {
      // split on x if width >= height (not ideal...)
      sort(all(vp), x1 - x0 >= y1 - y0 ? on_x : on_y);
      // divide by taking half the array for each child (not
      // best performance with many duplicates in the middle)
      int half = sz(vp)/2;
      first = new Node({vp.begin(), vp.begin() + half});
      second = new Node({vp.begin() + half, vp.end()});
    }
  }
};

struct KDTree {
  Node* root;
  KDTree(const vector<P>& vp) : root(new Node({all(vp)})) {}
```

```
  pair<T, P> search(Node *node, P p) {
    if (!node->first) {
      // uncomment if we should not find the point itself:
      // if (p == node->pt) return {INF, P()};
      return make_pair((p - node->pt).dist2(), node->pt);
    }

    Node *f = node->first, *s = node->second;
    T bfirst = f->distance(p), bsec = s->distance(p);
    if (bfirst > bsec) swap(bsec, bfirst), swap(f, s);

    // search closest side first, other side if needed
    auto best = search(f, p);
    if (bsec < best.first)
      best = min(best, search(s, p));
    return best;
  }

  // find nearest point to a point, and its squared distance
  // (requires an arbitrary operator< for Point)
  pair<T, P> nearest(P p) {
    return search(root, p);
  }
};
```

FastDelaunay.h

Description: Fast Delaunay triangulation. Each circumcircle contains none of the input points. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in 'circ'. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ... }, all counter-clockwise.
Time: $\mathcal{O}(n \log n)$

"Point.h" eefdf5, 88 lines

```
typedef Point<ll> P;
typedef struct Quad* Q;
typedef __int128_t lll; // (can be ll if coords are < 2e4)
P arb(LLONG_MAX,LLONG_MAX); // not equal to any other point

struct Quad {
  Q rot, o; P p = arb; bool mark;
  P& F() { return r()->p; }
  Q& r() { return rot->rot; }
  Q prev() { return rot->o->rot; }
  Q next() { return r()->prev(); }
} *H;

bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
  lll p2 = p.dist2(), A = a.dist2()-p2,
      B = b.dist2()-p2, C = c.dist2()-p2;
  return p.cross(a,b)*C + p.cross(b,c)*A + p.cross(c,a)*B > 0;
}
Q makeEdge(P orig, P dest) {
  Q r = H ? H : new Quad{new Quad{new Quad{new Quad{0}}}};
  H = r->o; r->r()->r() = r;
  rep(i,0,4) r = r->rot, r->p = arb, r->o = i & 1 ? r : r->r();
  r->p = orig; r->F() = dest;
  return r;
}
void splice(Q a, Q b) {
  swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
}
Q connect(Q a, Q b) {
  Q q = makeEdge(a->F(), b->p);
  splice(q, a->next());
  splice(q->r(), b);
  return q;
}
pair<Q,Q> rec(const vector<P>& s) {
  if (sz(s) <= 3) {
    Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
    if (sz(s) == 2) return { a, a->r() };
    splice(a->r(), b);
    auto side = s[0].cross(s[1], s[2]);
    Q c = side ? connect(b, a) : 0;
    return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
  }

#define H(e) e->F(), e->p
#define valid(e) (e->F().cross(H(base)) > 0)
  Q A, B, ra, rb;
  int half = sz(s) / 2;
  tie(ra, A) = rec({all(s) - half});
  tie(B, rb) = rec({sz(s) - half + all(s)});
  while ((B->p.cross(H(A)) < 0 && (A = A->next())) ||
         (A->p.cross(H(B)) > 0 && (B = B->r()->o)));
  Q base = connect(B->r(), A);
  if (A->p == ra->p) ra = base->r();
  if (B->p == rb->p) rb = base;

#define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
    while (circ(e->dir->F(), H(base), e->F())) { \
      Q t = e->dir; \
      splice(e, e->prev()); \
      splice(e->r(), e->r()->prev()); \
      e->o = H; H = e; e = t; \
    }
  for (;;) {
    DEL(LC, base->r(), o);  DEL(RC, base, prev());
    if (!valid(LC) && !valid(RC)) break;
    if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
      base = connect(RC, base->r());
    else
      base = connect(base->r(), LC->r());
  }
  return { ra, rb };
}

vector<P> triangulate(vector<P> pts) {
  sort(all(pts));  assert(unique(all(pts)) == pts.end());
  if (sz(pts) < 2) return {};
  Q e = rec(pts).first;
  vector<Q> q = {e};
  int qi = 0;
  while (e->o->F().cross(e->F(), e->p) < 0) e = e->o;
#define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
  q.push_back(c->r()); c = c->next(); } while (c != e); }
  ADD; pts.clear();
  while (qi < sz(q)) if (!(e = q[qi++])->mark) ADD;
  return pts;
}
```

9.5 3D

PolyhedronVolume.h

Description: Magic formula for the volume of a polyhedron. Faces should point outwards.

3058c3, 6 lines

```
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilist) {
  double v = 0;
  for (auto i : trilist) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
  return v / 6;
}
```

Point3D.h

Description: Class to handle points in 3D space. T can be e.g. double or long long.

a94b7c, 31 lines

```
template<class T> struct Point3D {
  typedef Point3D P;
  T x, y, z;
  explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
  bool operator<(P p) const {
    return tie(x, y, z) < tie(p.x, p.y, p.z); }
  bool operator==(P p) const {
    return tie(x, y, z) == tie(p.x, p.y, p.z); }
  P operator+(P p) const { return P(x+p.x, y+p.y, z+p.z); }
  P operator-(P p) const { return P(x-p.x, y-p.y, z-p.z); }
  P operator*(T d) const { return P(x*d, y*d, z*d); }
  P operator/(T d) const { return P(x/d, y/d, z/d); }
  T dot(P p) const { return x*p.x + y*p.y + z*p.z; }
  P cross(P p) const {
    return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x);
  }
  T dist2() const { return x*x + y*y + z*z; }
  double dist() const { return sqrt((double)dist2()); }
  //Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
  double phi() const { return atan2(y, x); }
  //Zenith angle (latitude) to the z-axis in interval [0, pi]
  double theta() const { return atan2(sqrt(x*x+y*y),z); }
  P unit() const { return *this/(T)dist(); } //makes dist()=1
  //returns unit vector normal to *this and p
  P normal(P p) const { return cross(p).unit(); }
  //returns point rotated 'angle' radians ccw around axis
  P rotate(double angle, P axis) const {
    double s = sin(angle), c = cos(angle); P u = axis.unit();
    return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
  }
};
```

3dHull.h

Description: Computes all faces of the 3-dimension hull of a point set. *No four points must be coplanar*, or else random results will be returned. All faces will point outwards.
Time: $\mathcal{O}(n^2)$

"Point3D.h" 5b45fc, 49 lines

```
typedef Point3D<double> P3;

struct PR {
  void ins(int x) { (a == -1 ? a : b) = x; }
  void rem(int x) { (a == x ? a : b) = -1; }
  int cnt() { return (a != -1) + (b != -1); }
  int a, b;
};

struct F { P3 q; int a, b, c; };

vector<F> hull3d(const vector<P3>& A) {
  assert(sz(A) >= 4);
  vector<vector<PR>> E(sz(A), vector<PR>(sz(A), {-1, -1}));
#define E(x,y) E[f.x][f.y]
  vector<F> FS;
  auto mf = [&](int i, int j, int k, int l) {
    P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
    if (q.dot(A[l]) > q.dot(A[i]))
      q = q * -1;
    F f{q, i, j, k};
    E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
    FS.push_back(f);
  };
  rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
    mf(i, j, k, 6 - i - j - k);
```

```
  rep(i,4,sz(A)) {
    rep(j,0,sz(FS)) {
      F f = FS[j];
      if(f.q.dot(A[i]) > f.q.dot(A[f.a])) {
        E(a,b).rem(f.c);
        E(a,c).rem(f.b);
        E(b,c).rem(f.a);
        swap(FS[j--], FS.back());
        FS.pop_back();
      }
    }
    int nw = sz(FS);
    rep(j,0,nw) {
      F f = FS[j];
#define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
      C(a, b, c); C(a, c, b); C(b, c, a);
    }
  }
  for (F& it : FS) if ((A[it.b] - A[it.a]).cross(
    A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
  return FS;
};
```

sphericalDistance.h

Description: Returns the shortest distance on the sphere with radius radius between the points with azimuthal angles (longitude) f1 (ϕ_1) and f2 (ϕ_2) from x axis and zenith angles (latitude) t1 (θ_1) and t2 (θ_2) from z axis (0 = north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows. dx*radius is then the difference between the two points in the x direction and d*radius is the total distance between the points.

611f07, 8 lines

```
double sphericalDistance(double f1, double t1,
    double f2, double t2, double radius) {
  double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
  double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
  double dz = cos(t2) - cos(t1);
  double d = sqrt(dx*dx + dy*dy + dz*dz);
  return radius*2*asin(d/2);
}
```

Various (10)

10.1 Intervals

IntervalContainer.h

Description: Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).
Time: $\mathcal{O}(\log N)$

edce47, 23 lines

```
set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
  if (L == R) return is.end();
  auto it = is.lower_bound({L, R}), before = it;
  while (it != is.end() && it->first <= R) {
    R = max(R, it->second);
    before = it = is.erase(it);
  }
  if (it != is.begin() && (--it)->second >= L) {
    L = min(L, it->first);
    R = max(R, it->second);
    is.erase(it);
  }
  return is.insert(before, {L,R});
}

void removeInterval(set<pii>& is, int L, int R) {
  if (L == R) return;
  auto it = addInterval(is, L, R);
  auto r2 = it->second;
  if (it->first == L) is.erase(it);
  else (int&)it->second = L;
  if (R != r2) is.emplace(R, r2);
}
```

IntervalCover.h

Description: Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add `|| R.empty()`. Returns empty set on failure (or if G is empty).
Time: $\mathcal{O}(N \log N)$

9e9d8d, 19 lines

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
  vi S(sz(I)), R;
  iota(all(S), 0);
  sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
  T cur = G.first;
  int at = 0;
  while (cur < G.second) { // (A)
    pair<T, int> mx = make_pair(cur, -1);
    while (at < sz(I) && I[S[at]].first <= cur) {
      mx = max(mx, make_pair(I[S[at]].second, S[at]));
      at++;
    }
    if (mx.second == -1) return {};
    cur = mx.first;
    R.push_back(mx.second);
  }
  return R;
}
```

ConstantIntervals.h

Description: Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.
Usage: `constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});`
Time: $\mathcal{O}\left(k \log \frac{n}{k}\right)$

753a4c, 19 lines

```
template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
  if (p == q) return;
  if (from == to) {
    g(i, to, p);
    i = to; p = q;
  } else {
    int mid = (from + to) >> 1;
    rec(from, mid, f, g, i, p, f(mid));
    rec(mid+1, to, f, g, i, p, q);
  }
}
template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
  if (to <= from) return;
  int i = from; auto p = f(i), q = f(to-1);
  rec(from, to-1, f, g, i, p, q);
  g(i, to, q);
}
```

10.2 Misc. algorithms

TernarySearch.h

Description: Find the smallest i in $[a, b]$ that maximizes $f(i)$, assuming that $f(a) < \ldots < f(i) \geq \cdots \geq f(b)$. To reverse which of the sides allows non-strict inequalities, change the < marked with (A) to <=, and reverse the loop at (B). To minimize f, change it to >, also at (B).
Usage: `int ind = ternSearch(0,n-1,[&](int i){return a[i];});`
Time: $\mathcal{O}(\log(b-a))$

9155b4, 11 lines

```
template<class F>
int ternSearch(int a, int b, F f) {
  assert(a <= b);
  while (b - a >= 5) {
    int mid = (a + b) / 2;
    if (f(mid) < f(mid+1)) a = mid; // (A)
    else b = mid+1;
  }
  rep(i,a+1,b+1) if (f(a) < f(i)) a = i; // (B)
  return a;
}
```

LIS.h

Description: Compute indices for the longest increasing subsequence.
Time: $\mathcal{O}(N \log N)$

2932a0, 17 lines

```
template<class I> vi lis(const vector<I>& S) {
  if (S.empty()) return {};
  vi prev(sz(S));
  typedef pair<I, int> p;
  vector<p> res;
  rep(i,0,sz(S)) {
    // change 0 -> i for longest non-decreasing subsequence
    auto it = lower_bound(all(res), p{S[i], 0});
    if (it == res.end()) res.emplace_back(), it = res.end()-1;
    *it = {S[i], i};
    prev[i] = it == res.begin() ? 0 : (it-1)->second;
  }
  int L = sz(res), cur = res.back().second;
  vi ans(L);
  while (L--) ans[L] = cur, cur = prev[cur];
  return ans;
}
```

FastKnapsack.h

Description: Given N non-negative integer weights w and a non-negative target t, computes the maximum S <= t such that S is the sum of some subset of the weights.
Time: $\mathcal{O}(N \max(w_i))$

b20ccc, 16 lines

```
int knapsack(vi w, int t) {
  int a = 0, b = 0, x;
  while (b < sz(w) && a + w[b] <= t) a += w[b++];
  if (b == sz(w)) return a;
  int m = *max_element(all(w));
  vi u, v(2*m, -1);
  v[a+m-t] = b;
  rep(i,b,sz(w)) {
    u = v;
    rep(x,0,m) v[x+w[i]] = max(v[x+w[i]], u[x]);
    for (x = 2*m; --x > m;) rep(j, max(0,u[x]), v[x])
      v[x-w[j]] = max(v[x-w[j]], j);
  }
  for (a = t; v[a+m-t] < 0; a--) ;
  return a;
}
```

10.3 Dynamic programming

KnuthDP.h

Description: When doing DP on intervals: $a[i][j] = \min_{i<k<j}(a[i][k] + a[k][j]) + f(i,j)$, where the (minimal) optimal k increases with both i and j, one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j-1]$ and $p[i+1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b,c) \leq f(a,d)$ and $f(a,c) + f(b,d) \leq f(a,d) + f(b,c)$ for all $a \leq b \leq c \leq d$. Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.

Time: $\mathcal{O}\left(N^2\right)$

DivideAndConquerDP.h

Description: Given $a[i] = \min_{lo(i) \le k < hi(i)}(f(i,k))$ where the (minimal) optimal k increases with i, computes $a[i]$ for $i = L..R-1$.
Time: $\mathcal{O}\left((N + (hi - lo))\log N\right)$ d38d2b, 18 lines

```
struct DP { // Modify at will:
  int lo(int ind) { return 0; }
  int hi(int ind) { return ind; }
  ll f(int ind, int k) { return dp[ind][k]; }
  void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

  void rec(int L, int R, int LO, int HI) {
    if (L >= R) return;
    int mid = (L + R) >> 1;
    pair<ll, int> best(LLONG_MAX, LO);
    rep(k, max(LO,lo(mid)), min(HI,hi(mid)))
      best = min(best, make_pair(f(mid, k), k));
    store(mid, best.second, best.first);
    rec(L, mid, LO, best.second+1);
    rec(mid+1, R, best.second, HI);
  }
  void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

10.4 Debugging tricks

- `signal(SIGSEGV, [](int) { _Exit(0); });` converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). `_GLIBCXX_DEBUG` failures generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- `feenableexcept(29);` kills the program on NaNs (1), 0-divs (4), infinities (8) and denormals (16).

10.5 Optimization tricks

`__builtin_ia32_ldmxcsr(40896);` disables denormals (which make floats 20x slower near their minimum value).

10.5.1 Bit hacks

- `x & -x` is the least bit in `x`.
- `for (int x = m; x; ) { --x &= m; ... }` loops over all subset masks of `m` (except `m` itself).
- `c = x&-x, r = x+c; (((r^x) >> 2)/c) | r` is the next number after `x` with the same number of bits set.
- `rep(b,0,K) rep(i,0,(1 << K)) if (i & 1 << b) D[i] += D[i^(1 << b)];` computes all sums of subsets.

10.5.2 Pragmas

- `#pragma GCC optimize ("Ofast")` will make GCC auto-vectorize loops and optimizes floating points better.
- `#pragma GCC target ("avx2")` can double performance of vectorized code, but causes crashes on old machines.
- `#pragma GCC optimize ("trapv")` kills the program on integer overflows (but is really slow).

FastMod.h

Description: Compute $a\%b$ about 5 times faster than usual, where b is constant but not known at compile time. Returns a value congruent to a (mod b) in the range $[0, 2b)$. 751a02, 8 lines

```
typedef unsigned long long ull;
struct FastMod {
  ull b, m;
  FastMod(ull b) : b(b), m(-1ULL / b) {}
  ull reduce(ull a) { // a % b + (0 or b)
    return a - (ull)((__uint128_t(m) * a) >> 64) * b;
  }
};
```

FastInput.h

Description: Read an integer from stdin. Usage requires your program to pipe in input from file.
Usage: `./a.out < input.txt`
Time: About 5x as fast as cin/scanf. 7b3c70, 17 lines

```
inline char gc() { // like getchar()
  static char buf[1 << 16];
  static size_t bc, be;
  if (bc >= be) {
    buf[0] = 0, bc = 0;
    be = fread(buf, 1, sizeof(buf), stdin);
  }
  return buf[bc++]; // returns 0 on EOF
}

int readInt() {
  int a, c;
  while ((a = gc()) < 40);
  if (a == '-') return -readInt();
  while ((c = gc()) >= 48) a = a * 10 + c - 480;
  return a - 48;
}
```

BumpAllocator.h

Description: When you need to dynamically allocate many objects and don't care about freeing them. "new X" otherwise has an overhead of something like 0.05us + 16 bytes per allocation. 745db2, 8 lines

```
// Either globally or in a single class:
static char buf[450 << 20];
void* operator new(size_t s) {
  static size_t i = sizeof buf;
  assert(s < i);
  return (void*)&buf[i -= s];
}
void operator delete(void*) {}
```

SmallPtr.h

Description: A 32-bit pointer that points into BumpAllocator memory.
"BumpAllocator.h" 2dd6c9, 10 lines

```
template<class T> struct ptr {
  unsigned ind;
  ptr(T* p = 0) : ind(p ? unsigned((char*)p - buf) : 0) {
    assert(ind < sizeof buf);
  }
  T& operator*() const { return *(T*)(buf + ind); }
  T* operator->() const { return &**this; }
  T& operator[](int a) const { return (&**this)[a]; }
  explicit operator bool() const { return ind; }
};
```

BumpAllocatorSTL.h

Description: BumpAllocator for STL containers.
Usage: `vector<vector<int, small<int>>> ed(N);` bb66d4, 14 lines

```
char buf[450 << 20] alignas(16);
size_t buf_ind = sizeof buf;

template<class T> struct small {
  typedef T value_type;
  small() {}
  template<class U> small(const U&) {}
  T* allocate(size_t n) {
    buf_ind -= n * sizeof(T);
    buf_ind &= 0 - alignof(T);
    return (T*)(buf + buf_ind);
  }
  void deallocate(T*, size_t) {}
};
```

SIMD.h

Description: Cheat sheet of SSE/AVX intrinsics, for doing arithmetic on several numbers at once. Can provide a constant factor improvement of about 4, orthogonal to loop unrolling. Operations follow the pattern "_mm(256)?_name_(si(128|256)|epi(8|16|32|64)|pd|ps)". Not all are described here; grep for _mm_ in /usr/lib/gcc/*/4.9/include/ for more. If AVX is unsupported, try 128-bit operations, "emmintrin.h" and #define __SSE__ and __MMX__ before including it. For aligned memory use _mm_malloc(size, 32) or int buf[N] alignas(32), but prefer loadu/storeu. 551b82, 43 lines

```
#pragma GCC target ("avx2") // or sse4.1
#include "immintrin.h"

typedef __m256i mi;
#define L(x) _mm256_loadu_si256((mi*)&(x))

// High-level/specific methods:
// load(u)?_si256, store(u)?_si256, setzero_si256, _mm_malloc
// blendv_(epi8|ps|pd) (z?y:x), movemask_epi8 (hibits of bytes)
// i32gather_epi32(addr, x, 4): map addr[] over 32-b parts of x
// sad_epu8: sum of absolute differences of u8, outputs 4xi64
// maddubs_epi16: dot product of unsigned i7's, outputs 16xi15
// madd_epi16: dot product of signed i16's, outputs 8xi32
// extractf128_si256(, i) (256->128), cvtsi128_si32 (128->lo32)
// permute2f128_si256(x,x,1) swaps 128-bit lanes
// shuffle_epi32(x, 3*64+2*16+1*4+0) == x for each lane
// shuffle_epi8(x, y) takes a vector instead of an imm

// Methods that work with most data types (append e.g. _epi32):
// set1, blend (i8?x:y), add, adds (sat.), mullo, sub, and/or,
// andnot, abs, min, max, sign(1,x), cmp(gt|eq), unpack(lo|hi)

int sumi32(mi m) { union {int v[8]; mi m;} u; u.m = m;
  int ret = 0; rep(i,0,8) ret += u.v[i]; return ret; }
mi zero() { return _mm256_setzero_si256(); }
mi one() { return _mm256_set1_epi32(-1); }
bool all_zero(mi m) { return _mm256_testz_si256(m, m); }
bool all_one(mi m) { return _mm256_testc_si256(m, one()); }

ll example_filteredDotProduct(int n, short* a, short* b) {
  int i = 0; ll r = 0;
  mi zero = _mm256_setzero_si256(), acc = zero;
  while (i + 16 <= n) {
    mi va = L(a[i]), vb = L(b[i]); i += 16;
    va = _mm256_and_si256(_mm256_cmpgt_epi16(vb, va), va);
    mi vp = _mm256_madd_epi16(va, vb);
    acc = _mm256_add_epi64(_mm256_unpacklo_epi32(vp, zero),
      _mm256_add_epi64(acc, _mm256_unpackhi_epi32(vp, zero)));
  }
  union {ll v[4]; mi m;} u; u.m = acc; rep(i,0,4) r += u.v[i];
```

```
  for (;i<n;++i) if (a[i] < b[i]) r += a[i]*b[i]; // <— equiv
  return r;
}
```

Techniques (A)

techniques.txt 159 lines

```
Recursion
Divide and conquer
  Finding interesting points in N log N
Algorithm analysis
  Master theorem
  Amortized time complexity
Greedy algorithm
  Scheduling
  Max contiguous subvector sum
  Invariants
  Huffman encoding
Graph theory
  Dynamic graphs (extra book-keeping)
  Breadth first search
  Depth first search
  * Normal trees / DFS trees
  Dijkstra's algorithm
  MST: Prim's algorithm
  Bellman-Ford
  Konig's theorem and vertex cover
  Min-cost max flow
  Lovasz toggle
  Matrix tree theorem
  Maximal matching, general graphs
  Hopcroft-Karp
  Hall's marriage theorem
  Graphical sequences
  Floyd-Warshall
  Euler cycles
  Flow networks
  * Augmenting paths
  * Edmonds-Karp
  Bipartite matching
  Min. path cover
  Topological sorting
  Strongly connected components
  2-SAT
  Cut vertices, cut-edges and biconnected components
  Edge coloring
  * Trees
  Vertex coloring
  * Bipartite graphs (=> trees)
  * 3^n (special case of set cover)
  Diameter and centroid
  K'th shortest path
  Shortest cycle
Dynamic programming
  Knapsack
  Coin change
  Longest common subsequence
  Longest increasing subsequence
  Number of paths in a dag
  Shortest path in a dag
  Dynprog over intervals
  Dynprog over subsets
  Dynprog over probabilities
  Dynprog over trees
  3^n set cover
  Divide and conquer
  Knuth optimization
  Convex hull optimizations
  RMQ (sparse table a.k.a 2^k-jumps)
  Bitonic cycle
  Log partitioning (loop over most restricted)
Combinatorics
  Computation of binomial coefficients
  Pigeon-hole principle
  Inclusion/exclusion
  Catalan number
  Pick's theorem
Number theory
  Integer parts
  Divisibility
  Euclidean algorithm
  Modular arithmetic
  * Modular multiplication
  * Modular inverses
  * Modular exponentiation by squaring
  Chinese remainder theorem
  Fermat's little theorem
  Euler's theorem
  Phi function
  Frobenius number
  Quadratic reciprocity
  Pollard-Rho
  Miller-Rabin
  Hensel lifting
  Vieta root jumping
Game theory
  Combinatorial games
  Game trees
  Mini-max
  Nim
  Games on graphs
  Games on graphs with loops
  Grundy numbers
  Bipartite games without repetition
  General games without repetition
  Alpha-beta pruning
Probability theory
Optimization
  Binary search
  Ternary search
  Unimodality and convex functions
  Binary search on derivative
Numerical methods
  Numeric integration
  Newton's method
  Root-finding with binary/ternary search
  Golden section search
Matrices
  Gaussian elimination
  Exponentiation by squaring
Sorting
  Radix sort
Geometry
  Coordinates and vectors
  * Cross product
  * Scalar product
  Convex hull
  Polygon cut
  Closest pair
  Coordinate-compression
  Quadtrees
  KD-trees
  All segment-segment intersection
Sweeping
  Discretization (convert to events and sweep)
  Angle sweeping
  Line sweeping
  Discrete second derivatives
Strings
  Longest common substring
  Palindrome subsequences
  Knuth-Morris-Pratt
  Tries
  Rolling polynomial hashes
  Suffix array
  Suffix tree
  Aho-Corasick
  Manacher's algorithm
  Letter position lists
Combinatorial search
  Meet in the middle
  Brute-force with pruning
  Best-first (A*)
  Bidirectional search
  Iterative deepening DFS / A*
Data structures
  LCA (2^k-jumps in trees in general)
  Pull/push-technique on trees
  Heavy-light decomposition
  Centroid decomposition
  Lazy propagation
  Self-balancing trees
  Convex hull trick (wcipeg.com/wiki/Convex_hull_trick)
  Monotone queues / monotone stacks / sliding queues
  Sliding queue using 2 stacks
  Persistent segment tree
```