

CCNA – RIPv2 Commands

Basic RIPv2 Commands

Enabling the RIPv2 process

```
Router(config)# router rip  
Router(config-router)# version 1|2
```

Enabling the RIP on an interface

```
Router(config-router)# network network
```

Summarization Commands

RIPv2 Commands

```
Router(config-router)# no auto-summary
```

- Like RIPv1, RIPv2 automatically summarizes at major network boundaries.
- This command turns off automatic summarization, useful for discontinuous networks.
- This command can only be used with RIPv2, and not with RIPv1.

Extra: Interface Commands for summarization

```
Router(config-if)# ip summary-address rip ip-address ip_network_mask
```

Propagating a Default Route

```
Router(config)# ip route 0.0.0.0 0.0.0.0 exit-interface|next hop ip-address
```

```
Router(config)# router rip
```

```
Router(config-router)# default-information originate
```

- Required starting with IOS 12.1

Passive Interface

```
Router(config)# router rip
```

```
Router(config-router)# passive-interface interface number
```

Basic RIPng Commands

Enable device IPv6 unicast forwarding

```
Router(config)# ipv6 unicast-routing
```

Enter IPv6 RIP router configuration mode

```
router(config)#ipv6 router rip process-name
```

Enter interface configuration mode

```
router(config)#interface interface
```

Enable RIPng on the interface

```
router(config-if)#ipv6 rip process-name enable
```