




NATIONAL UNIVERSITY OF SCIENCE AND TECHNOLOGY

DEPARTMENT OF COMPUTER SCIENCE

COMPUTER NETWORKS LAB

Name	Ayesha Imran
Class	CS-A
Lab	OEL 2
Course	Computer Networks
Date	18 th -December-25
Submitted To	Lec. Naveed Yousaf
Lab Instructor	Lec. Naveed Ahmed

Topology:



CS ROUTER:

```
Router>enable
Router#config ter
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int fa0/0
Router(config-if)#ip address 192.168.10.1 255.255.255.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
exit
Router(config)#int se2/0
Router(config-if)#ip address 11.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface Serial2/0, changed state to down
Router(config-if)#exit
Router(config)#int se3/0
Router(config-if)#ip address 10.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface Serial3/0, changed state to down
Router(config-if)#exit
Router(config)#router rip
Router(config-router)#network 192.168.10.0
Router(config-router)#network 10.0.0.0
Router(config-router)#network 11.0.0.0
Router(config-router)#exit
Router(config)#
%LINK-5-CHANGED: Interface Serial2/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up

%LINK-5-CHANGED: Interface Serial3/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial3/0, changed state to up
```

AI ROUTER:

```

Router>enable
Router#config ter
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#int fa0/0
Router(config-if)#ip address 192.168.11.1 255.255.255.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
exit
Router(config)#int se2/0
Router(config-if)#ip address 11.0.0.2 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface Serial2/0, changed state to up

Router(config-if)#exit
Router(config)#
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up

Router(config)#int se3/0
Router(config-if)#ip address 12.0.0.1 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface Serial3/0, changed state to down
Router(config-if)#exit
Router(config)#router rip
Router(config-router)#network 192.168.11.0
Router(config-router)#network 11.0.0.0
Router(config-router)#network 12.0.0.0
Router(config-router)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG-I: Configured from console by console

```

IT ROUTER:

```

Router>enable
Router#config ter
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int fa0/0
Router(config-if)#ip address 192.168.12.1 255.255.255.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

Router(config-if)#exit
Router(config)#int se2/0
Router(config-if)#ip address 12.0.0.2 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface Serial2/0, changed state to up

Router(config-if)#exit
Router(config)#int se3/0
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial2/0, changed state to up

Router(config-if)#ip address 10.0.0.2 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface Serial3/0, changed state to up

Router(config-if)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial3/0, changed state to up

```

ACL:









```

Router#config ter
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#access-list 1 permit 192.168.10.0 0.0.0.255
Router(config)#access-list 1 deny 192.168.11.0 0.0.0.255
Router(config)#interface fa0/0
Router(config-if)#ip access-group 1 in
Router(config-if)#


```

Packets:

Only CS is communicating:

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit	Delete
	Successful	Laptop0	Laptop2	ICMP		0.000	N	3	(edit)	(delete)
	Failed	Laptop0	Laptop3	ICMP		0.000	N	4	(edit)	(delete)
	Successful	Laptop0	Laptop3	ICMP		0.000	N	5	(edit)	(delete)
	Failed	Laptop2	Laptop4	ICMP		0.000	N	6	(edit)	(delete)

AI not Communication to IT department:

<div><div>🕒 Realtime</div><div>🏠 Simulation</div></div>										
Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit	Delete
	Failed	Laptop2	Laptop4	ICMP		0.000	N	6	(edit)	(delete)
	Failed	Laptop2	Laptop4	ICMP		0.000	N	7	(edit)	(delete)
	Failed	Laptop0	Laptop5	ICMP		0.000	N	8	(edit)	(delete)