Captured 2026-11-10T15:41:01Z from https://api.jellyfin.org/

Search...

- System
- Authentication
- Artist
- Audio
- Backup
- Branding
- Channel
- Collection
- Plugin
- Device
- DisplayPreference
- Environment
- Filter
- Genre
- Image
- InstantMix
- ItemLookup
- Library
- UserData
- ItemUpdate
- LibraryStructure
- LiveTv
- Localization
- Lyric
- MediaInfo
- MediaSegment
- Movie
- MusicGenre
- Person
- Playlist
- Session
- RemoteImage
- ScheduledTask
- Search
- Startup
- Studio
- Subtitle
- Suggestion
- SyncPlay
- Trailer
- TrickPlay
- Show
- User
- UserView
- Video
- Year

Jellyfin API (12.4.0)

Download OpenAPI specification: Download

System

Gets activity log entries.

AUTHORIZATIONS: *CustomAuthentication*

QUERY PARAMETERS

`startIndex`	integer <int32> The record index to start at. All items with a lower index will be dropped from the results.
`limit`	integer <int32> The maximum number of records to return.
`minDate`	string <date-time> The minimum date.
`maxDate`	string <date-time> The maximum date.
`hasUserId`	boolean Filter log entries if it has user id, or not.
`name`	string Filter by name.
`overview`	string Filter by overview.
`shortOverview`	string Filter by short overview.
`type`	string Filter by type.
`itemId`	string <uuid> Filter by item id.
`username`	string Filter by username.
`severity`	string Enum: `"Trace"` `"Debug"` `"Information"` `"Warning"` `"Error"` `"Critical"` `"None"` Filter by log severity.
`sortBy`	Array of strings (ActivityLogSortBy) Items Enum: `"Name"` `"Overiew"` `"ShortOverview"` `"Type"` `"DateCreated"` `"Username"` `"LogSeverity"` Specify one or more sort orders. Format: SortBy=Name,Type.
`sortOrder`	Array of strings (SortOrder) Items Enum: `"Ascending"` `"Descending"` Sort Order..

Responses

- **200** Activity log returned.
- **401** Unauthorized
- **403** Forbidden
- **503** The server is currently starting or is temporarily not available.

GET `/System/ActivityLog/Entries`

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
  - "Items": [
      + { … }
    ],
    "TotalRecordCount": 0,
    "StartIndex": 0
}
```

Upload a document.

AUTHORIZATIONS: *CustomAuthentication*

REQUEST BODY SCHEMA: text/plain

string <binary>

Responses

- **200** Document saved.
- **401** Unauthorized
- **403** Event logging disabled.
- **413** Upload size too large.
- **503** The server is currently starting or is temporarily not available.

POST `/ClientLog/Document`

Response samples

200 403 413

Content type
application/json

Copy

```
{
    "FileName": "string"
}
```

Gets application configuration.

AUTHORIZATIONS: *CustomAuthentication*

Responses

- **200** Application configuration returned.
- **401** Unauthorized
- **403** Forbidden
- **503** The server is currently starting or is temporarily not available.

GET `/System/Configuration`

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "LogFileRetentionDays": 0,
    "IsStartupWizardCompleted": true,
    "CachePath": "string",
    "PreviousVersion": "string",
    "PreviousVersionStr": "string",
    "EnableMetrics": true,
    "EnableNormalizedItemByNameIds": true,
    "IsPortAuthorized": true,
    "QuickConnectAvailable": true,
    "EnableCaseSensitiveItemIds": true,
    "DisableLiveTvChannelUserDataName": true,
    "MetadataPath": "string",
    "PreferredMetadataLanguage": "string",
    "MetadataCountryCode": "string",
  - "SortReplaceCharacters": [
        "string"
    ],
  - "SortRemoveCharacters": [
        "string"
    ],
  - "SortRemoveWords": [
        "string"
    ],
    "MinResumePct": 0,
    "MaxResumePct": 0,
    "MinResumeDurationSeconds": 0,
    "MinAudiobookResume": 0,
    "MaxAudiobookResume": 0,
    "InactiveSessionThreshold": 0,
    "LibraryMonitorDelay": 0,
    "LibraryUpdateDuration": 0,
    "CacheSize": 0,
    "ImageSavingConvention": "Legacy",
  - "MetadataOptions": [
      + { … }
    ],
    "SkipDeserializationForBasicTypes": true,
    "ServerName": "string",
    "UICulture": "string",
    "SaveMetadataHidden": true,
  - "ContentTypes": [
      + { … }
    ],
    "RemoteClientBitrateLimit": 0,
    "EnableFolderView": true,
    "EnableGroupingMoviesIntoCollections": true,
    "EnableGroupingShowsIntoCollections": true,
    "DisplaySpecialsWithinSeasons": true,
  - "CodecsUsed": [
        "string"
    ],
  - "PluginRepositories": [
      + { … }
    ],
    "EnableExternalContentInSuggestions": true,
    "ImageExtractionTimeoutMs": 0,
  - "PathSubstitutions": [
      + { … }
    ],
    "EnableSlowResponseWarning": true,
    "SlowResponseThresholdMs": 0,
  - "CorsHosts": [
        "string"
    ],
    "ActivityLogRetentionDays": 0,
    "LibraryScanFanoutConcurrency": 0,
    "LibraryMetadataRefreshConcurrency": 0,
    "AllowClientLogUpload": true,
    "DummyChapterDuration": 0,
    "ChapterImageResolution": "MatchSource",
    "ParallelImageEncodingLimit": 0,
  - "CastReceiverApplications": [
      + { … }
    ],
  - "TrickplayOptions": {
        "EnableHwAcceleration": true,
        "EnableHwEncoding": true,
        "EnableKeyFrameOnlyExtraction": true,
        "ScanBehavior": "Blocking",
        "ProcessPriority": "Normal",
        "Interval": 0,
      + "WidthResolutions": [ … ],
        "TileWidth": 0,
        "TileHeight": 0,
        "Qscale": 0,
        "JpegQuality": 0,
        "ProcessThreads": 0
    },
    "EnableLegacyAuthorization": true
}
```

Updates application configuration.

AUTHORIZATIONS: *CustomAuthentication*

REQUEST BODY SCHEMA: application/json
required

Configuration.

`LogFileRetentionDays`	integer <int32> Gets or sets the number of days we should retain log files.
`IsStartupWizardCompleted`	boolean Gets or sets a value indicating whether this instance is first run.
`CachePath`	string or null Gets or sets the cache path.
`PreviousVersion`	string or null Gets or sets the last known version that was ran using the configuration.
`PreviousVersionStr`	string or null Gets or sets the stringified PreviousVersion to be stored/loaded, because System.Version itself isn't xml-serializable.
`EnableMetrics`	boolean Gets or sets a value indicating whether to enable prometheus metrics exporting.
`EnableNormalizedItemByNameIds`	boolean
`IsPortAuthorized`	boolean Gets or sets a value indicating whether this instance is port authorized.
`QuickConnectAvailable`	boolean Gets or sets a value indicating whether quick connect is available for use on this server.
`EnableCaseSensitiveItemIds`	boolean Gets or sets a value indicating whether [enable case-sensitive item ids].
`DisableLiveTvChannelUserDataName`	boolean
`MetadataPath`	string Gets or sets the metadata path.
`PreferredMetadataLanguage`	string Gets or sets the preferred metadata language.
`MetadataCountryCode`	string Gets or sets the metadata country code.
`SortReplaceCharacters`	Array of strings Gets or sets characters to be replaced with a ' ' in strings to create a sort name.
`SortRemoveCharacters`	Array of strings Gets or sets characters to be removed from strings to create a sort name.
`SortRemoveWords`	Array of strings Gets or sets words to be removed from strings to create a sort name.
`MinResumePct`	integer <int32> Gets or sets the minimum percentage of an item that must be played in order for playstate to be updated.
`MaxResumePct`	integer <int32> Gets or sets the maximum percentage of an item that can be played while still saving playstate. If this percentage is crossed playstate will be reset to the beginning and the item will be marked watched.
`MinResumeDurationSeconds`	integer <int32> Gets or sets the minimum duration that an item must have in order to be eligible for playstate updates..
`MinAudiobookResume`	integer <int32> Gets or sets the minimum minutes of a book that must be played in order for playstate to be updated.
`MaxAudiobookResume`	integer <int32> Gets or sets the remaining minutes of a book that can be played while still saving playstate. If this percentage is crossed playstate will be reset to the beginning and the item will be marked watched.
`InactiveSessionThreshold`	integer <int32> Gets or sets the threshold in minutes after a inactive session gets closed automatically. If set to 0 the check for inactive sessions gets disabled.
`LibraryMonitorDelay`	integer <int32> Gets or sets the delay in seconds that we will wait after a file system change to try and discover what has been added/removed Some delay is necessary with some items because their creation is not atomic. It involves the creation of several different directories and files.
`LibraryUpdateDuration`	integer <int32> Gets or sets the duration in seconds that we will wait after a library updated event before executing the library changed notification.
`CacheSize`	integer <int32> Gets or sets the maximum amount of items to cache.
`ImageSavingConvention`	string Enum: `"Legacy"` `"Compatible"` Gets or sets the image saving convention.
`MetadataOptions` ›	Array of objects (MetadataOptions)
`SkipDeserializationForBasicTypes`	boolean
`ServerName`	string
`UICulture`	string
`SaveMetadataHidden`	boolean
`ContentTypes` ›	Array of objects (NameValuePair)
`RemoteClientBitrateLimit`	integer <int32>
`EnableFolderView`	boolean
`EnableGroupingMoviesIntoCollections`	boolean
`EnableGroupingShowsIntoCollections`	boolean
`DisplaySpecialsWithinSeasons`	boolean
`CodecsUsed`	Array of strings
`PluginRepositories` ›	Array of objects (RepositoryInfo)
`EnableExternalContentInSuggestions`	boolean
`ImageExtractionTimeoutMs`	integer <int32>
`PathSubstitutions` ›	Array of objects (PathSubstitution)
`EnableSlowResponseWarning`	boolean Gets or sets a value indicating whether slow server responses should be logged as a warning.
`SlowResponseThresholdMs`	integer <int64> Gets or sets the threshold for the slow response time warning in ms.
`CorsHosts`	Array of strings Gets or sets the cors hosts.
`ActivityLogRetentionDays`	integer or null <int32> Gets or sets the number of days we should retain activity logs.
`LibraryScanFanoutConcurrency`	integer <int32> Gets or sets the how the library scan fans out.
`LibraryMetadataRefreshConcurrency`	integer <int32> Gets or sets the how many metadata refreshes can run concurrently.
`AllowClientLogUpload`	boolean Gets or sets a value indicating whether clients should be allowed to upload logs.
`DummyChapterDuration`	integer <int32> Gets or sets the dummy chapter duration in seconds, use 0 (zero) or less to disable generation altogether.
`ChapterImageResolution`	string Enum: `"MatchSource"` `"P144"` `"P240"` `"P360"` `"P480"` `"P720"` `"P1080"` `"P1440"` `"P2160"` Gets or sets the chapter image resolution.
`ParallelImageEncodingLimit`	integer <int32> Gets or sets the limit for parallel image encoding.
`CastReceiverApplications` ›	Array of objects (CastReceiverApplication) Gets or sets the list of cast receiver applications.
`TrickplayOptions` ›	object Gets or sets the trickplay options.
`EnableLegacyAuthorization`	boolean Gets or sets a value indicating whether old authorization methods are allowed.

Responses

- **204** Configuration updated.
- **401** Unauthorized
- **403** Forbidden
- **503** The server is currently starting or is temporarily not available.

POST `/System/Configuration`

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
    "LogFileRetentionDays": 0,
    "IsStartupWizardCompleted": true,
    "CachePath": "string",
    "PreviousVersion": "string",
    "PreviousVersionStr": "string",
    "EnableMetrics": true,
    "EnableNormalizedItemByNameIds": true,
    "IsPortAuthorized": true,
    "QuickConnectAvailable": true,
    "EnableCaseSensitiveItemIds": true,
    "DisableLiveTvChannelUserDataName": true,
    "MetadataPath": "string",
    "PreferredMetadataLanguage": "string",
    "MetadataCountryCode": "string",
  - "SortReplaceCharacters": [
        "string"
    ],
  - "SortRemoveCharacters": [
        "string"
    ],
  - "SortRemoveWords": [
        "string"
    ],
    "MinResumePct": 0,
    "MaxResumePct": 0,
    "MinResumeDurationSeconds": 0,
    "MinAudiobookResume": 0,
    "MaxAudiobookResume": 0,
    "InactiveSessionThreshold": 0,
    "LibraryMonitorDelay": 0,
    "LibraryUpdateDuration": 0,
    "CacheSize": 0,
    "ImageSavingConvention": "Legacy",
  - "MetadataOptions": [
      + { … }
    ],
    "SkipDeserializationForBasicTypes": true,
    "ServerName": "string",
    "UICulture": "string",
    "SaveMetadataHidden": true,
  - "ContentTypes": [
      + { … }
    ],
    "RemoteClientBitrateLimit": 0,
    "EnableFolderView": true,
    "EnableGroupingMoviesIntoCollections": true,
    "EnableGroupingShowsIntoCollections": true,
    "DisplaySpecialsWithinSeasons": true,
  - "CodecsUsed": [
        "string"
    ],
  - "PluginRepositories": [
      + { … }
    ],
    "EnableExternalContentInSuggestions": true,
    "ImageExtractionTimeoutMs": 0,
  - "PathSubstitutions": [
      + { … }
    ],
    "EnableSlowResponseWarning": true,
    "SlowResponseThresholdMs": 0,
  - "CorsHosts": [
        "string"
    ],
    "ActivityLogRetentionDays": 0,
    "LibraryScanFanoutConcurrency": 0,
    "LibraryMetadataRefreshConcurrency": 0,
    "AllowClientLogUpload": true,
    "DummyChapterDuration": 0,
    "ChapterImageResolution": "MatchSource",
    "ParallelImageEncodingLimit": 0,
  - "CastReceiverApplications": [
      + { … }
    ],
  - "TrickplayOptions": {
        "EnableHwAcceleration": true,
        "EnableHwEncoding": true,
        "EnableKeyFrameOnlyExtraction": true,
        "ScanBehavior": "Blocking",
        "ProcessPriority": "Normal",
        "Interval": 0,
      + "WidthResolutions": [ … ],
        "TileWidth": 0,
        "TileHeight": 0,
        "Qscale": 0,
        "JpegQuality": 0,
        "ProcessThreads": 0
    },
    "EnableLegacyAuthorization": true
}
```

Gets a named configuration.

AUTHORIZATIONS: *CustomAuthentication*

PATH PARAMETERS

`key` required	string Configuration key.

Responses

- **200** Configuration returned.
- **401** Unauthorized
- **403** Forbidden
- **503** The server is currently starting or is temporarily not available.

GET `/System/Configuration/{key}`

Response samples

200

Content type
application/json

Copy

```
"string"
```

Updates named configuration.

AUTHORIZATIONS: *CustomAuthentication*

PATH PARAMETERS

`key` required	string Configuration key.

REQUEST BODY SCHEMA: application/json
required

Configuration.
any

Responses

- **204** Named configuration updated.
- **401** Unauthorized
- **403** Forbidden
- **503** The server is currently starting or is temporarily not available.

POST `/System/Configuration/{key}`

Request samples

Payload

Content type
application/json

Copy

```
null
```

Updates branding configuration.

AUTHORIZATIONS: › *CustomAuthentication*

REQUEST BODY SCHEMA: application/json
required

Branding configuration.

`LoginDisclaimer`	string or null Gets or sets the login disclaimer.
`CustomCss`	string or null Gets or sets the custom CSS.
`SplashscreenEnabled`	boolean Gets or sets a value indicating whether to enable the splashscreen.

Responses

— **204** Branding configuration updated.

— **401** Unauthorized

— **403** Forbidden

› **503** The server is currently starting or is temporarily not available.

POST `/System/Configuration/Branding`

Request samples

Payload

Content type
application/json

Copy

```
{
    "LoginDisclaimer": "string",
    "CustomCss": "string",
    "SplashscreenEnabled": true
}
```

Gets a default MetadataOptions object.

AUTHORIZATIONS: › *CustomAuthentication*

Responses

› **200** Metadata options returned.

— **401** Unauthorized

— **403** Forbidden

› **503** The server is currently starting or is temporarily not available.

GET `/System/Configuration/MetadataOptions/Default`

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "ItemType": "string",
  - "DisabledMetadataSavers": [
        "string"
    ],
  - "LocalMetadataReaderOrder": [
        "string"
    ],
  - "DisabledMetadataFetchers": [
        "string"
    ],
  - "MetadataFetcherOrder": [
        "string"
    ],
  - "DisabledImageFetchers": [
        "string"
    ],
  - "ImageFetcherOrder": [
        "string"
    ]
}
```

Gets information about the request endpoint.

AUTHORIZATIONS: › *CustomAuthentication*

Responses

› **200** Information retrieved.

— **401** Unauthorized

› **403** User does not have permission to get endpoint information.

› **503** The server is currently starting or is temporarily not available.

GET `/System/Endpoint`

Response samples

200 403

Content type
application/json

Copy

```
{
    "IsLocal": true,
    "IsInNetwork": true
}
```

Gets information about the server.

AUTHORIZATIONS: › *CustomAuthentication*

Responses

› **200** Information retrieved.

— **401** Unauthorized

› **403** User does not have permission to retrieve information.

› **503** The server is currently starting or is temporarily not available.

GET `/System/Info`

Response samples

200 403

Content type
application/json

Copy Expand all Collapse all

```
{
    "LocalAddress": "string",
    "ServerName": "string",
    "Version": "string",
    "ProductName": "string",
    "OperatingSystem": "string",
    "Id": "string",
    "StartupWizardCompleted": true,
    "OperatingSystemDisplayName": "string",
    "PackageName": "string",
    "HasPendingRestart": true,
    "IsShuttingDown": true,
    "SupportsLibraryMonitor": true,
    "WebSocketPortNumber": 0,
  - "CompletedInstallations": [
      + { … }
    ],
    "CanSelfRestart": true,
    "CanLaunchWebBrowser": false,
    "ProgramDataPath": "string",
    "WebPath": "string",
    "ItemsByNamePath": "string",
    "CachePath": "string",
    "LogPath": "string",
    "InternalMetadataPath": "string",
    "TranscodingTempPath": "string",
  - "CastReceiverApplications": [
      + { … }
    ],
    "HasUpdateAvailable": false,
    "EncoderLocation": "System",
    "SystemArchitecture": "X64"
}
```

Gets public information about the server.

Responses

› **200** Information retrieved.

› **503** The server is currently starting or is temporarily not available.

GET `/System/Info/Public`

Response samples

200

Content type
application/json

Copy

```
{
    "LocalAddress": "string",
    "ServerName": "string",
    "Version": "string",
    "ProductName": "string",
    "OperatingSystem": "string",
    "Id": "string",
    "StartupWizardCompleted": true
}
```

Gets information about the server.

AUTHORIZATIONS: › *CustomAuthentication*

Responses

› **200** Information retrieved.

— **401** Unauthorized

› **403** User does not have permission to retrieve information.

› **503** The server is currently starting or is temporarily not available.

GET `/System/Info/Storage`

Response samples

200 403

Content type
application/json

Copy Expand all Collapse all

```
{
  - "ProgramDataFolder": {
        "Path": "string",
        "FreeSpace": 0,
        "UsedSpace": 0,
        "StorageType": "string",
        "DeviceId": "string"
    },
  - "WebFolder": {
        "Path": "string",
        "FreeSpace": 0,
        "UsedSpace": 0,
        "StorageType": "string",
        "DeviceId": "string"
    },
  - "ImageCacheFolder": {
        "Path": "string",
        "FreeSpace": 0,
        "UsedSpace": 0,
        "StorageType": "string",
        "DeviceId": "string"
    },
  - "CacheFolder": {
        "Path": "string",
        "FreeSpace": 0,
        "UsedSpace": 0,
        "StorageType": "string",
        "DeviceId": "string"
    },
  - "LogFolder": {
        "Path": "string",
        "FreeSpace": 0,
        "UsedSpace": 0,
        "StorageType": "string",
        "DeviceId": "string"
    },
  - "InternalMetadataFolder": {
        "Path": "string",
        "FreeSpace": 0,
        "UsedSpace": 0,
        "StorageType": "string",
        "DeviceId": "string"
    },
  - "TranscodingTempFolder": {
        "Path": "string",
        "FreeSpace": 0,
        "UsedSpace": 0,
        "StorageType": "string",
        "DeviceId": "string"
    },
  - "Libraries": [
      + { … }
    ]
}
```

Gets a list of available server log files.

AUTHORIZATIONS: › *CustomAuthentication*

Responses

› **200** Information retrieved.

— **401** Unauthorized

› **403** User does not have permission to get server logs.

› **503** The server is currently starting or is temporarily not available.

GET `/System/Logs`

Response samples

200 403

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
        "DateCreated": "2019-08-24T14:15:22Z",
        "DateModified": "2019-08-24T14:15:22Z",
        "Size": 0,
        "Name": "string"
    }
]
```

Gets a log file.

AUTHORIZATIONS: › *CustomAuthentication*

QUERY PARAMETERS

`name` required	string The name of the log file to get.

Responses

› **200** Log file retrieved.

— **401** Unauthorized

› **403** User does not have permission to get log files.

› **404** Could not find a log file with the name.

› **503** The server is currently starting or is temporarily not available.

GET `/System/Logs/Log`

Response samples

403 404

Content type
application/json

Copy

```
{
    "type": "string",
    "title": "string",
    "status": 0,
    "detail": "string",
    "instance": "string",
    "property1": null,
    "property2": null
}
```

Pings the system.

Responses

› **200** Information retrieved.

› **503** The server is currently starting or is temporarily not available.

GET `/System/Ping`

Response samples

200

Content type
application/json

Copy

```
"string"
```

Pings the system.

Responses

› **200** Information retrieved.

› **503** The server is currently starting or is temporarily not available.

POST `/System/Ping`

Response samples

200

Content type
application/json

Copy

```
"string"
```

Restarts the application.

AUTHORIZATIONS: › *CustomAuthentication*

Responses

— **204** Server restarted.

— **401** Unauthorized

› **403** User does not have permission to restart server.

› **503** The server is currently starting or is temporarily not available.

POST `/System/Restart`

Response samples

403

Content type
application/json

Copy

```
{
    "type": "string",
    "title": "string",
    "status": 0,
    "detail": "string",
    "instance": "string",
    "property1": null,
    "property2": null
}
```

Shuts down the application.

AUTHORIZATIONS: › *CustomAuthentication*

Responses

— **204** Server shut down.

— **401** Unauthorized

› **403** User does not have permission to shutdown server.

› **503** The server is currently starting or is temporarily not available.

POST `/System/Shutdown`

Response samples

403

Content type
application/json

Copy

```
{
    "type": "string",
    "title": "string",
    "status": 0,
    "detail": "string",
    "instance": "string",
    "property1": null,
    "property2": null
}
```

Gets the current UTC time.

Responses

› **200** Time returned.

› **503** The server is currently starting or is temporarily not available.

GET `/GetUtcTime`

Response samples

200

Content type
application/json

Copy

```
{
    "RequestReceptionTime": "2019-08-24T14:15:22Z",
    "ResponseTransmissionTime": "2019-08-24T14:15:22Z"
}
```

Authentication

Get all keys.

AUTHORIZATIONS: › *CustomAuthentication*

Responses

› **200** Api keys retrieved.

— **401** Unauthorized

— **403** Forbidden

› **503** The server is currently starting or is temporarily not available.

GET `/Auth/Keys`

Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  - "Items": [
      + { … }
    ],
    "TotalRecordCount": 0,
    "StartIndex": 0
}
```

Create a new api key.

AUTHORIZATIONS: *CustomAuthentication*

QUERY PARAMETERS

`app` required	string Name of the app using the authentication key.

Responses

— **204** Api key created.

— **401** Unauthorized

— **403** Forbidden

› **503** The server is currently starting or is temporarily not available.

POST `/Auth/Keys`

Remove an api key.

AUTHORIZATIONS: *CustomAuthentication*

PATH PARAMETERS

`key` required	string