Imbera®

VERTICAL COOLER
EVC04

ESTABLISHING A NEW STANDARD IN THE COMERCIAL REFRIGERATION INDUSTRY

Energy efficient HC unit, designed for checkout locations with special steel top, ideal for small footprint areas.



KEY FEATURES



ECO-FRIENDLY HC NATURAL REFRIGERANT

New R290 HFC-free refrigerant gas that reduces environmental impact and increases efficiency.



NEWLY DESIGNED CONDENSER

New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.




ELECTRONIC TEMPERATURE CONTROLLER

Electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.



ELECTRONIC FAN MOTORS

Enhances performance and efficiency. Uses only a fraction of the energy and offers longer life expectancy than industry standard shaded-pole motors.



LED EFFICIENCY +220 LUX MINIMUM OUTPUT

New 5th generation constant power ultra-high efficiency LED uses lowest energy possible, with highest light output.



SPARK-FREE REFRIGERATION COMPONENTS

All HC models will have spark free refrigeration components for optimal safety, per UL requirements.

UL ENERGY STAR DOE

Imbera®

VERTICAL COOLER
EVC04

TECHNICAL SPECIFICATIONS

Exterior dimensions	Internal dimensions	Usable interior capacity
H: 33 1/4" (84cm)	H: 28 5/8" (76cm)	H: 28 5/8" (76cm)
W: 21 1/8" (53cm)	W: 18" (46cm)	W: 17 3/10"(44cm)
D: 25 3/4" (65cm)	D: 18 3/8" (47cm)	D: 12 3/5" (32cm)

Usable volume	3.92 ft³ (111 lts)
Doors	1
Door construction	Plastic frame
Shelves	3
Shelf size	W: 17 3/10"(44cm) D: 12 3/5" (32cm)
External material	Pre-painted steel
Internal material	Pre-painted steel

DATA CAPACITY**

08 oz can capacity

Total:	136
Front:	8
Display:	32

12 oz can capacity (2 shelves)

Total:	84
Front:	7
Display:	21

REFRIGERATION PERFORMANCE DATA

Refrigerant	R600a 1.1oz (0.03 kg)	
Energy consumption	0.780 kwh / 24 h	
Compressor power	1/12 HP 157 watts	
Condenser	Finless	
Thermostat setting default	Cut-out 32°F (0°C)	Cut-in 44.6°F (7°C)

ELECTRICAL DATA


Power supply	115V / 60 Hz
Amps	2.0
Length of cord	118" (300cm)
Lighting	4 modules 32 total LED's
Plug type	B
Controller	ETC1H

LOGISTIC DATA

Trailer loads	20': 54 40': 108 53': 160
Unit weight w/packaging	126.3 lb (57.3kg)
Dimensions w/packaging	H: 34 5/8" (88cm) W: 23 7/10"(60cm) D: 26 1/5" (67cm)

PRODUCT VIEWS


Top view



Front view



Side view



*Energy consumption based on C condition
*BMAD System (Low maintenance high performance)
*Dimensions rounded up to the nearest inch or millimeter
*Specifications subject to change without notice
*H: Heigth, W: Width, D: Depth
**Product capacity expressed at its highest level

Customer service and warranty

Operators must follow installation and operational guidelines per Imbera Users Manual
Each cooler must be connected directly to a single power supply, otherwise warranty will be voided

04/12/2024