

Validation Report for **adoptr** package

Kevin Kunzmann & Maximilian Pilz

2019-03-31

Contents

1	Introduction	5
1.1	Concept	5
1.2	Local validation	5
1.3	Brief Introdcutio to Two-Stage Designs	5
1.4	Validation strategy	6
2	Scenario I: large effect, point alternative	13
2.1	Details	13
2.2	Case I-1: Minimizing Expected Sample Size under Point Prior	13
2.3	Case I-2: Minimizing Expected Sample Size under Null Hypothesis	17
2.4	Case I-3: Conditional Power Constraint	19
2.5	Plot Two-Stage Designs	21
3	Scenario II	23
3.1	Details	23
3.2	Case II-1: Minimizing Expected Sample Size under Point Prior	23
3.3	Case II-2: Minimizing Expected Sample Size under Null Hypothesis	26
3.4	Case II-3: Conditional Power Constraint	27
3.5	Plot Two-Stage Designs	29
4	Scenario III: large effect, uniform prior alternative	31
4.1	Details	31
4.2	Case III.1: Convergence under prior concentration	32
5	Scenario IV: smaller effect, point alternative	37
5.1	Details	37
5.2	Case IV-1: Minimizing Expected Sample Size under Point Prior	38
5.3	Case IV-2: Increase Power	41
5.4	Case IV-3: Increase Type One Error rate	44
5.5	Plot Two-Stage Designs	47
6	Secenario V	49
6.1	Details	49
6.2	Case V-1, sensitivity to integration order	49
6.3	Case V-2, utility maximization	53
6.4	Case V-3, n1-penalty	55
6.5	Case V-4, n2-penalty	57

Chapter 1

Introduction

1.1 Concept

The goal of `adoptrValidation` is to provide a comprehensive suit of test for the `adoptr` package. The package is not directly intended to be used but to automatically deploy a weekly validation report via github pages to <https://kkmann.github.io/adoptrValidation/>. The report is implemented as a set of vignettes which are compiled into a static web page using `pkgdown`. For details on the class of supported designs, see <https://github.com/kkmann/adoptr>.

1.2 Local validation

...

1.3 Brief Introduction to Two-Stage Designs

In `adoptrValidation` a suitable set of cases is tested in order to validate the performance of the package `adoptr`. This package allows to compute optimal designs (adaptive two-stage, group-sequential two-stage and one-stage) for normally distributed data. For a treatment group T and a control group C where the observations $X_i^T \sim \mathcal{N}(\mu_T, \sigma^2)$, $X_i^C \sim \mathcal{N}(\mu_C, \sigma^2)$ the following hypotheses are tested:

$$\mathcal{H}_0 : \delta := \mu_T - \mu_C \leq 0 \text{ v.s. } \mathcal{H}_\infty : \delta > 0.$$

The power of a test procedure is computed on an alternative effect size $\delta_1 > 0$ where a prior distribution $\delta_1 \sim \pi(\vartheta, \tau^2)$ is imaginable.

The trial evaluation happens as follows. After n_1 patients (per group) finished the trial an interim analysis is conducted. The interim test statistic Z_1 for a standard z-test is computed and the trial is stopped early for futility, if $Z_1 < c_f$. If $Z_1 > c_e$ the null hypothesis is rejected and the trial is stopped early for efficacy. Otherwise, i.e. if $c_f \leq Z_1 \leq c_e$, the trial enters in the second stage. Due to the adaptiveness of the trial design, the stage-two sample size is a function of Z_1 , i.e. $n_2(Z_1)$. Also the final rejection boundary c_2 depends on Z_1 . At the final analysis the stage-two test statistic Z_2 is computed and the null hypothesis is rejected if $Z_2 > c_2(Z_1)$.

A design D is a five-tuple consisting of the first-stage sample size n_1 , early stopping boundaries c_f (futility) and c_e (efficacy) and stage-two functions $n_2(\cdot)$ (sample size) and $c_2(\cdot)$ (rejection boundary). All these

elements can be computed optimally in **adoptr**. The incorporation of continuous priors is possible as well as including conditional and unconditional constraints.

Given a design D and a objective function f the default setting in [adoptr] is the following.

min	$f(D)$
such that	Type One Error Rate $\leq \alpha$
and	Power $\geq 1 - \beta$

Often in clinical practice one is not willing to enter in a second stage when the conditional power (i.e., the probability to reject at the final analysis given the first-stage results) is too low or too high because in these cases the stage-two result is likely predictable. Therefore, introducing conditional power constraints of the form

$$1 - \beta_2 \leq \text{Conditional Power}(z_1, D) \leq 1 - \beta_3$$

may be desirable and are supported by **adoptr**.

In **adoptrValidation** different scenarios are investigated. Each scenario is determined by the assumed effect size δ_1 and its prior distribution π . In each scenario, different tests are performed. All tests are indicated by a bullet point.

1.4 Validation strategy

adoptrValidation essentially extends the test suit of **adoptr** to cover more different scenarios. In order to generate a proper validation report the test Variants are not managed using a unit testing framework like testthat but are directly included in a set of vignettes (one per sceanrio). These vignettes are automatically built and published (here) once per week using pkgdown to keep the validation report up to date with the latest CRAN release [TODO: we currently use our master!]. The overall failure/pass status of the latest build can be checked using the Travis-CI badge. In the following, all Scenarios and their respective sub-Variants are outlined. **Scenarios** are defined by the joint distribution of the test statistic and the location parameter, while **Variants** are given by the respective optimization problem (objective, constraints).

1.4.1 Technical Setup

Initially, the both packages are loaded and the seed for simulation is set. Additionally, the options for optimization are modified by increasing the maximum number of evaluations to ensure convergence.

```
library(adoptr)
library(tidyverse)

# load custom functions in folder subfolder '/R'
for (nm in list.files("R", pattern = "\\.[RrSsQq]"))
  source(file.path("R", nm))

# define seed value
seed <- 42

# define custom tolerance and iteration limit for nloptr
opts = list(
  algorithm = "NLOPT_LN_COBYLA",
  xtol_rel = 1e-5,
```

```

maxeval    = 100000
)

```

1.4.2 Scenario I

This is the default scenario.

- **Data distribution:** Two-armed trial with normally distributed test statistic
- **Prior:** $\delta \sim \delta_{0.4}$
- **Null hypothesis:** $\mathcal{H}_0 : \delta \leq 0$

1.4.2.1 Variant I.1: Minimizing Expected Sample Size under the Alternative

- **Objective:** $ESS := E[n(X_1) | \delta = 0.4]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta = 0.4] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$
 3. Three variants: two-stage, group-sequential, one-stage.
- **Formal tests:**
 1. All three **adoptr** variants (two-stage, group-sequential, one-stage) comply with constraints. Internally validated by testing vs. simulated values of the power curve at respective points.
 2. ESS of optimal two-stage design is lower than ESS of optimal group-sequential one and that is in turn lower than the one of the optimal one-stage design.
 3. ESS of optimal group-sequential design is lower than ESS of externally computed group-sequential design using the **rpact** package.
 4. Are the ESS values obtained from simulation the same as the ones obtained by using numerical integration via **adoptr::evaluate**?
 5. Is $n()$ of the optimal two-stage design monotonously decreasing on continuation area?

1.4.2.2 Variant I.2: Minimizing Expected Sample Size under the Null Hypothesis

- **Objective:** $ESS := E[n(X_1) | \delta = 0.0]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta = 0.4] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$
- **Formal tests:**
 1. Validate constraint compliance by testing vs. simulated values of the power curve at respective points.
 2. $n()$ of optimal design is monotonously increasing on continuation area. TODO
 3. ESS of optimal two-stage design is lower than ESS of externally computed group-sequential design using the **rpact** package.
 4. Are the ESS values obtained from simulation the same as the ones obtained by using numerical integration via **adoptr::evaluate**?

1.4.2.3 Variant I.3: Conditional Power Constraint

- **Objective:** $ESS := E[n(X_1) | \delta = 0.4]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta = 0.4] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$

3. $CP := \Pr[c_2(X_1) < X_2 | \delta = 0.4, X_1 = x_1] \geq 0.7$ for all $x_1 \in (c_1^f, c_1^e)$
- **Formal tests:**
 1. Check *Power* and *TOER* constraints with simulation. Check *CP* constraint on three different values of x_1 in (c_1^f, c_1^e)
 2. Are the *CP* values at the three test-pivots obtained from simulation the same as the ones obtained by using numerical integration via `adoptr::evaluate`?
 3. Is *ESS* of optimal two-stage design with *CP* constraint higher than *ESS* of optimal two-stage design without this constraint?

1.4.3 Scenario II

Similar in scope to Scenario I, but with a continuous Gaussian prior on δ .

- **Data distribution:** Two-armed trial with normally distributed test statistic
- **Prior:** $\delta \sim \mathcal{N}(0.4, 3)$
- **Null hypothesis:** $\mathcal{H}_0 : \delta \leq 0$

1.4.3.1 Variant II.1: Minimizing Expected Sample Size

- **Objective:** $ESS := E[n(X_1)]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta > 0.0] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$
 3. Three variants: two-stage, group-sequential, one-stage.
- **Formal tests:**
 1. All designs comply with type one error rate constraints (tested via simulation).
 2. *ESS* of optimal two-stage design is lower than *ESS* of optimal group-sequential one and that is in turn lower than the one of the optimal one-stage design.

1.4.3.2 Variant II.2: Minimizing Expected Sample Size under the Null hypothesis

- **Objective:** $ESS := E[n(X_1) | \delta \leq 0]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta > 0.0] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$
- **Formal tests:**
 1. Does the design comply with *TOER* constraint (via simulation)?
 2. Check *CP* constraint on three different values of x_1 in (c_1^f, c_1^e)
 3. TODO: Is the sample size function monotonously increasing?
 4. Is *ESS* lower than expected sample size under the null hypothesis for the optimal two stage design from Variant II-1?

1.4.3.3 Variant II.3: Conditional Power Constraint

- **Objective:** $ESS := E[n(X_1)]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta > 0.0] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$
 3. $CP := \Pr[c_2(X_1) < X_2 | \delta > 0.0, X_1 = x_1] \geq 0.7$ for all $x_1 \in (c_1^f, c_1^e)$
- **Formal tests:**

1. Check *TOER* constraint with simulation. Check *CP* constraint on three different values of x_1 in (c_1^f, c_1^e)
2. Is *ESS* of optimal two-stage design with *CP* constraint higher than *ESS* of optimal two-stage design without the constraint?

1.4.4 Scenario III:

- **Data distribution:** Two-armed trial with normally distributed test statistic
- **Prior:** sequence of uniform distributions $\delta \sim \text{Unif}(0.4 - \Delta_i, 0.4 + \Delta_i)$ around 0.4 with $\Delta_i = (3 - i)/10$ for $i = 0 \dots 3$. I.e., for $\Delta_3 = 0$ reduces to a point prior on $\delta = 0.4$.
- **Null hypothesis:** $\mathcal{H}_0 : \delta \leq 0$

1.4.4.1 Variant III.1: Convergence under Prior Concentration

- **Objective:** $ESS := E[n(X_1)]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta > 0.0] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$
- **Formal tests:**
 1. Simulated type one error rate is compared to *TOER* constraint for each design.
 2. Number of iterations are checked against default maximum to ensure proper convergence.
 3. TODO: *ESS* decreases with prior variance.

Additionally, the designs are compared graphically. Inspect the plot to see convergence pattern.

1.4.5 Scenario IV: Smaller effect size, larger trials.

1.4.5.1 Variant IV.1: Minimizing Expected Sample Size under the Alternative

- **Objective:** $ESS := E[n(X_1) | \delta = 0.2]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta = 0.2] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$
 3. Three variants: two-stage, group-sequential, one-stage.
- **Formal tests:**
 1. All three adoptr variants (two-stage, group-sequential, one-stage) comply with constraints. Internally validated by testing vs. simulated values of the power curve at respective points.
 2. *ESS* of optimal two-stage design is lower than *ESS* of optimal group-sequential one and that is in turn lower than the one of the optimal one-stage design.
 3. *ESS* of optimal group-sequential design is lower than *ESS* of externally computed group-sequential design using the rpact package.
 4. Are the *ESS* values obtained from simulation the same as the ones obtained by using numerical integration via `adoptr::evaluate`?
 5. Is $n()$ of the optimal two-stage design monotonously decreasing on continuation area? TODO

1.4.5.2 Variant IV.2: Increasing Power

- **Objective:** $ESS := E[n(X_1) | \delta = 0.2]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta = 0.2] \geq 0.9$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$

- 3. Three variants: two-stage, group-sequential, one-stage.
- **Formal tests:**
 1. Does the design respect all constraints (via simulation)?
 2. ESS of optimal two-stage design is lower than ESS of optimal group-sequential one and that is in turn lower than the one of the optimal one-stage design.
 3. ESS of optimal group-sequential design is lower than ESS of externally computed group-sequential design using the rpact package.
 4. Are the ESS values obtained from simulation the same as the ones obtained by using numerical integration via `adoptr::evaluate`?
 5. Is $n()$ of the optimal two-stage design monotonously decreasing on continuation area? TODO

1.4.5.3 Variant IV.3: Increasing Maximal Type One Error Rate

- **Objective:** $ESS := E[n(X_1) | \delta = 0.2]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta = 0.2] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.05$
 3. Three variants: two-stage, group-sequential, one-stage.
- **Formal tests:**
 1. Does the design respect all constraints (via simulation)?
 2. ESS of optimal two-stage design is lower than ESS of optimal group-sequential one and that is in turn lower than the one of the optimal one-stage design.
 3. ESS of optimal group-sequential design is lower than ESS of externally computed group-sequential design using the rpact package.
 4. Are the ESS values obtained from simulation the same as the ones obtained by using numerical integration via `adoptr::evaluate`?
 5. Is $n()$ of the optimal two-stage design monotonously decreasing on continuation area? TODO

1.4.6 Scenario V: Single-arm design, medium effect size.

- **Data distribution:** One-armed trial with normally distributed test statistic
- **Prior:** $\delta \sim \delta_{0.3}$
- **Null hypothesis:** $\mathcal{H}_0 : \delta \leq 0$

1.4.6.1 Variant V.1: Sensitivity to Integration Order

- **Objective:** $ESS := E[n(X_1) | \delta = 0.3]$
- **Constraints:**
 1. $Power := \Pr[c_2(X_1) < X_2 | \delta = 0.3] \geq 0.8$
 2. $TOER := \Pr[c_2(X_1) < X_2 | \delta = 0.0] \leq 0.025$
 3. Three variants: integration order 5, 8, 11 two-stage designs [TODO: maybe more?].
- **Formal tests:**
 1. Do all designs respect all constraints (via simulation)?
 2. Do all designs converge within the respective iteration limit?
 3. Does constraint compliance get better with increased order?
 4. Does the simulated ESS get better with increased order?

1.4.6.2 Variant V.2: Utility Maximization

- **Objective:** $\lambda Power - ESS := \lambda \Pr[c_2(X_1) < X_2 | \delta = 0.3] - E[n(X_1) | \delta = 0.3]$. for $\lambda = 100$ and 200

- **Constraints:**
 1. $TOER := \Pr[c_2(X_1) < X_2 \mid \delta = 0.0] \leq 0.025$
- **Formal tests:**
 1. Do both designs respect the type one error rate constraint (via simulation)?
 2. Is the power of the design with larger λ larger?

1.4.6.3 Variant V.3: n_1 penalty

- **Objective:** $ESS := E[n(X_1) \mid \delta = 0.3] + \lambda n_1$ for $\lambda = 0.05$ and 0.2 .
- **Constraints:**
 1. $TOER := \Pr[c_2(X_1) < X_2 \mid \delta = 0.0] \leq 0.025$
 2. $Power := \Pr[c_2(X_1) < X_2 \mid \delta = 0.3] \geq 0.8$
- **Formal tests:**
 1. Is n_1 for the optimal design smaller than the order-5 design in V.1?

1.4.6.4 Variant V.4: n_2 penalty

- **Objective:** $ESS := E[n(X_1) \mid \delta = 0.3] + \text{AverageN2}$
- **Constraints:**
 1. $TOER := \Pr[c_2(X_1) < X_2 \mid \delta = 0.0] \leq 0.025$
 2. $Power := \Pr[c_2(X_1) < X_2 \mid \delta = 0.3] \geq 0.8$
- **Formal tests:**
 1. Is the AverageN2 for the optimal design smaller than for the order-5 design in V.1?

Chapter 2

Scenario I: large effect, point alternative

2.1 Details

In this scenario an alternative effect size of $\delta = 0.4$ with point prior distribution is investigated. The null hypothesis is $\delta \leq 0$. Currently, `adoptr` only supports normal distributed data what is widely spread in the development of adaptive designs. We protect the one-sided type one error rate at $\alpha = 0.025$ and require the power of the design to be at least $1 - \beta = 0.8$.

2.1.1 Data distribution

Two-armed trial with normally distributed test statistic

```
datadist <- Normal(two_armed = TRUE)
```

2.1.2 Null hypothesis

The null hypothesis is $\mathcal{H}_0 : \delta \leq 0$

```
H_0 <- PointMassPrior(.0, 1)
```

2.1.3 Prior assumptions

A point mass prior with probability mass on $\delta = 0.4$ is assumed.

```
prior <- PointMassPrior(.4, 1)
```

2.2 Case I-1: Minimizing Expected Sample Size under Point Prior

2.2.1 Objective

Expected sample size under the respective prior is minimized, i.e., $E[n(\mathcal{D})]$.

```
ess <- expected(ConditionalSampleSize(datadist, prior))
```

2.2.2 Constrains

The type one error rate is controlled at 0.025 on the boundary of the null hypothesis.

```
toer_cnstr <- expected(ConditionalPower(datadist, H_0)) <= .025
```

Power must be larger than 0.8.

```
pow_cnstr <- expected(ConditionalPower(datadist, prior)) >= .8
```

2.2.3 Initial Design

`adoptr` requires the definition of an initial design for optimization. We start with a group-sequential design from the package `rpact` that fulfills these constraints and is used later for comparison. The order of integration is set to

```
order <- 7L
```

For usage as two-stage design with variable sample size, it has to be converted to a `TwoStageDesign`.

```
init_design_gs <- rpact_design(0.4, 0.025, 0.8, TRUE, order)
```

```
init_design <- TwoStageDesign(init_design_gs)
```

2.2.4 Optimization

The optimal design is computed in three variants: two-stage, group-sequential and one-stage. The input only differs with regard to the initial design.

```
opt_design <- function(initial_design) {
  minimize(
    ess,
    subject_to(
      toer_cnstr,
      pow_cnstr
    ),
    initial_design = initial_design,
    opts = opts
  )
}

opt1_ts <- opt_design(initial_design)
opt1_gs <- opt_design(initial_design_gs)
opt1_os <- opt_design(OneStageDesign(200, 2.0))
```

2.2.5 Test Cases

Check if the optimization algorithm converged in all cases.

```
iters <- sapply(list(opt1_ts, opt1_gs, opt1_os),
               function(x) x$nlptr_return$iterations)

print(iters)
```

```
## [1] 3402 985 24
```

```
testthat::expect_true(all(iters < opts$maxeval))
```

The n_2 function of the optimal two-stage design is expected to be monotonously decreasing.

```
testthat::expect_equal(
  sign(diff(opt1_ts$design@n2_pivots)),
  rep(-1, (order - 1))
)
```

Type one error rate constraint is tested for the three designs. Due to numerical issues we allow a relative error of 2%.

```
tmp <- sapply(list(opt1_ts, opt1_gs, opt1_os),
              function(x) sim_pr_reject(x$design, .0, datadist))
df_toer <- data.frame(
  toer = as.numeric(tmp[1, ]),
  se = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_toer$toer <= .025*(1.02)))

df_toer
```

```
##           toer           se
## 1 0.024951 0.0001559759
## 2 0.024978 0.0001560581
## 3 0.025116 0.0001564775
```

The power constraint can also be tested via simulation. Due to numerical issues we allow a relative error of 2%.

```
tmp <- sapply(list(opt1_ts, opt1_gs, opt1_os),
              function(x) sim_pr_reject(x$design, .4, datadist))
df_pow <- data.frame(
  pow = as.numeric(tmp[1, ]),
  se = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_pow$pow >= .8 * (1 - 0.02)))

df_pow
```

```
##           pow           se
## 1 0.798641 0.0004010159
## 2 0.799669 0.0004002482
```

```
## 3 0.799317 0.0004005115
```

The expected sample sizes should be ordered in a specific way.

```
testthat::expect_gte(
  evaluate(ess, opt1_os$design),
  evaluate(ess, opt1_gs$design)
)

testthat::expect_gte(
  evaluate(ess, init_design_gs),
  evaluate(ess, opt1_gs$design)
)

testthat::expect_gte(
  evaluate(ess, opt1_gs$design),
  evaluate(ess, opt1_ts$design)
)
```

The expected sample size of the optimal designs is simulated and compared to the outcome of `adoptr::evaluate()`. The tolerance is set to 0.5 what is due to rounding one patient per group in the worst case.

```
ess_0 <- expected(ConditionalSampleSize(datadist, H_0))

testthat::expect_equal(
  sim_n(opt1_os$design, .0, datadist),
  evaluate(ess_0, opt1_os$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt1_gs$design, .0, datadist),
  evaluate(ess_0, opt1_gs$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt1_ts$design, .0, datadist),
  evaluate(ess_0, opt1_ts$design),
  tolerance = .5
)
```

Additionally, the sample sizes under the point prior are compared.

```
testthat::expect_equal(
  sim_n(opt1_os$design, .4, datadist),
  evaluate(ess, opt1_os$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt1_gs$design, .4, datadist),
  evaluate(ess, opt1_gs$design),
  tolerance = .5
)
```



```
testthat::expect_equal(
  sim_n(opt1_ts$design, .4, datadist),
  evaluate(ess, opt1_ts$design),
  tolerance = .5
)
```

2.3 Case I-2: Minimizing Expected Sample Size under Null Hypothesis

2.3.1 Objective

Expected sample size under the null hypothesis prior is minimized, i.e.,

```
ess_0 <- expected(ConditionalSampleSize(datadist, H_0))
```

2.3.2 Constrains

The constraints remain the same as before.

2.3.3 Initial Design

For runtime issues the previous initial design has to be updated. It turns out that a constant c_2 -starting value is much more efficient in this case. Furthermore, a more strict upper-boundary design than the default one needs to be defined because stopping for efficacy would otherwise only happen for very large values of x_1 due to optimization under the null hypothesis.

```
init_design_2 <- init_design
init_design_2@c2_pivots <- rep(2, order)

ub_design <- TwoStageDesign(
  opt1_os$design@n1,
  opt1_os$design@c1f,
  3,
  rep(300, order),
  rep(3.0, order)
)
```

2.3.4 Optimization

The optimal two-stage design is computed.

```
opt2_ts <- minimize(
  ess_0,
  subject_to(
    toer_cnstr,
```

```

        pow_cnstr

    ),

    initial_design = init_design_2,

    upper_boundary_design = ub_design,

    opts = opts

)

## Warning in minimize(ess_0, subject_to(toer_cnstr, pow_cnstr),
## initial_design = init_design_2, : initial design is infeasible!

```

2.3.5 Test Cases

Check if the optimization algorithm converged.

```

print(opt2_ts$nlptr_return$iterations)

## [1] 20640

testthat::expect_true(opt2_ts$nlptr_return$iterations < opts$maxeval)

```

The n_2 function of the optimal two-stage design is expected to be monotonously increasing.

```

testthat::expect_equal(
  sign(diff(opt2_ts$design@n2_pivots)),
  rep(1, (order - 1))
)

```

Type one error rate constraint is tested for the optimal design. Due to numerical issues we allow a relative error of 2%.

```

tmp      <- sim_pr_reject(opt2_ts$design, .0, datadist)
df_toer2 <- data.frame(
  toer = as.numeric(tmp[1]),
  se   = as.numeric(tmp[2])
)
rm(tmp)

testthat::expect_true(all(df_toer2$toer <= .025*(1.02)))

df_toer2

```

```

##           toer           se
## 1 0.024971 0.0001560368

```

The power constraint can also be tested via simulation. Due to numerical issues we allow a relative error of 2%.

```

tmp      <- sim_pr_reject(opt2_ts$design, .4, datadist)
df_pow2  <- data.frame(
  pow = as.numeric(tmp[1]),
  se  = as.numeric(tmp[2])
)

```

```
rm(tmp)

testthat::expect_true(all(df_pow2$pow >= .8 * (1 - 0.02)))

df_pow2
```

```
##          pow          se
## 1 0.80175 0.0003986817
```

The expected sample size under the null should be lower than the ess under the null of the initial design derived from `rpact`.

```
testthat::expect_gte(
  evaluate(ess_0, init_design),
  evaluate(ess_0, opt2_ts$design)
)
```

The expected sample size of the optimal designs is simulated and compared to the outcome of `adoptr::evaluate()`. The tolerance is set to 0.5 what is due to rounding one patient per group in the worst case.

```
testthat::expect_equal(
  sim_n(opt2_ts$design, .0, datadist),
  evaluate(ess_0, opt2_ts$design),
  tolerance = .5
)
```

Additionally, the sample sizes under the point prior are compared.

```
testthat::expect_equal(
  sim_n(opt2_ts$design, .4, datadist),
  evaluate(ess, opt2_ts$design),
  tolerance = .5
)
```

2.4 Case I-3: Conditional Power Constraint

2.4.1 Objective

Expected sample size under the point prior is minimized and has already been defined.

2.4.2 Constrains

The constraints remain the same as before, additionally to a constraint on conditional power.

```
cp <- ConditionalPower(datadist, prior)

cp_cnstr <- cp >= .7
```

2.4.3 Initial Design

The previous initial design can still be applied.

2.4.4 Optimization

The optimal two-stage design is computed.

```
opt3_ts <- minimize(
  ess,
  subject_to(
    toer_cnstr,
    pow_cnstr,
    cp_cnstr
  ),
  initial_design = init_design,
  opts = opts
)

## Warning in minimize(ess, subject_to(toer_cnstr, pow_cnstr, cp_cnstr),
## initial_design = init_design, : initial design is infeasible!
```

2.4.5 Test Cases

Check if the optimization algorithm converged.

```
print(opt3_ts$nlptr_return$iterations)

## [1] 3316

testthat::expect_true(opt3_ts$nlptr_return$iterations < opts$maxeval)
```

Type one error rate constraint is tested for the optimal design. Due to numerical issues we allow a relative error of 2%.

```
tmp <- sim_pr_reject(opt3_ts$design, .0, datadist)
df_toer3 <- data.frame(
  toer = as.numeric(tmp[1]),
  se = as.numeric(tmp[2])
)
rm(tmp)

testthat::expect_true(all(df_toer3$toer <= .025*(1.02)))

df_toer3
```

```
##      toer      se
## 1 0.02496 0.0001560033
```

The power constraint can also be tested via simulation. Due to numerical issues we allow a relative error of 2%.

```
tmp <- sim_pr_reject(opt3_ts$design, .4, datadist)
df_pow3 <- data.frame(
```

```

    pow = as.numeric(tmp[1]),
    se   = as.numeric(tmp[2])
  )
rm(tmp)

testthat::expect_true(all(df_pow3$pow >= .8 * (1 - 0.02)))

df_pow3

```

```

##           pow           se
## 1 0.798916 0.0004008109

```

The expected sample size under the prior should be higher than in the case without the constraint that was analyzed in I.1.

```

testthat::expect_gte(
  evaluate(ess, opt3_ts$design),
  evaluate(ess, opt1_ts$design)
)

```

The conditional power constraint needs to be tested. Select three points for this and check the constraint.

```

x <- adoptr::scaled_integration_pivots(opt3_ts$design)[c(1, 3, 5)]


cp_val <- sapply(x, function(z) evaluate(cp, opt3_ts$design, z))

testthat::expect_true(all(cp_val >= 0.7))

```

2.5 Plot Two-Stage Designs

The optimal two-stage designs stemming from the different variants are plotted together.



Chapter 3

Scenario II

3.1 Details

In this scenario a Gaussian prior on the effect size $\delta \sim \mathcal{N}(0.4, 0.2^2)$ is investigated. The null hypothesis is $\delta \leq 0$. Currently, `adoptr` only supports normal distributed data what is widely spread in the development of adaptive designs. We protect the one-sided type one error rate at $\alpha = 0.025$ and require the power of the design to be at least $1 - \beta = 0.8$.

3.1.1 Data distribution

Two-armed trial with normally distributed test statistic

```
datadist <- Normal(two_armed = TRUE)
```

3.1.2 Null hypothesis

The null hypothesis is $\mathcal{H}_0 : \delta \leq 0$

```
H_0 <- PointMassPrior(.0, 1)
```

3.1.3 Prior assumptions

A Gaussian prior with mean $\delta = 0.4$ and standard deviation $\tau = .2$ is defined.

```
prior <- ContinuousPrior(function(delta) dnorm(delta, mean = .4, sd = .2),  
                          support = c(-5, 5),  
                          tighten_support = TRUE)
```

3.2 Case II-1: Minimizing Expected Sample Size under Point Prior

3.2.1 Objective

Expected sample size under the prior is minimized, i.e., $E[n(\mathcal{D})]$.

```
ess <- expected(ConditionalSampleSize(datadist, prior))
```

3.2.2 Constrains

The type one error rate is controlled at 0.025 on the boundary of the null hypothesis.

```
toer_cnstr <- expected(ConditionalPower(datadist, H_0)) <= .025
```

Expected Power (rejection probability for positive effect sizes) must be larger than 0.8.

```
pow_cnstr <- expected(
  ConditionalPower(datadist, condition(prior, c(0,3)))
) >= .8
```

3.2.3 Initial Design

`adoptr` requires the definition of an initial design for optimization. We start with a group-sequential design from the package `rpact` that fulfills the type-one error rate constraint and the power constraint for a point effect size at $\delta = 0.4$. The order of integration is set to 5. For usage as two-stage design with variable sample size, it has to be converted to a `TwoStageDesign`.

```
order <- 5L

init_design_gs <- rpact_design(0.4, 0.025, 0.8, TRUE, order)

init_design <- TwoStageDesign(init_design_gs)
```

3.2.4 Optimization

The optimal design is computed in three variants: two-stage, group-sequential and one-stage. The input only differs with regard to the initial design.

```
opt_design <- function(initial_design) {
  minimize(

    ess,

    subject_to(

      toer_cnstr,
      pow_cnstr

    ),

    initial_design = initial_design,

    opts = opts

  )
}

opt1_gs <- opt_design(init_design_gs)
```



```
## Warning in minimize(ess, subject_to(toer_cnstr, pow_cnstr), initial_design
## = initial_design, : initial design is infeasible!

opt1_os <- opt_design(OneStageDesign(300, 2.0))
opt1_ts <- opt_design(TwoStageDesign(opt1_gs$design))

## Warning in minimize(ess, subject_to(toer_cnstr, pow_cnstr), initial_design
## = initial_design, : initial design is infeasible!
```

3.2.5 Test Cases

Check if the optimization algorithm converged in all cases.

```
iters <- sapply(list(opt1_ts, opt1_gs, opt1_os),
               function(x) x$nlptr_return$iterations)

print(iters)

## [1] 1368 449 31

testthat::expect_true(all(iters < opts$maxeval))
```

Type one error rate constraint is tested for the three designs. Due to numerical issues we allow a relative error of 2%.

```
tmp <- sapply(list(opt1_ts, opt1_gs, opt1_os),
              function(x) sim_pr_reject(x$design, .0, datadist))
df_toer <- data.frame(
  toer = as.numeric(tmp[1, ]),
  se = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_toer$toer <= .025*(1.02)))

df_toer

##           toer           se
## 1 0.024986 0.0001560824
## 2 0.024904 0.0001558327
## 3 0.025116 0.0001564775
```

The expected sample sizes should be ordered in a specific way.

```
testthat::expect_gte(
  evaluate(ess, opt1_os$design),
  evaluate(ess, opt1_gs$design)
)

testthat::expect_gte(
  evaluate(ess, opt1_gs$design),
  evaluate(ess, opt1_ts$design)
)
```

3.3 Case II-2: Minimizing Expected Sample Size under Null Hypothesis

3.3.1 Objective

Expected sample size conditioned on negative effect sizes is minimized, i.e.,

```
ess_0 <- expected(ConditionalSampleSize(datadist, condition(prior, c(-3, 0))))
```

3.3.2 Constrains

The constraints remain the same as before.

3.3.3 Initial Design

The previous initial design can still be applied.

3.3.4 Optimization

The optimal group-sequential design and based on this the optimal two-stage design are computed.

```
opt2 <- function(initial_design) {
  minimize(
    ess_0,
    subject_to(
      toer_cnstr,
      pow_cnstr
    ),
    initial_design = initial_design,
    opts = opts
  )
}

opt2_gs <- opt2(init_design_gs)

## Warning in minimize(ess_0, subject_to(toer_cnstr, pow_cnstr),
## initial_design = initial_design, : initial design is infeasible!
opt2_ts <- opt2(TwoStageDesign(opt2_gs$design))

## Warning in minimize(ess_0, subject_to(toer_cnstr, pow_cnstr),
## initial_design = initial_design, : initial design is infeasible!
```

3.3.5 Test Cases

Check if the optimization algorithm converged.

```
print(opt2_ts$nlptr_return$iterations)
```

```
## [1] 1348
```

```
testthat::expect_true(opt2_ts$nlptr_return$iterations < opts$maxeval)
```

Type one error rate constraint is tested for the optimal design. Due to numerical issues we allow a relative error of 2%.

```
tmp      <- sim_pr_reject(opt2_ts$design, .0, datadist)
df_toer2 <- data.frame(
  toer = as.numeric(tmp[1]),
  se   = as.numeric(tmp[2])
)
rm(tmp)

testthat::expect_true(all(df_toer2$toer <= .025*(1.02)))

df_toer2
```

```
##          toer          se
## 1 0.024804 0.0001555274
```

The expected sample size under the null hypothesis should be lower than of the design from variant II.1 where expected sample size under the full prior was minimized.

```
testthat::expect_lte(
  evaluate(ess_0, opt2_ts$design),
  evaluate(ess_0, opt1_ts$design)
)
```

3.4 Case II-3: Conditional Power Constraint

3.4.1 Objective

Expected sample size under the prior is minimized and has already been defined.

3.4.2 Constrains

The constraints remain the same as before, additionally to a constraint on conditional power.

```
cp <- ConditionalPower(datadist, condition(prior, c(0, 3)))

cp_cnstr <- cp >= .7
```

3.4.3 Initial Design

The previous initial design can still be applied.

3.4.4 Optimization

The optimal two-stage design is computed.

```
opt3_ts <- minimize(
  ess,
  subject_to(
    toer_cnstr,
    pow_cnstr,
    cp_cnstr
  ),
  initial_design = init_design,
  opts = opts
)

## Warning in minimize(ess, subject_to(toer_cnstr, pow_cnstr, cp_cnstr),
## initial_design = init_design, : initial design is infeasible!
```

3.4.5 Test Cases

Check if the optimization algorithm converged.

```
print(opt3_ts$nlptr_return$iterations)

## [1] 2503

testthat::expect_true(opt3_ts$nlptr_return$iterations < opts$maxeval)
```

Type one error rate constraint is tested for the optimal design. Due to numerical issues we allow a relative error of 2%.

```
tmp <- sim_pr_reject(opt3_ts$design, .0, datadist)
df_toer3 <- data.frame(
  toer = as.numeric(tmp[1]),
  se = as.numeric(tmp[2])
)
rm(tmp)

testthat::expect_true(all(df_toer3$toer <= .025*(1.02)))

df_toer3

##      toer      se
## 1 0.024991 0.0001560976
```

The expected sample size under the prior should be higher than in the case without the constraint that was analyzed in II.1.

```
testthat::expect_gte(
  evaluate(ess, opt3_ts$design),
```


```
evaluate(ess, opt1_ts$design)
)
```

The conditional power constraint needs to be tested. Select three points for this and check the constraint.

```
x <- adoptr::scaled_integration_pivots(opt3_ts$design)[c(1, 3, 5)]
cp_val <- sapply(x, function(z) evaluate(cp, opt3_ts$design, z))
testthat::expect_true(all(cp_val >= 0.7))
```

3.5 Plot Two-Stage Designs

The optimal two-stage designs stemming from the different variants are plotted together.



Chapter 4

Scenario III: large effect, uniform prior alternative

4.1 Details

This scenario is a variant of Scenario I. The purpose is to assess whether placing uniform priors with decreasing width of support centered at the $\delta = 0.4$ leads to a sequence of optimal designs which converges towards the solution in Case I-1.

4.1.1 Data distribution

Two-armed trial with normally distributed test statistic

```
datadist <- Normal(two_armed = TRUE)
```

4.1.2 Null hypothesis

The null hypothesis is $\mathcal{H}_0 : \delta \leq 0$

```
H_0 <- PointMassPrior(.0, 1)
```

4.1.3 Prior assumptions

In this scenario we consider a sequence of uniform distributions $\delta \sim \text{Unif}(0.4 - \Delta_i, 0.4 + \Delta_i)$ around 0.4 with $\Delta_i = (3 - i)/10$ for $i = 0 \dots 3$. I.e., for $\Delta_3 = 0$ reduces to `PointMassPrior` on $\delta = 0.4$.

```
prior <- function(delta) {  
  if (delta == 0)  
    return(PointMassPrior(.4, 1.0))  
  a <- .4 - delta; b <- .4 + delta  
  ContinuousPrior(function(x) dunif(x, a, b), support = c(a, b))  
}
```

4.2 Case III.1: Convergence under prior concentration

Make sure that the optimal solution converges as the prior is more and more concentrated at a point mass.

4.2.1 Objective

Expected sample size under the respective prior is minimized, i.e., $\mathbf{E}[n(\mathcal{D})]$.

```
objective <- function(delta) {
  expected(ConditionalSampleSize(datadist, prior(delta)))
}
```

4.2.2 Constrains

The type one error rate is controlled at 0.025 on the boundary of the null hypothesis.

```
toer_cstr <- expected(ConditionalPower(datadist, H_0)) <= .025
```

Expected power $\Pr[c_2(\mathcal{D}, X_1) < X_2 | \delta \geq 0.0]$ must be larger than 0.8.

```
ep_cnstr <- function(delta) {
  prior      <- prior(delta)
  cnd_prior <- condition(prior, c(0, bounds(prior)[2]))
  return( expected(ConditionalPower(datadist, cnd_prior)) >= 0.8 )
}
```

4.2.3 Optimization problem

The optimization problem depending on Δ_i is defined below. The default optimization paramters, 5 pivot points, and a fixed initial design is used. [TODO: rationale for initial design?]

```
init <- TwoStageDesign(
  n1    = 150,
  c1f   = 0,
  c1e   = 2.3,
  n2    = 125.0,
  c2    = 2.0,
  order = 5
)

optimal_design <- function(delta) {

  minimize(

    objective(delta),

    subject_to(

      toer_cstr,
      ep_cnstr(delta)

    ),

  )
```



```

        initial_design = init
    )
}

```

Compute the sequence of optimal designs

```

deltas <- 3:0/10
results <- lapply(deltas, optimal_design)

```

4.2.4 Test cases

Check that iteration limit was not exceeded in any case.

```

iters <- sapply(results, function(x) x$nlptr_return$iterations)

print(iters)

```

```
## [1] 1746 1857 2438 2684
```

```
testthat::expect_true(all(iters <= 10000))
```

Check type one error rate control

```

sim_toer <- function(design) {
  simdata <- simulate(
    design,
    nsim = 10^6,
    dist = datadist,
    theta = .0,
    seed = 42
  )
  return(list(
    toer = mean(simdata$reject),
    se = sd(simdata$reject) / sqrt(nrow(simdata))
  ))
}

tmp <- sapply(results, function(x) sim_toer(x$design))
df_toer <- data.frame(
  toer = as.numeric(tmp[1, ]),
  se = as.numeric(tmp[2, ])
)
rm(tmp)

```

```
testthat::expect_true(all(df_toer$toer < .025))
```

```
df_toer
```


```
##      toer      se
## 1 0.024979 0.0001560611
## 2 0.024957 0.0001559941
## 3 0.024972 0.0001560398
## 4 0.024979 0.0001560611
```

4.2.5 Plot designs

Plot and assess for convergence

```
z1 <- seq(0, 3, by = .01)

tibble(
  delta = deltas,
  design = lapply(results, function(x) x$design)
) %>%
  group_by(delta) %>%
  do(
    z1 = z1,
    n = adoptr::n(.$design[[1]], z1),
    c2 = c2(.$design[[1]], z1)
  ) %>%
  unnest() %>%
  mutate(
    section = ifelse(
      is.finite(c2),
      "continuation",
      ifelse(c2 == -Inf, "efficacy", "futility")
    )
  ) %>%
  gather(variable, value, n, c2) %>%
  ggplot(aes(z1, value, color = delta)) +
  geom_line(aes(group = interaction(section, delta))) +
  facet_wrap(~variable, scales = "free_y") +
  theme_bw() +
  scale_color_continuous(bquote(Delta)) +
  theme(
    panel.grid = element_blank(),
    legend.position = "bottom"
  )
```



Chapter 5

Scenario IV: smaller effect, point alternative

5.1 Details

In this scenario an alternative effect size of $\delta = 0.2$ with point prior distribution is investigated. This smaller effect size should lead to larger sample sizes than in scenario I. The null hypothesis is $\delta \leq 0$. Currently, `adoptr` only supports normal distributed data what is widely spread in the development of adaptive designs. We protect the one-sided type one error rate at $\alpha = 0.025$ and require the power of the design to be at least $1 - \beta = 0.8$ in the first case and vary these values in the following cases.

5.1.1 Data distribution

Two-armed trial with normally distributed test statistic

```
datadist <- Normal(two_armed = TRUE)
```

5.1.2 Null hypothesis

The null hypothesis is $\mathcal{H}_0 : \delta \leq 0$

```
H_0 <- PointMassPrior(.0, 1)
```

5.1.3 Prior assumptions

A point mass prior with probability mass on $\delta = 0.2$ is assumed.

```
prior <- PointMassPrior(.2, 1)
```

5.2 Case IV-1: Minimizing Expected Sample Size under Point Prior

5.2.1 Objective

Expected sample size under the respective prior is minimized, i.e., $E[n(\mathcal{D})]$.

```
ess <- expected(ConditionalSampleSize(datadist, prior))
```

5.2.2 Constrains

The type one error rate is controlled at 0.025 on the boundary of the null hypothesis.

```
toer_cnstr <- expected(ConditionalPower(datadist, H_0)) <= .025
```

Power must be larger than 0.8.

```
pow_cnstr <- expected(ConditionalPower(datadist, prior)) >= .8
```

5.2.3 Initial Design

`adoptr` requires the definition of an initial design for optimization. We start with a group-sequential design from the package `rpact` that fulfills these constraints and is used later for comparison. The order of integration is set to 5.

```
order <- 5L
```

```
init_design_gs <- rpact_design(0.2, 0.025, 0.8, TRUE, order)
```

5.2.4 Optimization

The optimal design is computed in three variants: two-stage, group-sequential and one-stage. The input only differs with regard to the initial design. The optimal group-sequential design is used as initial design to compute the optimal two-stage design.

```
opt_design <- function(initial_design) {
  minimize(
    ess,
    subject_to(
      toer_cnstr,
      pow_cnstr
    ),
    initial_design = initial_design,
    opts = opts
  )
}
```

```

}

opt1_gs <- opt_design(init_design_gs)
opt1_ts <- opt_design(TwoStageDesign(opt1_gs$design))

## Warning in minimize(ess, subject_to(toer_cnstr, pow_cnstr), initial_design
## = initial_design, : initial design is infeasible!

opt1_os <- opt_design(OneStageDesign(500, 2.0))

```

5.2.5 Test Cases

Check if the optimization algorithm converged in all cases.

```

iters <- sapply(list(opt1_ts, opt1_gs, opt1_os),
               function(x) x$nlptr_return$iterations)

print(iters)

## [1] 1960  912   20
testthat::expect_true(all(iters < opts$maxeval))

```

The n_2 function of the optimal two-stage design is expected to be monotonously decreasing.

```

testthat::expect_equal(
  sign(diff(opt1_ts$design@n2_pivots)),
  rep(-1, (order - 1))
)

```

Type one error rate constraint is tested for the three designs. Due to numerical issues we allow a relative error of 2%.

```

tmp <- sapply(list(opt1_ts, opt1_gs, opt1_os),
              function(x) sim_pr_reject(x$design, .0, datadist))
df_toer <- data.frame(
  toer = as.numeric(tmp[1, ]),
  se   = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_toer$toer <= .025*(1.02)))

df_toer

```

```

##           toer           se
## 1 0.024975 0.0001560489
## 2 0.024978 0.0001560581
## 3 0.025116 0.0001564775

```

The power constraint can also be tested via simulation. Due to numerical issues we allow a relative error of 2%.

```

tmp <- sapply(list(opt1_ts, opt1_gs, opt1_os),
              function(x) sim_pr_reject(x$design, .2, datadist))
df_pow <- data.frame(
  pow = as.numeric(tmp[1, ]),

```

```

    se    = as.numeric(tmp[2, ])
  )
rm(tmp)

testthat::expect_true(all(df_pow$pow >= .8 * (1 - 0.02)))

df_pow

##           pow           se
## 1 0.799799 0.0004001509
## 2 0.799670 0.0004002475
## 3 0.799317 0.0004005115

```

The expected sample sizes should be ordered in a specific way.

```

testthat::expect_gte(
  evaluate(ess, opt1_os$design),
  evaluate(ess, opt1_gs$design)
)

testthat::expect_gte(
  evaluate(ess, init_design_gs),
  evaluate(ess, opt1_gs$design)
)

testthat::expect_gte(
  evaluate(ess, opt1_gs$design),
  evaluate(ess, opt1_ts$design)
)

```

The expected sample size of the optimal designs is simulated and compared to the outcome of `adoptr::evaluate()`. The tolerance is set to 0.5 what is due to rounding one patient per group in the worst case.

```

ess_0 <- expected(ConditionalSampleSize(datadist, H_0))

testthat::expect_equal(
  sim_n(opt1_os$design, .0, datadist),
  evaluate(ess_0, opt1_os$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt1_gs$design, .0, datadist),
  evaluate(ess_0, opt1_gs$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt1_ts$design, .0, datadist),
  evaluate(ess_0, opt1_ts$design),
  tolerance = .5
)

```

Additionally, the sample sizes under the point prior are compared.


```
testthat::expect_equal(
  sim_n(opt1_os$design, .2, datadist),
  evaluate(ess, opt1_os$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt1_gs$design, .2, datadist),
  evaluate(ess, opt1_gs$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt1_ts$design, .2, datadist),
  evaluate(ess, opt1_ts$design),
  tolerance = .5
)
```

5.3 Case IV-2: Increase Power

5.3.1 Objective

The objective remains the same as before.

5.3.2 Constrains

The power is increased to 90%.

```
pow_cnstr_2 <- expected(ConditionalPower(datadist, prior)) >= .9
```

5.3.3 Initial Design

The initial design is updated to a group-sequential design that fulfills the new power constraint.

```
order <- 5L

init_design_2_gs <- rpact_design(0.2, 0.025, 0.9, TRUE, order)

init_design_2 <- TwoStageDesign(init_design_2_gs)
```

5.3.4 Optimization

The optimal two-stage design is computed.

```
opt_design <- function(initial_design) {
  minimize(
    ess,
    subject_to(
```

```

        toer_cnstr,
        pow_cnstr_2

    ),

    initial_design = initial_design,

    opts = opts

)
}

opt2_ts <- opt_design(init_design_2)
opt2_gs <- opt_design(init_design_2_gs)
opt2_os <- opt_design(OneStageDesign(500, 2.0))

## Warning in minimize(ess, subject_to(toer_cnstr, pow_cnstr_2),
## initial_design = initial_design, : initial design is infeasible!

```

5.3.5 Test Cases

Check if the optimization algorithm converged in all cases.

```

iters <- sapply(list(opt2_ts, opt2_gs, opt2_os),
               function(x) x$nlptr_return$iterations)

print(iters)

## [1] 3008 1168 30

testthat::expect_true(all(iters < opts$maxeval))

```

The n_2 function of the optimal two-stage design is expected to be monotonously decreasing.

```

testthat::expect_equal(
  sign(diff(opt2_ts$design@n2_pivots)),
  rep(-1, (order - 1))
)

```

Type one error rate constraint is tested for the three designs. Due to numerical issues we allow a relative error of 2%.

```

tmp      <- sapply(list(opt2_ts, opt2_gs, opt2_os),
                  function(x) sim_pr_reject(x$design, .0, datadist))
df_toer <- data.frame(
  toer = as.numeric(tmp[1, ]),
  se   = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_toer$toer <= .025*(1.02)))

df_toer

##      toer      se

```

```
## 1 0.024980 0.0001560642
## 2 0.024946 0.0001559606
## 3 0.025116 0.0001564775
```

The power constraint can also be tested via simulation. Due to numerical issues we allow a relative error of 2%.

```
tmp      <- sapply(list(opt2_ts, opt2_gs, opt2_os),
                   function(x) sim_pr_reject(x$design, .2, datadist))
df_pow <- data.frame(
  pow  = as.numeric(tmp[1, ]),
  se   = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_pow$pow >= .9 * (1 - 0.02)))

df_pow
```

```
##           pow           se
## 1 0.900126 0.0002998321
## 2 0.899828 0.0003002293
## 3 0.899523 0.0003006351
```

The expected sample sizes should be ordered in a specific way.

```
testthat::expect_gte(
  evaluate(ess, opt2_os$design),
  evaluate(ess, opt2_gs$design)
)

testthat::expect_gte(
  evaluate(ess, init_design_2_gs),
  evaluate(ess, opt2_gs$design)
)

testthat::expect_gte(
  evaluate(ess, opt2_gs$design),
  evaluate(ess, opt2_ts$design)
)
```

The expected sample size of the optimal designs is simulated and compared to the outcome of `adoptr::evaluate()`. The tolerance is set to 0.5 what is due to rounding one patient per group in the worst case.

```
ess_0 <- expected(ConditionalSampleSize(datadist, H_0))

testthat::expect_equal(
  sim_n(opt2_os$design, .0, datadist),
  evaluate(ess_0, opt2_os$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt2_gs$design, .0, datadist),
  evaluate(ess_0, opt2_gs$design),
  tolerance = .5
)
```

```
)

testthat::expect_equal(
  sim_n(opt2_ts$design, .0, datadist),
  evaluate(ess_0, opt2_ts$design),
  tolerance = .5
)
```

Additionally, the sample sizes under the point prior are compared.

```
testthat::expect_equal(
  sim_n(opt2_os$design, .2, datadist),
  evaluate(ess, opt2_os$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt2_gs$design, .2, datadist),
  evaluate(ess, opt2_gs$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt2_ts$design, .2, datadist),
  evaluate(ess, opt2_ts$design),
  tolerance = .5
)
```

5.4 Case IV-3: Increase Type One Error rate

5.4.1 Objective

Expected sample size under the point prior is minimized and has already been defined.

5.4.2 Constrains

The maximal type one error rate is increased to 5%.

```
toer_cnstr_2 <- expected(ConditionalPower(datadist, H_0)) <= .05
```

5.4.3 Initial Design

The initial design is updated to a group-sequential design that fulfills the new type one error rate constraint.

```
order <- 5L

init_design_3_gs <- rpact_design(0.2, 0.05, 0.9, TRUE, order)

init_design_3 <- TwoStageDesign(init_design_3_gs)
```

5.4.4 Optimization

The optimal two-stage design is computed.

```
opt_design <- function(initial_design) {
  minimize(

    ess,

    subject_to(

      toer_cnstr_2,
      pow_cnstr_2

    ),

    initial_design = initial_design,

    opts = opts

  )
}

opt3_ts <- opt_design(init_design_3)
opt3_gs <- opt_design(init_design_3_gs)
opt3_os <- opt_design(OneStageDesign(500, 2.0))

## Warning in minimize(ess, subject_to(toer_cnstr_2, pow_cnstr_2),
## initial_design = initial_design, : initial design is infeasible!
```

5.4.5 Test Cases

Check if the optimization algorithm converged in all cases.

```
iters <- sapply(list(opt3_ts, opt3_gs, opt3_os),
  function(x) x$nlptr_return$iterations)

print(iters)

## [1] 3294 880 27

testthat::expect_true(all(iters < opts$maxeval))
```

The n_2 function of the optimal two-stage design is expected to be monotonously decreasing.

```
testthat::expect_equal(
  sign(diff(opt3_ts$design@n2_pivots)),
  rep(-1, (order - 1))
)
```

Type one error rate constraint is tested for the three designs. Due to numerical issues we allow a relative error of 2%.

```
tmp <- sapply(list(opt3_ts, opt3_gs, opt3_os),
  function(x) sim_pr_reject(x$design, .0, datadist))
df_toer <- data.frame(
```

```

    toer = as.numeric(tmp[1, ]),
    se   = as.numeric(tmp[2, ])
  )
rm(tmp)

testthat::expect_true(all(df_toer$toer <= .055*(1.02)))

df_toer

##           toer           se
## 1 0.050175 0.0002183060
## 2 0.049981 0.0002179058
## 3 0.050150 0.0002182545

```

The power constraint can also be tested via simulation. Due to numerical issues we allow a relative error of 2%.

```

tmp <- sapply(list(opt3_ts, opt3_gs, opt3_os),
              function(x) sim_pr_reject(x$design, .2, datadist))
df_pow <- data.frame(
  pow = as.numeric(tmp[1, ]),
  se  = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_pow$pow >= .9 * (1 - 0.02)))

df_pow

##           pow           se
## 1 0.900057 0.0002999241
## 2 0.900318 0.0002995757
## 3 0.899606 0.0003005248

```

The expected sample sizes should be ordered in a specific way.

```

testthat::expect_gte(
  evaluate(ess, opt3_os$design),
  evaluate(ess, opt3_gs$design)
)

testthat::expect_gte(
  evaluate(ess, init_design_3_gs),
  evaluate(ess, opt3_gs$design)
)

testthat::expect_gte(
  evaluate(ess, opt3_gs$design),
  evaluate(ess, opt3_ts$design)
)

```

The expected sample size of the optimal designs is simulated and compared to the outcome of `adoptr::evaluate()`. The tolerance is set to 0.5 what is due to rounding one patient per group in the worst case.

```

ess_0 <- expected(ConditionalSampleSize(datadist, H_0))

```

```

testthat::expect_equal(
  sim_n(opt3_os$design, .0, datadist),
  evaluate(ess_0, opt3_os$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt3_gs$design, .0, datadist),
  evaluate(ess_0, opt3_gs$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt3_ts$design, .0, datadist),
  evaluate(ess_0, opt3_ts$design),
  tolerance = .5
)

```

Additionally, the sample sizes under the point prior are compared.

```

testthat::expect_equal(
  sim_n(opt3_os$design, .2, datadist),
  evaluate(ess, opt3_os$design),
  tolerance = .5
)


testthat::expect_equal(
  sim_n(opt3_gs$design, .2, datadist),
  evaluate(ess, opt3_gs$design),
  tolerance = .5
)

testthat::expect_equal(
  sim_n(opt3_ts$design, .2, datadist),
  evaluate(ess, opt3_ts$design),
  tolerance = .5
)

```

5.5 Plot Two-Stage Designs

The optimal two-stage designs stemming from the three different variants are plotted together.



Chapter 6

Secenario V

6.1 Details

In this scenario an alternative effect size of $\delta = 0.3$ with point prior distribution is investigated. This smaller effect size should lead to larger sample sizes than in scenario I. The null hypothesis is $\delta \leq 0$. Currently, `adoptr` only supports normal distributed data what is widely spread in the development of adaptive designs.

6.1.1 Data distribution

One-armed trial with normally distributed test statistic

```
datadist <- Normal(two_armed = FALSE)
```

6.1.2 Null hypothesis

The null hypothesis is $\mathcal{H}_0 : \delta \leq 0$

```
H_0 <- PointMassPrior(.0, 1)
```

6.1.3 Prior assumptions

A point mass prior with probability mass on $\delta = 0.3$ is assumed.

```
prior <- PointMassPrior(.3, 1)
```

6.2 Case V-1, sensitivity to integration order

6.2.1 Objective

Expected sample size under the respective prior is minimized, i.e., $\mathbf{E}[n(\mathcal{D})]$.

```
ess <- expected(ConditionalSampleSize(datadist, prior))
```

6.2.2 Constrains

The type one error rate is controlled at 0.025 on the boundary of the null hypothesis.

```
toer_cnstr <- expected(ConditionalPower(datadist, H_0)) <= .025
```

Power must be larger than 0.8.

```
pow_cnstr <- expected(ConditionalPower(datadist, prior)) >= .8
```

6.2.3 Initial Design

A fixed design for these parameters would require 176 subjects per group. We use the half of this as initial values for the sample sizes. The initial stop for futility is at $c_1^f = 0$, i.e., if the effect shows in the opponent direction to the alternative. The starting values for the efficacy stop and for c_2 is the $1 - \alpha$ - quantile of the normal distribution.

```
init_design <- function(order) {
  TwoStageDesign(
    n1 = ceiling(pwr::pwr.t.test(d = .3, sig.level = .025, power = .8, alternative = "greater")$n),
    c1f = 0,
    c1e = qnorm(1 - 0.025),
    n2 = ceiling(pwr::pwr.t.test(d = .3, sig.level = .025, power = .8, alternative = "greater")$n),
    c2 = qnorm(1 - 0.025),
    order = order
  )
}
```

6.2.4 Optimization

The optimal design is computed for three different integration orders: 5, 8, and 11.

```
opt_design <- function(order) {
  minimize(

    ess,

    subject_to(

      toer_cnstr,
      pow_cnstr

    ),

    initial_design = init_design(order),

    opts = opts

  )
}

opt1 <- lapply(c(5, 8, 11), function(x) opt_design(x))
```

```
## Warning in minimize(ess, subject_to(toer_cnstr, pow_cnstr), initial_design
```

```
## = init_design(order), : initial design is infeasible!

## Warning in minimize(ess, subject_to(toer_cnstr, pow_cnstr), initial_design
## = init_design(order), : initial design is infeasible!

## Warning in minimize(ess, subject_to(toer_cnstr, pow_cnstr), initial_design
## = init_design(order), : initial design is infeasible!
```

6.2.5 Test cases

Check if the optimization algorithm converged in all cases.

```
iters <- sapply(opt1, function(x) x$nlptr_return$iterations)

print(iters)
```

```
## [1] 2044 4660 8826

testthat::expect_true(all(iters < opts$maxeval))
```

Check type one error rate control. Due to numerical issues we allow a relative error of 2%.

```
sim_toer <- function(design) {
  simdata <- simulate(
    design,
    nsim = 10^6,
    dist = datadist,
    theta = .0,
    seed = 42
  )
  return(list(
    toer = mean(simdata$reject),
    se = sd(simdata$reject) / sqrt(nrow(simdata))
  ))
}

tmp <- sapply(opt1, function(x) sim_toer(x$design))
df_toer <- data.frame(
  toer = as.numeric(tmp[1, ]),
  se = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_toer$toer < .025 * (1 + .02)))

df_toer
```

```
##      toer      se
## 1 0.024978 0.0001560581
## 2 0.024955 0.0001559881
## 3 0.024951 0.0001559759
```

Check power

```
sim_pow <- function(design) {
  simdata <- simulate(
```

```

    design,
    nsim = 10^6,
    dist = datadist,
    theta = .3,
    seed = 42
  )
  return(list(
    pow = mean(simdata$reject),
    se = sd(simdata$reject) / sqrt(nrow(simdata))
  ))
}

tmp      <- sapply(opt1, function(x) sim_pow(x$design))
df_pow <- data.frame(
  power = as.numeric(tmp[1, ]),
  se     = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_pow$pow > 0.8 * (1 - .02)))

df_pow

```

```

##      power      se
## 1 0.799817 0.0004001374
## 2 0.799668 0.0004002490
## 3 0.799646 0.0004002655

```

Check expected sample size under the prior

```

sim_ess <- function(design) {
  simdata <- simulate(
    design,
    nsim = 10^6,
    dist = datadist,
    theta = .3,
    seed = 42
  )
  return(list(
    n = mean(simdata$n1 + simdata$n2),
    se = sd(simdata$n1 + simdata$n2) / sqrt(nrow(simdata))
  ))
}

tmp      <- sapply(opt1, function(x) sim_ess(x$design))
df_ess <- data.frame(
  n = as.numeric(tmp[1, ]),
  se = as.numeric(tmp[2, ])
)
rm(tmp)

df_ess

```

```

##      n      se
## 1 70.98114 0.02437353

```

```
## 2 70.99017 0.02438000
## 3 70.99167 0.02437997
```

6.3 Case V-2, utility maximization

6.3.1 Objective

In this case, a utility function consisting of expected sample size and power is minimized.

```
pow <- expected(ConditionalPower(datadist, prior))

obj <- function(lambda) {
  expected(ConditionalSampleSize(datadist, prior)) +
    (-lambda) * pow
}
```

6.3.2 Constrains

The type one error rate is controlled at 0.025 on the boundary of the null hypothesis. Hence, the previous inequality can still be used.

6.3.3 Initial Design

The previous initial design with order 5 is applied.

6.3.4 Optimization

The optimal design is computed for two values of λ : 100 and 200.

```
opt2_design <- function(lambda) {

  minimize(

    obj(lambda),

    subject_to(

      toer_cnstr

    ),

    initial_design = init_design(5),

    opts = opts

  )
}

opt2 <- lapply(c(100, 200), function(x) opt2_design(x))
```

```
## Warning in minimize(obj(lambda), subject_to(toer_cnstr), initial_design =
## init_design(5), : initial design is infeasible!

## Warning in minimize(obj(lambda), subject_to(toer_cnstr), initial_design =
## init_design(5), : initial design is infeasible!
```

6.3.5 Test cases

Check if the optimization algorithm converged in all cases.

```
iters <- sapply(opt2, function(x) x$nlptr_return$iterations)

print(iters)
```

```
## [1] 3378 3024

testthat::expect_true(all(iters < opts$maxeval))
```

Check type one error rate control for both designs via simulation. Due to numerical issues we allow a relative error of 2%.

```
tmp      <- sapply(opt2, function(x) sim_toer(x$design))
df_toer <- data.frame(
  toer = as.numeric(tmp[1, ]),
  se   = as.numeric(tmp[2, ])
)
rm(tmp)

testthat::expect_true(all(df_toer$toer < .025 * (1 + .02)))


df_toer
```

```
##           toer           se
## 1 0.025022 0.0001561919
## 2 0.024971 0.0001560368
```

Check if the power of the design with higher λ is larger.

```
testthat::expect_gte(
  evaluate(pow, opt2[[2]]$design),
  evaluate(pow, opt2[[1]]$design)
)
```

Finally the three designs computed so far are plotted together to allow comparison.



6.4 Case V-3, n1-penalty

In this case, the influence of the regularization term $N1()$ is investigated.

6.4.1 Objective

In this case, a mixed criterion consisting of expected sample size and n_1 is minimized.

```
N1 <- N1()

obj3 <- function(lambda) {
  ess + lambda * N1
}
```

6.4.2 Constrains

The inequalities from variant V.1 can still be used.

6.4.3 Initial Design

The previous initial design with order 5 is applied.

6.4.4 Optimization

The optimal design is computed for two values of λ : 0.05 and 0.2.

```
opt3_design <- function(lambda) {

  minimize(

    obj3(lambda),

    subject_to(

      toer_cnstr,
      pow_cnstr

    ),

    initial_design = init_design(5),

    opts = opts

  )
}

opt3 <- lapply(c(.05, .2), function(x) opt3_design(x))

## Warning in minimize(obj3(lambda), subject_to(toer_cnstr, pow_cnstr),
## initial_design = init_design(5), : initial design is infeasible!

## Warning in minimize(obj3(lambda), subject_to(toer_cnstr, pow_cnstr),
## initial_design = init_design(5), : initial design is infeasible!
```

6.4.5 Test cases

Check if the optimization algorithm converged in all cases.

```
iters <- sapply(opt3, function(x) x$nlptr_return$iterations)

print(iters)

## [1] 2222 2222


testthat::expect_true(all(iters < opts$maxeval))
```

Check if the n1 regularizer of the design with higher λ is lower.

```
testthat::expect_lte(
  evaluate(N1, opt3[[2]]$design),
  evaluate(N1, opt3[[1]]$design)
)

testthat::expect_lte(
  evaluate(N1, opt3[[1]]$design),
  evaluate(N1, opt1[[1]]$design)
)
```


Finally the three designs computed so far are plotted together to allow comparison.



6.5 Case V-4, n2-penalty

In this case the average over n_2 is penalized by the predefined score `AverageN2`.

6.5.1 Objective

In this case, a mixed criterion consisting of expected sample size and average of n_2 is minimized.

```
avn2 <- AverageN2()

obj4 <- function(lambda) {
  ess + lambda * avn2
}
```

6.5.2 Constrains

The inequalities from variant V.1 can still be used.

6.5.3 Initial Design

The previous initial design with order 5 is applied.

6.5.4 Optimization

The optimal design is computed for two values of λ : 0.01 and 0.1.

```
opt4_design <- function(lambda) {

  minimize(

    obj4(lambda),

    subject_to(

      toer_cnstr,
      pow_cnstr

    ),

    initial_design = init_design(5),
    upper_boundary_design = get_upper_boundary_design(init_design(5), c2_buffer=3),

    opts = opts

  )
}

opt4 <- lapply(c(.01, .1), function(x) opt4_design(x))

## Warning in minimize(obj4(lambda), subject_to(toer_cnstr, pow_cnstr),
## initial_design = init_design(5), : initial design is infeasible!

## Warning in minimize(obj4(lambda), subject_to(toer_cnstr, pow_cnstr),
## initial_design = init_design(5), : initial design is infeasible!
```

6.5.5 Test cases

Check if the optimization algorithm converged in all cases.

```
iters <- sapply(opt4, function(x) x$nlptr_return$iterations)

print(iters)

## [1] 1952 1530

testthat::expect_true(all(iters < opts$maxeval))
```

Check if the average n_2 regularizer of the design with higher λ is lower.

```
testthat::expect_lte(
  evaluate(avn2, opt4[[2]]$design),
  evaluate(avn2, opt4[[1]]$design)
)
```

```
testthat::expect_lte(
  evaluate(avn2, opt4[[1]]$design),
  evaluate(avn2, opt1[[1]]$design)
)
```

Finally the three designs computed so far are plotted together to allow comparison.

