

AI Agent Guide: Webhook Return Response

Piece: @activepieces/piece-webhook | **Action:** return_response | **Version:** ~0.1.24

This action sends an HTTP response back to the webhook caller. It **MUST** be the **last step** in every webhook-triggered flow. No connection required.

1. Input Settings

Property	Type	Required	Default	Options
responseType	STATIC_DROPDOWN	No	"json"	"json", "raw", "redirect"
fields	DYNAMIC (depends on response- Type)	Yes	—	See section 2
respond	STATIC_DROPDOWN	No	"stop"	"stop" (end flow), "respond" (continue flow)

2. fields sub-properties by responseType

responseType = “json” (most common)

Sub-field	Type	Required	Default	Description
status	NUMBER	No	200	HTTP status code
headers	OBJECT	No	{}	Custom response headers
body	JSON	Yes	—	JSON response body. Use <code>{{step_N['...']}}</code> to reference upstream data.

`responseType = "raw"`

Sub-field	Type	Required	Default
status	NUMBER	No	200
headers	OBJECT	No	{}
body	TEXT	Yes	—

`responseType = "redirect"`

Sub-field	Type	Required
url	TEXT	Yes

3. Full Example — ADD then UPDATE

Step 1: ADD_ACTION

```
Update_flow(  
  flow_id = "<flow_id>",  
  operation = "ADD_ACTION",  
  operation_body = {  
    "parentStep": "step_3",  
    "stepLocationRelativeToParent": "AFTER",  
    "action": {  
      "name": "step_4",  
      "displayName": "Return Response",  
      "type": "PIECE",  
      "valid": false,  
      "settings": {  
        "pieceName": "@activepieces/piece-webhook",  
        "actionName": "return_response",  
        "pieceVersion": "~0.1.24",  
        "input": {},  
        "propertySettings": {},  
        "errorHandlingOptions": {}  
      }  
    }  
  }  
)
```

Step 2: UPDATE_ACTION

```
Update_flow(  
  flow_id = "<flow_id>",  
  operation = "UPDATE_ACTION",  
  operation_body = {  
    "parentStep": "step_3",  
    "stepLocationRelativeToParent": "AFTER",  
    "action": {  
      "name": "step_4",  
      "displayName": "Return Response",  
      "type": "PIECE",  
      "valid": false,  
      "settings": {  
        "pieceName": "@activepieces/piece-webhook",  
        "actionName": "return_response",  
        "pieceVersion": "~0.1.24",  
        "input": {},  
        "propertySettings": {},  
        "errorHandlingOptions": {}  
      }  
    }  
  }  
)
```

```

flow_id = "<flow_id>",
operation = "UPDATE_ACTION",
operation_body = {
    "name": "step_4",
    "displayName": "Return Response",
    "type": "PIECE",
    "valid": true,
    "skip": false,
    "settings": {
        "pieceName": "@activepieces/piece-webhook",
        "actionName": "return_response",
        "pieceVersion": "~0.1.24",
        "input": {
            "responseType": "json",
            "fields": {
                "status": 200,
                "headers": {},
                "body": {
                    "success": true,
                    "full_name": "{{step_1['success'] [0] ['data'] ['properties'] ['full_name']}}",
                    "company": "{{step_1['success'] [0] ['data'] ['properties'] ['company']}}",
                    "record_id": "{{step_2['success'] ['recordId']}}"
                }
            },
            "respond": "stop"
        },
        "propertySettings": {
            "responseType": { "type": "MANUAL" },
            "fields": {
                "type": "MANUAL",
                "schema": {
                    "status": { "displayName": "Status", "required": false, "defaultValue": 200, "type": "NUMBER" },
                    "headers": { "displayName": "Headers", "required": false, "type": "OBJECT" },
                    "body": { "displayName": "JSON Body", "required": true, "type": "JSON" }
                }
            },
            "respond": { "type": "MANUAL" }
        },
        "errorHandlingOptions": {
            "continueOnFailure": { "value": false },
            "retryOnFailure": { "value": false }
        }
    }
}
)

```

4. `verify_flow` checklist

- `responseType` set (usually `"json"`)
- `fields` matches chosen `responseType` (see section 2)
- `respond` set (`"stop"` for last step)
- `propertySettings` has `schema` for `fields` (DYNAMIC property)
- `errorHandlingOptions` present with `{ "value": false }` entries
- `valid = true`