

## MOSIL BRB - 1100

### Multipurpose Moly Grease

Most VERSATILE complex soap based grease blended with Molybdenum disulphide which develops a tenacious low friction film with an excellent load carrying capacity. It is also fortified with additives such as E. P. Rust and Corrosion inhibitor and anti-oxidant to reduce wear, provide good water repellency and oxidation stability.

#### AREA OF APPLICATION

All types of plain and anti friction Ball and Roller Bearings and Bushings, Rack and Pinion, Gears, Linkages, Slides, Universal joints, Kingpins, Guides, Chains, Centralized lubrication systems, Electric motors, Pumps, EOT Cranes, Forklifts and other greasing applications.

#### BENEFITS

- ➔ Multipurpose application thereby reducing grease inventory.
- ➔ Extends re-lubrication interval.
- ➔ Reduces maintenance downtime.
- ➔ Increases bearing life by reduction in wear and tear.
- ➔ Protects from rust and corrosion.
- ➔ Reduces the co-efficient of friction of the lubricated system.

#### PACKING: 1 Kg Jar, 20 Kg Pail

Owing to evolving packaging solutions, user is requested to kindly check the availability of a specific pack size prior to standardization.



## CHARACTERISTICS

## TYPICAL VALUES

1. Appearance	Smooth Homogeneous Grease
2. Base Oil	Synthetic (PAO, Ester)
3. Thickener	Complex Lithium Soap
4. Colour	Black to Gray Black
5. Specific Gravity	0.90 ± 0.05
6. Drop Point (°C)	180 min.
7. Consistency (NLGI)	# 2
8. Worked Penetration	265 - 295
9. Water Resistance	Excellent
10. Copper Strip Corrosion	Negative
11. Additives	Anti-oxidant, Anti-rust Anti-corrosion & E.P.
12. Temperature Range (°C)	-40 to +150

*Material Safety Information required for safe usage of this product may not be included in this product bulletin and may be sought by contacting MOSIL. Users are advised to go through the Material Safety Data Sheet (MSDS) of this product prior to application / usage of this product.*

*All statements and information contained in this document are based on the laboratory testing and user experience on actual applications. Owing to the exhaustive possibility of application for which this product may be used and the variety of equipments, performance parameters, environmental conditions and unpredictable human factors, we strongly recommend that this product be tested on the actual application prior to its standardization. All information contained herewith is offered in good faith but without any expressed or implied warranty. This Product Bulletin may already have been revised considering the availability of raw components, legislation, user experience & expectations and enhancement of knowledge of the development team of MOSIL. Users are requested to kindly seek the latest version of this product bulletin by contacting MOSIL. Information provided in this Product Bulletin is based on the generalised expectations and requirements of users. Additional information for this product may also be sought by contacting MOSIL.*

Rev 02, Issue 00

### **Mosil Lubricants Private Limited**

**Technical Services Dept:** "ANIRA" Plot No. A-791/3, MIDC Khairne, Navi Mumbai - 400710. INDIA  
T: +91 22 2464 0500 / 0501 | F: +91 22 2778 8505 | E: corporate@mosil.com | W: www.mosil.com  
Regd Office: 166/1, KALANIDHI, Sion(West), Mumbai - 400 022 | CIN # U23200 MH 2000 PT C124177

