



Litz Wire

Cable for high frequency, high power applications

A selection of high quality litz wires designed for use in high frequency power systems such as induction heating, specialist motors, transformers and Tesla Coils.

Current ratings are approximate as the capacity will vary with frequency and length used.

Current	3A	3A	5A	6A	12A	18A	20A (polyimide film)	40A	70A
Strand Size (mm)	0.1	0.07	0.2	0.15	0.05	0.05	0.05	0.1	0.1
No. of Strands	75	160	25	60	1000	1500	1740	1000	2000

Cable Specification @ 25 °C

Current (amps)	3	3	5	6	12	18	20	40	70
Strand Quantity (Configuration)	75	160 (32x5)	25	60	1000	1500 (60x5x5)	1740	1000	2000
Strand Diameter (mm)	0.1	0.07	0.2	0.15	0.05	0.05	0.05	0.1	0.1
Total Diameter (mm)	1.23	1.25	1.42	1.55	2.55	2.95	3.5x2.4	4.4	6.65
Breakdown Voltage	3100	2600	2600	3900	2600	2600	2600	3500	3400
Outer Coating	Silk ¹	Silk ¹	Silk ¹	Silk ¹	Silk ²	Silk ²	Tape ³	Silk ²	Silk ²
Thermal Class	130	155	155	155	155	155	155	155	155
Max Resistance (Ω/km)	29.8	28.4	ND	16.06	8.9	6.15	5.36	2.13	1.06

¹ Polyester Silk Wrapping, 1 layer

² Polyester Silk Wrapping, 2 layers

³ Polyimide Tape Wrapping, 1 layer

ND: No Data available

We also offer custom soldering, coils, and fully custom cable assemblies

If you need sizes other than what we stock, we can make it to order. Lead time for fully custom litz wire is approximately 6 weeks with a minimum order of £1000