Electric Detonator

Short Delay Detonators (SDD)

Delay No.	Designated Delay Time	Acceptable Range
0	0ms	+10
1	25ms	25 ± 10ms
2	50ms	50 ± 10ms
3	75ms	75 ± 10ms
4	100ms	100 ± 10ms
5	125ms	125 ± 10ms
6	150ms	150 ± 10ms
7	175ms	175 ± 10ms
8	200ms	200 ± 10ms
9	225ms	225 ± 10ms
10	250ms	250 ± 10ms

Long Delay Detonators (LDD)

Delay No.	Designated Delay Time	Acceptable Range
1	500ms	500 ± 10ms
2	1000ms	1000 ± 10ms
3	1500ms	1500 ± 10ms
4	2000ms	2000 ± 10ms
5	2500ms	2500 ± 10ms
6	3000ms	3000 ± 10ms
7	3500ms	3500 ± 10ms
8	4000ms	4000 ± 10ms
9	4500ms	4500 ± 10ms
10	5000ms	5000 ± 10ms
11	5500ms	5500 ± 10ms
12	6000ms	6000 ± 10ms
13	6500ms	6500 ± 10ms
14	7000ms	7000 ± 10ms
15	7500ms	7500 ± 10ms
16	8000ms	8000 ± 10ms
17	8500ms	8500 ± 10ms
18	9000ms	9000 ± 10ms
19	9500ms	9500 ± 10ms
20	10000ms	10000 ± 10ms
21	10500ms	10500 ± 10ms