## **Cheatsheet: Python Coding Practices and Packaging Concepts**



Estimated time needed: 5 minutes

| Package/Method          | Description  | Code Example   |
|-------------------------|--|--|
| Packaging               | To create a package, the folder structure is as follows:  1. Project folder → Package name →initpy, module_1.py, module_2.py, and so on.  2. In theinitpy file, add code to reference the modules in the package.  | <pre>module1.py def function_1(arg):     return <operation output="">     _initpy:     from . import function_1</operation></pre>  |
| Python Style<br>Guide   | <ul> <li>Four spaces for indentation</li> <li>Use blank lines to separate functions and classes</li> <li>Use spaces around operators and after commas</li> <li>Add larger blocks of code inside functions</li> <li>Name functions and files using lowercase with underscores</li> <li>Name classes using CamelCase</li> <li>Name constants in capital letters with underscores separating words</li> </ul> | <pre>def function_1(a, b):     if a &gt; b:         c = c + 5     else:         c = c - 3     return c c = function_1(a, b) Constant Definition example MAX_FILE_UPLOAD_SIZE</pre> |
| Static Code<br>Analysis | Use Static code analysis method to evaluate your code against a predefined style and standard without executing the code.  | Shell code:  pylint code.py  |

| Package/Method | Description  | Code Example   |
|----------------|--|--|
|                | For example, use Pylint to perform static code analysis.   |  |
| Unit Testing   | Unit testing is a method to validate if units of code are operating as designed.  During code development, each unit is tested. The unit is tested in a continuous integration/continuous delivery test server environment.  You can use different test functions to build unit tests and review the unit test output to determine if the test passed or failed. | <pre>import unittest  from mypackage.mymodule import my_function  class TestMyFunction(unittest.TestCase):     def test_my_function(self):         result = my_function(<args>)         self.asserEqual(result,</args></pre> |

## Author(s)

Abhishek Gagneja

## Other Contributor(s)

Andrew Pfeiffer, Sina Nazeri