Assignment 12 Solutions

Q1. Does assigning a value to a string's indexed character violate Python's string immutability?

ANS: String's indexed character cannot to be assigned a New value, as Strings are immutable.

Example:

```
name = "Reinforcement"

print(id(name) ) #73472

name[0] = "V" # Raises TypeError
```

Q2. Does using the += operator to concatenate strings violate Python's string immutability? Why or why not?

ANS: += operator is used to concatenate strings, it does not voilate Python's string immutability Property. Because doing so new creates a new association with data andvariable. E.g. str_1="a" and str_1+="b". effect of this statements to create string ab and reassign it to variable str 1, any string data is not actually modified.

```
In [1]:
    str_1 = 'a'
    print(id(str_1))
    str_1 += 'b'
    print(id(str_1)) # Does not Modify existing string, Creates a new String

2236957116336
2237048537136
```

Q3. In Python, how many different ways are there to index a character?

ANS: A Character in string can be indexed using string name followed by index number of character in square bracket. **Positive Indexing** i.e. first index is 0 an so on, or **Negative Indexing** i.e. last letter is -1 and so on can be used to index a character

```
in_string = "iNeuron Full Stack Data Science"
print(in_string[8],in_string[10],in_string[3]) # Positive Indexing
print(in_string[-2],in_string[-4],in_string[-3]) # Negative Indexing
F l u
c e n
```

Q4. What is the relationship between indexing and slicing?

ANS: We can access elements of sequence datatypes by using slicing and indexing. Indexing is used to obtaining individual element while slicing for sequence of elements.

```
in_string = "iNeuron Full Stack Data Science"
    print(in_string[2],in_string[4],in_string[6]) #Indexing
    print(in_string[2:15]) # Slicing

e r n
    euron Full St
```

Q5. What is an indexed character's exact data type? What is the data form of a slicing-generated substring?

ANS: Indexed characters and sliced substrings have datatype String.

```
In [7]: in string - Willowson Eull Stock Data Coioncell
```

```
print(type(in_string[2])) # Indexing -> str
print(type(in_string[3:10])) # Indexing -> str

<class 'str'>
<class 'str'>
```

Q6. What is the relationship between string and character "types" in Python?

ANS: object that contains sequence of character datatypes are called String.

Q7. Identify at least two operators and one method that allow you to combine one or more smaller strings to create a larger string?

ANS: +, += and * allow to combine one or more smaller strings to create a larger string. .join() method joins element of iterable type like list and tuple to get a combined string.

```
in_string = 'iNeuron '
in_string += 'Full Stack Data Science'
print(in_string + 'FSDS')
print('FSDS '*2)
print(" ".join(['I','N','E','U','R','0','N'])) # List Iterable
print(" ".join(('I','N','E','U','R','0','N')).lower()) # Tuple Iterable

iNeuron Full Stack Data Science FSDS
FSDS FSDS
I N E U R O N
i n e u r o n
```

Q8. What is the benefit of first checking the target string with in or not in before using the index method to find a substring?

ANS: Checking the target string with **in** or **not** Operators before using the index method to find a substring just helps confirming availability of substring and thus avoid raising of **ValueError.

Example:

```
in_string = "ineuron"
in_string.index('x') , # Raises ValueError
in_string.index('u') # 3
```

Q9. Which operators and built-in string methods produce simple Boolean (true/false) results?

ANS: The String Operators and built-in methods to Produce Simple Boolean (True/False) Result are:

- in
- not
- .isalpha()
- .isalnum()
- .isdecimal()
- · .isdigit()
- .islower()
- .isnumeric()
- .isprintable()
- .isspace()
- .istitle()

In []:

Loading [MathJax]/jax/output/CommonHTML/fonts/TeX/fontdata.js