

BRNO UNIVERSITY OF TECHNOLOGY
FACULTY OF INFORMATION TECHNOLOGY

Modelling and Simulation – Project (T5: SHO Model of logistics)
The use of electric and autonomous cars in the
transport company Packeta

Contents

1	Introduction	2
1.1	Study sources	2
1.2	Model validation	2
1.3	Used technologies and procedures	2
2	Facts and Hypotheses	2
3	Model Design	3
4	Architecture of the simulation model	3
5	Experiments	3
6	Conclusion	3

1 Introduction

The objective of this project is to formulate a model [[8], slide 7] for the logistics, transport, and parcel delivery operations of Packeta, a company specializing in these services. The primary aim of this model [[8], slide 7] is to determine the optimal ratio of conventional, electric, and autonomous vehicles for practical implementation in last-mile delivery. Concurrently, the simulation [[8], slide 8] experiments are designed to explain the financial implications associated with employing different modes of transport and to assess efficiency under varying loads, measured by the number of parcels for delivery.

To achieve these goals, a specific depot within the Žilina region was selected for the study, namely, the Žilina, Strečno depot.

[[K čemu chcete dospět. K čemu jste dospěli, případně ešte upravit' úvod podl'a potreby vid' prezentácia k projektu slide 22]]

1.1 Study sources

The primary source of resources for this project was derived from the official website of Packeta [6]. Due to the company's reluctance to disclose internal information beyond what is officially published, supplementary data essential for model creation was gathered from articles [3], [5], [2], the internet [9], and professional papers. Notably, information about autonomous cars was predominantly sourced from scientific articles [1], [4].

1.2 Model validation

[[Ako sa nám podarilo overit' validitu modelu]]

1.3 Used technologies and procedures

The implementation of the project utilized the C++ programming language along with the SIMLIB library [7]. These technologies were chosen for their suitability in addressing the specified problem, offering a requisite interface, ease of use, and being freely accessible.

2 Facts and Hypotheses

The factual basis for the project primarily relied on information about the vehicles used by Packeta, sourced from the official website of the vehicle manufacturer. The number of parcels a courier can deliver daily was derived from article [2] on the internet, featuring the CEO of Packeta, who highlighted the effectiveness of parcel lockers and address deliveries. According to the article, a courier can deliver approximately 100 parcels to an address and up to 2500 parcels per day to parcel lockers. This information was cross-referenced with data on the popularity of various delivery destinations [5] to calculate the average number of parcels that the courier can deliver per day.

The model also incorporates the cost of courier services, a factor considered due to its elimination with autonomous cars. The price of courier work was obtained from job portals and the official website of Packeta, where such job details are available.

The characteristics of autonomous cars were chosen hypothetically, drawing from articles [1] and [4]. These values were adjusted with a forward-looking perspective, aiming for a greater range and capacity to enhance their significance for a company like Packeta. The delivery time for autonomous cars was determined hypothetically, considering the optimization of traffic navigation, an advantage inherent in sophisticated control systems.

Average delivery distances were determined based on the delivery locations map available on Packeta's official website [6] and the geographical structure of the Žilina region. Specifically, areas in the north of Slovakia were identified as being 65 – 75 kilometers away from the distribution depot (Žilina, Strečno). The

circular route of an electric delivery vehicle covering such distances could pose challenges, particularly in the winter months when the range of electric cars tends to decrease.

3 Model Design

Parcels are delivered from the designated depot daily and they are categorized into two distinct groups. The initial group contains parcels necessitating delivery beyond the operational range of electric or autonomous vehicles, constituting 2–8% [6] of the entire parcel volume. The average distance covered for deliveries in this group spans 180–200 kilometers [6]. The fuel cost for the vehicle employed by the designated company is 1,705€ per liter, with a fuel consumption rate of 8.8 liters per 100 kilometers [9].

The second group, constituting 98–92% [6] of the parcels, encompasses those amenable to delivery through all available means. The average distance covered for deliveries in this category ranges from 130–150 kilometers [6], [3]. Each courier is equipped to handle 1274–1574 parcels [2], [5], inclusive of loading, transportation, and unloading, within their 8-hour work shift. Couriers utilizing electric cars recharge their vehicles overnight at the depot, ensuring they are ready for the next day's deliveries. The cost of electricity is approximately 0.185€ per kilowatt-hour (kWh), and the electric car in use has a consumption rate of 0.35 kWh per 100 kilometers [9].

Upon completion of their work hours, couriers leave and return the subsequent day. The courier's salary, ranging from 1600–2000€ per day, is counted into the daily operational costs for both electric and conventional vehicles. Autonomous vehicles exclusively rely on electricity and require charging. Nevertheless, they are capable of delivering parcels throughout the day. If some parcels destined for the address or the pick-up place are not delivered in time, their delivery is moved to the next day. It is assumed that during the night, autonomous vehicles either charge or deliver parcels to designated parcel lockers. Consequently, parcels destined for pick-up places and specific addresses receive priority. The preference for delivery destinations is distributed as follows: 44% for direct delivery to addresses, 35% for delivery to pick-up places, and 21% for the favored option of delivery to parcel lockers [5].

An autonomous car possesses an average transport capacity of 400–600 parcels per battery charge, and the average delivery time for parcels ranges from 2 to 6 hours. The charging time is 30 minutes and during this time the car can also be loaded with packages for delivery. This loading takes 30-60 minutes. An autonomous car in use has a consumption rate of 0.25 kWh of electricity per 100 kilometers [1].

Model created with Petri net [[8], 126] is in figure 1.

4 Architecture of the simulation model

[[Ako model v skutočnosti funguje (naprogramovaný)]]

[[Popis implementácie]]

5 Experiments

[[Popis vykonaných experimentov, ich dôvod, výsledky a zistenia]]

6 Conclusion

[[Čo sa nám podarilo experimentami dokázať]]

Sources

- [1] FIGLIOZZI, M. A. Carbon emissions reductions in last mile and grocery deliveries utilizing air and ground autonomous vehicles. *Transportation Research Part D: Transport and Environment* [[online]]. 2020, vol. 85, p. 102443. DOI: <https://doi.org/10.1016/j.trd.2020.102443>. ISSN 1361-9209. [06.12.2023]. Available at: <https://www.sciencedirect.com/science/article/pii/S1361920920306301>.
- [2] JURINOVÁ, M. *Packeta Slovakia doručila medziročne o 36 percent viac zásielok. Ľudia si oblúbili najmä Z-Boxy* [[online]]. 30. august 2023. [06.12.2023]. Available at: <https://www.forbes.sk/packeta-slovakia-dorucila-medzirocne-o-36-percent-viac-zasielok-ludia-si-oblubili-najm>
- [3] KEBÍSKOVÁ, R. *Rastúci e-commerce vs. emisie* [[online]]. 31. october 2023. [06.12.2023]. Available at: <https://transport.sk/logistika/rastuci-e-commerce-vs-emisie/>.
- [4] LI, J., ROMBAUT, E. and VANHAVERBEKE, L. A systematic review of agent-based models for autonomous vehicles in urban mobility and logistics: Possibilities for integrated simulation models. *Computers, Environment and Urban Systems* [[online]]. 2021, vol. 89, p. 101686. DOI: <https://doi.org/10.1016/j.compenvurbsys.2021.101686>. ISSN 0198-9715. [06.12.2023]. Available at: <https://www.sciencedirect.com/science/article/pii/S0198971521000934>.
- [5] MAREK, M. *Nad boxy stále jasne vede doručení domů* [[online]]. 21. september 2023. [06.12.2023]. Available at: <https://komoraplus.cz/2023/09/21/nad-boxy-stale-jasne-vede-doruceni-domu/>.
- [6] PACKETA SLOVAKIA S.R.O.. *Packeta official web site* [[online]]. [06.12.2023]. Available at: <https://www.packeta.sk>.
- [7] PERINGER, P. and HRUBÝ, M. *SIMLIB/C++ (SIMulation LIBrary for C++)* [[online]]. 3.09. 1. november 2022. [06.12.2023]. Available at: <https://www.fit.vutbr.cz/~peringer/SIMLIB/>.
- [8] PERINGER, P. and HRUBÝ, M. *Text for the lectures of the Modeling and Simulation course* [[online]]. 14. september 2023. [06.12.2023]. Available at: <https://www.fit.vutbr.cz/study/courses/IMS/public/prednasky/IMS.pdf>.
- [9] PEUGEOT S.R.O.. *Peugeot official web site* [[online]]. [06.12.2023]. Available at: <https://www.peugeot.sk/nase-modely/boxer.html>.




Figure 1: Petri net [[8], 126] model