Actividad - Creación de usuario en linux
Jorge Eduardo de León Reyna
A00829759

1. Iniciando sesion en servidor

2. Creando usuario


```
● ● ●    🖥 jorge — root@ubuntu-s-1vcpu-2gb-sfo3-01: ~ — -zsh — 80×34

Adding new user `newuser' to supplemental / extra groups `users' ...
Adding user `newuser' to group `users' ...
(base) root@ubuntu-s-1vcpu-2gb-sfo3-01:~# adduser JorgeDeLeonA00829759
adduser: Please enter a username matching the regular expression
         configured via the NAME_REGEX configuration variable.  Use the
         `--allow-badname' option to relax this check or reconfigure
         NAME_REGEX in /etc/adduser.conf.
(base) root@ubuntu-s-1vcpu-2gb-sfo3-01:~#
(base) root@ubuntu-s-1vcpu-2gb-sfo3-01:~# adduser jorgedeleona00829759
Adding user `jorgedeleona00829759' ...
Adding new group `jorgedeleona00829759' (1010) ...
Adding new user `jorgedeleona00829759' (1010) with group `jorgedeleona00829759 (
1010)' ...
Creating home directory `/home/jorgedeleona00829759' ...
Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for jorgedeleona00829759
Enter the new value, or press ENTER for the default
        Full Name []: Jorge Eduardo de Leon Reyna
        Room Number []:
        Work Phone []:
        Home Phone []:
        Other []:
Is the information correct? [Y/n] Y
Adding new user `jorgedeleona00829759' to supplemental / extra groups `users' ..
.
Adding user `jorgedeleona00829759' to group `users' ...
(base) root@ubuntu-s-1vcpu-2gb-sfo3-01:~#
(base) root@ubuntu-s-1vcpu-2gb-sfo3-01:~# exit
logout
Connection to 146.190.32.150 closed.
jorge@MacBook-Pro-de-Jorge ~ %
```

3. Iniciado sesión con usuario nuevo