




RHODES
ARCHITECTURAL
STONE
NATURAL STONE EXPERTS



AMANDE LIMESTONE

Amande Limestone's warm color range and soft texture speak volumes for its popularity in sunny and inviting climates. Quarried in the hot landlocked valleys in central China, the stone has been slow baked for hundreds of millions of years since its creation. This high density limestone, much harder than common limestone, is used widely for veneer, stair block, and paver applications. In general, limestone remains much cooler underfoot than either sandstone or granite, making it an ideal material for pool decks and other surfaces where contact with hot stone would

be uncomfortable. Amande Limestone's distinctive white veining delicately traverses the stone panels or shows up intermittently like a rock skipping on calm waters. Sometimes small black fossils lightly populate cross-sections, lending subtle, natural variations. Available in all our hand finishes, Amande Limestone's highlights are particularly compelling in point stalk and adze, and it can be installed in any of the standard setting techniques – mortar, thinset, or sand set on slab.



RECOMMENDED USES

PAVERS / PLANKS	SILLS / LINTELS
VENEER	CARVED OBJECTS
STAIR BLOCKS	COLUMNS
QUOINS	SINKS / TUBS
COPING / CAPS	SLABS
CURBS	COBBLESTONES



55 BELL STREET, SUITE 100
SEATTLE, WA 98121, USA
TEL 206.709.3000 FAX 206.709.3004
www.rhodes.org

58-74 STATION STREET
NUNAWADING VIC 3131, AUSTRALIA
TEL +61 3 8199-9555 FAX +61 3 9894-1804

57 HU BIN BEI LU, XIAMEN
FUJIAN, CHINA
TEL +86 592-533-0273
FAX +86 592-537-6000 EXT. 93181



AMANDE LIMESTONE



HONED
0.75" min thickness



SANDBLASTED
0.75" min thickness



SPLIT
3" min thickness



HAND BUSH HAMMER
1.5" min thickness



FINE ADZE
1.5" min thickness



COARSE ADZE
2" min thickness



4 POINT STALK
2" min thickness



2 POINT STALK
2" min thickness



PINEAPPLE
3" min thickness

MATERIAL SPECIFICATIONS

COUNTRY OF ORIGIN : China

COLOR RANGE : camel - caramel

STANDARD BLOCK SIZE : 60" X 24" X 20"

MAX SPECIAL BLOCK SIZE : 80" X 30" X 20"

STANDARD VENEER SIZES :

3" X 3" MIN TO 16" X 26" MAX; 3" THICK

STANDARD PAVING SIZES :

12" X 12" TO 24" X 30" ; 0.75" TO 3" THICK



TECHNICAL DATA

ASTM C97	absorption %	1.43
ASTM C97	bulk gravity lbs/ft ³	159.9
ASTM C99	mod. of rupture psi	2,600
ASTM C170	compressive strength psi	8,800
ASTM	C666 freeze thaw %	0.35
ASTM C880	flexural strength psi	1,000

