



RHODES
ARCHITECTURAL
STONE
NATURAL STONE EXPERTS

NEW YANGTZE LIMESTONE

New Yangtze Limestone is a high-density limestone quarried in the Yangtze River Valley in China, near the source of its ancient relative, Antique Yangtze Limestone. While both display rich fossil deposits, New Yangtze differs from its antique relative in its darker and more consistent color. Seen up close, it appears peppered with small crystalline inclusions and occasional white veins. When worked, the light-colored tooling marks of our hand finishes accentuate the deep, chocolate tones of this unique and eye-catching material. A versatile stone, New Yangtze can be specified for many applications and is particularly

striking when used for oversized architectural elements like lintels, sills, and stair blocks. In addition, limestone is particularly suited for pavements of all kinds since it remains cooler underfoot than either sandstone or granite. Because they come from the same geological source, New and Antique Yangtze blend seamlessly. New Yangtze accepts finishes on all faces, but needs to be mortar set since its strong primary grain can cause edges to chip under pressure. For veneer installation, New Yangtze may be mortar set with an exposed or raked joint or set more tightly in the wedge mortar method.



RECOMMENDED USES

| | |
|---------------|-----------------|
| PAVERS | CARVED OBJECTS |
| VENEER | COLUMNS |
| STAIR BLOCKS | SINKS / TUBS |
| QUOINS | SLABS |
| COPING / CAPS | COBBLESTONES |
| CURBS | SILLS / LINTELS |



55 BELL STREET, SUITE 100
SEATTLE, WA 98121, USA
TEL 206.709.3000 FAX 206.709.3004
www.rhodes.org

58-74 STATION STREET
NUNAWADING VIC 3131, AUSTRALIA
TEL +61 3 8199-9555 FAX +61 3 9894-1804

57 HU BIN BEI LU, XIAMEN
FUJIAN, CHINA
TEL +86 592-533-0273
FAX +86 592-537-6000 EXT. 93181



NEW YANGTZE LIMESTONE



BUSH HAMMERED
1.5" min thickness



FINE ADZE
1.5" min thickness



COARSE ADZE
2" min thickness



4 POINT STALK
1.25" min thickness



2 POINT STALK
1.25" min thickness



PINEAPPLE
3" min thickness



SPLIT
3" min thickness



MATERIAL SPECIFICATIONS

COUNTRY OF ORIGIN : China

COLOR RANGE : grey - chocolate

STANDARD BLOCK SIZE : 60"x 24"x 18"

MAX SPECIAL BLOCK SIZE : 100"x 20"x 13"

STANDARD VENEER SIZES :

3"x 8" min to 16"x 26" max; 2 - 3" thick

STANDARD PAVING SIZES :

12" x 12" min to 24" x 30" max; 1.25 - 3" thick

4" x 4"; 2.5 - 4" thick cobblestones

8" x 4"; 2.5 - 4" thick cobblestones



TECHNICAL DATA

| | | |
|-----------|---------------------------------|--------|
| ASTM C666 | freeze thaw % | 0.015 |
| ASTM C97 | bulk gravity lb/ft ³ | 169 |
| ASTM C97 | absorption % | 0.07 |
| ASTM C99 | mod. of rupture psi | 2,139 |
| ASTM C880 | flexural strength psi | 3,864 |
| ASTM C170 | compressive strength psi | 15,674 |
| ASTM C241 | abrasion resistance | 22 Ha |



Imperial



Metric