




RHODES
ARCHITECTURAL
STONE
NATURAL STONE EXPERTS

RIVER BLACK SANDSTONE

Geologically rare, this exotic jet black sandstone captures the essence of the cosmic void. The absence of light gives this stone a magical, unusual, bottomless presence. Composed of billions of fine, individual grains of black gneiss, washed, compressed and welded together by hundreds of millions of years of heat and pressure, the result is without geologic parallel. Strong and durable, this stone withstands heavy weather and heavy foot traffic. Its dense structure retains carved detail and crisp arises with aplomb. Even when worked with hand-finishes, it will not refract light, so tool marks lend texture

but minimize color variation. We know of no other building stone with such magnificent characteristics. Like all sandstones, River Black is inert; it is unaffected by chlorine and will not discolor with pollution or acid rain. When wet, the stone displays an equally striking jet black sheen. River Black is often used as a border to highlight other materials, and brings out the depths of fountains and pools. Modernist architecture often draws on its pure color to contrast other legacy materials like glass and stainless steel. Whatever the form, whatever the shape or application, River Black Sandstone makes a timeless statement.



RECOMMENDED USES

PAVERS	CARVED OBJECTS
VENEER	COLUMNS
QUOINS	SINKS / TUBS
COPING / CAPS	SLABS
CURBS	COBBLESTONES
SILLS / LINTELS	DRAIN GRATES



55 BELL STREET, SUITE 100
SEATTLE, WA 98121, USA
TEL 206.709.3000 FAX 206.709.3004
www.rhodes.org

58-74 STATION STREET
NUNAWADING VIC 3131, AUSTRALIA
TEL +61 3 8199-9555 FAX +61 3 9894-1804

57 HU BIN BEI LU, XIAMEN
FUJIAN, CHINA
TEL +86 592-533-0273
FAX +86 592-537-6000 EXT. 93181



RHODES
ARCHITECTURAL
STONE
NATURAL STONE EXPERTS

RIVER BLACK SANDSTONE




HONED
0.75" min thickness




FLAMED
0.75" min thickness




SAND RUBBED
0.75" min thickness



FINE ADZE
1.5" min thickness




COARSE ADZE
2.5" min thickness




BUSH HAMMERED
1.5" min thickness



2 POINT STALK
2.5" min thickness



PINEAPPLE
1.5" min thickness



SPLIT
3" min thickness



MATERIAL SPECIFICATIONS

COUNTRY OF ORIGIN : China


COLOR RANGE : black

STANDARD BLOCK SIZE : 60" x 24" x 16"

MAX SPECIAL BLOCK SIZE : 80" x 32" x 16"

STANDARD VENEER SIZES :
3" x 8" min to 16" x 26" max; 2 - 3" thick

STANDARD PAVING SIZES :
12" x 12" min to 24" x 30" max; .75 - 3" thick



TECHNICAL DATA

ASTM C666	freeze thaw %	0.42
ASTM C97	absorption %	0.86
ASTM C97	bulk gravity lbs/ft ³	163.8
ASTM C99	mod. of rupture psi	2,900
ASTM C880	flexural strength psi	2,500
ASTM C170	compressive strength psi	20,000
ASTM C241	abrasion resistance	12 Ha



Imperial



Metric