## Class 1.2 - Data types, variables and taking inputs

Saturday, August 23, 2025 2:50 PM

If Type costeins 3 changing data type
from one type
to another

(by R) > (hort) > (log) & (love) > (log) & (love)

If Type costing in \_ Mathematical operation

int fint 2 into

int peak 2 plan


letit etit dtf tf

D String + anything = String

(u v v)

- appearing adding two strings is Called String concert election It Bosic Mathes operation s atb -1 a-5 3 axb quitiblet > "3 remainder 10 1 modeles operation a 16%63 # Assign ment operator (C= (x2))

# Taking input in Java [Scarner class] Scannel (System); 3 Scanner is a part of util library of Joven import java. util . Scarrer J. scarrer Empere joura. util 1 Ja pooré # Toking String Input In Java Screet () & takes input tiel it does not Sc. reet (ine () tiel it doesn't get onter of Show of knowledge (wx + 4 dy) > 5 32 bill 24 60 7



# Roletional operators

Soly 60 Cos From Cos From Cos From Legal 7 5<u>2</u>3] 9 false De Relation de 6 persons always give baoleons 7 7:7 8 xue == ] equals [=] Not equal # logical opention

> kue 66 tur 11 feets 5 x 3/2 + 5-= 10

5 x 3/2 + 5-= 10