

OH Xblow

AUTOMATED NECK-SPLIT CLEANING

BOOST PRODUCTIVITY WITH ON- THE-FLY NECK SPLIT CLEANING.

OH Xblow enables preform production lines to run three times longer between cleaning shutdowns. OH Xblow directs a pulsating, focused jet of air onto the neck splits to dislodge dust from sublimates before it can accumulate. It's that simple: less dust means less cleaning. OH Xblow significantly boosts the output and efficiency of preform production lines.



Slide bars

Blown away: Sublimates subdued

PET preform manufacturers are well aware of the problem caused by sublimates. These unwanted deposits from the injection process are formed when the holding pressure is released and the hot gases around the preform cool down.

These accumulations clog the mould venting holes and when that happens, the cavities no longer fill completely, especially at the support rings or threads of the preform. Visible flow lines and rounded edges are the early warning signs of this unwelcome development.

rPET increases the need for cleaning

Today, the growing use of rPET increases the formation of sublimates. In addition to dust, oily excretions of color residues in the rPET also promote the formation of deposits. Obviously, the extent of accumulated production grime determines the need for maintenance stops.

And with the growing use of recyclates, the need for cleaning increases. But there is a simple, effective way to keep PET preform lines up and running: OH Xblow gets rid a big part of the dust before it accumulates. It's the smart way to lengthen the time between cleaning shutdowns.

OH Xblow works!

OH Xblow can significantly slow the accumulation of sublimate dusts on neck splits. Systems that use OH Xblow can skip three out of four cleaning cycles. Thus, down-time for cleaning is reduced by 75 percent. The production line can continue to produce highest quality preforms and operators can focus on other issues.

OH Xblow's advantages

OH Xblow is fully automatic, clearing away dust before it can accumulate on the neck split's contact surfaces. OH Xblow's on-the-fly cleaning does not disrupt production. No time is lost and no material is wasted.

Where to use OH Xblow

OH Xblow can be installed on all new preform moulds. And it can also be retrofitted to most Otto Hofstetter injection moulding tools already in operation. OH Xblow only requires compressed air to operate and OH Xport serves as its control unit.

OH Xblow's rapid ROI

The math is simple: The less you need to clean, the faster OH Xblow pays for itself. Rapid return on investment is assured with Xblow.

Case Study

Calculation basis	– A preform mould with 96 cavities and 11.5 seconds cycle time, processing 100% rPET – Before installation of OH Xblow: 1 cleaning cycle per day, 340 production days per year
Savings with OH Xblow	3 out of 4 cleanings cycles can be skipped now 85 instead of 340 cleaning cycles per year 255 saved cleanings of 50 minutes each
Profit	212.5 hours of additional production time per year

With OH Xblow, over 6 million additional preforms are produced every year

OH Xblow ROI: less than one year!

OH XBLOW SUBSTANTIALLY REDUCES A MAJOR CAUSE OF SHUTDOWNS. CONTACT US AND LET'S SEE HOW OH XBLOW CAN BENEFIT YOU.
