

PYTHON PROGRAMMING LANGUAGE PRACTICE/POSSIBLE QUESTIONS +ANSWERS ON EACH SECTION

This set of Python Questions & Answers focuses on “Core Data Types” .

1. Which of these is not a core datatype?

- a) Lists
- b) Dictionary
- c) Tuples
- d) Class

[View Answer](#)

Answer:d

Explanation:Class is a user defined datatype.

2. Given a function that does not return any value, What value is thrown by it by default when executed in shell.

- a) int
- b) bool
- c) void
- d) None

[View Answer](#)

Answer:d

Explanation:Python shell throws a NoneType object back.

3. Following set of commands are executed in shell, what will be the output?

```
>>>str="hello"
```

```
>>>str[:2]
```

```
>>>
```

- a) he
- b) lo
- c) olleh
- d) hello

[View Answer](#)

Answer:a

4. Which of the following will run without errors(multiple answers possible) ?

- a) round(45.8)
- b) round(6352.898,2)
- c) round()
- d) round(7463.123,2,1)

[View Answer](#)

Answer:a,b

Explanation:Execute help(round) in the shell to get details of the parameters that are passed into the round function.

5. What is the return type of function id ?

- a) int
- b) float
- c) bool
- d) dict

[View Answer](#)

Answer:a

Explanation:Execute help(id) to find out details in python shell.id returns a integer value that is unique.

6. In python we do not specify types,it is directly interpreted by the compiler, so consider the following operation to be performed.

```
>>>x = 13 / 2
```

advertisements

objective is to make sure x has a integer value, select all that apply (python 3.xx)

- a) `x = 13 // 2`
- b) `x = int(13 / 2)`
- c) `x = 13 / 2`
- d) `x = 13 % 2`

[View Answer](#)

Answer:a,b

Explanation:// is integer operation in python 3.0 and int(..) is a type cast operator.

7. What error occurs when you execute?

```
apple = mango
```

- a) SyntaxError
- b) NameError
- c) ValueError
- d) TypeError

[View Answer](#)

Answer:b

Explanation:Banana is not defined hence name error.

8. Carefully observe the code and give the answer.

```
def example(a):
```

```
    a = a + '2'
```

```
    a = a*2
```

```
    return a
```

```
>>>example("hello")
```

- a) indentation Error
- b) cannot perform mathematical operation on strings
- c) hello2
- d) hello2hello2

[View Answer](#)

Answer:a

Explanation:Python codes have to be indented properly.

9. What datatype is the object below ?

L = [1, 23, 'hello', 1] a) List

b) dictionary

c) array

d) tuple

[View Answer](#)

Answer:a

Explanation:List datatype can store any values within it.

10. In order to store values in terms of key and value we use what core datatype.

a) List

b) tuple

c) class

d) dictionary

[View Answer](#)

Answer:d

Explanation:Dictionary stores values in terms of keys and values.

11. Which of the following results in a SyntaxError(Multiple answers possible) ?

a) " " Once upon a time... " , she said.'

b) "He said, "Yes!" "

c) '3\'

d) " " That ' s okay " "

[View Answer](#)

Answer:b,c

Explanation:Carefully look at the colons.

12. The following is displayed by a print function call:

tom

dick

harry

advertisements

Select all of the function calls that result in this output

a) print(" tom

\ndick

\nharry")

b) print(" tom

dick

harry")

c) `print( 'tom\ndick\nharry' )`

d) `print( 'tom`

`dick`

`harry' )`

[View Answer](#)

Answer:b,c

Explanation:The `\n` adds a new line.

13. What is the average value of the code that is executed below ?

```
>>>grade1 = 80
```

```
>>>grade2 = 90
```

```
>>>average = (grade1 + grade2) / 2
```

a) 85

b) 85.0

c) 95

d) 95.0

[View Answer](#)

Answer:b

Explanation:Cause a decimal value to appear as output.

14. Select all options that print

hello-how-are-you

a) `print( 'hello' , 'how' , 'are' , 'you' )`

b) `print( 'hello' , 'how' , 'are' , 'you' + '-' * 4)`

c) `print( 'hello-' + 'how-are-you' )`

d) `print( 'hello' + '-' + 'how' + '-' + 'are' + '-' + 'you' )`

[View Answer](#)

Answer:c,d

Explanation:Execute in the shell.

15. What is the return value of `trunc()` ?

a) int

b) bool

c) float

d) None

[View Answer](#)

Answer:a

Explanation:Execute `help(math.trunc)` to get details.

This section on Python aptitude questions and answers focuses on “Basic Operators” .

1. Which is the correct operator for `power(x^y)`?

- a) X^y
- b) $X^{**}y$
- c) $X^{^^}y$
- d) None of the mentioned

[View Answer](#)

Answer: b

Explanation: In python, power operator is $x^{**}y$ i.e. $2^{**}3=8$.

2. Which one of these is floor division?

- a) /
- b) //
- c) %
- d) None of the mentioned

[View Answer](#)

Answer: b

Explanation: When both of the operands are integer then python chops out the fraction part and gives you the round off value, to get the accurate answer use floor division. This is floor division.

For ex, $5/2 = 2.5$ but both of the operands are integer so answer of this expression in python is

2. To get the 2.5 answer, use floor division.

3. What is the order of precedence in python?

- i) Parentheses
 - ii) Exponential
 - iii) Division
 - iv) Multiplication
 - v) Addition
 - vi) Subtraction
- a) i,ii,iii,iv,v,vi
 - b) ii,i,iii,iv,v,vi
 - c) ii,i,iv,iii,v,vi
 - d) i,ii,iii,iv,vi,v

[View Answer](#)

Answer: a

Explanation: For order of precedence, just remember this PEDMAS.

4. What is answer of this expression, $22 \% 3$ is?

- a) 7
- b) 1
- c) 0
- d) 5

[View Answer](#)

Answer: b

Explanation: Modulus operator gives remainder. So, $22\%3$ gives 1 remainder.

advertisements

5. You can perform mathematical operation on String?

a) True

b) False

[View Answer](#)

Answer: b

Explanation: You can't perform mathematical operation on string even if string looks like integers.

6. Operators with the same precedence are evaluated in which manner?

a) Left to Right

b) Right to Left

[View Answer](#)

Answer: a

Explanation: None.

7. What is the output of this expression, $3*1**3$?

a) 27

b) 9

c) 3

d) 1

[View Answer](#)

Answer: c

Explanation: First this expression will solve $1**3$ because exponential have higher precedence than multiplication, so $1**3 = 1$ and $3*1 = 3$. Final answer is 3.

8. Which one of the following have the same precedence?

a) Addition and Subtraction

b) Multiplication and Division

c) a and b

d) None of the mentioned

[View Answer](#)

Answer: c

Explanation: None.

9. $\text{Int}(x)$ means variable x is converted to integer.

a) True

b) False

[View Answer](#)

Answer: a

Explanation: None.

advertisements

10. Which one of the following have the highest precedence in the expression?

a) Exponential

- b) Addition
- c) Multiplication
- d) Parentheses

View Answer

Answer: d

Explanation: None.

This set of Python Multiple Choice Questions & Answers (MCQs) focuses on “Variable Names”.

1. Is Python case sensitive when dealing with identifiers?

- a) yes
- b) no
- c) sometimes only
- d) none of the mentioned

View Answer

Answer: a

Explanation: Case is always significant.

2. What is the maximum possible length of an identifier?

- a) 31 characters
- b) 63 characters
- c) 79 characters
- d) none of the mentioned

View Answer

Answer: d

Explanation: Identifiers can be of any length.

3. Which of the following is invalid?

- a) `_a = 1`
- b) `__a = 1`
- c) `__str__ = 1`
- d) none of the mentioned

View Answer

Answer: d

Explanation: All the statements will execute successfully but at the cost of reduced readability.

advertisements

4. Which of the following is an invalid variable?

- a) `my_string_1`
- b) `1st_string`
- c) `foo`
- d) `_`

View Answer

Answer: b

Explanation: Variable names should not start with a number.

5. Why are local variable names beginning with an underscore discouraged?

- a) they are used to indicate a private variables of a class
- b) they confuse the interpreter
- c) they are used to indicate global variables
- d) they slow down execution

[View Answer](#)

Answer: a

Explanation: As Python has no concept of private variables, leading underscores are used to indicate variables that must not be accessed from outside the class.

6. Which of the following is not a keyword?

- a) eval
- b) assert
- c) nonlocal
- d) pass

[View Answer](#)

Answer: a

Explanation: eval can be used as a variable.

7. All keywords in Python are in

- a) lower case
- b) UPPER CASE
- c) Capitalized
- d) none

[View Answer](#)

Answer: d

Explanation: True, False and None are capitalized while the others are in lower case.

8. Which of the following is true for variable names in Python?

- a) unlimited length
- b) all private members must have leading and trailing underscores
- c) underscore and ampersand are the only two special charaters allowed
- d) none

[View Answer](#)

Answer: a

Explanation: Variable names can be of any length.

advertisements

9. Which of the following is an invalid statement?

- a) `abc = 1,000,000`
- b) `a b c = 1000 2000 3000`
- c) `a,b,c = 1000, 2000, 3000`

d) `a_b_c = 1,000,000`

[View Answer](#)

Answer: b

Explanation: Spaces are not allowed in variable names.

10. Which of the following cannot be a variable?

a) `__init__`

b) `in`

c) `it`

d) `on`

[View Answer](#)

Answer: b

Explanation: `in` is a keyword.

This set of Python Multiple Choice Questions & Answers (MCQs) focuses on “Regular Expressions” .

1. Which module in Python supports regular expressions?

a) `re`

b) `regex`

c) `pyregex`

d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: `re` is a part of the standard library and can be imported using: `import re`.

2. Which of the following creates a pattern object?

a) `re.create(str)`

b) `re.regex(str)`

c) `re.compile(str)`

d) `re.assemble(str)`

[View Answer](#)

Answer: c

Explanation: It converts a given string into a pattern object.

3. What does the function `re.match` do?

a) matches a pattern at the start of the string

b) matches a pattern at any position in the string

c) such a function does not exist

d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: It will look for the pattern at the beginning and return None if it isn't found.

4. What does the function `re.search` do?

- a) matches a pattern at the start of the string
- b) matches a pattern at any position in the string
- c) such a function does not exist
- d) none of the mentioned

[View Answer](#)

Answer: b

Explanation: It will look for the pattern at any position in the string.

5. What is the output of the following?

```
sentence = 'we are humans'
matched = re.match(r'(.*) (.*) (.*)', sentence)
print(matched.groups())
```

- a) ('we' , 'are' , 'humans')
- b) (we, are, humans)
- c) ('we' , 'humans')
- d) 'we are humans'

[View Answer](#)

Answer: a

Explanation: This function returns all the subgroups that have been matched.

advertisements

6. What is the output of the following?

```
sentence = 'we are humans'
matched = re.match(r'(.*) (.*) (.*)', sentence)
print(matched.group())
```

- a) ('we' , 'are' , 'humans')
- b) (we, are, humans)
- c) ('we' , 'humans')
- d) 'we are humans'

[View Answer](#)

Answer: d

Explanation: This function returns the entire match.

7. What is the output of the following?

```
sentence = 'we are humans'
matched = re.match(r'(.*) (.*) (.*)', sentence)
print(matched.group(2))
```

- a) 'are'
- b) 'we'
- c) 'humans'

d) 'we are humans'

[View Answer](#)

Answer: c

Explanation: This function returns the particular subgroup.

8. What is the output of the following?

```
sentence = 'horses are fast'
```

```
regex = re.compile('(P<animal>\w+) (P<verb>\w+) (P<adjective>\w+)')
```

```
matched = re.search(regex, sentence)
```

```
print(matched.groupdict())
```

a) { 'animal' : 'horses' , 'verb' : 'are' , 'adjective' : 'fast' }

b) ('horses' , 'are' , 'fast')

c) 'horses are fast'

d) 'are'

[View Answer](#)

Answer: a

Explanation: This function returns a dictionary that contains all the matches.

advertisements

9. What is the output of the following?

```
sentence = 'horses are fast'
```

```
regex = re.compile('(P<animal>\w+) (P<verb>\w+) (P<adjective>\w+)')
```

```
matched = re.search(regex, sentence)
```

```
print(matched.groups())
```

a) { 'animal' : 'horses' , 'verb' : 'are' , 'adjective' : 'fast' }

b) ('horses' , 'are' , 'fast')

c) 'horses are fast'

d) 'are'

[View Answer](#)

Answer: b

Explanation: This function returns all the subgroups that have been matched.

10. What is the output of the following?

```
sentence = 'horses are fast'
```

```
regex = re.compile('(P<animal>\w+) (P<verb>\w+) (P<adjective>\w+)')
```

```
matched = re.search(regex, sentence)
```

```
print(matched.group(2))
```

a) { 'animal' : 'horses' , 'verb' : 'are' , 'adjective' : 'fast' }

b) ('horses' , 'are' , 'fast')

c) 'horses are fast'

d) 'are'

[View Answer](#)

Answer: d

Explanation: This function returns the particular subgroup.

This set of Python Multiple Choice Questions & Answers (MCQs) focuses on “Numeric Types”.

1. What is the output of `print 0.1 + 0.2 == 0.3`?

- a) True
- b) False
- c) Machine dependent
- d) Error

[View Answer](#)

2. Which of the following is not a complex number?

- a) `k = 2 + 3j`
- b) `k = complex(2, 3)`
- c) `k = 2 + 3l`
- d) `k = 2 + 3J`

[View Answer](#)

advertisements

3. What is the type of `inf`?

- a) Boolean
- b) Integer
- c) Float
- d) Complex

[View Answer](#)

4. What does `~4` evaluate to?

- a) -5
- b) -4
- c) -3
- d) +3

[View Answer](#)

5. What does `~~~~~5` evaluate to?

- a) +5
- b) -11
- c) +11
- d) -5

[View Answer](#)

advertisements

6. Which of the following is incorrect?

- a) x = 0b101
- b) x = 0x4f5
- c) x = 19023
- d) x = 03964

View Answer

7. What is the result of cmp(3, 1)?

- a) 1
- b) 0
- c) True
- d) False

View AnswerAnswer: a

Explanation: cmp(x, y) returns 1 if x > y, 0 if x == y and -1 if x < y.[/expand]

8. Which of the following is incorrect? a) float('inf') b) float('nan') c) float('56'+78') d) float('12+34') [expand title="View Answer"]Answer: d Explanation: '+' cannot be converted to a float.[/expand]

9. What is the result of round(0.5) - round(-0.5)? a) 1.0 b) 2.0 c) 0.0 d) None of the mentioned [expand title="View Answer"]Answer: b Explanation: Python rounds off numbers away from 0 when the number to be rounded off is exactly halfway through. round(0.5) is 1 and round(-0.5) is -1.[/expand]

10. What does 3 ^ 4 evaluate to? a) 81 b) 12 c) 0.75 d) 7 [expand title="View Answer"]Answer: d Explanation: ^ is the Binary XOR operator.[/expand]

This set of Python Multiple Choice Questions & Answers (MCQs) focuses on “While and For Loops” .

1. What is the output of the following?

```
x = ['ab', 'cd']
```

```
for i in x:
```

```
    i.upper()
```

```
print(x)
```

- a) ['ab' , 'cd'] b) ['AB' , 'CD'] c) [None, None] d) none of the mentioned

View Answer

Answer: a

Explanation: The function upper() does not modify a string in place, it returns a new string which isn't being stored anywhere.

2. What is the output of the following?

```
x = ['ab', 'cd']
```

```
for i in x:
```

```
    x.append(i.upper())
```

```
print(x)
```

- a) ['AB' , 'CD'] b) ['ab' , 'cd' , 'AB' , 'CD'] c) ['ab' , 'cd'] d) none of the mentioned

View Answer

Answer: d

Explanation: The loop does not terminate as new elements are being added to the list in each iteration.

3. What is the output of the following?

```
i = 1
while True:
    if i%3 == 0:
        break
    print(i)
    i += 1
```

- a) 1 2
- b) 1 2 3
- c) error
- d) none of the mentioned

[View Answer](#)

4. What is the output of the following?

```
i = 1
while True:
    if i%007 == 0:
        break
    print(i)
    i += 1
```

advertisements

- a) 1 2 3 4 5 6
- b) 1 2 3 4 5 6 7
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: Control exits the loop when i becomes 7.

5. What is the output of the following?

```
i = 5
while True:
    if i%0011 == 0:
        break
    print(i)
    i += 1
```

- a) 5 6 7 8 9 10
- b) 5 6 7 8

c) 5 6

d) error

[View Answer](#)

Answer: b

Explanation: 0011 is an octal number.

6. What is the output of the following?

```
i = 5
```

```
while True:
```

```
    if i%009 == 0:
```

```
        break
```

```
    print(i)
```

```
    i += 1
```

a) 5 6 7 8

b) 5 6 7 8 9

c) 5 6 7 8 9 10 11 12 13 14 15 ...

d) error

[View Answer](#)

Answer: d

Explanation: 9 isn't allowed in an octal number.

7. What is the output of the following?

```
i = 1
```

```
while True:
```

```
    if i%2 == 0:
```

```
        break
```

```
    print(i)
```

```
    i += 2
```

a) 1

b) 1 2

c) 1 2 3 4 5 6 ...

d) 1 3 5 7 9 11 ...

[View Answer](#)

Answer: d

Explanation: The loop does not terminate since i is never an even number.

advertisements

8. What is the output of the following?

```
i = 2
```

```
while True:
```

```
    if i%3 == 0:
```

```
        break
```

```
print(i)
i += 2
```

a) 2 4 6 8 10 ...
b) 2 4
c) 2 3
d) error

[View Answer](#)

Answer: b

Explanation: The numbers 2 and 4 are printed. The next value of i is 6 which is divisible by 3 and hence control exits the loop.

9. What is the output of the following?

```
i = 1
while False:
    if i%2 == 0:
        break
    print(i)
    i += 2
```

a) 1
b) 1 3 5 7 ...
c) 1 2 3 4 ...
d) none of the mentioned

[View Answer](#)

Answer: d

Explanation: Control does not enter the loop because of False.

10. What is the output of the following?

```
True = False
while True:
    print(True)
    break
```

a) True
b) False
c) None
d) none of the mentioned

[View Answer](#)

Answer: d

Explanation: SyntaxError, True is a keyword and it's value cannot be changed.

Python Questions and Answers - While and For Loops - 2

This set of Advanced Python Questions & Answers focuses on “While and For Loops” .

1. What is the output of the following?

```
i = 0
while i < 5:
    print(i)
    i += 1
    if i == 3:
        break
else:
    print(0)
```

a) 0 1 2 0
b) 0 1 2
c) error
d) none of the mentioned

[View Answer](#)

Answer: b

Explanation: The else part is not executed if control breaks out of the loop.

2. What is the output of the following?

```
i = 0
while i < 3:
    print(i)
    i += 1
else:
    print(0)
```

a) 0 1 2 3 0
b) 0 1 2 0
c) 0 1 2
c) error

[View Answer](#)

Answer: b

Explanation: The else part is executed when the condition in the while statement is false.

3. What is the output of the following?

```
x = "abcdef"
while i in x:
    print(i, end=" ")
```

a) a b c d e f
b) abcdef
c) i i i i i ...
d) error

[View Answer](#)

Answer: d

Explanation: NameError, i is not defined.

4. What is the output of the following?

```
x = "abcdef"
i = "i"
while i in x:
    print(i, end=" ")
advertisements
```

a) no output

b) i i i i i ...

c) a b c d e f

d) abcdef

[View Answer](#)

Answer: a

Explanation: "i" is not in "abcdef" .

5. What is the output of the following?

```
x = "abcdef"
i = "a"
while i in x:
    print(i, end = " ")
```

a) no output

b) i i i i i ...

c) a a a a a ...

d) a b c d e f

[View Answer](#)

Answer: c

Explanation: As the value of i or x isn't changing, the condition will always evaluate to True.

6. What is the output of the following?

```
x = "abcdef"
i = "a"
while i in x:
    print('i', end = " ")
```

a) no output

b) i i i i i ...

c) a a a a a ...

d) a b c d e f

[View Answer](#)

Answer: b

Explanation: As the value of i or x isn't changing, the condition will always evaluate to True.

7. What is the output of the following?

```
x = "abcdef"
i = "a"
while i in x:
    x = x[:-1]
    print(i, end = " ")
```

- a) i i i i i
- b) a a a a a
- c) a a a a a
- d) none of the mentioned

[View Answer](#)

Answer: b

Explanation: The string x is being shortened by one character in each iteration.

advertisements

8. What is the output of the following?

```
x = "abcdef"
i = "a"
while i in x[:-1]:
    print(i, end = " ")
```

- a) a a a a a
- b) a a a a a
- c) a a a a a ...
- d) a

[View Answer](#)

Answer: c

Explanation: String x is not being altered and i is in x[:-1].

9. What is the output of the following?

```
x = "abcdef"
i = "a"
while i in x:
    x = x[1:]
    print(i, end = " ")
```

- a) a a a a a
- b) a
- c) no output
- d) error

[View Answer](#)

Answer: b

Explanation: The string x is being shortened by one character in each iteration.

10. What is the output of the following?

```
x = "abcdef"
i = "a"
while i in x[1:]:
    print(i, end = " ")
```

a) a a a a a a

b) a

c) no output

d) error

[View Answer](#)

Answer: c

Explanation: i is not in x[1:].

Python Questions and Answers - While and For Loops - 3

This set of Tough Python Questions & Answers focuses on “While and For Loops” .

1. What is the output of the following?

```
x = 'abcd'
for i in x:
    print(i)
    x.upper()
```

a) a B C D

b) a b c d

c) A B C D

d) error

[View Answer](#)

Answer: b

Explanation: Changes do not happen in-place, rather a new instance of the string is returned.

2. What is the output of the following?

```
x = 'abcd'
for i in x:
    print(i.upper())
```

a) a b c d

b) A B C D

c) a B C D

d) error

[View Answer](#)

Answer: b

Explanation: The instance of the string returned by upper() is being printed.

3. What is the output of the following?

```
x = 'abcd'
for i in range(x):
    print(i)
```

- a) a b c d
- b) 0 1 2 3
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: range(str) is not allowed.

4. What is the output of the following?

```
x = 'abcd'
for i in range(len(x)):
    print(i)
```

- advertisements
- a) a b c d
 - b) 0 1 2 3
 - c) error
 - d) none of the mentioned

[View Answer](#)

Answer: b

Explanation: i takes values 0, 1, 2 and 3.

5. What is the output of the following?

```
x = 'abcd'
for i in range(len(x)):
    print(i.upper())
```

- a) a b c d
- b) 0 1 2 3
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: Objects of type int have no attribute upper().

6. What is the output of the following?

```
x = 'abcd'
for i in range(len(x)):
    i.upper()
print (x)
```

a) a b c d
b) 0 1 2 3
c) error
d) none of the mentioned

[View Answer](#)

Answer: c
Explanation: Objects of type int have no attribute upper().

7. What is the output of the following?

```
x = 'abcd'
for i in range(len(x)):
    x[i].upper()
print (x)
```

a) abcd
b) ABCD
c) error
d) none of the mentioned

[View Answer](#)

Answer: a
Explanation: Changes do not happen in-place, rather a new instance of the string is returned.

advertisements

8. What is the output of the following?

```
x = 'abcd'
for i in range(len(x)):
    i[x].upper()
print (x)
```

a) abcd
b) ABCD
c) error
d) none of the mentioned

[View Answer](#)

Answer: c
Explanation: Objects of type int aren't subscriptable.

9. What is the output of the following?

```
x = 'abcd'
for i in range(len(x)):
```

```
x = 'a'
print(x)
```

- a) a
- b) abcd abcd abcd
- c) a a a a
- d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: range() is computed only at the time of entering the loop.

10. What is the output of the following?

```
x = 'abcd'
for i in range(len(x)):
    print(x)
    x = 'a'
```

- a) a
- b) abcd abcd abcd abcd
- c) a a a a
- d) none of the mentioned

[View Answer](#)

Answer: d

Explanation: abcd a a a is the output as x is modified only after 'abcd' has been printed once.

Python Questions and Answers - While and For Loops - 4

This set of Python Questions & Answers focuses on “While and For Loops” and is useful for freshers who are preparing for their interviews.

1. What is the output of the following?

```
x = 123
for i in x:
    print(i)
```

- a) 1 2 3
- b) 123
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: Objects of type int are not iterable.

2. What is the output of the following?

```
d = {0: 'a', 1: 'b', 2: 'c'}
```

```
for i in d:
```

```
    print(i)
```

a) 0 1 2

b) a b c

c) 0 a 1 b 2 c

d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: Loops over the keys of the dictionary.

3. What is the output of the following?

```
d = {0: 'a', 1: 'b', 2: 'c'}
```

```
for x, y in d:
```

```
    print(x, y)
```

a) 0 1 2

b) a b c

c) 0 a 1 b 2 c

d) none of the mentioned

[View Answer](#)

Answer: d

Explanation: Error, objects of type int aren't iterable.

4. What is the output of the following?

```
d = {0: 'a', 1: 'b', 2: 'c'}
```

```
for x, y in d.items():
```

```
    print(x, y)
```

advertisements

a) 0 1 2

b) a b c

c) 0 a 1 b 2 c

d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: Loops over key, value pairs.

5. What is the output of the following?

```
d = {0: 'a', 1: 'b', 2: 'c'}
```

```
for x in d.keys():
```

```
    print(d[x])
```

a) 0 1 2

b) a b c

- c) 0 a 1 b 2 c
- d) none of the mentioned

[View Answer](#)

Answer: b

Explanation: Loops over the keys and prints the values.

6. What is the output of the following?

```
d = {0: 'a', 1: 'b', 2: 'c'}
```

```
for x in d.values():
```

```
    print(x)
```

- a) 0 1 2
- b) a b c
- c) 0 a 1 b 2 c
- d) none of the mentioned

[View Answer](#)

Answer: b

Explanation: Loops over the values.

7. What is the output of the following?

```
d = {0: 'a', 1: 'b', 2: 'c'}
```

```
for x in d.values():
```

```
    print(d[x])
```

- a) 0 1 2
- b) a b c
- c) 0 a 1 b 2 c
- d) none of the mentioned

[View Answer](#)

Answer: d

Explanation: Causes a KeyError.

8. What is the output of the following?

```
d = {0, 1, 2}
```

```
for x in d.values():
```

```
    print(x)
```

```
advertisements
```

- a) 0 1 2
- b) None None None
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: Objects of type set have no attribute values.

9. What is the output of the following?

```
d = {0, 1, 2}
```

```
for x in d:
```

```
    print(x)
```

a) 0 1 2

b) {0, 1, 2} {0, 1, 2} {0, 1, 2}

c) error

d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: Loops over the elements of the set and prints them.

10. What is the output of the following?

```
d = {0, 1, 2}
```

```
for x in d:
```

```
    print(d.add(x))
```

a) 0 1 2

b) 0 1 2 0 1 2 0 1 2 ...

c) None None None

d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: Variable x takes the values 0, 1 and 2. set.add() returns None which is printed.

11. What is the output of the following?

```
for i in range(0):
```

```
    print(i)
```

a) 0

b) (nothing is printed)

c) error

d) none of the mentioned

[View Answer](#)

Answer: b

Explanation: range(0) is empty.

This set of Python Technical Questions & Answers focuses on “While/For Loops” .

1. What is the output of the following?

```
for i in range(10):
    if i == 5:
        break
    else:
        print(i)
```

else:

```
    print("Here")
```

a) 0 1 2 3 4 Here

b) 0 1 2 3 4 5 Here

c) 0 1 2 3 4

d) 1 2 3 4 5

[View Answer](#)

Answer: c

Explanation: The else part is executed if control doesn't break out of the loop.

2. What is the output of the following?

```
for i in range(5):
```

```
    if i == 5:
```

```
        break
```

```
    else:
```

```
        print(i)
```

else:

```
    print("Here")
```

a) 0 1 2 3 4 Here

b) 0 1 2 3 4 5 Here

c) 0 1 2 3 4

d) 1 2 3 4 5

[View Answer](#)

Answer: a

Explanation: The else part is executed if control doesn't break out of the loop.

3. What is the output of the following?

```
x = (i for i in range(3))
```

```
for i in x:
```

```
    print(i)
```

a) 0 1 2

b) error

c) 0 1 2 0 1 2

d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: The first statement creates a generator object.

4. What is the output of the following?

```
x = (i for i in range(3))
```

```
for i in x:
```

```
    print(i)
```

```
for i in x:
```

```
    print(i)
```

advertisements

a) 0 1 2

b) error

c) 0 1 2 0 1 2

d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: We can loop over a generator object only once.

5. What is the output of the following?

```
string = "my name is x"
```

```
for i in string:
```

```
    print (i, end=" , ")
```

a) m, y , n, a, m, e , i, s , , x,

b) m, y , n, a, m, e , i, s , , x

c) my, name, is, x,

d) error

[View Answer](#)

Answer: a

Explanation: Variable i takes the value of one character at a time.

6. What is the output of the following?

```
string = "my name is x"
```

```
for i in string.split():
```

```
    print (i, end=" , ")
```

a) m, y , n, a, m, e , i, s , , x,

b) m, y , n, a, m, e , i, s , , x

c) my, name, is, x,

d) error

[View Answer](#)

Answer: c

Explanation: Variable i takes the value of one word at a time.

7. What is the output of the following?

```
a = [0, 1, 2, 3]
for a[-1] in a:
    print(a[-1])
```

- a) 0 1 2 3
- b) 0 1 2 2
- c) 3 3 3 3
- d) error

[View Answer](#)

Answer: b

Explanation: The value of a[-1] changes in each iteration.

advertisements

8. What is the output of the following?

```
a = [0, 1, 2, 3]
for a[0] in a:
    print(a[0])
```

- a) 0 1 2 3
- b) 0 1 2 2
- c) 3 3 3 3
- d) error

[View Answer](#)

Answer: a

Explanation: The value of a[0] changes in each iteration. Since the first value that it takes is itself, there is no visible error in the current example.

9. What is the output of the following?

```
a = [0, 1, 2, 3]
i = -2
for i not in a:
    print(i)
    i += 1
```

- a) -2 -1
- b) 0
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: SyntaxError, not in isn't allowed in for loops.

10. What is the output of the following?

```
string = "my name is x"
for i in ''.join(string.split()):
```

```
print(i, end=" ")
```

- a) m, y, , n, a, m, e, , i, s, , x,
- b) m, y, , n, a, m, e, , i, s, , x
- c) my, name, is, x,
- d) error

[View Answer](#)

Answer: a

Explanation: Variable i takes the value of one character at a time

- Strings - 1

This set of Python Questions & Answers focuses on “Strings” .

1. What is the output when following statement is executed ?

```
>>>"a"+"bc"
```

- a) a
- b) bc
- c) bca
- d) abc

[View Answer](#)

Answer:d

Explanation:+ operator is concatenation operator.

2. What is the output when following statement is executed ?

```
>>>"abcd"[2:]
```

- a) a
- b) ab
- c) cd
- d) dc

[View Answer](#)

Answer:c

Explanation:Slice operation is performed on string.

3. The output of executing string.ascii_letters can also be achieved by:

- a) string.ascii_lowercase_string.digits
- b) string.ascii_lowercase+string.ascii_uppercase
- c) string.letters
- d) string.lowercase_string.uppercase

[View Answer](#)

Answer:b

Explanation:Execute in shell and check.

4. What is the output when following code is executed ?

```
>>> str1 = 'hello'
>>> str2 = ','
>>> str3 = 'world'
>>> str1[-1:]
```

advertisements

- a) olleh
- b) hello
- c) h
- d) o

[View Answer](#)

Answer:d

Explanation:-1 corresponds to the last index.

5. What arithmetic operators cannot be used with strings ?

- a) +
- b) *
- c) -
- d) **

[View Answer](#)

Answer:c,d

Explanation:+ is used to concatenate and * is used to multiply strings.

6. What is the output when following code is executed ?

```
>>>print r"\nhello"
```

The output is

- a) a new line and hello
- b) \nhello
- c) the letter r and then hello
- d) Error

[View Answer](#)

Answer:b

Explanation:When prefixed with the letter 'r' or 'R' a string literal becomes a raw string and the escape sequences such as \n are not converted.

7. What is the output when following statement is executed ?

```
>>>print 'new' 'line'
```

- a) Error
- b) Output equivalent to print 'new\nline'
- c) newline
- d) new line

[View Answer](#)

Answer:c

Explanation:String literals separated by white space are allowed. They are concatenated.
advertisements

8. What is the output when following statement is executed ?

```
>>>print '\x97\x98'
```

a) Error

b) 97

98

c) _~

d) \x97\x98

View Answer

Answer:c

Explanation:\x is an escape sequence that means the following 2 digits are a hexadecimal number encoding a character.

9. What is the output when following code is executed ?

```
>>>str1="helloworld"
```

```
>>>str1[::-1]
```

a) dlrowolleh

b) hello

c) world

d) helloworld

View Answer

Answer:a

Explanation:Execute in shell to verify.

10. print 0xA + 0xB + 0xC :

a) 0xA0xB0xC

b) Error

c) 0x22

d) 33

View Answer

Answer:d

Explanation:0xA and 0xB and 0xC are hexadecimal integer literals representing the decimal values 10,11 and 12 respectively. Their sum is 33.

- Strings - 2

This set of Advanced Python Interview Questions & Answers focuses on “Strings” .

1. What is the output of the following code ?

```
class father:
```



```
def __init__(self, param):  
    self.o1 = param
```

```
class child(father):  
    def __init__(self, param):  
        self.o2 = param
```

```
>>>obj = child(22)  
>>>print "%d %d" % (obj.o1, obj.o2)
```

- a) None None
- b) None 22
- c) 22 None
- d) Error is generated

[View Answer](#)

Answer:d

Explanation:self.o1 was never created.

2. What is the output of the following code ?

```
class tester:  
    def __init__(self, id):  
        self.id = str(id)  
        id="224"
```

```
>>>temp = tester(12)  
>>>print temp.id
```

- a) 224
- b) Error
- c) 12
- d) None

[View Answer](#)

Answer:c

Explanation:id in this case will be the attribute of the class.

3. What is the output of the following code ?

```
>>>example = "snow world"  
>>>print "%s" % example[4:7]
```

- a) wo
- b) world
- c) sn
- d) rl

[View Answer](#)

Answer:a

Explanation:Execute in the shell and verify.

advertisements

4. What is the output of the following code ?

```
>>>example = "snow world"
```

```
>>>example[3] = 's'
```

```
>>>print example
```

- a) snow
- b) snow world
- c) Error
- d) snos world

[View Answer](#)

Answer:c

Explanation:Strings cannot be modified.

5. What is the output of the following code ?

```
>>>max("what are you")
```

- a) Error
- b) u
- c) t
- d) y

[View Answer](#)

Answer:d

Explanation:Max returns the character with the highest ascii value.

6. Given a string example=" hello" what is the output of example.count(l)

- a) 2
- b) 1
- c) None
- d) 0

[View Answer](#)

Answer:a

Explanation:l occurs twice in hello.

7. What is the output of the following code ?

```
>>>example = "helle"
```

```
>>>example.find("e")
```

advertisements

- a) Error
- b) -1
- c) 1
- d) 0

View Answer

Answer:c

Explanation:returns lowest index .

8. What is the output of the following code ?

```
>>>example = "helle"  
>>>example.rfind("e")
```

- a) -1
- b) 4
- c) 3
- d) 1

View Answer

Answer:b

Explanation:returns highest index.

9. What is the output of the following code ?

```
>>>example="helloworld"  
>>>example[::-1].startswith("d")
```

- a) dlrowolleh
- b) True
- c) -1
- d) None

View Answer

Answer:b

Explanation:Starts with checks if the given string starts with the parameter that is passed.

10. To concatenate two strings to a third what statements are applicable (multiple answers are allowed) ?

- a) s3 = s1 + s2
- b) s3 = s1.add(s2)
- c) s3 = s1.__add__(s2)
- d) s3 = s1 * s2

View Answer

Answer:a,c

Explanation:.__add__ is another method that can be used for concatenation.

Python Questions and Answers - Strings - 3

This set of Python Technical Interview Questions & Answers focuses on “Strings” .

1. What is the output when following statement is executed ?

```
>>>chr(ord('A'))
```

- a) A
- b) B
- c) a
- d) Error

[View Answer](#)

Answer:a

Explanation:Execute in shell to verify.

2. What is the output when following statement is executed ?

```
>>>print(chr(ord('b')+1))
```

- a) a
- b) b
- c) c
- d) A

[View Answer](#)

Answer:c

Explanation:Execute in the shell to verify.

advertisements

3. Which of the following statement prints hello\example\test.txt ?

- a) print("hello\example\test.txt")
- b) print("hello\\example\\test.txt")
- c) print("hello\" example\" test.txt")
- d) print("hello" \example" \test.txt")

[View Answer](#)

Answer:b

Explanation:\is used to indicate that the next \ is not an escape sequence.

4. Suppose s is " \t\tWorld\n" , what is s.strip() ?

- a) \t\tWorld\n
- b) \t\tWorld\n
- c) \t\tWORLD\n
- d) World

[View Answer](#)

Answer:d

Explanation:Execute help(string.strip) to find details.

5. The format function returns :

- a) Error
- b) int
- c) bool
- d) str

[View Answer](#)

Answer:d

Explanation:Format function returns a string.

6. What is the output of "hello" +1+2+3 ?

- a) hello123
- b) hello
- c) Error
- d) hello6

[View Answer](#)

Answer:c

Explanation:Cannot concatenate str and int objects.

7. What is the output when following code is executed ?

```
>>>print("D", end = ' ')\n>>>print("C", end = ' ')\n>>>print("B", end = ' ')\n>>>print("A", end = ' ')
```

- a) DCBA
- b) A, B, C, D
- c) D C B A
- d) A, B, C, D will be displayed on four lines

[View Answer](#)

Answer:c

Explanation:Execute in the shell.

advertisements

8. What is the output when following statement is executed ?(python 3.xx)

```
>>>print(format("Welcome", "10s"), end = '#')\n>>>print(format(111, "4d"), end = '#')\n>>>print(format(924.656, "3.2f"))
```

- a) Welcome# 111#924.66
- b) Welcome#111#924.66
- c) Welcome#111#.66
- d) Welcome # 111#924.66

[View Answer](#)

Answer:d

Explanation:Execute in the shell to verify.

9. What will be displayed by print(ord('b') - ord('a')) ?

- a) 0
- b) 1
- c) -1
- d) 2

[View Answer](#)

Answer:b

Explanation:ascii value of b is one more than a.

10. Say s=" hello" what will be the return value of type(s) ?

- a) int
- b) bool
- c) str
- d) String

View Answer

Answer:c

Explanation:str is used to represent strings in python.

Python Questions and Answers - Strings - 4

This set of Python Coding Questions & Answers focuses on "Strings" .

1. What is "Hello".replace("l", "e")

- a) Heeeo
- b) Heelo
- c) Heleo
- d) None

View Answer

Answer:a

Explanation:Execute in shell to verify.

2. To retrieve the character at index 3 from string s=" Hello" what command do we execute (multiple answers allowed) ?

- a) s[3] b) s.getitem(3)
- c) s.__getitem__(3)
- d) s.getItem(3)

View Answer

Answer:a, c

Explanation:__getitem__(..) can be used to get character at index specified as parameter.

3. To return the length of string s what command do we execute (multiple answers allowed) ?

- a) s.__len__()
- b) len(s)
- c) size(s)
- d) s.size()

View Answer

Answer:a,b

Explanation:Execute in shell to verify.

4. If a class defines the __str__(self) method, for an object obj for the class, you can use which

command to invoke the `__str__` method.(multiple answers allowed)

- a) `obj.__str__()`
- b) `str(obj)`
- c) `print obj`
- d) `__str__(obj)`

View Answer

Answer:a,b,c

Explanation:Execute in shell to verify.

5. To check whether string `s1` contains `s2`, use

- a) `s1.__contains__(s2)`
- b) `s1 in s2`
- c) `s1.contains(s2)`
- d) `si.in(s2)`

View Answer

Answer:a,b

Explanation:`s1 in s2` works in the same way as calling the special function `__contains__` .
advertisements

6. Suppose `i` is 5 and `j` is 4, `i + j` is same as

- a) `i.__add(j)`
- b) `i.__add__(j)`
- c) `i.__Add(j)`
- d) `i.__ADD(j)`

View Answer

Answer:b

Explanation:Execute in shell to verify.

7. What is the output of the following code ?

```
class Count:
```

```
    def __init__(self, count = 0):  
        self.__count = count
```

```
c1 = Count(2)
```

```
c2 = Count(2)
```

```
print(id(c1) == id(c2), end = " ")
```

```
s1 = "Good"
```

```
s2 = "Good"
```

```
print(id(s1) == id(s2))
```

- a) True False
- b) True True
- c) False True
- d) False False

View Answer

Answer:c

Explanation:Execute in the shell objects cannot have same id, however in the case of strings its different.

8. What is the output of the following code ?

```
class Name:
```

```
    def __init__(self, firstName, mi, lastName):
        self.firstName = firstName
        self.mi = mi
        self.lastName = lastName
```

```
firstName = "John"
```

```
name = Name(firstName, 'F', "Smith")
```

```
firstName = "Peter"
```

```
name.lastName = "Pan"
```

```
print(name.firstName, name.lastName)
```

advertisements

a) Peter Pan.

b) John Pan.

c) Peter Smith.

d) John Smith.

View Answer

Answer:b

Explanation:Execute in the shell to verify.

9. What function do you use to read a string?

a) input("Enter a string")

b) eval(input("Enter a string"))

c) enter("Enter a string")

d) eval(enter("Enter a string"))

View Answer

Answer:a

Explanation:Execute in shell to verify.

10. Suppose x is 345.3546, what is format(x, "10.3f") (_ indicates space)

a) __345.355

b) __345.355

c) ____345.355

d) _____345.354

View Answer

Answer:b

Explanation:Execute in the shell to verify

This set of Basic Python Questions & Answers focuses on “Strings” .

1. What is the output of the following?

```
print("abc DEF".capitalize())
```

- a) abc def
- b) ABC DEF
- c) Abc def
- d) Abc Def

[View Answer](#)

Answer: c

Explanation: The first letter of the string is converted to uppercase and the others are converted to lowercase.

2. What is the output of the following?

```
print("abc. DEF".capitalize())
```

- a) abc def
- b) ABC DEF
- c) Abc def
- d) Abc Def

[View Answer](#)

Answer: c

Explanation: The first letter of the string is converted to uppercase and the others are converted to lowercase.

3. What is the output of the following?

```
print("abcdef".center())
```

- a) cd
- b) abcdef
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: The function center() takes atleast one parameter.

4. What is the output of the following?

```
print("abcdef".center(0))
```

advertisements

- a) cd
- b) abcdef
- c) error
- d) none of the mentioned

View Answer

Answer: c

Explanation: The entire string is printed when the argument passed to center() is less than the length of the string.

5. What is the output of the following?

```
print('*', "abcdef".center(7), '*')
```

- a) * abcdef *
- b) * abcdef *
- c) *abcdef *
- d) * abcdef*

View Answer

Answer: b

Explanation: Padding is done towards the left-hand-side first when the final string is of odd length.

Extra spaces are present since we haven't overridden the value of sep.

6. What is the output of the following?

```
print('*', "abcdef".center(7), '*', sep="")
```

- a) * abcdef *
- b) * abcdef *
- c) *abcdef *
- d) * abcdef*

View Answer

Answer: d

Explanation: Padding is done towards the left-hand-side first when the final string is of odd length.

7. What is the output of the following?

```
print('*', "abcde".center(6), '*', sep="")
```

- a) * abcde *
- b) * abcde *
- c) *abcde *
- d) * abcde*

View Answer

Answer: c

Explanation: Padding is done towards the right-hand-side first when the final string is of even length.

advertisements

8. What is the output of the following?

```
print("abcdef".center(7, 1))
```

- a) 1abcdef
- b) abcdef1
- c) abcdef
- d) error

[View Answer](#)

Answer: d

Explanation: TypeError, the fill character must be a character, not an int.

9. What is the output of the following?

```
print("abcdef".center(7, '1'))
```

- a) 1abcdef
- b) abcdef1
- c) abcdef
- d) error

[View Answer](#)

Answer: a

Explanation: The character '1' is used for padding instead of a space.

10. What is the output of the following?

```
print("abcdef".center(10, '12'))
```

- a) 12abcdef12
- b) abcdef1212
- c) 1212abcdef
- d) error

[View Answer](#)

Answer: d

Explanation: The fill character must be exactly one character long.

Python Questions and Answers - Strings - 6

This set of Python Quiz focuses on “Strings” .

1. What is the output of the following?

```
print("xyyzxyzxyzxy".count('yy'))
```

- a) 2
- b) 0
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: Counts the number of times the substring 'yy' is present in the given string.

2. What is the output of the following?

```
print("xyyzxyzxyzxy".count('yy', 1))
```

- a) 2
- b) 0
- c) 1
- d) none of the mentioned

View Answer

Answer: a

Explanation: Counts the number of times the substring 'yy' is present in the given string, starting from position 1.

3. What is the output of the following?

```
print("xyyzxyzxyzxy".count('yy', 2))
```

- a) 2
- b) 0
- c) 1
- d) none of the mentioned

View Answer

Answer: c

Explanation: Counts the number of times the substring 'yy' is present in the given string, starting from position 2.

advertisements

4. What is the output of the following?

```
print("xyyzxyzxyzxy".count('xyy', 0, 100))
```

- a) 2
- b) 0
- c) 1
- d) error

View Answer

Answer: a

Explanation: An error will not occur if the end value is greater than the length of the string itself.

5. What is the output of the following?

```
print("xyyzxyzxyzxy".count('xyy', 2, 11))
```

- a) 2
- b) 0
- c) 1

d) error

[View Answer](#)

Answer: b

Explanation: Counts the number of times the substring 'xyy' is present in the given string, starting from position 2 and ending at position 11.

6. What is the output of the following?

```
print("xyyzyzxxxyy".count('xyy', -10, -1))
```

a) 2

b) 0

c) 1

d) error

[View Answer](#)

Answer: b

Explanation: Counts the number of times the substring 'xyy' is present in the given string, starting from position 2 and ending at position 11.

7. What is the output of the following?

```
print('abc'.encode())
```

advertisements

a) abc

b) 'abc'

c) b' abc'

d) h' abc'

[View Answer](#)

Answer: c

Explanation: A bytes object is returned by encode.

8. What is the default value of encoding in encode()?

a) ascii

b) qwerty

c) utf-8

d) utf-16

[View Answer](#)

Answer: c

Explanation: The default value of encoding is utf-8.

9. What is the output of the following?

```
print("xyyzyzxxxyy".endswith("xyy"))
```

a) 1

b) True

c) 3

d) 2

[View Answer](#)

Answer: b

Explanation: The function returns True if the given string ends with the specified substring.

10. What is the output of the following?

```
print("xyzyxyzxyzxy".endswith("xyy", 0, 2))
```

a) 0

b) 1

c) True

d) False

[View Answer](#)

Answer: d

Explanation: The function returns False if the given string does not end with the specified substring.

This set of Python Question Bank focuses on “Strings” .

1. What is the output of the following?

```
print('abcdefcdghcd'.split('cd', 2))
```

a) ['ab' , 'ef' , 'ghcd'] b) ['ab' , 'efcdghcd'] c) ['abcdef' , 'ghcd'] d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: The string is split into a maximum of maxsplit+1 substrings.

2. What is the output of the following?

```
print('ab\ncd\nef'.splitlines())
```

a) ['ab' , 'cd' , 'ef'] b) ['ab\n' , 'cd\n' , 'ef\n'] c) ['ab\n' , 'cd\n' , 'ef'] d) ['ab' , 'cd' , 'ef\n'] [View Answer](#)

Answer: a

Explanation: It is similar to calling split('\n').

3. What is the output of the following?

```
print('Ab!2'.swapcase())
```

a) AB!@

b) ab12

c) aB!2

d) aB1@

[View Answer](#)

Answer: c

Explanation: Lowercase letters are converted to uppercase and vice-versa.

4. What is the output of the following?

```
print('ab cd ef'.title())
```

advertisements

- a) Ab cd ef
- b) Ab cd eF
- c) Ab Cd Ef
- d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: The first letter of every word is capitalized.

5. What is the output of the following?

```
print('ab cd-ef'.title())
```

- a) Ab cd-ef
- b) Ab Cd-ef
- c) Ab Cd-Ef
- d) none of the mentioned

[View Answer](#)

Answer: c

Explanation: The first letter of every word is capitalized. Special symbols terminate a word.

6. What is the output of the following?

```
print('abcd'.translate('a'.maketrans('abc', 'bcd')))
```

- a) bcde
- b) abcd
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: d

Explanation: The output is bcdd since no translation is provided for d.

7. What is the output of the following?

```
print('abcd'.translate({97: 98, 98: 99, 99: 100}))
```

- a) bcde
- b) abcd
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: d

Explanation: The output is bcdd since no translation is provided for d.

advertisements

8. What is the output of the following?

```
print('abcd'.translate({'a': '1', 'b': '2', 'c': '3', 'd': '4'}))
```

- a) abcd
- b) 1234
- c) error
- d) none of the mentioned

[View Answer](#)

Answer: a

Explanation: The function translate expects a dictionary of integers. Use maketrans() instead of doing the above.

9. What is the output of the following?

```
print('ab'.zfill(5))
```

- a) 000ab
- b) 00ab0
- c) 0ab00
- d) ab000

[View Answer](#)

Answer: a

Explanation: The string is padded with zeroes on the left hand side. It is useful for formatting numbers.

10. What is the output of the following?

```
print('+99'.zfill(5))
```

- a) 00+99
- b) 00099
- c) +0099
- d) +++99

[View Answer](#)

Answer: c

Explanation: Zeroes are filled in between the first sign and the rest of the string.

Python Questions and Answers - Lists - 1

This set of Python Questions & Answers focuses on “Lists” .

1. Which of the following commands will create a list(multiple answers allowed) ?

- a) list1 = list()
- b) list1 = [] c) list1 = list([1, 2, 3])
- d) list1 = [1, 2, 3] View Answer

Answer:a,b,c,d

Explanation:Execute in the shell to verify

2. What is the output when we execute list("hello")?

- a) ['h' , 'e' , 'l' , 'l' , 'o'] b) ['hello'] c) ['llo'] d) ['olleh'] View Answer

Answer:a

Explanation:execute in the shell to verify.

3. Suppose listExample is ['h' , 'e' , 'l' , 'l' , 'o'], what is len(listExample)?

- a) 5
- b) 4
- c) None
- d) Error

View Answer

Answer:a

Explanation:Execute in the shell and verify.

4. Suppose list1 is [2445,133,12454,123], what is max(list1) ?

- a) 2445
- b) 133
- c) 12454
- d) 123

View Answer

Answer:c

Explanation:max returns the maximum element in the list.

advertisements

5. Suppose list1 is [3, 5, 25, 1, 3], what is min(list1) ?

- a) 3
- b) 5
- c) 25
- d) 1

View Answer

Answer:d

Explanation:min returns the minimum element in the list.

6. Suppose list1 is [1, 5, 9], what is sum(list1) ?

- a) 1
- b) 9
- c) 15
- d) Error

View Answer

Answer:c

Explanation:Sum returns the sum of all elements in the list.

7. To shuffle the list(say list1) what function do we use ?

- a) list1.shuffle()
- b) shuffle(list1)
- c) random.shuffle(list1)
- d) random.shuffleList(list1)

View Answer

Answer:c

Explanation:Execute in the shell to verify .

8. Suppose list1 is [4, 2, 2, 4, 5, 2, 1, 0], Which of the following is correct (multiple answers allowed) ?

- a) print(list1[0])
- b) print(list1[:2])
- c) print(list1[:-2])
- d) print(list1[4:6])

View Answer

Answer:a, b, c, d

Explanation:Slicing is allowed in lists just as in the case of strings.

advertisements

9. Suppose list1 is [2, 33, 222, 14, 25], What is list1[-1] ?

- a) Error
- b) None
- c) 25
- d) 2

View Answer

Answer:c

Explanation:-1 corresponds to the last index in the list.

10. Suppose list1 is [2, 33, 222, 14, 25], What is list1[:-1] ?

- a) [2, 33, 222, 14] b) Error
- c) 25
- d) [25, 14, 222, 33, 2] View Answer

Answer:a

Explanation:Execute in the shell to verify.

Python Questions and Answers - Lists - 2

This set of Python Coding Interview Questions & Answers focuses on “Lists” .

1. What is the output when following code is executed ?

```
>>>names = ['Amir', 'Bear', 'Charlton', 'Daman']
>>>print names[-1][-1]
```

- a) A
- b) Daman
- c) Error
- d) n

[View Answer](#)

Answer:d

Explanation:Execute in the shell to verify.

2. What is the output when following code is executed ?

```
names1 = ['Amir', 'Bear', 'Charlton', 'Daman']
names2 = names1
names3 = names1[:]
```

```
names2[0] = 'Alice'
names3[1] = 'Bob'
```

```
sum = 0
for ls in (names1, names2, names3):
    if ls[0] == 'Alice':
        sum += 1
    if ls[1] == 'Bob':
        sum += 10
```

```
print sum
```

- a) 11
- b) 12
- c) 21
- d) 22

[View Answer](#)

Answer:b

Explanation:When assigning names1 to names2, we create a second reference to the same list. Changes to names2 affect names1. When assigning the slice of all elements in names1 to names3, we are creating a full copy of names1 which can be modified independently.

advertisements

3. Suppose list1 is [1, 3, 2], What is list1 * 2 ?

- a) [2, 6, 4] b) [1, 3, 2, 1, 3] c) [1, 3, 2, 1, 3, 2] D) [1, 3, 2, 3, 2, 1] [View Answer](#)

Answer:c

Explanation:Execute in the shell and verify.

4. Suppose list1 = [0.5 * x for x in range(0, 4)], list1 is :

- a) [0, 1, 2, 3] b) [0, 1, 2, 3, 4] c) [0.0, 0.5, 1.0, 1.5] d) [0.0, 0.5, 1.0, 1.5, 2.0] [View Answer](#)

Answer:c

Explanation:Execute in the shell to verify.

5. What is the output when following code is executed ?

```
>>>list1 = [11, 2, 23]
```

```
>>>list2 = [11, 2, 2]
```

```
>>>list1 < list2 is
```

a) True

b) False

c) Error

d) None

[View Answer](#)

Answer:b

Explanation:Elements are compared one by one.

6. To add a new element to a list we use which command ?

a) list1.add(5)

b) list1.append(5)

c) list1.addLast(5)

d) list1.addEnd(5)

[View Answer](#)

Answer:b

Explanation:We use the function append to add an element to the list.
advertisements

7. To insert 5 to the third position in list1, we use which command ?

a) list1.insert(3, 5)

b) list1.insert(2, 5)

c) list1.add(3, 5)

d) list1.append(3, 5)

[View Answer](#)

Answer:a

Explanation:Execute in the shell to verify.

8. To remove string “hello” from list1, we use which command ?

a) list1.remove(“hello”)

b) list1.remove(hello)

c) list1.removeAll(“hello”)

d) list1.removeOne(“hello”)

[View Answer](#)

Answer:a

Explanation:Execute in the shell to verify.

9. Suppose list1 is [3, 4, 5, 20, 5], what is list1.index(5) ?

- a) 0
- b) 1
- c) 4
- d) 2

[View Answer](#)

Answer:d

Explanation:Execute `help(list.index)` to get details.

10. Suppose list1 is [3, 4, 5, 20, 5, 25, 1, 3], what is `list1.count(5)` ?

- a) 0
- b) 4
- c) 1
- d) 2

[View Answer](#)

Answer:d

Explanation:Execute in the shell to verify.

Python Questions and Answers - Lists - 3

This set of Python Programming Questions & Answers focuses on “Lists” .

1. Suppose list1 is [3, 4, 5, 20, 5, 25, 1, 3], what is list1 after `list1.reverse()` ?

- a) [3, 4, 5, 20, 5, 25, 1, 3] b) [1, 3, 3, 4, 5, 5, 20, 25] c) [25, 20, 5, 5, 4, 3, 3, 1] d) [3, 1, 25, 5, 20, 5, 4, 3]
- [View Answer](#)

Answer:d

Explanation:Execute in the shell to verify.

2. Suppose listExample is [3, 4, 5, 20, 5, 25, 1, 3], what is list1 after `listExample.extend([34, 5])` ?

- a) [3, 4, 5, 20, 5, 25, 1, 3, 34, 5] b) [1, 3, 3, 4, 5, 5, 20, 25, 34, 5] c) [25, 20, 5, 5, 4, 3, 3, 1, 34, 5] d) [1, 3, 4, 5, 20, 5, 25, 3, 34, 5]
- [View Answer](#)

Answer:a

Explanation:Execute in the shell to verify.

3. Suppose listExample is [3, 4, 5, 20, 5, 25, 1, 3], what is list1 after `listExample.pop(1)` ?

- a) [3, 4, 5, 20, 5, 25, 1, 3] b) [1, 3, 3, 4, 5, 5, 20, 25] c) [3, 5, 20, 5, 25, 1, 3] d) [1, 3, 4, 5, 20, 5, 25]

[View Answer](#)

Answer:c

Explanation:`pop()` removes the element at the position specified in the parameter.

4. Suppose listExample is [3, 4, 5, 20, 5, 25, 1, 3], what is list1 after `listExample.pop()`?

- a) [3, 4, 5, 20, 5, 25, 1] b) [1, 3, 3, 4, 5, 5, 20, 25] c) [3, 5, 20, 5, 25, 1, 3] d) [1, 3, 4, 5, 20, 5, 25]

[View Answer](#)

Answer:a

Explanation:pop() by default will remove the last element.

5. What is the output when following code is executed ?

```
>>>"Welcome to Python".split()
```

- a) ["Welcome" , "to" , "Python"]
- b) ("Welcome" , "to" , "Python")
- c) { "Welcome" , "to" , "Python" }
- d) "Welcome" , "to" , "Python"

View Answer

Answer:a

Explanation:split() function returns the elements in a list.

6. What is the output when following code is executed ?

```
>>>list("a#b#c#d".split('#'))
```

advertisements

- a) ['a' , 'b' , 'c' , 'd']
- b) ['a b c d']
- c) ['a#b#c#d']
- d) ['abcd']

View Answer

Answer:a

Explanation:Execute in the shell to verify.

7. What is the output when following code is executed ?

```
myList = [1, 5, 5, 5, 5, 1]
max = myList[0]
indexOfMax = 0
for i in range(1, len(myList)):
    if myList[i] > max:
        max = myList[i]
        indexOfMax = i
```

```
>>>print(indexOfMax)
```

- a) 1
- b) 2
- c) 3
- d) 4

View Answer

Answer:a

Explanation:First time the highest number is encountered is at index 1.

8. What is the output when following code is executed ?

```
myList = [1, 2, 3, 4, 5, 6]
for i in range(1, 6):
    myList[i - 1] = myList[i]

for i in range(0, 6):
```

```
print(myList[i], end = " ")
```

- a) 2 3 4 5 6 1
- b) 6 1 2 3 4 5
- c) 2 3 4 5 6 6
- d) 1 1 2 3 4 5

[View Answer](#)

Answer:c

Explanation:Execute in the shell to verify.

advertisements

9. What is the output when following code is executed ?

```
>>>list1 = [1, 3]
>>>list2 = list1
>>>list1[0] = 4
>>>print(list2)
```

- a) [1, 3] b) [4, 3] c) [1, 4] d) [1, 3, 4]
- [View Answer](#)

10. What is the output when following code is executed ?

```
def f(values):
    values[0] = 44
```

```
v = [1, 2, 3]
f(v)
print(v)
```

- a) [1, 44] b) [1, 2, 3, 44] c) [44, 2, 3] d) [1, 2, 3]
- [View Answer](#)

Answer:c

Explanation:Execute in the shell to verify.

Python Questions and Answers - Lists - 4

This set of Python Programming Interview Questions & Answers focuses on “Lists” .

1. What will be the output?

```
def f(i, values = []):
    values.append(i)
    return values
```

```
f(1)
f(2)
v = f(3)
print(v)
```

- a) [1] [2] [3] b) [1] [1, 2] [1, 2, 3] c) [1, 2, 3] d) 1 2 3

[View Answer](#)

Answer:c

Explanation:execute in the shell to verify

2. What will be the output?

```
names1 = ['Amir', 'Bala', 'Chales']
```

```
if 'amir' in names1:
```

```
    print 1
```

```
else:
```

```
    print 2
```

a) None

b) 1

c) 2

d) Error

[View Answer](#)

Answer:c

Explanation:execute in the shell to verify.

3. What will be the output?

```
names1 = ['Amir', 'Bala', 'Charlie']
```

```
names2 = [name.lower() for name in names1]
```

```
print names2[2][0]
```

a) None

b) a

c) b

d) c

[View Answer](#)

4. What will be the output?

```
numbers = [1, 2, 3, 4]
```

```
numbers.append([5,6,7,8])
```

```
print len(numbers)
```

advertisements

a) 4

b) 5

c) 8

d) 12

View Answer

Answer:b

Explanation:a list is passed in append so the length is 5.

5. To which of the following the “in” operator can be used to check if an item is in it?

- a) Lists
- b) Dictionary
- c) Set
- d) All of The Above

View Answer

Answer:d

Explanation:in can be used in all data structures.

6. What will be the output?

```
list1 = [1, 2, 3, 4]
```

```
list2 = [5, 6, 7, 8]
```

```
print len(list1 + list2)
```

- a) 2
- b) 4
- c) 5
- d) 8

View Answer

Answer:d

Explanation:+ appends all the elements individually into a new list.

7. What will be the output?

```
def addItem(listParam):  
    listParam += [1]
```

```
mylist = [1, 2, 3, 4]
```

```
addItem(mylist)
```

```
print len(mylist)
```

- a) 1
- b) 4
- c) 5
- d) 8

View Answer

Answer:c

Explanation:+ will append the element to the list.

8. What will be the output?

```
def increment_items(L, increment):
```

```
    i = 0
```

```
    while i < len(L):
```

```
        L[i] = L[i] + increment
```

```
        i = i + 1
```

```
values = [1, 2, 3]
```

```
print(increment_items(values, 2))
```

```
print(values)
```

advertisements

a) None

[3, 4, 5] b) None

[1, 2, 3] c) [3, 4, 5] [1, 2, 3] d) [3, 4, 5] None

View Answer

Answer:a

Explanation:Execute in the shell to verify.

9. What will be the output?

```
def example(L):
```

```
    """ (list) -> list
```

```
    """
```

```
    i = 0
```

```
    result = []
```

```
    while i < len(L):
```

```
        result.append(L[i])
```

```
        i = i + 3
```

```
    return result
```

a) Return a list containing every third item from L starting at index 0.

b) Return an empty list

c) Return a list containing every third index from L starting at index 0.

d) Return a list containing the items from L starting from index 0, omitting every third item.

View Answer

Answer:a

Explanation:Run the code to get a better understanding with many arguments.

10. What will be the output?

```
veggies = ['carrot', 'broccoli', 'potato', 'asparagus']
```

```
veggies.insert(veggies.index('broccoli'), 'celery')
```

```
print(veggies)
```

a) ['carrot' , 'celery' , 'broccoli' , 'potato' , 'asparagus'] Correct 1.00

b) ['carrot' , 'celery' , 'potato' , 'asparagus'] c) ['carrot' , 'broccoli' , 'celery' , 'potato' , 'asparagus'] d) ['celery' , 'carrot' , 'broccoli' , 'potato' , 'asparagus']

View Answer

Answer:a

Explanation:Execute in the shell to verify

Python Questions and Answers - Dictionary - 1

This set of Python Questions & Answers focuses on “Dictionaries” .

1. Which of the following statements create a dictionary?(multiple answers allowed)

- a) `d = {}`
- b) `d = { "john" :40, "peter" :45}`
- c) `d = {40:" john" , 45:" peter" }`
- d) `d = (40:" john" , 45:" peter" )`

[View Answer](#)

Answer:a,b,c

Explanation:Dictionaries are created by specifying keys and values

2. What are the keys?

- ```
d = {"john":40, "peter":45}
```
- a) “john” , 40, 45, and “peter”
  - b) “john” and “peter”
  - c) 40 and 45
  - d) `d = (40:" john" , 45:" peter" )`

[View Answer](#)

Answer:b

Explanation:Dictionaries appear in the form of keys and values.

3. What will be the output?

- ```
d = {"john":40, "peter":45}
"john" in d
```
- a) True
 - b) False
 - c) None
 - d) Error

[View Answer](#)

Answer:a

Explanation:In can be used to check if the key is int dictionary.

4. What will be the output?

- ```
d1 = {"john":40, "peter":45}
d2 = {"john":466, "peter":45}
d1 == d2
```

advertisements

- a) True
- b) False
- c) None
- d) Error

View Answer

Answer:b

Explanation:If d2 was initialized as d2 = d1 the answer would be true.

5. What will be the output?

```
d1 = {"john":40, "peter":45}
d2 = {"john":466, "peter":45}
d1 > d2
```

- a) True
- b) False
- c) Error
- d) None

View Answer

Answer:c

Explanation:Arithmetic > operator cannot be used with dictionaries.

6. What is the output?

```
d = {"john":40, "peter":45}
d["john"]
```

- a) 40
- b) 45
- c) "john"
- d) "peter"

View Answer

Answer:a

Explanation:Execute in the shell to verify.

advertisements

7. Suppose d = { "john" :40, "peter" :45}, to delete the entry for "john" what command do we use

- a) d.delete( "john" :40)
- b) d.delete( "john" )
- c) del d[ "john" ] d) del d( "john" :40)

View Answer

Answer:c

Explanation:Execute in the shell to verify.

8. Suppose d = { "john" :40, "peter" :45}, to obtain the number of entries in dictionary what command do we use

- a) d.size()
- b) len(d)
- c) size(d)
- d) d.len()

View Answer

Answer:b

Explanation:Execute in the shell to verify.

9. What will be the output?

```
d = {"john":40, "peter":45}
```

```
print(list(d.keys()))
```

- a) [ "john" , "peter" ]
- b) [ "john" :40, "peter" :45]
- c) ( "john" , "peter" )
- d) ( "john" :40, "peter" :45)

View Answer

Answer:a

Explanation:Execute in the shell to verify.

10. Suppose d = {"john":40, "peter":45}, what happens when retrieving a value using d["susan"]?

- a) Since "susan" is not a value in the set, Python raises a KeyError exception.
- b) It is executed fine and no exception is raised, and it returns None.
- c) Since "susan" is not a key in the set, Python raises a KeyError exception.
- d) Since "susan" is not a key in the set, Python raises a syntax error.

View Answer

Answer:c

Explanation:Execute in the shell to verify.

## Python Questions and Answers - Tuples

This set of Python Questions & Answers focuses on "tuples" .

1. Which of the following is a Python tuple?

- a) [1, 2, 3]
- b) (1, 2, 3)
- c) {1, 2, 3}
- d) {}

View Answer

Answer:b

Explanation:Tuples are characterised by their round brackets.

2. Suppose t = (1, 2, 4, 3), which of the following is incorrect?

- a) print(t[3])
- b) t[3] = 45
- c) print(max(t))
- d) print(len(t))

[View Answer](#)

Answer:b

Explanation:Values cannot be modified in the case of tuple.

3. What will be the output?

```
>>>t=(1,2,4,3)
```

```
>>>t[1:3]
```

a) (1, 2)

b) (1, 2, 4)

c) (2, 4)

d) (2, 4, 3)

[View Answer](#)

Answer:c

Explanation:Slicing just as in the case of strings takes place in tuples.

4. What will be the output?

```
>>>t=(1,2,4,3)
```

```
>>>t[1:-1]
```

a) (1, 2)

b) (1, 2, 4)

c) (2, 4)

d) (2, 4, 3)

[View Answer](#)

Answer:c

Explanation:Slicing just as in the case of strings takes place in tuples.

5. What will be the output?

```
>>>t = (1, 2, 4, 3, 8, 9)
```

```
>>>[t[i] for i in range(0, len(t), 2)]
```

advertisements

a) [2, 3, 9] b) [1, 2, 4, 3, 8, 9] c) [1, 4, 8] d) (1, 4, 8)

[View Answer](#)

Answer:c

Explanation:Execute in the shell to verify.

6. What will be the output?

```
d = {"john":40, "peter":45}
```

```
d["john"]
```

a) 40

b) 45

c) “john”

d) "peter"

[View Answer](#)

Answer:a

Explanation:Execute in the shell to verify.

7. What will be the output?

```
>>>t = (1, 2)
```

```
>>>2 * t
```

a) (1, 2, 1, 2)

b) [1, 2, 1, 2] c) (1, 1, 2, 2)

d) [1, 1, 2, 2] [View Answer](#)

Answer:a

Explanation:\* operator concatenates tuple.

8. What will be the output?

```
>>>t1 = (1, 2, 4, 3)
```

```
>>>t2 = (1, 2, 3, 4)
```

```
>>>t1 < t2
```

advertisements

a) True

b) False

c) Error

d) None

[View Answer](#)

Answer:b

Explanation:Elements are compared one by one in this case.

9. What will be the output?

```
>>>my_tuple = (1, 2, 3, 4)
```

```
>>>my_tuple.append((5, 6, 7))
```

```
>>>print len(my_tuple)
```

a) 1

b) 2

c) 5

d) Error

[View Answer](#)

Answer:d

Explanation:Tuples are immutable and don't have an append method. An exception is thrown in this case..

10. What will be the output?

```
numberGames = {}
numberGames[(1,2,4)] = 8
numberGames[(4,2,1)] = 10
numberGames[(1,2)] = 12

sum = 0
for k in numberGames:
 sum += numberGames[k]
```

```
print len(numberGames) + sum
```

a) 30

b) 24

c) 33

d) 12

[View Answer](#)

Answer:c

Explanation:Tuples can be used for keys into dictionary. The tuples can have mixed length and the order of the items in the tuple is considered when comparing the equality of the keys

~

J

A

Y

G

O

O

D

Y

~

CARES..... BEST OF LUCK IN YOUR TEST