

SETTING UP ENVIRONMENT VARIABLES IN BITBUCKET

The screenshot shows the Bitbucket 'Settings' page for a repository. The left sidebar contains a list of settings categories: GENERAL, WORKFLOW, FEATURES, and PIPELINES. Under GENERAL, 'Environment variables' is highlighted with a red box and an arrow pointing to it, with the annotation '1. Click here'. The main content area is titled 'Environment variables' and contains explanatory text. Below the text is a table with one row of variables. This row is highlighted with a red box, and an arrow points to the 'Secured' checkbox with the annotation '2. Add key as above. Remember to click [x] Secured'. The table has columns for 'variable name', 'value', and 'Actions'.

Settings

GENERAL

- Repository details
- User and group access
- Access keys
- Username aliases

WORKFLOW

- Branch permissions
- Default reviewers
- Webhooks
- Links

FEATURES

- Git LFS
- Wiki
- Issue tracker

PIPELINES

- Settings
- Environment variables**
- SSH keys
- Integrations

Environment variables

Environment variables added on the repository level can be accessed by any users with push permissions in the repository. To access a variable, put the \$ symbol in front of its name. For example, access AWS_SECRET by using \$AWS_SECRET. For more information, see [Environment variables](#).

Repository variables override variables added on the account level. [View account variables](#)

variable name	value	Actions
AWS_SECRET_ACCESS_KEY	AKIAIB6AAVHQWR3SMDLA	<input checked="" type="checkbox"/> Secured <button>Add</button>

You haven't added any variables yet.

1. Click here

2. Add key as above. Remember to click [x] Secured

AWS CODEDEPLOY – DEPLOYMENT TYPE

- ▶ <http://docs.aws.amazon.com/codedeploy/latest/userguide/welcome.html#welcome-deployment-overview>
- ▶ In-place Deployment
- ▶ Blue/Green Deployment

