

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

PCBU DETAILS				Client Name	
Name	Sky5 Pty Ltd	ABN	33 616 468 261	Contact Name	
Address	Unit 8 Harcourt Business Park, 809-821 Botany Road, NSW, Rosebery, 2018			Address	
Office Phone	1300 301 214	Mobile	0424382197	Work location	
Work activity	Perform Window Cleaning via Rope Access	Manager	Robert Wojtas	JSEA/SWMS #	PR004
				Site specific	☒ Yes Version

Job Safety and Environmental Analysis					
Person responsible for preparation of JSEA				Person(s) responsible for reviewing the JSEA	
Date prepared:				Last JSEA review date	
Date JSEA provided to client				Signature	
HIGH RISK CONSTRUCTION WORK: Identify the High Risk Construction Work that may be present in the working environment.					
X	Risk of a person falling more than 2 meters		Temporary load-bearing support for structural alterations or repairs		Demolition of a load-bearing structure
	Likely to involve disturbing asbestos		Work on a telecommunications tower		Work in or near a confined space
	Work in or near a shaft or trench deeper than 1.5m or a tunnel		Use of explosives		Work on or around pressurised gas distribution mains or piping
	Work on or near chemical, fuel or refrigerant lines		Work on or near energised electrical installations or services		Work in an area that may have a contaminated or flammable atmosphere
	Tilt-up or precast concrete elements		Work on, in or adjacent to a road, railway, shipping lane or other traffic corridor that is in use by traffic other than pedestrians		Work in an area with movement of powered mobile plant
	Work in areas with artificial extremes of temperature		Work in or near water or other liquid that involves a risk of drowning		Diving
HAZARDS: Identify the hazards and risks that may be present in the work activity being carried out.					
X	Falling from Height		Demolition or dismantling		Hot work (welding, cutting, grinding)
X	Falling Objects, Exclusion Zones	X	Edge protection		Noise
X	Public and Pedestrian safety	X	Electricity, electrical tools and equipment		Plant and Equipment Operation
X	Access and Egress	X	UV Radiation (sunlight)	X	Traffic on site / traffic control
	Building Maintenance Unit		Flammable and Combustible Liquids	X	Fatigue i.e. long or late shift, long travel
	Elevated Work Platform		Paints/Coatings/Solvents	X	Overhead electrical wiring
	Scaffolding and/or Ladders	X	Hazardous Chemicals	X	Lifting Equipment i.e. slings, tackle, etc.
X	Radio Frequency Radiation	X	Manual Handling / Work Posture	X	Exposure to Extreme weather
Required Plant:					



JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Safe Work Method Statement																
Person responsible for preparation of SWMS										Person(s) responsible for reviewing the SWMS						
Date prepared										Last SWMS review date						
Date SWMS provided to client										Signature						
Date work performed on										Start Time						
Monitoring and review of SWMS and control measures										Chemicals that will be required					Hazardous	
- SWMS will be reviewed every 6 months or if an incident occurs - The completion of the SWMS will be reviewed by the site supervisor and WHS Manager - While on site if the controls are deemed inadequate work is to stop and controls reviewed - The implementation of the controls measure in the SWMS will be monitored by the site supervisor by completing a behaviour observation form F002										Glass Glean 3 (GG3)					YES	
															YES NO	
															YES NO	
															YES NO	
Mandatory Personal Protective Clothing and Equipment (Please tick accordingly)																
Gloves  ☐ Yes	Face Masks  ☐ Yes	Eye Protection  ☐ Yes	Full face Respirator  ☐ Yes	Full Face Protection  ☐ Yes	Hearing Protection  ☐ Yes	Protective clothing  ☐ Yes	Hi Viz  ☐ Yes	Steel toecap  ☐ Yes	Half face Respirator  ☐ Yes	Fall Protection  ☐ Yes	Hard Hat  ☐ Yes	Sun Rated Clothing  ☐ Yes	Sun Glasses  ☐ Yes	Sun Hat  ☐ Yes	Sun Screen  ☐ Yes	All PPE as per PR016 ☐ Yes
Pre-start requirements, certification, authorisations or permits required:										Legislation / Standards applicable:						
☐	Site Specific Induction					Work Health and Safety Act 2011										
☐	General Induction					Work Health and Safety Regulation 2017										
☐	Access Permit to work					AS/NZS1891.1-4:2009 Fall Arrest System & Devices										
☐	Roof Access Permit					AS/NZS 1657 1992 – Fixed Platforms, Walkways, Stairs and Ladders										
☐	Working at Heights Permit					AS/NZS ISO 22846.1:2020 Rope access systems, Part 1										
Codes of Practice applicable:																
Managing the Risks of a Fall at the Workplace August 2019										Managing the Risks of a Fall at the Workplace August 2019						
First aid in the workplace code of practice January 2020										First aid in the workplace code of practice January 2020						
Hazardous manual tasks code of practice August 2019										Hazardous manual tasks code of practice August 2019						
How to manage work health and safety risks code of practice August 2019										How to manage work health and safety risks code of practice August 2019						
Work near power lines code of practice 2006										Work near power lines code of practice 2006						
On site role and responsibilities					Name					Qualifications					Current	
Site Supervisor										IRATA/SPRAT Lv 3					☒ Yes ☐ No	
First Aid officer										Provide First Aid					☒ Yes ☐ No	
Technician										IRATA/SPRAT Technici					☒ Yes ☐ No	
Copies of qualifications and certificates are available upon request please contact head office on 1300 301 214																
Total number of workers present on site																
Person responsible for ensuring compliance																

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

STEP 1: Consider how likely a risk is encountered, and what might happen. STEP 2: Use the risk level calculator to determine the likely risk level (outcome) following exposure to the hazard(s).		STEP 3: Identify and develop effective control measures. (Consult the hierarchy of risk control measures when carrying out this step).				
LEVEL OF CONSEQUENCES	CONSEQUENCES OF EVENT OCCURRING <i>What is the likely outcome of an exposure to the risk?</i>	LIKELIHOOD OF EVENT OCCURRING				
		Almost certain (5)	Likely (4)	Possible (3)	Unlikely (2)	Rare (1)
Catastrophic (5)	Fatality or permanent disability; toxic release of chemicals, long-term or irreversible environmental impact; loss of facilities; very high \$ loss	E (25)	E (24)	E (22)	E (19)	H (15)
High (4)	Long-term illness or serious injury; serious but reversible environmental impact; major property damage; loss of production; high \$ loss	E (23)	E (21)	E (18)	H (14)	H (10)
Moderate (3)	Medical treatment requiring up to several days off work; reversible environmental impact; significant property damage; med – high \$ loss	E (20)	H (17)	H (13)	M (9)	M (6)
Low (2)	Minor injury requiring First-Aid; minor reversible environmental impact; moderate property damage; low-med. \$ loss	H (16)	H (12)	M (8)	L (5)	L (3)
Insignificant (1)	No injuries or first aid only; minor property damage or environmental nuisance; very low \$ loss	M (11)	M (7)	L (4)	L (2)	L (1)
LIKELIHOOD OF EVENT OCCURRING <i>How likely is it that an exposure will occur?</i>		DETERMINATION OF RISK CONTROL ACTIONS				
		RISK LEVEL (OUTCOME) (from matrix)		ACTION REQUIRED (refer to the hierarchy of risk controls)		
Almost certain	Event is expected to occur in most circumstances					
Likely	Event will probably occur in most circumstances	E (EXTREME)		URGENT - Immediate action required to control risk.		
Possible	Event might occur at some time	H (HIGH)		Highest management decision required urgently.		
Unlikely	Event could occur at some time	M (MEDIUM)		Follow management instructions regarding risk.		
Rare	Event may occur only in exceptional circumstances	L (LOW)		These risks may not require immediate attention - monitor.		
LIKELIHOOD OF EVENT OCCURRING – Consider the following:		LIKELY CONSEQUENCES OF EVENT OCCURRING – Consider the following:			HIERARCHY OF CONTROLS	
How often is the task/activity performed? How many people are exposed to the hazard? How long is the exposure? Are engineering controls preventing exposure at present? Does workplace layout and condition affect exposure? Are abnormal conditions which may result in a greater exposure reasonably foreseeable? What are the results of any biological or atmospheric monitoring? Do workers have appropriate skills and knowledge to perform tasks? Do current work practices expose workers to a hazard? Are there other contributing factors?		What are the consequences in the short term? What are the consequences in the long term? What is the history of injuries related to exposure to the hazard? How close are workers to the hazard? What is the energy level of the hazard (i.e., weight, voltage, volume, height above ground, temperature, amplitude, concentration, aggressive state)? If a substance is hazardous, what are the health effects associated with – Inhaling it Ingestion (swallowing) it Skin contact, or Eye contact?			1. Elimination of the risk. If it is not reasonably practicable to eliminate the risk, minimise it by (in descending order) – 2. Substitution 3. Isolation 4. Engineering Means 5. Administrative Controls 6. Personal protective equipment (PPE)	

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | **SAFE WORK METHOD STATEMENT**

Section 1: Accessing site and Set up

ACTIVITY		HAZARDS AND RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
1.1	Prepare equipment and Load/unload Vehicle	Using incorrect manual handling technique to lift heavy equipment causes injury	E19	- Use correct manual handling technique - Use a minimum of two people for heavy loads - Separate larger loads in to smaller bags or containers - Make multiple trips with smaller loads	L1	Supervisor ☒ All Technicians ☐ Technician ☐
1.2	Site access and egress	Unauthorised access to work site causes a noncompliance with site safety procedures	M8	- All Technicians to have completed site induction prior to arrival - Facilities manager to be contacted on arrival where necessary - Roof access/Working at height permit to be obtained where necessary - Technicians to identify emergency evacuation procedure and alarm system - Sign in procedure to be completed	L1	Supervisor ☐ All Technicians ☒ Technician ☐
1.3	Access to roof via plant rooms/areas	Non-compliance with mandatory PPE signage (white sign with blue circle) causes incident or injury	H14	- Technicians to observe and follow all mandatory PPE signage - Supervisor to ensure that all Technicians have mandatory PPE available and accessible	L2	Supervisor ☒ All Technicians ☐ Technician ☐

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Section 1: Accessing site and Set up

ACTIVITY		HAZARDS AND RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
1.4	Planning and preparing to Perform work tasks	Non-completion of required documentation causes noncompliance with safe work procedures	M8	- Site supervisor to facilitate Donesafe Pre Start meeting and complete via Donesafe - SWMS to be read, understood and signed by each technician, then uploaded to Donesafe via Fill and Sign - Rope Access checklist to be completed via Donesafe	L1	Supervisor ☒ All Technicians ☐ Technician ☐
1.5	Planning and preparing to Perform work tasks	Working in a changing environment and extreme weather conditions causes work conditions to become unsafe	M8	- Weather report to be obtained and reviewed prior to accessing roof and a decision to proceed if conditions are safe - A continuous review of conditions with supervisor to decide if work should cease due to conditions deteriorating - Wind speed to be recorded in Pre Start - No matter what wind speed is recorded, if the Site Supervisor feels it is unsafe to continue working, work is to cease.	L1	Supervisor ☒ All Technicians ☐ Technician ☐
1.6	Planning and preparing to Perform work tasks in and around hazardous roof environment	Continuous exposure to cooling towers and Radio Frequency Antennas on the roof causes injury or harm to technicians	E18	- Monthly cooling tower inspection report to be obtained from facilities manager - Locations of any RF antennas on roof area to be identified and safe work area to be established	L4	Supervisor ☒ All Technicians ☐ Technician ☐
1.77	Access to work site through clients premises	Carrying equipment and large loads through building causes damage to premises or injures a member of the public	H13	- Correct manual handling techniques to be used - Equipment bags are not to be over loaded, and multiple trips to be undertaken if necessary - Safe clear routes through premises to be identified and used	L2	Supervisor ☐ All Technicians ☒ Technician ☐

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Section 1: Accessing site and Set up					
ACTIVITY		HAZARDS AND RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK
1.8	Access to roof via plant rooms	Low level plant and machinery throughout room and poor lighting causes worker to impact with plant and sustain an injury	M8	- Technicians to use caution and be observant - Use safe access walk ways - Technicians to adhere to any safety signage - Technicians to avoid moving in and around plant and machinery	L1
1.9	Performing window cleaning via rope access system	Falling object or water hits pedestrian or causing injury or incident	E22	- Establish a dedicated exclusion zone by placing bollards and barricade tape/plastic chain at the base of the suspended ropes - Erect A-Frame danger sign within the dedicated exclusion zone	L3
1.10	Access to roof area	uneven low friction surfaces cause injury from slip, trip or fall to the technician	M8	- Technicians to wear adequate footwear - Technicians to use designated walk way where possible - Extra caution to be taken after rain on wet surfaces	L1
1.11	Establishing a safe and effective rope access system	Inexperienced technician uses incorrect technique or equipment to establish system causing it to fail and an injury or death	E22	- Use competent and inducted personnel - All technicians to hold a minimum of an IRATA/SPRAT level 1 qualification and Safe Work at Height certificate. - A supervisor with a minimum of a level 2 IRATA/SPRAT qualification is to supervise and inspect all systems prior to use. - All PPE to be within date of the 6 monthly inspection schedule and logged in Gearlog	L3
1.12	Establishing rope access system	Exposure to unprotected fall edge while establishing rope access system causes technician to fall from height	E22	- All Technicians are to be in full PPE and attached to a safety line when working within 3 metres of a fall edge - Buddy checks are to be performed prior to committing to and loading any safety system	L2

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Section 1: Accessing site and Set up

ACTIVITY		HAZARDS AND RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
1.13	Establishing rope access system	Damaged or corroded anchors/structure used in system fail causing a fall from height	E22	- All anchors are to be inspected prior to use - All anchors are to be tagged and within the 12-month inspection date - A minimum of two independent anchors must be used - If no safe anchors are available work must cease and manager contacted - L3 rope access technician to sign off rigging or installing anchors utilising structure	L3	Supervisor ☒ All Technicians ☐ Technician ☐
1.14	Establishing rope access system	Rigging ropes running over sharp or abrasive edges fail causing a fall from height	E22	- Sharp edges are to be avoided when rigging rope systems - All ropes are to be protected from sharp edges with rope protectors or another effective identified method	L3	Supervisor ☒ All Technicians ☐ Technician ☐
1.15	Establishing rope access system	Working in and around brittle roof and weak roof structure causes technician to fall from height	E22	- All weak and brittle roof areas are to be identified and avoided - All technicians to observe safety signs - If technicians are unsure as to their safety at any point work is to cease and manager contacted	L3	Supervisor ☐ All Technicians ☒ Technician ☐
1.16	Preparing to perform work task	Incorrect use of Hazardous chemical causes exposure to worker resulting in injury or harm	E21	- Hazardous chemicals are not to be issued unless technicians have received the necessary training, and must be identified and made known to all technicians signing on to the SWMS - SDS is to be reviewed and if necessary technicians trained in safe use, and documented in a tool box talk on Donesafe - All technicians to be provided with necessary PPE to ensure safe use of chemical	L3	Supervisor ☒ All Technicians ☐ Technician ☐

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Section 1: Accessing site and Set up

ACTIVITY		HAZARDS AND RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
1.17	Establishing rope access system	Ropes reaching ground level within a carpark causes incident with moving vehicle	E22	- If possible an exclusion zone is to be established at ground level beneath work area. - If unable to establish an exclusion zone technicians are suspend ropes beneath them, ensuring the ropes do not reach the ground, but are able to be deployed in the event of an emergency	L3	Supervisor ☐ All Technicians ☒ Technician ☐
1.18	Performing work tasks	Exposure to live electrical current causes electrocution resulting in injury or death	E24	- All electrical installations and services to be located and identified if live - Any work areas with live installations and services to be made safe by implementing isolation where required - Installations to be inspected for any exposed live wiring and sound generated from arcing	L3	Supervisor ☐ All Technicians ☒ Technician ☐
1.19	Establishing rope access system	Ropes impacting with overhead power lines causes incident or injury	E22	- Technicians and all equipment are to remain a minimum of three metres from power lines - Technicians to take care on windy days, to ensure ropes don't blow on/near power lines by coiling or bundling ropes securely away from power lines	M6	Supervisor ☐ All Technicians ☒ Technician ☐
1.20	Preparing to perform work task	Restricted Access and Egress in emergency	H14	- Technicians to have 2 keys/swipes or - Building Manager/Security able to provide access in emergency - If only 1 key/swipe available and no building manager/security to provide access in emergency, technicians must work in close proximity at all times - Direct communication with Facilities manager to be established - First aid kit to be taken to work site - Qualified first aider to be present at all times - A minimum of two technicians to be present on site at all times	L1	Supervisor ☒ All Technicians ☐ Technician ☐

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Section 2: Performing Work Tasks

ACTIVITY		HAZARD(S) and RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
2.1	Performing window cleaning via rope access system	Non Compliance with Sky5 PPE and Safety Equipment procedures causes an incident or injury to a worker	E22	- All technicians are to have read and signed PR016 PPE and PFPE SOP prior to performing any work tasks - All technicians to have with them the minimum equipment stated in PR016 PPE and PFPE SOP as per their role and level of responsibility	L2	Supervisor ☐ All Technicians ☒ Technician ☐
2.2	Performing window cleaning via rope access system	Loose item or equipment falls from height causing injury, death or damage to property	E22	- All equipment in use is to be attached to the Technician via a lockable rated attachment - When not in use cleaning equipment is to be placed in the bucket while suspended - All equipment not in use is to be secured 3 meters from the fall edge	L3	Supervisor ☐ All Technicians ☒ Technician ☐
2.3	Performing window cleaning via rope access system	Continuous exposure to sun, heat, rain and cold temperatures causes injury or incident or heat stroke	H13	- Staff uniform is to be worn that is adequate for the conditions on the day as per the PPE and Safety Equipment Procedures - Supervisors are to ensure all technicians are provided with adequate rest breaks - If sleeves are rolled up/shorts are worn, sun screen with a minimum of SPF 50 is to be applied - Sun glasses should be worn when working if possible/practical - Sufficient water must be available throughout the day - All team members to monitor each other and work is to stop if conditions are too dangerous	L3	Supervisor ☐ All Technicians ☒ Technician ☐
2.4	Performing window cleaning via rope access system	Unauthorised access to roof area by members of the public	M9	Where possible keys are to be obtained from the building manager to enable all access doors to be locked while work is being performed	L1	Supervisor ☐ All Technicians ☒ Technician ☐
2.5	Performing window cleaning via rope access system	Debris or damage to building becomes loose and falls from height causing injury, death or damage to property	E18	All technicians are to be cautious when descending and observant to any hazards that could be present, such as decorative stones or features	L3	Supervisor ☐ All Technicians ☒ Technician ☐

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Section 2: Performing Work Tasks

ACTIVITY		HAZARD(S) and RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
2.6	Performing window cleaning via rope access system	Contact with venomous animal causes injury or illness to worker	E18	- All work areas are to be inspected thoroughly to identify any animal habitats - If any nests or hives are identified work is to cease building managers informed, and a Donesafe hazard report form completed	L5	Supervisor ☐ All Technicians ☒ Technician ☐
2.6	Performing a Rescue	Difficult or restricted access in an emergency causes a delay in a worker being rescued and emergency medical care accessing the casualty	E22	- Rescue system to be identified and discussed prior to any technician descending a rope - Preparation for either contact rescue or a pre rigged rescue must be made - First aid kit to be onsite at all times	L5	Supervisor ☒ All Technicians ☐ Technician ☐
2.7	Performing window cleaning via rope access system	Working long hours completing physically demanding work tasks causes fatigue leading to an incident or injury	E18	- Technicians to alert supervisor if they are becoming fatigued - Supervisor to monitor technicians and the conditions and implement regular breaks if concerned - Technicians to have access to water and rest facilities	L3	Supervisor ☐ All Technicians ☒ Technician ☐
2.8	Evacuation in the event of an emergency	Restricted access and egress due the high risk working environment causes a delay in evacuating the building in an emergency	E22	- Direct communication with Facilities manager to be established before work begins to test phone reception - Technicians to familiarise themselves with the emergency evacuation procedure and alarm systems - First aid kit to be present on site at all times	L5	Supervisor ☒ All Technicians ☐ Technician ☐

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Section 2: Performing Work Tasks

ACTIVITY		HAZARD(S) and RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
2.9	Performing Work tasks	Unidentified hazards causes injury or incident to occur	E18	- All technicians are to be vigilant and dynamically risk assess the changing environment - If a new hazard is identified technicians are to complete hazard report form and cease work until controls are implemented	L3	Supervisor ☐ All Technicians ☒ Technician ☐
2.10	Performing Work tasks	Technician is unable to raise the alarm in an emergency due to working alone causing severe injury or death	E24	- Lone working is not permitted while working suspended - Technicians to remain in line of sight where possible - If working out of view regular communications are to be made	L3	Supervisor ☒ All Technicians ☐ Technician ☐
2.11	Performing Work tasks	Technician makes contact with overhead power lines resulting in electrocution	E22	- Technicians to ensure they remain at least 3m away from power lines whilst working (if power lines are identified as higher than 132kv, larger exclusion zones apply) - Site Supervisor to review exclusion zone/voltage, if unsure, stop work and seek clarification	M9	Supervisor ☒ All Technicians ☐ Technician ☐
2.12	Performing Work tasks	Ropes impact with moving vehicle causing incident injury or death	E24	- Technicians and all equipment are to remain clear of all vehicles or plant - Technicians to take care on windy days, to ensure ropes don't blow on/near moving vehicles or plant by coiling or bundling ropes securely beneath them	L3	Supervisor ☐ All Technicians ☒ Technician ☐

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Section 2: Performing Work Tasks

ACTIVITY		HAZARD(S) and RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
2.13	Performing window cleaning via rope access system	High winds and deteriorating weather conditions cause the working environment to become too dangerous for work to continue	H13	- All technicians to be vigilant to the changing conditions - Site supervisor to communicate with technicians and cease all works if conditions become too dangerous - Wind speed to be recorded in Pre Start - If wind speeds are in excess of 6 on the Beaufort Scale (39-49km/h – Movement of Strong Branches) are recorded work is to cease. Unless work can be conducted safely in the lee side of the building - Watch for wind direction changes - If wind speeds are in excess of 5 on the Beaufort Scale (29-38 km/h – Movement of small trees) are recorded then work is only permitted on buildings of less than 10 storeys. Unless work can be conducted safely in the lee side of the building - Watch for wind direction changes - No matter what wind speed is recorded, if the Site Supervisor feels it is unsafe to continue working, work is to cease.	L3	Supervisor ☐ All Technicians ☒ Technician ☐

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | SAFE WORK METHOD STATEMENT

Section 3: Site Clean-up and Egress

ACTIVITY		HAZARD(S) and RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
3.1	Breaking down rope access system	Exposure to unprotected fall edge while de rigging rope access system causes technician to fall from height	E22	All Technicians are to be in full PPE and attached to a safety line when working within 3 metres of the fall edge	L2	Supervisor ☐ All Technicians ☒ Technician ☐
3.2	Cleaning and tidying work area post work tasks	Leaving litter and equipment on roof and work area causes a non-compliance with site safety procedures and potential trip hazards	H13	- All litter and equipment is to be packed away and secured once work has been completed - If leaving equipment onsite overnight, it must be in a secure area allocated by the building manager	L1	Supervisor ☐ All Technicians ☒ Technician ☐
3.3	Carrying equipment down from roof work site	Carrying equipment and large loads through building causes damage to premises or injures a member of the public	H13	- Correct manual handling techniques be used - Equipment bags are not to be over loaded, and multiple trips to be undertaken if necessary - Safe clear routes through premises to be identified and used - Exclusion zone barricades and A frame to be removed and packed away	L3	Supervisor ☐ All Technicians ☒ Technician ☐
3.4	Site access and egress	Not following sign out procedure causes a non-compliance with site safety procedures	M8	- Facilities manager to be notified once work is complete on departure - Site sign out procedure to be completed - End of Day Checklist to be completed via Donesafe	L1	Supervisor ☒ All Technicians ☐ Technician ☐

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | **SAFE WORK METHOD STATEMENT**

Identified onsite Hazards

ACTIVITY	HAZARD(S) and RISKS	RISK RATING	RISK CONTROL(S)	RESIDUAL RISK	PERSON RESPONSIBLE
Break job down into discrete steps Each step should accomplish some major task and be in a logical sequence.	Identify the hazards associated with each step, and examine each to identify possibilities that could lead to an accident.	Refer to the Risk Matrix	Consider number of people required to carry out a task, training, skills and competencies required, licences, permits, etc., environmental controls, plant, tools and equipment, safety equipment and PPE, etc.	Refer to Risk Matrix	List persons responsible for this.

Amendments to workers present on site

On site role and responsibilities	Name	Qualifications	Current	
Site Supervisor			☐ Yes	☐ No
First Aid officer		Provide First Aid	☐ Yes	☐ No
Technician		IRATA/SPRAT Technician	☐ Yes	☐ No
Technician		IRATA/SPRAT Technician	☐ Yes	☐ No

JOB SAFETY AND ENVIRONMENTAL ANALYSIS | **SAFE WORK METHOD STATEMENT**

Attached Relevant Documentation (Include copies of SDSs, and specific Emergency Procedures and Rescue Plans)

No.	TYPE	DETAILS	DATE
PR016	Procedure	PPE and PFPE SOP	
PR018	Procedure	Incident Response Procedure	
PR021	Procedure	Rescue plan	

EMPLOYEE ACKNOWLEDGEMENT

This SWMS has been developed in consultation and cooperation with workers and relevant Persons Conducting Business or Undertaking (PCBU).
 I have read the above SWMS and I understand its contents.
 I can confirm that I have the skills and training including relevant certification to conduct the task as described.
 I agree to comply with safety requirements within this SWMS including safe work instructions and Personal Protective Equipment described.

Worker's name	Role/Responsibility	Site Induction Completed	Sign	Date	Time
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			

Facilities Manager Name:		Signature:		Date:	
--------------------------	--	------------	--	-------	--

Review No.	12	13	14	15	16	17	18	19	20	21	22	23
Initials	ZJ	ZJ	ZJ	ZJ								
Date	15/09/21	22/03/22	05/09/22	10/03/23								



JOB SAFETY AND ENVIRONMENTAL ANALYSIS | **SAFE WORK METHOD STATEMENT**

Worker's name	Role/Responsibility	Site Induction Completed	Sign	Date	Time
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			
		☐ Yes ☐ No			