

# Package ‘imotionsApi’

October 25, 2021

**Type** Package

**Title** iMotions Data Library

**Version** 2.1.3

**Date** 2020-04-16

**Author** Amandine Grappe, Paolo Masulli

**Maintainer** iMotions <support@imotions.com>

**Description** Provides functions to access your iMotions studies.

**Copyright** iMotions

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 3.2.2)

**Imports** jsonlite (>= 1.5),  
httr (>= 1.2.1),  
data.table (>= 1.12.8),  
arrow (>= 0.16.0),  
tidyselect,  
tidyr,  
dplyr,  
methods,  
purrr,  
stringr

**Suggests** testthat (>= 1.0.2),  
stubthat (>= 1.2.0),  
mockr (>= 0.1),  
lintr (>= 1.0.0),  
knitr,  
markdown,  
rmarkdown

**URL** <https://imotions.com>,  
<https://my.imotions.com/#studies>

**RoxygenNote** 7.1.1

**VignetteBuilder** knitr

## R topics documented:

imotionsApi-package . . . . .	2
convertRecordingTsToIntervals . . . . .	3
createExport . . . . .	4
getAOI . . . . .	4
getAOIRespondentData . . . . .	5
getAOIRespondentMetrics . . . . .	6
getAOIs . . . . .	7
getRespondent . . . . .	8
getRespondentIntervals . . . . .	9
getRespondents . . . . .	10
getRespondentSensors . . . . .	11
getSegment . . . . .	12
getSegments . . . . .	12
getSensorData . . . . .	13
getSensorMetaData . . . . .	14
getStimuli . . . . .	14
getStimulus . . . . .	15
imConnection . . . . .	16
imStudy . . . . .	16
listLoadedStudies . . . . .	17
listStudies . . . . .	18
privateAOIFiltering.imRespondent . . . . .	18
truncateSignalsByIntervals . . . . .	19
unloadStudies . . . . .	20
uploadAOIRespondentMetrics . . . . .	20
uploadSensorData . . . . .	21
<b>Index</b>	<b>23</b>

---

imotionsApi-package	<i>iMotions R API package</i>
---------------------	-------------------------------

---

## Description

A client for accessing data from the iMotions Biometrics Research Platform.

## Details

Use tokens (found on a study's R Analysis page) to load information from the iMotions API

## See Also

Useful links:

- <https://imotions.com>
- <https://my.imotions.com/#studies>

## Examples

```
myToken <- "xxxxx-xxxx-xxxxx-xxxxx"
connection <- motionsApi::imConnection(myToken)
```

---

```
convertRecordingTsToIntervals
```

*Convert recording's timestamps (relative to data recording start) into stimulus/scene/AOI timestamps (relative to the interval first fragment start). Fragments are concatenated to give new array of timestamps in range [0, concatenated duration of stimulus/scene/AOI].*

---

## Description

Timestamps falling between an interval start/end will be kept, others will be discarded.

## Usage

```
convertRecordingTsToIntervals(recordingTs, intervals)
```

## Arguments

recordingTs	An array of recording's timestamps (relative to data recording start). Scalar, imSignals object as returned by <a href="#">getSensorData</a> or data.table with a column Timestamp are also accepted.
intervals	An imInterval or imIntervalList object with start/end of a stimulus/scene/AOI as given by <a href="#">getRespondentIntervals</a> or <a href="#">getAOIRespondentData</a> .

## Value

A new array/scalar/data.table with timestamps in range [0, concatenated duration of stimulus/scene/AOI].

## Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
respondents <- imotionsApi::getRespondents(study)
sensors <- imotionsApi::getRespondentSensors(study, respondents[1, ])
signals <- imotionsApi::getSensorData(study, sensors[3, ])
intervals <- imotionsApi::getRespondentIntervals(study, respondents[1, ])

# get a new signal with timestamps in range [0, concatenated duration of stimulus/scene/AOI].
signals <- imotionsApi::convertRecordingTsToIntervals(signals, intervals[1, ])

## End(Not run)
```

---

createExport	<i>Create an export file at a specific location and append metadata to it if provided. Note that a column with the study name will be appended to each export.</i>
--------------	--

---

### Description

Create an export file at a specific location and append metadata to it if provided. Note that a column with the study name will be appended to each export.

### Usage

```
createExport(study, data, outputDirectory, fileName, metadata = NULL)
```

### Arguments

study	An imStudy object as returned from <a href="#">imStudy</a> .
data	A data.table containing the export metrics to save.
outputDirectory	The path where the file should be created.
fileName	The name of the file to create (should finish with .csv).
metadata	Optional - a data.table with metadata information. Column names will be converted to metadata headers and there must be a row corresponding to each data column.

### Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
data <- data.frame("Respondent Name" = "Test", "Metric1" = seq(1:100), "Metric2" = rep(0, 100))
createExport(study, data, outputDirectory = "C:/Documents", fileName = "textExport.csv")

# Adding some metadata to the data
metadata <- data.table("Units" = c("", "ms", ""), "Description" = c("Desc1", "Desc2", "Desc"))
createExport(study, data, outputDirectory = "C:/Documents", fileName = "textExport.csv", metadata)

## End(Not run)
```

---

getAOI	<i>Get a specific AOI from a study.</i>
--------	---

---

### Description

Available AOIs can be found with [getAOIs](#). In case no AOI is found, return NULL.

### Usage

```
getAOI(study, AOIId)
```

**Arguments**

study	An imStudy object as returned from <a href="#">imStudy</a> .
AOIId	The id of the AOI you would like to retrieve.

**Value**

An imAOI object (data.table) containing the AOI of interest.

**Examples**

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
AOIs <- imotionsApi::getAOIs(study)
AOI <- imotionsApi::getAOI(study, AOIs$id[1])

## End(Not run)
```

---

getAOIRespondentData	<i>Get the inOutGaze information, inOutMouseClicked information and AOI's intervals for a specific AOI/respondent combination. Note that imAOI object, by definition, are linked to a specific stimulus.</i>
----------------------	--

---

**Description**

The inOutGaze data.table has a IsGazeInAOI column that is TRUE when a gaze was recorded inside the AOI and FALSE if outside (timestamps correspond to the actual gazepoint Timestamp). To reduce the size of the file created, only timestamps where a change of value occur are given. If the AOI was never active, the table is empty.

**Usage**

```
getAOIRespondentData(study, AOI, respondent)
```

**Arguments**

study	An imStudy object as returned from <a href="#">imStudy()</a>
AOI	An imAOI object as returned from <a href="#">getAOIs</a> .
respondent	An imRespondent object as returned from <a href="#">getRespondents</a> .

**Details**

The inOutMouseClicked data.table has a IsMouseInAOI column that is TRUE when a click was recorded inside the AOI and FALSE if outside (timestamps correspond to the actual Timestamp of each click). If no click was recorded or if the AOI was never active, the table is empty.

**Value**

A list with inOutGaze/inOutMouseClicked information for the specific AOI/respondent combination and an imIntervalList object (data.table) composed of the start, end, duration, id and name of this AOI.

**Examples**

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
AOIs <- imotionsApi::getAOIs(study)
respondents <- imotionsApi::getRespondents(study, AOI = AOIs[1, ])
AOIData <- imotionsApi::getAOIRespondentData(study, AOIs[1, ], respondents[1, ])

# Retrieving list items
inOutData <- AOIData$inOutData
intervals <- AOIData$intervals

## End(Not run)
```

---

getAOIRespondentMetrics

*Get the metrics for a specific AOI/respondent combination.*

---

**Description**

Get the metrics for a specific AOI/respondent combination.

**Usage**

```
getAOIRespondentMetrics(study, AOI, respondent)
```

**Arguments**

study	An imStudy object as returned from imStudy()
AOI	An imAOI object as returned from <a href="#">getAOIs</a> .
respondent	An imRespondent object as returned from <a href="#">getRespondents</a> .

**Value**

A data.table of one row (imMetrics object) with metrics for the AOI /respondent combination of interest.

**Examples**

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
AOIs <- imotionsApi::getAOIs(study)
respondents <- imotionsApi::getRespondents(study, AOI = AOIs[1, ])
AOImetrics <- imotionsApi::getAOIRespondentMetrics(study, AOIs[1, ], respondents[1, ])

## End(Not run)
```

---

getAOIs	<i>Get AOIs from a study.</i>
---------	-------------------------------

---

## Description

Generic getAOIs function that takes as parameter a study object and optionally a respondent/stimulus object. In case no AOIs is defined for the combination, return NULL.

## Usage

```
getAOIs(study, stimulus = NULL, respondent = NULL, generateInOutFiles = FALSE)
```

## Arguments

study	An imStudy object as returned from <a href="#">imStudy</a> .
stimulus	Optional - An imStimulus object as returned from <a href="#">getStimuli</a> .
respondent	Optional - An imRespondent object as returned from <a href="#">getRespondents</a> .
generateInOutFiles	A boolean indicating whether the corresponding InOut files should be generated and linked to each imAOI object.

## Details

Important to note: to speed up the computation of gazes falling in/out AOIs at the respondent/stimulus level, an optional parameter generateInOutFiles can be enabled (both stimulus AND respondent arguments need to be provided). When enabled, a file will be generated for each AOI of this stimulus/respondent combination containing information regarding AOI activation/deactivation and gazes/clicks falling in. Filepaths to these newly generated files will be stored in their corresponding AOI object. If available, these filepaths will then directly be used by the [getAOIRespondentData](#) function instead of re-generating the files. This is particularly useful in case multiple AOIs are defined for the same stimulus.

## Value

An imAOIList object (data.table) with all AOIs of interest.

## Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
stimuli <- imotionsApi::getStimuli(study)
respondents <- imotionsApi::getRespondents(study)

## Get all AOIs in the study
AOIs <- imotionsApi::getAOIs(study)

## Get all AOIs defined for a specific stimulus
AOIs <- imotionsApi::getAOIs(study, stimulus = stimuli[1, ])

## Get all AOIs defined for a specific respondent
```

```

AOIs <- imotionsApi::getAOIs(study, respondent = respondents[1, ])

## Get all AOIs defined for a specific stimulus/respondent combination
AOIs <- imotionsApi::getAOIs(study, respondent = respondents[1, ], stimulus = stimuli[1, ])

## Get all AOIs defined for a specific stimulus/respondent combination and process their InOut data
AOIs <- imotionsApi::getAOIs(study, respondent = respondents[1, ], stimulus = stimuli[1, ],
                             generateInOutFiles = T)

print(AOIs$fileId) # a field "fileId" should have been added with the path to the InOut file

## End(Not run)

```

---

getRespondent	<i>Get a specific respondent from a study.</i>
---------------	--

---

## Description

Available respondents can be found with [getRespondents](#).

## Usage

```
getRespondent(study, respondentId)
```

## Arguments

study	An imStudy object as returned from <a href="#">imStudy</a> .
respondentId	The id of the respondent you would like to retrieve.

## Value

An imRespondent object (data.table) containing the respondent of interest.

## Examples

```

## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
respondents <- imotionsApi::getRespondents(study)
respondent <- imotionsApi::getRespondent(study, respondents$id[1])

## End(Not run)

```



---

getRespondentIntervals

*Get the list of time intervals (imIntervalList) for a given respondent.*


---

## Description

This imIntervalList is composed of stimuli/scenes/annotations intervals. Note that AOIs intervals can be retrieved using [getAOIRespondentData](#).

## Usage

```
getRespondentIntervals(
  study,
  respondent,
  type = c("Stimulus", "Scene", "Annotation")
)
```

## Arguments

study	An imStudy object as returned from <a href="#">imStudy</a> .
respondent	An imRespondent object as returned from <a href="#">getRespondents</a> .
type	The type of intervals to retrieve (can be set to Stimulus, Scene and/or Annotation).

## Value

An imIntervalList object (data.table) composed of the start, end, duration, parent stimulus, id and name of each stimulus/scene/annotation. Annotations comments are also included.

## Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
respondents <- imotionsApi::getRespondents(study)
intervals <- imotionsApi::getRespondentIntervals(study, respondents[1, ])

# Get only the stimuli intervals
intervals <- imotionsApi::getRespondentIntervals(study, respondents[1, ], type = "Stimulus")

## End(Not run)
```

---

getRespondents	<i>Get respondents from a study.</i>
----------------	--------------------------------------

---

## Description

Generic getRespondents function that takes as parameter a study object and optionally a stimulus/AOI/segment object. As AOIs are linked to a stimulus, it is not possible to provide both of them.

## Usage

```
getRespondents(
  study,
  stimulus = NULL,
  AOI = NULL,
  segment = NULL,
  keepRespondentVariables = FALSE
)
```

## Arguments

study	An imStudy object as returned from <a href="#">imStudy</a> .
stimulus	Optional - An imStimulus object as returned from <a href="#">getStimuli</a> .
AOI	Optional - An imAOI object as returned from <a href="#">getAOIs</a> .
segment	Optional - An imSegment object as returned from <a href="#">getSegments</a> .
keepRespondentVariables	Optional - A boolean indicating whether respondent variables should be kept (if they are available). If this has the default value of FALSE, only the "group" variable is exposed.

## Value

An imRespondentList object (data.table) with all respondents of interest.

## Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
stimuli <- imotionsApi::getStimuli(study)
segments <- imotionsApi::getSegments(study)
AOIs <- imotionsApi::getAOIs(study)

## Get all respondents in the study
respondents <- imotionsApi::getRespondents(study)

## Get all respondents exposed to a specific stimulus
respondents <- imotionsApi::getRespondents(study, stimulus = stimuli[1, ])

## Get all respondents in a specific segment
```

```

respondents <- imotionsApi::getRespondents(study, segment = segments[1, ])

## Get all respondents for whom a specific AOI has been defined
respondents <- imotionsApi::getRespondents(study, AOI = AOIs[1, ])

## Get all respondents in a specific segment exposed to a specific stimulus
respondents <- imotionsApi::getRespondents(study, stimulus = stimuli[1, ], segment = segments[1, ])

## Get all respondents in a specific segment for whom a specific AOI has been defined
respondents <- imotionsApi::getRespondents(study, AOI = AOIs[1, ], segment = segments[1, ])

## Get all respondents in the study and access their available variables
respondents <- imotionsApi::getRespondents(study, keepRespondentVariables = TRUE)

## End(Not run)

```

---

getRespondentSensors    *Get all sensors available for a given respondent.*

---

## Description

Retrieves detailed information about sensors available for a given respondent.

## Usage

```
getRespondentSensors(study, respondent, stimulus = NULL)
```

## Arguments

study	An imStudy object as returned from <a href="#">imStudy</a> .
respondent	An imRespondent object as returned from <a href="#">getRespondents</a> .
stimulus	Optional - an imStimulus object as returned from <a href="#">getStimuli</a> to retrieve sensors specific to this stimulus.

## Value

An imSensorList object (data.table) with all sensors collected for the respondent of interest.

## Examples

```

## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
respondents <- imotionsApi::getRespondents(study)
sensors <- imotionsApi::getRespondentSensors(study, respondents[1, ])

# Get sensors for a specific stimulus
stimuli <- imotionsApi::getStimuli(study)
sensors <- imotionsApi::getRespondentSensors(study, respondents[1, ], stimuli[1, ])

## End(Not run)

```

---

getSegment	<i>Get a specific segment from a study.</i>
------------	---

---

**Description**

Available segments can be found with [getSegments](#).

**Usage**

```
getSegment(study, segmentId)
```

**Arguments**

study	An imStudy object as returned from <a href="#">imStudy</a> .
segmentId	The id of the segment you would like to retrieve.

**Value**

An imSegment object (data.table) containing the segment of interest.

**Examples**

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
segments <- imotionsApi::getSegments(study)
segment <- imotionsApi::getSegment(study, segments$id[1])

## End(Not run)
```

---

getSegments	<i>Get all segments from a study.</i>
-------------	---------------------------------------

---

**Description**

Retrieves detailed information about segments in the study.

**Usage**

```
getSegments(study)
```

**Arguments**

study	An imStudy object as returned from <a href="#">imStudy</a> .
-------	--

**Value**

An imSegmentList object (data.table) containing all segments from the study.

## Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
segments <- imotionsApi::getSegments(study)

## End(Not run)
```

---

getSensorData	<i>Download data corresponding to a specific sensor (signals/metrics).</i>
---------------	--

---

## Description

Available sensors in your study can be listed using the [getRespondentSensors](#).

## Usage

```
getSensorData(study, sensor, signalsName = NULL, intervals = NULL)
```

## Arguments

study	An imStudy object as returned from <a href="#">imStudy</a> .
sensor	An imSensor object as returned from <a href="#">getRespondentSensors</a> .
signalsName	Optional - A vector of specific signals name you would like to return.
intervals	Optional - An imInterval or imIntervalList object with start/end of data to subset as given by <a href="#">getRespondentIntervals</a> .

## Details

Signals always have a "Timestamp" column and are unique to a given respondent and a given sensor source. Metrics are stored as a special sensor, also specific to a given respondent.

## Value

An imData object (data.table) containing the signals (imSignals) or metrics (imMetrics) for the sensor of interest.

## Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
respondents <- imotionsApi::getRespondents(study)
sensors <- imotionsApi::getRespondentSensors(study, respondents[1, ])
data <- imotionsApi::getSensorData(study, sensors[1, ])

## End(Not run)
```

---

getSensorMetaData	<i>Download metadata corresponding to a specific sensor (sensor and signals metadata).</i>
-------------------	--

---

### Description

Available sensors in your study can be listed using the [getRespondentSensors](#).

### Usage

```
getSensorMetaData(sensor)
```

### Arguments

sensor                      An imSensor object as returned from [getRespondentSensors](#).

### Details

Metadata contains sensor metadata and signal metadata

### Value

A list of two data frames containing respectively the sensor and the signals metadata.

### Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
respondents <- imotionsApi::getRespondents(study)
sensors <- imotionsApi::getRespondentSensors(study, respondents[1, ])
metadata <- imotionsApi::getSensorMetaData(study, sensors[1, ])

## End(Not run)
```

---

getStimuli	<i>Get all stimuli from a study.</i>
------------	--------------------------------------

---

### Description

Retrieves detailed information about stimuli in the study.

### Usage

```
getStimuli(study, respondent = NULL, relevant = TRUE)
```

**Arguments**

study	An imStudy object as returned from <a href="#">imStudy</a> .
respondent	Optional - An imRespondent object as returned from <a href="#">getRespondents</a> .
relevant	A boolean indicating whether only relevant stimuli should be kept, by default non-relevant stimuli are discarded.

**Value**

An imStimulusList object (data.table) containing all stimuli from the study.

**Examples**

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
respondents <- imotionsApi::getRespondents(study)

## Get all stimuli in the study
stimuli <- imotionsApi::getStimuli(study)

## Get all stimuli for a specific respondent
stimuli <- imotionsApi::getStimuli(study, respondents[1, ])

## End(Not run)
```

---

getStimulus

*Get a specific stimulus from a study.*

---

**Description**

Available stimuli can be found with [getStimuli](#).

**Usage**

```
getStimulus(study, stimulusId)
```

**Arguments**

study	An imStudy object as returned from <a href="#">imStudy</a> .
stimulusId	The id of the stimulus you would like to retrieve.

**Value**

An imStimulus object (data.table) containing the stimulus of interest.

**Examples**

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
stimuli <- imotionsApi::getStimuli(study)
stimulus <- imotionsApi::getStimulus(study, stimuli$id[1])

## End(Not run)
```

---

imConnection

---

*Create a connection with the iMotions API.*


---

**Description**

Tokens can be found on a study's R Analysis page or given directly by the iMotions software

**Usage**

```
imConnection(token, baseUrl = "https://my.imotions.com/api")
```

**Arguments**

token	The token to be used for authentication.
baseUrl	The iMotions server to connect to, normally you do not need to change the default.

**Value**

An imConnection object to be passed to other methods.

**Examples**

```
## Not run:
myToken <- "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx"
connection <- imotionsApi::imConnection(myToken)

## End(Not run)
```

---

imStudy

---

*Load an iMotions study by id.*


---

**Description**

Retrieves detailed information about a study including stimuli, respondents, segments, and more.

**Usage**

```
imStudy(connection, studyId)
```



### Arguments

connection	An imConnection object as returned from <a href="#">imConnection</a> .
studyId	The id of the study you would like to retrieve.

### Details

Available studies can be found with [listStudies](#).

### Value

An imStudy object to be passed to other methods.

### Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
studyId <- studies$id[1]
study <- imotionsApi::imStudy(connection, studyId)

## End(Not run)
```

---

listLoadedStudies	<i>List studies that have been loaded in the current session.</i>
-------------------	---

---

### Description

More detailed information about a study can be retrieved using [imStudy](#).

### Usage

```
listLoadedStudies()
```

### Value

A list of the studies that have been loaded in the current session.

### Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
studyId <- studies$id[1]
study <- imotionsApi::imStudy(connection, studyId)
listLoadedStudies()

## End(Not run)
```

---

listStudies	<i>List available studies.</i>
-------------	--------------------------------

---

### Description

More detailed information about a study can be retrieved using [imStudy](#).

### Usage

```
listStudies(connection)
```

### Arguments

connection      An imConnection object as returned from [imConnection](#).

### Value

A data frame containing names and ids of studies.

### Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)

## End(Not run)
```

---

privateAOIFiltering.imRespondent	<i>Get AOIs for a specific respondent.</i>
----------------------------------	--

---

### Description

S3 method to get all AOIs for a specific respondent.

### Usage

```
## S3 method for class 'imRespondent'
privateAOIFiltering(study, stimulus = NULL, respondent)
```

### Arguments

study            An imStudy object as returned from [imStudy](#).  
stimulus        Optional - An imStimulus object as returned from [getStimuli](#).  
respondent      An imRespondent object as returned from [getRespondents](#) for which you want to get the AOIs.

### Value

A data.table with all AOIs defined for a specific respondent.

---

truncateSignalsByIntervals

*Truncate signals data based on given intervals.*


---

## Description

Any interval combination can be asked. Timestamps falling between an interval start/end will be kept, others will be discarded. If dropIntervals is set to TRUE, Timestamps falling between an interval start/end will be discarded.

## Usage

```
truncateSignalsByIntervals(signals, intervals, dropIntervals = FALSE)
```

## Arguments

signals	An imSignals object as returned by <a href="#">getSensorData</a> or a data.table including a "Timestamp" column that needs to be cut.
intervals	An imInterval or imIntervalList object with start/end of data to subset as given by <a href="#">getRespondentIntervals</a> or <a href="#">getAOIRespondentData</a> .
dropIntervals	A boolean indicating whether Timestamps falling between an interval start/end should be discarded, by default there are kept and other Timestamps are removed.

## Value

A truncated imSignals object.

## Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
respondents <- imotionsApi::getRespondents(study)
sensors <- imotionsApi::getRespondentSensors(study, respondents[1, ])
signals <- imotionsApi::getSensorData(study, sensors[3, ])
intervals <- imotionsApi::getRespondentIntervals(study, respondents[1, ])

# get the 3 first intervals
dataSubset <- imotionsApi::truncateSignalsByIntervals(signals, intervals[1:3, ])

# remove the second interval
dataSubset <- imotionsApi::truncateSignalsByIntervals(signals, intervals[2, ], dropIntervals = TRUE)

## End(Not run)
```

---

unloadStudies	<i>Remove studies that have been loaded in the current session.</i>
---------------	---

---

### Description

This function can be used when new changes have been made to already loaded studies.

### Usage

```
unloadStudies()
```

### Value

"Studies successfully removed from the current session" if success.

### Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
studyId <- studies$id[1]
study <- imotionsApi::imStudy(connection, studyId)
unloadStudies()

## End(Not run)
```

---

uploadAOIRespondentMetrics	<i>Upload metrics for a specific respondent and AOI in a study.</i>
----------------------------	---

---

### Description

Upload metrics for a specific respondent and AOI in a study.

### Usage

```
uploadAOIRespondentMetrics(study, AOI, respondent, metrics)
```

### Arguments

study	An imStudy object as returned from <code>imStudy()</code>
AOI	An imAOI object as returned from <a href="#">getAOIs</a> .
respondent	An imRespondent object as returned from <a href="#">getRespondents</a> .
metrics	A data.table containing the metrics to upload.

## Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
AOIs <- imotionsApi::getAOIs(study)
respondents <- imotionsApi::getRespondents(study, AOI = AOIs[1, ])
metrics <- data.frame("metric1" = 2, "metric2" = 234, "metric3" = 1234)
uploadAOIRespondentMetrics(study, AOIs[1, ], respondents[1, ], metrics)

## End(Not run)
```

---

uploadSensorData	Create a new sensor for a specific respondent in a study.
------------------	---

---

## Description

Either signals (with a Timestamp column) or metrics (single values, with no Timestamp) can be uploaded. After processing, the sensor can then be viewed and exported locally through the iMotions Desktop.

## Usage

```
uploadSensorData(
  params,
  study,
  data,
  target,
  sensorName,
  scriptName,
  metadata = NULL,
  stimulus = NULL
)
```

## Arguments

params	The list of parameters provided to the script - specific parameters value will be stored as metadata.
study	An imStudy object as returned from <a href="#">imStudy</a> .
data	A data.table containing the signals/metrics to upload (imData object are also accepted).
target	The target respondent for the sensor (an imRespondent object as returned from <a href="#">getRespondents</a> ).
sensorName	The name of the new sensor you would like to create.
scriptName	The name of the script used to produce these signals/metrics.
metadata	Optional - a data.table with metadata information. Column names will be converted to metadata headers and there must be a row corresponding to each data column.
stimulus	Optional - an imStimulus object as returned from <a href="#">getStimuli</a> to upload data specific to this stimulus.

## Details

Params required field are "iMotionsVersion" and "flowName" (flow name will be use as "instance" of the new sensor)

## Examples

```
## Not run:
connection <- imotionsApi::imConnection("xxxxxxx")
studies <- imotionsApi::listStudies(connection)
study <- imotionsApi::imStudy(connection, studies$id[1])
respondents <- imotionsApi::getRespondents(study)
data <- data.frame("Timestamp" = seq(1:100), "Thresholded value" = rep(0, 100))
params <- list("iMotionsVersion" = 8, "flowName" = "Test")
uploadSensorData(params, study, data, respondents[1, ], sensorName = "New sensor",
  scriptName = "Example Script")

# Uploading data to a specific stimulus
stimuli <- imotionsApi::getStimuli(study)
uploadSensorData(params, study, data, respondents[1, ], sensorName = "New sensor",
  scriptName = "Example Script", stimulus = stimuli[1, ])

# Adding some metadata to the data
metadata <- data.table("Units" = c("ms", ""), "Show" = c("FALSE", "TRUE"))
uploadSensorData(params, study, data, respondents[1, ], sensorName = "New sensor",
  scriptName = "Example Script", metadata)
```

## End(Not run)

# Index

convertRecordingTsToIntervals, 3  
createExport, 4

getAOI, 4  
getAOIRespondentData, 3, 5, 7, 9, 19  
getAOIRespondentMetrics, 6  
getAOIs, 4–6, 7, 10, 20  
getRespondent, 8  
getRespondentIntervals, 3, 9, 13, 19  
getRespondents, 5–9, 10, 11, 15, 18, 20, 21  
getRespondentSensors, 11, 13, 14  
getSegment, 12  
getSegments, 10, 12, 12  
getSensorData, 3, 13, 19  
getSensorMetaData, 14  
getStimuli, 7, 10, 11, 14, 15, 18, 21  
getStimulus, 15

imConnection, 16, 17, 18  
imotionsApi (imotionsApi-package), 2  
imotionsApi-package, 2  
imStudy, 4, 5, 7–13, 15, 16, 17, 18, 21

listLoadedStudies, 17  
listStudies, 17, 18

privateAOIFiltering.imRespondent, 18

truncateSignalsByIntervals, 19

unloadStudies, 20  
uploadAOIRespondentMetrics, 20  
uploadSensorData, 21