

Multi PCSM

IEC

Easy maintenance.


Integrated MV solution in the same enclosure.

Up to 4 independent DC inputs.

Advanced grid support.

Compatible with all battery technologies.






REFERENCES	FP5150MH2	FP5150MH4	FP5151MH2	FP5151MH4	
AC	AC Output Power (kVA/kW) @30 °C ^[1]	5360			
	AC Output Power (kVA/kW) @35 °C ^[1]	5150			
	AC Output Power (kVA/kW) @40 °C ^[1]	4940			
	AC Output Power (kVA/kW) @50 °C ^[1]	4520			
	Operating Grid Voltage (kV)	34.5 kV ±10%	33 kV ±10%		
	Rated Impulse Withstand Voltage	145 kV	150 kV		
	Operating Grid Frequency (Hz)	60 Hz	50 Hz		
	Current Harmonic Distortion (THDi)	< 3% per IEEE 519			
	Power Factor (CosPhi) ^[2]	0.5 leading ... 0.5 lagging			
	Reactive Power Compensation	Four quadrant operation			
	Overload Capability	166% - 100 ms / 150% - 5 s / 120% - 8 s / 110% - 15 s			
DC	DC Voltage Range ^[3]	1019 V – 1500 V			
	Maximum DC Voltage	1500 V			
	DC Voltage Ripple	< 3%			
	Max. DC Continuous Current (A)	2684	1342	2684	1342
	Max. DC Short Circuit Current per Input (kA)	500 kA with a time constant of 1 ms			
	Battery Technology	All type of batteries (BMS required)			
	Number of Separated DC Inputs	2	4	2	4
EFFICIENCY & AUX. SUPPLY	Efficiency (Max) (η)	98.00% including MV transformer			
	CEC (η)	97.53% including MV transformer			
CABINET	Dimensions [WxDxH] (ft)	21.3 x 6.5 x 7.5			
	Dimensions [WxDxH] (m)	6.5 x 2.0 x 2.3			
	Weight (lbs)	30865			
	Weight (kg)	14000			
	Type of Ventilation	Forced air cooling			
ENVIRONMENT	Degree of Protection	IP55			
	Operating Temperature Range ^[4]	From -40 °C to +60 °C, >30 °C power derating			
	Operating Relative Humidity Range	From 4% to 100%			
	Storage Temperature Range	From -40 °C to +60 °C			
	Max. Altitude (above sea level) ^[5]	2000 m			
CONTROL	Communication Protocol	Modbus TCP			
	Grid Forming (VISMA) / Black Start Capable	Standard			
PROTECTIONS	Ground Fault Protection	Insulation monitoring device			
	Humidity Control	Active heating			
	General AC Protection & Disconnection	36 kV MV switchgear (2L+V)			
	General DC Protection & Disconnection	High-speed fuses, Motorized DC disconnect switches ^[6]			
	Overvoltage Protection	Type II for AC and Type I+II for DC			
STANDARDS	Safety	IEC 62109-1 / IEC 62109-2 / IEC 62477-1 / IEC 62477-2			
	Utility Interconnect ^[7]	IEC 62116 / G99 / VDE 4110-4120-4130 / CEI 0-16 / NTS 2.1 / EN 50549			

NOTES

- [1] Values at 1.00-Vac nom and CosPhi=1. Consult Power Electronics for derating curves.
[2] Consult P-Q charts available: $Q(kVar) = \sqrt{(S(kVA))^2 - P(kW)^2}$.
[3] Consult Power Electronics for derating curves. In the event of overvoltage in the grid, the minimum DC voltage will vary proportionally with the AC voltage.
[4] Optional available for temperatures below -25 °C.
[5] Consult Power Electronics for altitudes above 1000 m.
[6] Battery short circuit disconnection must be done on the battery side.
[7] Consult Power Electronics for other applicable standards / grid codes.



REFERENCES	FP5152MH2	FP5152MH4	FP5156MH2	FP5156MH4	
AC	AC Output Power (kVA/kW) @30 °C ^[1]		5360		
	AC Output Power (kVA/kW) @35 °C ^[1]		5150		
	AC Output Power (kVA/kW) @40 °C ^[1]		4940		
	AC Output Power (kVA/kW) @50 °C ^[1]		4520		
	Operating Grid Voltage (kV)	30 kV ±10%	33 kV ±10%		
	Rated Impulse Withstand Voltage	145 kV	150 kV		
	Operating Grid Frequency (Hz)	50 Hz	60 Hz		
	Current Harmonic Distortion (THDi)	< 3% per IEEE 519			
	Power Factor (CosPhi) ^[2]	0.5 leading ... 0.5 lagging			
	Reactive Power Compensation	Four quadrant operation			
	Overload Capability	166% - 100 ms / 150% - 5 s / 120% - 8 s / 110% - 15 s			
DC	DC Voltage Range ^[3]		1019 V – 1500 V		
	Maximum DC Voltage		1500 V		
	DC Voltage Ripple		< 3%		
	Max. DC Continuous Current (A)	2684	1342	2684	1342
	Max. DC Short Circuit Current per Input (kA)		500 kA with a time constant of 1 ms		
	Battery Technology		All type of batteries (BMS required)		
	Number of Separated DC Inputs	2	4	2	4
EFFICIENCY & AUX. SUPPLY	Efficiency (Max) (η)		98.00% including MV transformer		
	CEC (η)		97.53% including MV transformer		
CABINET	Dimensions [WxDxH] (ft)		21.3 x 6.5 x 7.5		
	Dimensions [WxDxH] (m)		6.5 x 2.0 x 2.3		
	Weight (lbs)		30865		
	Weight (kg)		14000		
	Type of Ventilation		Forced air cooling		
	ENVIRONMENT	Degree of Protection		IP55	
Operating Temperature Range ^[4]		From -40 °C to +60 °C, >30 °C power derating			
Operating Relative Humidity Range		From 4% to 100%			
Storage Temperature Range		From -40 °C to +60 °C			
Max. Altitude (above sea level) ^[5]		2000 m			
CONTROL	Communication Protocol		Modbus TCP		
	Grid Forming (VISMA) / Black Start Capable		Standard		
PROTECTIONS	Ground Fault Protection		Insulation monitoring device		
	Humidity Control		Active heating		
	General AC Protection & Disconnection		36 kV MV switchgear (2L+V)		
	General DC Protection & Disconnection		High-speed fuses, Motorized DC disconnect switches ^[6]		
	Overvoltage Protection		Type II for AC and Type I+II for DC		
STANDARDS	Safety		IEC 62109-1 / IEC 62109-2 / IEC 62477-1 / IEC 62477-2		
	Utility Interconnect ^[7]		IEC 62116 / G99 / VDE 4110-4120-4130 / CEI 0-16 / NTS 2.1 / EN 50549		

NOTES

- [1] Values at 1.00-Vac nom and CosPhi=1. Consult Power Electronics for derating curves.
[2] Consult P-Q charts available: $Q(kVar) = \sqrt{(S(kVA))^2 - P(kW)^2}$.
[3] Consult Power Electronics for derating curves. In the event of overvoltage in the grid, the minimum DC voltage will vary proportionally with the AC voltage.
[4] Optional available for temperatures below -25 °C.
[5] Consult Power Electronics for altitudes above 1000 m.
[6] Battery short circuit disconnection must be done on the battery side.
[7] Consult Power Electronics for other applicable standards / grid codes.