


---

**Easy maintenance.**  
**Integrated MV solution in the same enclosure.**  
**Advanced grid support.**  
**Compatible with all battery technologies.**






| REFERENCES      |                                                 | FP4010M                                                | FP4105M                         |
|-----------------|-------------------------------------------------|--------------------------------------------------------|---------------------------------|
| AC              | AC Output Power (kVA/kW) @40°C <sup>[6]</sup>   | 4010                                                   | 4105                            |
|                 | AC Output Power (kVA/kW) @50°C <sup>[6]</sup>   | 3720                                                   | 3810                            |
|                 | Operating Grid Voltage (kV)                     | 34.5 kV ±10%                                           |                                 |
| DC              | DC Voltage Range <sup>[7]</sup>                 | 891 V - 1500 V                                         | 913 V - 1500 V                  |
| EFFICIENCY      | Efficiency (Max) (η)                            | 97.91% including MV transformer                        | 97.93% including MV transformer |
|                 | CEC (η)                                         | 97.49% including MV transformer                        | 97.50% including MV transformer |
| COMMON FEATURES |                                                 |                                                        |                                 |
| AC              | Operating Grid Frequency (Hz)                   | 60 Hz                                                  |                                 |
|                 | Current Harmonic Distortion (THDi)              | < 3% per IEEE519                                       |                                 |
|                 | Power Factor (CosPhi) <sup>[1]</sup>            | 0.5 leading ... 0.5 lagging                            |                                 |
|                 | Reactive Power Compensation                     | Four quadrant operation                                |                                 |
|                 | Overload Capability <sup>[8]</sup>              | 166% - 100 ms / 150% - 5 s / 120% - 8 s / 110% - 15 s  |                                 |
| DC              | Maximum DC Voltage                              | 1500 V                                                 |                                 |
|                 | DC Voltage Ripple                               | < 3%                                                   |                                 |
|                 | Max. DC Continuous Current (A)                  | 4590                                                   |                                 |
|                 | Max. DC Short Circuit Current (kA)              | 500 kA with a time constant of 1 ms                    |                                 |
|                 | Battery Technology                              | All type of batteries (BMS required)                   |                                 |
| CABINET         | Dimensions [WxDxH] (ft)                         | 21.3 x 6.5 x 7.5                                       |                                 |
|                 | Dimensions [WxDxH] (m)                          | 6.5 x 2.0 x 2.3                                        |                                 |
|                 | Weight (lbs)                                    | 30865                                                  |                                 |
|                 | Weight (kg)                                     | 14000                                                  |                                 |
|                 | Type of Ventilation                             | Forced air cooling                                     |                                 |
| ENVIRONMENT     | Degree of Protection                            | NEMA 3R                                                |                                 |
|                 | Operating Temperature Range <sup>[2]</sup>      | From -40 °C to +60 °C, >40°C power derating            |                                 |
|                 | Operating Relative Humidity Range               | From 4% to 100%                                        |                                 |
|                 | Storage Temperature Range                       | From -40 °C to +60 °C                                  |                                 |
|                 | Max. Altitude (above sea level) <sup>[3]</sup>  | 2000m                                                  |                                 |
| CONTROL         | Communication Protocol                          | Modbus TCP                                             |                                 |
|                 | Power Plant Controller                          | Optional. Third party SCADA systems supported.         |                                 |
|                 | Keyed ON/OFF Switch                             | Standard                                               |                                 |
| PROTECTIONS     | Ground Fault Protection                         | Insulation monitoring device                           |                                 |
|                 | Humidity Control                                | Active heating                                         |                                 |
|                 | General AC Protection & Disconn.                | 38 kV MV switchgear (V)                                |                                 |
|                 | General DC Protection & Disconn. <sup>[4]</sup> | High-speed fuses, Motorized DC disconnect switches     |                                 |
|                 | Overvoltage Protection                          | Type II for AC and Type I+II for DC                    |                                 |
| STANDARDS       | Safety                                          | UL 1741 / CSA 22.2 No.1071-16                          |                                 |
|                 | Installation                                    | NEC 2023                                               |                                 |
|                 | Utility Interconnect <sup>[5]</sup>             | UL 1741 SA & SB / RULE 21 / RULE 14H / IEEE 15471:2020 |                                 |

#### NOTES

- [1] Consult P-Q charts available:  $Q(kVA) = \sqrt{(S(kVA))^2 - P(kW)^2}$ .  
[2] Optional available for temperatures below -25 °C.  
[3] Consult Power Electronics for altitudes above 1000m.  
[4] Battery short circuit disconnection must be done on the battery side.  
[5] Consult Power Electronics for other applicable standards / grid codes.  
[6] Values at 1.00-Vac nom and CosPhi=1. Consult Power Electronics for derating curves.  
[7] Consult Power Electronics for derating curves. In the event of overvoltage in the grid, the minimum DC voltage will vary proportionally with the AC voltage.  
[8] Available from January 2027.



| REFERENCES      | FP4200M                                         | FP4201M                                                 | FP4204M                            |
|-----------------|-------------------------------------------------|---------------------------------------------------------|------------------------------------|
| AC              | AC Output Power (kVA/kW) @40°C <sup>[6]</sup>   | 4200                                                    |                                    |
|                 | AC Output Power (kVA/kW) @50°C <sup>[6]</sup>   | 3900                                                    |                                    |
|                 | Operating Grid Voltage (kV)                     | 34.5 kV ±10%                                            | 13.8 kV ±10%                       |
| DC              | DC Voltage Range <sup>[7]</sup>                 | 934 V - 1500 V                                          |                                    |
| EFFICIENCY      | Efficiency (Max) (η)                            | 98.00% including MV transformer                         |                                    |
|                 | CEC (η)                                         | 97.53% including MV transformer                         |                                    |
| COMMON FEATURES |                                                 |                                                         |                                    |
| AC              | Operating Grid Frequency (Hz)                   | 60 Hz                                                   |                                    |
|                 | Current Harmonic Distortion (THDi)              | < 3% per IEEE519                                        |                                    |
|                 | Power Factor (CosPhi) <sup>[1]</sup>            | 0.5 leading ... 0.5 lagging                             |                                    |
|                 | Reactive Power Compensation                     | Four quadrant operation                                 |                                    |
|                 | Overload Capability <sup>[8]</sup>              | 166% - 100 ms / 150% - 5 s / 120% - 8 s / 110% - 15 s   |                                    |
| DC              | Maximum DC Voltage                              | 1500 V                                                  |                                    |
|                 | DC Voltage Ripple                               | < 3%                                                    |                                    |
|                 | Max. DC Continuous Current (A)                  | 4590                                                    |                                    |
|                 | Max. DC Short Circuit Current (kA)              | 500 kA with a time constant of 1 ms                     |                                    |
|                 | Battery Technology                              | All type of batteries (BMS required)                    |                                    |
| CABINET         | Dimensions [WxDxH] (ft)                         | 21.3 x 6.5 x 7.5                                        |                                    |
|                 | Dimensions [WxDxH] (m)                          | 6.5 x 2.0 x 2.3                                         |                                    |
|                 | Weight (lbs)                                    | 30865                                                   |                                    |
|                 | Weight (kg)                                     | 14000                                                   |                                    |
|                 | Type of Ventilation                             | Forced air cooling                                      |                                    |
| ENVIRONMENT     | Degree of Protection                            | NEMA 3R                                                 |                                    |
|                 | Operating Temperature Range <sup>[2]</sup>      | From -40 °C to +60 °C, >40°C power derating             |                                    |
|                 | Operating Relative Humidity Range               | From 4% to 100%                                         |                                    |
|                 | Storage Temperature Range                       | From -40°C to +60°C                                     |                                    |
|                 | Max. Altitude (above sea level) <sup>[3]</sup>  | 2000m                                                   |                                    |
| CONTROL         | Communication Protocol                          | Modbus TCP                                              |                                    |
|                 | Power Plant Controller                          | Optional. Third party SCADA systems supported.          |                                    |
|                 | Keyed ON/OFF Switch                             | Standard                                                |                                    |
| PROTECTIONS     | Ground Fault Protection                         | Insulation monitoring device                            |                                    |
|                 | Humidity Control                                | Active heating                                          |                                    |
|                 | General AC Protection & Disconn.                | 38 kV MV switchgear (V)                                 | 15.5 kV SF6 Free MV switchgear (V) |
|                 | General DC Protection & Disconn. <sup>[4]</sup> | High-speed fuses, Motorized DC disconnect switches      |                                    |
|                 | Overvoltage Protection                          | Type II for AC and Type I+II for DC                     |                                    |
| STANDARDS       | Safety                                          | UL 1741 / CSA 22.2 No.107.1-16                          |                                    |
|                 | Installation                                    | NEC 2023                                                |                                    |
|                 | Utility Interconnect <sup>[5]</sup>             | UL 1741 SA & SB / RULE 21 / RULE 14H / IEEE 1547.1:2020 |                                    |

#### NOTES

- [1] Consult P-Q charts available:  $Q(kVA) = \sqrt{(S(kVA)^2 - P(kW)^2)}$ .  
[2] Optional available for temperatures below -25 °C.  
[3] Consult Power Electronics for altitudes above 1000m.  
[4] Battery short circuit disconnection must be done on the battery side.  
[5] Consult Power Electronics for other applicable standards / grid codes.  
[6] Values at 1.00-Vac nom and CosPhi=1. Consult Power Electronics for derating curves.  
[7] Consult Power Electronics for derating curves. In the event of overvoltage in the grid, the minimum DC voltage will vary proportionally with the AC voltage.  
[8] Available from January 2027.