

Easy maintenance.
Integrated MV solution in the same enclosure.
Advanced grid support.
Compatible with all battery technologies.





REFERENCES		FP4200M	FP4201M	FP4204M
AC	AC Output Power (kVA/kW) @40°C ^[6]	4200		
	AC Output Power (kVA/kW) @50°C ^[6]	3900		
	Operating Grid Voltage (kV)	34.5 kV ±10%	13.8 kV ±10%	12.47 kV ±10%
DC	DC Voltage Range ^[7]	934V - 1500V		
EFFICIENCY	Efficiency (Max) (η)	98.00% including MV transformer		
	CEC (η)	97.53% including MV transformer		
REFERENCES		FP4105M	FP4010M	
AC	AC Output Power (kVA/kW) @40°C ^[6]	4105	4010	
	AC Output Power (kVA/kW) @50°C ^[6]	3810	3720	
	Operating Grid Voltage (kV)	34.5 kV ±10%		
DC	DC Voltage Range ^[7]	913V - 1500 V		891V - 1500 V
EFFICIENCY	Efficiency (Max) (η)	97.93% including MV transformer		97.91% including MV transformer
	CEC (η)	97.50% including MV transformer		97.49% including MV transformer
COMMON FEATURES				
AC	Operating Grid Frequency (Hz)	60Hz		
	Current Harmonic Distortion (THDi)	< 3% per IEEE519		
	Power Factor (CosPhi) ^[1]	0.5 leading ... 0.5 lagging		
	Reactive Power Compensation	Four quadrant operation		
	Overload Capability ^[8]	166% - 100 ms / 150% - 5 s / 120% - 8 s / 110% - 15 s		
DC	Maximum DC Voltage	1500V		
	DC Voltage Ripple	< 3%		
	Max. DC Continuous Current (A)	4590		
	Max. DC Short Circuit Current (kA)	500 kA with a time constant of 1 ms		
	Battery Technology	All type of batteries (BMS required)		
CABINET	Dimensions [WxDxH] (ft)	21.3 x 6.5 x 7.5		
	Dimensions [WxDxH] (m)	6.5 x 2.0 x 2.3		
	Weight (lbs)	30865		
	Weight (kg)	14000		
	Type of Ventilation	Forced air cooling		
ENVIRONMENT	Degree of Protection	NEMA 3R		
	Operating Temperature Range ^[2]	From -40 °C to +60 °C, >40°C power derating		
	Operating Relative Humidity Range	From 4% to 100% non-condensing		
	Storage Temperature Range	From -40°C to +60°C		
	Max. Altitude (above sea level) ^[3]	2000m		
CONTROL INTERFACE	Communication Protocol	Modbus TCP		
	Power Plant Controller	Optional. Third party SCADA systems supported.		
	Keyed ON/OFF Switch	Standard		
PROTECTIONS	Ground Fault Protection	Insulation monitoring device		
	Humidity Control	Active heating		
	General AC Protection & Disconn.	38 kV MV switchgear (20 or 25 kA)		
	General DC Protection & Disconn. ^[4]	High-speed fuses, Motorized DC disconnect switches		
	Overvoltage Protection	Type II for AC and Type I+II for DC		
STANDARDS	Safety	UL 1741 / CSA 22.2 No.107:1-16		
	Installation	NEC 2023		
	Utility Interconnect ^[5]	UL 1741 SA & SB / RULE 21 / RULE 14H / IEEE 1547:2020		

NOTES

- [1] Consult P-Q charts available: $Q(kVA) = \sqrt{(S(kVA))^2 - P(kW)^2}$.
[2] Optional available for temperatures below -25 °C.
[3] Consult Power Electronics for altitudes above 1000m.
[4] Battery short circuit disconnection must be done on the battery side.
[5] Consult Power Electronics for other applicable standards / grid codes.
[6] Values at 1.00-Vac nom and CosPhi=1. Consult Power Electronics for derating curves.
[7] Consult Power Electronics for derating curves. In the event of overvoltage in the grid, the minimum DC voltage will vary proportionally with the AC voltage.
[8] Available from January 2027.