


Fitting second-order acyclic Markovian Arrival Processes, Sansottera A., Casale G. and Cremonesi P., Dependable Systems and Network, 2013 [_____](#)



underlying




[mmap|mtree]_pc

[mmap|mtree]_sigma

[mmap|mtree]_sigma2

[map|tree]_gamma



map2m_fit_trace

mamap2m_fit_gamma_bf_trace

mamap22_fit_gamma_fs_trace

mamap22_fit_gamma_bs_trace

mmap2m_mixture_fit_trace

mamap2m_fit_trace

_mmap

```
>> MAP = {[-1,1/3;0,-2],[2/3 0; 1/4 7/4]};  
>> MMAP = {MAP{1},MAP{2},MAP{2}.* [2/3 0; 0 2/7],MAP{2}.*[1/3 0; 1 5/7]};  
>> mmap_isfeasible(MMAP)  
ans = 1
```

```
>> FIT = mamap2m_fit_gamma_fb_mmap(MMAP)  
FIT =  
    [2x2 double]    [2x2 double]    [2x2 double]    [2x2 double]
```

```
>> [T,C] = mmap_sample(MMAP,1e5);  
>> FIT = mamap22_fit_gamma_fs_trace(T,C);  
>> mtrace_forward_moment(T,C,1) - mmap_forward_moment(FIT,1)  
ans =  
    1.1102e-16  
   -2.8148e-06
```

